SITE REVIEW TECHNICAL ADVISORY COMMITTEE PORTSMOUTH, NEW HAMPSHIRE

WORK SESSION

Conference Room A City Hall, Municipal Complex, 1 Junkins Avenue

2:00 PM January 11, 2022

AGENDA

2:00 PM 2A Russell Street Port Harbor Land, LLC, Owner Tighe & Bond, Engineer

(LUTW-22-1)

Site Plan Review Lot Line Revision Conditional Use Permit



T5037-002 January 6, 2022

Mr. Peter Britz, Interim Planning Director City of Portsmouth Planning Department 1 Junkins Avenue Portsmouth, New Hampshire 03801

Re: Request for Design Review Proposed Mixed Use Development, 2 Russell Street, Portsmouth, NH

Dear Peter,

On behalf of Port Harbor Land, LLC (owner/applicant), we are pleased to submit the following information to support a request for Design Review with the Planning Board for the above referenced project:

- One (1) full size & one (1) half size copy of the Site Plan Set, dated January 4, 2022;
- One (1) copy of the Community Space Exhibit, dated January 4, 2022;
- One (1) copy of the Truck Turning Exhibit, dated January 4, 2022;
- One (1) copy of the Precedent Images Plans, prepared by SGA, dated January 5, 2022

Under a separate cover a Design Review application fee check of \$500 has been submitted to the Planning Department by the applicant.

The proposed project is located along Deer Street and Russell Street on properties identified as Map 118 Lot 28, Map 119 Lot 4, Map 124 Lot 12, and Map 125 Lot 21 on the City of Portsmouth Tax Maps which are located in the Character District 5 (CD5). The project includes three buildings consisting of office, retail/commercial, and residential uses. The buildings consist of a 4-story office building at the corner of Deer Street and Maplewood Avenue, 5-story mixed-use residential building at the corner of Deer Street and Russell Street with below ground parking, first floor residential lobby, commercial space and parking and upper floor residential units, and a 5-story mixed-use residential building along Russell Street with first floor residential lobby and commercial space and upper floor residential units. The project also consists of significant on-site and off-site improvements including wide sidewalks, roadway improvements, community space, stormwater management, lighting, landscaping, and utilities.

The project is proposing over 30% community space for Map 118 Lot 28 in order to meet the requirements to receive a Conditional Use Permit (CUP) for an increased building footprint. The CUP will allow the project to consolidate parking under the building on the corner of Deer and Russell Streets. The project is also providing 20% community space for Map 124 Lot 12 and Map 125 Lot 21 in order to receive the Incentives to Development Standards allowed in the North End Incentive Overlay District.

The applicant is seeking to meet with the Planning Board for Design Review Phase. As such, the applicant also respectfully requests a vote from the Planning Board at the January 20, 2022 meeting to accept a request for Design Review Phase so that public hearing can be scheduled for the February 17, 2022 Planning Board meeting.



If you have any questions or need any additional information, please contact Neil Hansen by phone at (603) 433-8818 or by email at nahansen@tighebond.com.

Sincerely,

TIGHE & BOND, INC.

Patrick M. Crimmins, PE

Vice President

Neil A. Hansen, PE Project Manager


Copy: Port Harbor Land, LLC (via email)

NORTH END MIXED USE DEVELOPMENT

RUSSELL STREET & DEER STREET PORTSMOUTH, NEW HAMPSHIRE JANUARY 4, 2021

LIST OF DRAWINGS					
SHEET NO.	LAST REVISED				
	COVER SHEET	1/4/2022			
G-100	GENERAL NOTES AND LEGEND	1/4/2022			
C-101	EXISTING CONDITIONS & DEMOLITION PLAN	1/4/2022			
C-102	SITE PLAN	1/4/2022			
C-103	GRADING & DRAINAGE PLAN	1/4/2022			
C-104	UTILITIES PLAN	1/4/2022			
C-501	EROSION CONTROL NOTES AND DETAILS SHEET	1/4/2022			
C-502	DETAILS SHEET	1/4/2022			
C-503	DETAILS SHEET	1/4/2022			
C-504	DETAILS SHEET	1/4/2022			
C-505	DETAILS SHEET	1/4/2022			

LIST OF PERMITS					
LOCAL	STATUS	DATE			
SITE PLAN REVIEW PERMIT	NOT SUBMITTED				
LOT LINE REVISION PERMIT	NOT SUBMITTED				
CONDITIONAL USE PERMIT	NOT SUBMITTED				
STATE					
NHDES - SEWER CONNECTION PERMIT	NOT SUBMITTED				
NHDES - ALTERATION OF TERRAIN PERMIT	NOT SUBMITTED				



PREPARED BY:

ligne&Bond

177 CORPORATE DRIVE
PORTSMOUTH, NEW HAMPSHIRE 03801
603-433-8818

OWNER/APPLICANT:

TAX MAP 118, LOT 28,
TAX MAP 124, LOT 12 &
TAX MAP 125, LOT 21
PORT HARBOR LAND, LLC
1000 MARKET STREET, BUILDING ONE
PORTSMOUTH, NEW HAMPSHIRE 03801

COMPLETE SET 11 SHEETS

<u>DEMOLITION NOTES:</u>

- 1. THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR THE ENGINEER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK.
- THE CONTRACTOR SHALL VERIFY LOCATION OF ALL EXISTING UTILITIES. CALL DIG SAFE AT LEAST 72 HOURS PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION/CONSTRUCTION
- ALL MATERIALS SCHEDULED TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTOR UNLESS OTHERWISE SPECIFIED. THE CONTRACTOR SHALL DISPOSE OF ALL MATERIALS OFF-SITE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCES AND CODES.
- COORDINATE REMOVAL, RELOCATION, DISPOSAL OR SALVAGE OF UTILITIES WITH THE OWNER AND APPROPRIATE UTILITY COMPANY.
- ANY EXISTING WORK OR PROPERTY DAMAGED OR DISRUPTED BY CONSTRUCTION/ DEMOLITION ACTIVITIES SHALL BE REPLACED OR REPAIRED TO MATCH ORIGINAL EXISTING CONDITIONS BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
- 6. SAW CUT AND REMOVE PAVEMENT ONE (1) FOOT OFF PROPOSED EDGE OF PAVEMENT OR EXISTING CURB LINE IN ALL AREAS WHERE PAVEMENT TO BE REMOVED ABUTS EXISTING PAVEMENT OR CONCRETE TO REMAIN.
- 7. IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE THEMSELVES WITH THE CONDITIONS OF ALL OF THE PERMIT APPROVALS.
- THE CONTRACTOR SHALL OBTAIN AND PAY FOR ADDITIONAL PERMITS, NOTICES AND FEES NECESSARY TO COMPLETE THE WORK AND ARRANGE FOR AND PAY FOR NECESSARY INSPECTIONS AND APPROVALS FROM THE AUTHORITIES HAVING JURISDICTION.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION AND OFF-SITE DISPOSAL OF MATERIALS REQUIRED TO COMPLETE THE WORK, EXCEPT FOR WORK NOTED TO BE COMPLETED BY OTHERS.
- 10. UTILITIES SHALL BE TERMINATED AT THE MAIN LINE PER UTILITY COMPANY STANDARDS. THE CONTRACTOR SHALL REMOVE ALL ABANDONED UTILITIES LOCATED WITHIN THE LIMITS
- 11. CONTRACTOR SHALL VERIFY ORIGIN OF ALL DRAINS AND UTILITIES PRIOR TO REMOVAL/TERMINATION TO DETERMINE IF DRAINS OR UTILITY IS ACTIVE, AND SERVICES ANY ON OR OFF-SITE STRUCTURE TO REMAIN. THE CONTRACTOR SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY SUCH UTILITY FOUND AND SHALL MAINTAIN THESE UTILITIES UNTIL PERMANENT SOLUTION IS IN PLACE.
- 12. PAVEMENT REMOVAL LIMITS ARE SHOWN FOR CONTRACTOR'S CONVENIENCE. ADDITIONAL PAVEMENT REMOVAL MAY BE REQUIRED DEPENDING ON THE CONTRACTOR'S OPERATION. CONTRACTOR TO VERIFY FULL LIMITS OF PAVEMENT REMOVAL PRIOR TO BID.
- 13. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL EXISTING STRUCTURES, CONCRETE PADS, UTILITIES AND PAVEMENT WITHIN THE WORK LIMITS SHOWN UNLESS SPECIFICALLY IDENTIFIED TO REMAIN. ITEMS TO BE REMOVED INCLUDE BUT ARE NOT LIMITED TO: CONCRETE, PAVEMENT, CURBS, LIGHTING, MANHOLES, CATCH BASINS, UNDER GROUND PIPING, POLES, STAIRS, SIGNS, FENCES, RAMPS, WALLS, BOLLARDS, BUILDING SLABS, FOUNDATION, TREES AND LANDSCAPING.
- 14. COORDINATE ALL WORK WITHIN THE PUBLIC RIGHT OF WAYS WITH THE CITY OF
- 15. REMOVE TREES AND BRUSH AS REQUIRED FOR COMPLETION OF WORK. CONTRACTOR SHALL GRUB AND REMOVE ALL STUMPS WITHIN LIMITS OF WORK AND DISPOSE OF OFF SITE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS
- 16. CONTRACTOR SHALL PROTECT ALL PROPERTY MONUMENTATION THROUGHOUT DEMOLITION AND CONSTRUCTION OPERATIONS. SHOULD ANY MONUMENTATION BE DISTURBED BY THE CONTRACTOR, THE CONTRACTOR SHALL EMPLOY A NEW HAMPSHIRE LICENSED SURVEYOR TO REPLACE DISTURBED MONUMENTS.
- 17. PROVIDE INLET PROTECTION BARRIERS AT ALL CATCH BASINS/CURB INLETS WITHIN CONSTRUCTION LIMITS AS WELL AS CATCH BASINS/CURB INLETS THAT RECEIVE RUNOFF FROM CONSTRUCTION ACTIVITIES. INLET PROTECTION BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT. INLET PROTECTION BARRIERS SHALL BE "STORMWATER INLET FILTER" BY BLOCKSOM & CO. OR EQUAL. INSPECT BARRIERS WEEKLY AND AFTER EACH RAIN EVENT OF 0.25 INCHES OR GREATER. CONTRACTOR SHALL COMPLETE A MAINTENANCE INSPECTION REPORT AFTER EACH INSPECTION. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED OR SEDIMENT HAS ACCUMULATED TO 1/3 THE DESIGN DEPTH OF THE BARRIER.
- 18. THE CONTRACTOR SHALL PHASE DEMOLITION AND CONSTRUCTION AS REQUIRED TO PROVIDE CONTINUOUS SERVICE TO EXISTING BUSINESSES AND HOMES THROUGHOUT THE CONSTRUCTION PERIOD. EXISTING BUSINESS AND HOME SERVICES INCLUDE, BUT ARE NOT LIMITED TO ELECTRICAL, COMMUNICATION, FIRE PROTECTION, DOMESTIC WATER AND SEWER SERVICES. TEMPORARY SERVICES, IF REQUIRED, SHALL COMPLY WITH ALL FEDERAL, STATE, LOCAL AND UTILITY COMPANY STANDARDS. CONTRACTOR SHALL PROVIDE DETAILED CONSTRUCTION SCHEDULE TO OWNER PRIOR TO ANY DEMOLITION/CONSTRUCTION ACTIVITIES AND SHALL COORDINATE TEMPORARY SERVICES TO ABUTTERS WITH THE UTILITY COMPANY AND AFFECTED ABUTTER.
- 19. SEE ROADWAY IMPROVEMENT PLANS FOR OFF-SITE DEMOLITION.
- 20. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO THE START OF ANY CLEARING OR DEMOLITION ACTIVITIES.
- 21. THE CONTRACTOR SHALL PAY ALL COSTS NECESSARY FOR TEMPORARY PARTITIONING, BARRICADING, FENCING, SECURITY AND SAFETY DEVICES REQUIRED FOR THE MAINTENANCE OF A CLEAN AND SAFE CONSTRUCTION SITE.
- 22. SAW CUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL UTILITIES TO BE REMOVED AND PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT
- 23. THE CONTRACTOR SHALL REMOVE AND SALVAGE EXISTING GRANITE CURB FOR REUSE.

EROSION CONTROL NOTES:

- INSTALL EROSION CONTROL BARRIERS AS SHOWN AS FIRST ORDER OF WORK. SEE GENERAL EROSION CONTROL NOTES ON "EROSION CONTROL NOTES & DETAILS SHEET".
- PROVIDE INLET PROTECTION AROUND ALL EXISTING AND PROPOSED CATCH BASIN INLETS WITHIN THE WORK LIMITS AS WELL AS CATCH BASINS/CURB INLETS THAT RECEIVE RUNOFF FROM CONSTRUCTION ACTIVITIES. MAINTAIN FOR THE DURATION OF THE PROJECT. INSTALL STABILIZED CONSTRUCTION EXIT(S).

INSPECT INLET PROTECTION AND PERIMETER EROSION CONTROL MEASURES DAILY AND

- AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS
- 1/3 THE FILTER HEIGHT. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM,
- SEED, FERTILIZER AND MULCH. CONSTRUCT EROSION CONTROL BLANKET ON ALL SLOPES STEEPER THAN 3:1.
- PRIOR TO ANY WORK OR SOIL DISTURBANCE COMMENCING ON THE SUBJECT PROPERTY, INCLUDING MOVING OF EARTH, THE APPLICANT SHALL INSTALL ALL EROSION AND SILTATION MITIGATION AND CONTROL MEASURES AS REQUIRED BY STATE AND LOCAL PERMITS AND APPROVALS.
- CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST AND WIND EROSION THROUGHOUT THE CONSTRUCTION PERIOD. DUST CONTROL MEASURES SHALL INCLUDE, BUT ARE NOT LIMITED TO, SPRINKLING WATER ON UNSTABLE SOILS SUBJECT TO ARID CONDITIONS.
- 10. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION.
- 11. ALL CATCH BASIN SUMPS AND PIPING SHALL BE THOROUGHLY CLEANED TO REMOVE ALL SEDIMENT AND DEBRIS AFTER THE PROJECT HAS BEEN FULLY PAVED.
- 12. TEMPORARY SOIL STOCKPILE SHALL BE SURROUNDED WITH PERIMETER CONTROLS AND SHALL BE STABILIZED BY TEMPORARY EROSION CONTROL SEEDING. STOCKPILE AREAS TO BE LOCATED AS FAR AS POSSIBLE FROM THE DELINEATED EDGE OF WETLANDS.

- 13. SAFETY FENCING SHALL BE PROVIDED AROUND STOCKPILES OVER 10 FT.
- 14. CONCRETE TRUCKS WILL BE REQUIRED TO WASH OUT (IF NECESSARY) SHOOTS ONLY WITHIN AREAS WHERE CONCRETE HAS BEEN PLACED. NO OTHER WASH OUT WILL BE ALLOWED.

- STRIPE PARKING AREAS AS SHOWN, INCLUDING PARKING SPACES, STOP BARS, ADA SYMBOLS, PAINTED ISLANDS, CROSS WALKS, ARROWS, LEGENDS AND CENTERLINES SHALL BE THERMOPLASTIC MATERIAL. THERMOPLASTIC MATERIAL SHALL MEET THE REQUIREMENTS OF AASHTO M249. (ALL MARKINGS EXCEPT CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING WHITE TRAFFIC PAINT. CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING YELLOW TRAFFIC PAINT. ALL TRAFFIC PAINT SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F").
- 2. ALL PAVEMENT MARKINGS AND SIGNS TO CONFORM TO "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", "STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS", AND THE AMERICANS WITH DISABILITIES ACT REQUIREMENTS, LATEST
- SEE DETAILS FOR PARKING STALL MARKINGS, ADA SYMBOLS, SIGNS AND SIGN POSTS.
- 4. CENTERLINES SHALL BE FOUR (4) INCH WIDE YELLOW LINES. STOP BARS SHALL BE EIGHTEEN
- 5. PAINTED ISLANDS SHALL BE FOUR (4) INCH WIDE DIAGONAL LINES AT 3'-0" O.C. BORDERED BY FOUR (4) INCH WIDE LINES.
- 6. THE CONTRACTOR SHALL EMPLOY A NEW HAMPSHIRE LICENSED LAND SURVEYOR TO DETERMINE ALL LINES AND GRADES.
- 7. CLEAN AND COAT VERTICAL FACE OF EXISTING PAVEMENT AT SAW CUT LINE WITH RS-1 EMULSION IMMEDIATELY PRIOR TO PLACING NEW BITUMINOUS CONCRETE.
- 8. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND CITY CODES & SPECIFICATIONS.
- 9. COORDINATE ALL WORK WITHIN PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH
- 10. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILE) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR.
- 11. SEE BUILDING DRAWINGS FOR ALL CONCRETE PADS & SIDEWALKS ADJACENT TO BUILDING.
- ALL WORK SHALL CONFORM TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS, STANDARD SPECIFICATIONS. 13. CONTRACTOR TO PROVIDE BACKFILL AND COMPACTION AT CURB LINE AFTER CONCRETE
- FORMS FOR SIDEWALKS AND PADS HAVE BEEN STRIPPED. COORDINATE WITH BUILDING CONTRACTOR.
- 14. COORDINATE ALL WORK ADJACENT TO BUILDING WITH BUILDING CONTRACTOR.
- 15. ALL DIMENSIONS ARE TO THE FACE OF CURB UNLESS OTHERWISE NOTED. 16. THE STREET LIGHTING TYPE TO BE DISTRICT STYLE FIXTURE AND POLE TO MATCH EXISTING
- LIGHTING ON SOUTH SIDE OF DEER STREET. 17. ALL CONDITIONS ON THIS PLAN SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO THE
- REQUIREMENTS OF THE SITE PLAN REVIEW REGULATIONS. 18. THE APPLICANT SHALL HAVE A SITE SURVEY CONDUCTED BY A RADIO COMMUNICATIONS CARRIER APPROVED BY THE CITY'S COMMUNICATIONS DIVISION. THE RADIO COMMUNICATIONS CARRIER MUST BE FAMILIAR AND CONVERSANT WITH THE POLICE AND RADIO CONFIGURATION. IF THE SITE SURVEY INDICATES IT IS NECESSARY TO INSTALL A SIGNAL REPEATER EITHER ON OR NEAR THE PROPOSED PROJECT, THOSE COSTS SHALL BE

THE RESPONSIBILITY OF THE PROPERTY OWNER. THE OWNER SHALL COORDINATE WITH THE

- SUPERVISOR OF RADIO COMMUNICATIONS FOR THE CITY. 19. ALL TREES PLANTED ARE TO BE INSTALLED UNDER THE SUPERVISION OF THE CITY OF
- PORTSMOUTH DPW USING STANDARD INSTALLATION METHODS. 20. THE APPLICANT SHALL PREPARE A CONSTRUCTION MITIGATION AND MANAGEMENT PLAN (CMMP) FOR REVIEW AND APPROVAL BY THE CITY'S LEGAL AND PLANNING DEPARTMENTS.
- 21. A TEMPORARY SUPPORT OF EXCAVATION (SOE) PLAN SHALL BE PREPARED BY THE APPLICANT'S CONTRACTOR TO CONFIRM ANY TEMPORARY ENCUMBRANCES OF THE CITY'S RIGHT-OF-WAY. IF LICENSES ARE REQUIRED FOR THE SOE, THE APPLICANT WILL BE
- REQUIRED TO OBTAIN THESE FROM THE CITY PRIOR TO CONSTRUCTION 22. ALL EXCESS SNOW SHALL BE HAULED OFF-SITE IN ACCORDANCE TO ALL LOCAL AND STATE LAWS. PROPOSED SNOW STAGING AREAS HAVE BEEN PROVIDED TO SHOW TEMPORARY
- 23. AREAS DESIGNATED FOR FIRE EMERGENCY ACCESS SHALL BE KEPT CLEAR OF SNOW.

SITE RECORDING NOTES:

- 1. THIS SITE PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.
- ALL IMPROVEMENTS SHOWN ON THIS SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE PORTSMOUTH PLANNING DIRECTOR.
- THIS IS NOT A BOUNDARY SURVEY AND SHALL NOT BE USED AS SUCH.

GRADING AND DRAINAGE NOTES:

COMPACTION REQUIREMENTS:

SNOW STORAGE AREAS.

- BELOW PAVED OR CONCRETE AREAS TRENCH BEDDING MATERIAL AND
- SAND BLANKET BACKFILL
- BELOW LOAM AND SEED AREAS
- * ALL PERCENTAGES OF COMPACTION SHALL BE OF THE MAXIMUM DRY DENSITY AT THE OPTIMUM MOISTURE CONTENT AS DETERMINED AND CONTROLLED IN ACCORDANCE WITH ASTM D-1557, METHOD C FIELD DENSITY TESTS SHALL BE MADE IN ACCORDANCE WITH ASTM D-1556 OR ASTM-2922.

95%

95%

90%

- 2. ALL STORM DRAINAGE PIPES SHALL BE HIGH DENSITY POLYETHYLENE (HANCOR HI-Q, ADS
- N-12 OR EQUAL) OR RCP CLASS IV, UNLESS OTHERWISE SPECIFIED.
- 3. SEE UTILITY PLAN FOR ALL SITE UTILITY INFORMATION.
- 4. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
- CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE AND LAWN AREAS FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE BUILDING ENTRANCES, EXITS, RAMPS AND LOADING DOCK AREAS ADJACENT TO THE BUILDING
- CONTRACTOR SHALL THOROUGHLY CLEAN ALL CATCH BASINS AND DRAIN LINES, WITHIN THE LIMIT OF WORK, OF SEDIMENT IMMEDIATELY UPON COMPLETION OF CONSTRUCTION.
- 7. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND LOCAL CODES.
- ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED FERTILIZER AND MULCH.
- ALL STORM DRAIN CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE NHDOT STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES, LATEST EDITION. 10. ALL PROPOSED CATCH BASINS SHALL BE EQUIPPED WITH OIL/GAS SEPARATOR HOODS AND 4'
- SUMPS. 11. ALL WORK SHALL CONFORM TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS, STANDARD SPECIFICATIONS AND WITH THE STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION, "STANDARD SPECIFICATIONS OF ROAD AND BRIDGE CONSTRUCTION",
- CURRENT EDITION. 12. CONTRACTOR TO SUBMIT AS-BUILT PLANS IN DIGITAL FORMAT (.DWG AND .PDF FILES) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR.
- 13. SEE EXISTING CONDITIONS & DEMOLITION PLAN FOR BENCH MARK INFORMATION.

UTILITY NOTES:

1. THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR ENGINEER. IT IS THE CONTRACTOR'S

RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES, AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK AT NO ADDITIONAL COST TO THE OWNER.

- COORDINATE ALL UTILITY WORK WITH APPROPRIATE UTILITY COMPANY.
- NATURAL GAS UNITIL
- WATER CITY OF PORTSMOUTH
- SEWER CITY OF PORTSMOUTH

• ELECTRIC - EVERSOURCE

- COMMUNICATIONS FAIRPOINT AND COMCAST
- SEE EXISTING CONDITIONS & DEMOLITION PLAN FOR BENCHMARK INFORMATION. 4. SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR PROPOSED GRADING AND EROSION CONTROL MEASURES.
- 5. ALL WATER MAIN INSTALLATIONS SHALL BE CLASS 52, CEMENT LINED DUCTILE IRON PIPE.
- 6. ALL WATER MAIN INSTALLATIONS SHALL BE PRESSURE TESTED AND CHLORINATED AFTER CONSTRUCTION PRIOR TO ACTIVATING THE SYSTEM. CONTRACTOR SHALL COORDINATE CHLORINATION AND TESTING WITH THE PORTSMOUTH WATER DEPARTMENT.
- ALL SEWER PIPE SHALL BE PVC SDR 35 UNLESS OTHERWISE STATED.
- COORDINATE ALL WORK WITHIN PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH. CONTRACTOR SHALL MAINTAIN UTILITY SERVICES TO ABUTTING PROPERTIES THROUGHOUT CONSTRUCTION.
- 10. CONNECTION TO EXISTING WATER MAIN SHALL BE CONSTRUCTED TO THE CITY OF PORTSMOUTH STANDARDS.
- 11. EXISTING UTILITIES TO BE REMOVED SHALL BE CAPPED AT THE MAIN AND MEET THE DEPARTMENT OF PUBLIC WORKS STANDARDS FOR CAPPING OF WATER AND SEWER SERVICES.
- 12. ALL ELECTRICAL MATERIAL WORKMANSHIP SHALL CONFORM TO THE NATIONAL ELECTRIC CODE, LATEST EDITION, AND ALL APPLICABLE STATE AND LOCAL CODES.
- 13. THE EXACT LOCATION OF NEW UTILITY SERVICES AND CONNECTIONS SHALL BE
- COORDINATED WITH THE BUILDING DRAWINGS AND THE APPLICABLE UTILITY COMPANIES. 14. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
- 15. ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES TO FACILITATE PULLING
- 16. THE CONTRACTOR SHALL OBTAIN, PAY FOR, AND COMPLY WITH ALL REQUIRED PERMITS, ARRANGE FOR ALL INSPECTIONS, AND SUBMIT COPIES OF ACCEPTANCE CERTIFICATES TO THE OWNER PRIOR TO THE COMPLETION OF THIS PROJECT.
- 17. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES, AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER INSTALLATION OF UTILITIES COMPLETE AND **OPERATIONAL**
- 18. CONTRACTOR SHALL PROVIDE EXCAVATION, BEDDING, BACKFILL AND COMPACTION FOR NATURAL GAS SERVICES.
- 19. A 10-FOOT MINIMUM EDGE TO EDGE HORIZONTAL SEPARATION SHALL BE PROVIDED BETWEEN ALL WATER AND SANITARY SEWER LINES. AN 18-INCH MINIMUM OUTSIDE TO OUTSIDE VERTICAL SEPARATION SHALL BE PROVIDED AT ALL WATER/SANITARY SEWER
- 20. THE CONTRACTOR SHALL CONTACT "DIG-SAFE" 72 HOURS PRIOR TO COMMENCING CONSTRUCTION. THE CONTRACTOR SHALL HAVE THE "DIG-SAFE" NUMBER ON SITE AT ALL
- 21. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILES) TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
- 22. SAW CUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN
- PORTSMOUTH. 24. COORDINATE TESTING OF SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH.

23. HYDRANTS, GATE VALVES, FITTINGS, ETC. SHALL MEET THE REQUIREMENTS OF THE CITY OF

- 25. ALL SEWER PIPE WITH LESS THAN 6' OF COVER IN PAVED AREAS OR LESS THAT 4' OF COVER IN UNPAVED AREAS SHALL BE INSULATED. 26. CONTRACTOR SHALL COORDINATE ALL ELECTRIC WORK INCLUDING BUT NOT LIMITED TO:
- CONDUIT CONSTRUCTION, MANHOLE CONSTRUCTION, UTILITY POLE CONSTRUCTION, OVERHEAD WIRE RELOCATION, AND TRANSFORMER CONSTRUCTION WITH POWER COMPANY. 27. CONTRACTOR SHALL PHASE UTILITY CONSTRUCTION, PARTICULARLY WATER MAIN AND GAS MAIN CONSTRUCTION AS TO MAINTAIN CONTINUOUS SERVICE TO ABUTTING PROPERTIES. CONTRACTOR SHALL COORDINATE TEMPORARY SERVICES TO ABUTTERS WITH THE UTILITY
- COMPANY AND AFFECTED ABUTTER. 28. SITE LIGHTING SPECIFICATIONS, CONDUIT LAYOUT AND CIRCUITRY FOR PROPOSED SITE LIGHTING AND SIGN ILLUMINATION SHALL BE PROVIDED BY THE PROJECT ELECTRICAL
- 29. CONTRACTOR SHALL CONSTRUCT ALL UTILITIES AND DRAINS TO WITHIN 10' OF THE FOUNDATION WALLS AND CONNECT THESE TO SERVICE STUBS FROM THE BUILDING.

LEGEND

______ PROPOSED SAWCUT LIMIT OF WORK ________ PROPOSED SILT SOCK APPROXIMATE LIMIT OF PAVEMENT TO BE REMOVED PROPOSED CONSTRUCTION EXIT **BUILDING TO BE REMOVED** LOCATION OF PROPOSED BUILDING PROPERTY LINE PROPOSED PROPERTY LINE PROPOSED EDGE OF PAVEMENT PROPOSED CURB PROPOSED BUILDING PROPOSED PAVEMENT SECTION PROPOSED CONCRETE SIDEWALK PROPOSED BRICK SIDEWALK PROPOSED BOLLARD

PROPOSED MAJOR CONTOUR LINE PROPOSED MINOR CONTOUR LINE PROPOSED DRAIN LINE (TYP) INLET PROTECTION SILT SACK PROPOSED CATCHBASIN

PROPOSED DOUBLE GRATE CATCHBASIN PROPOSED DRAIN MANHOLE PROPOSED YARD DRAIN EXISTING STORM DRAIN EXISTING SANITARY SEWER EXISTING SANITARY SEWER TO BE REMOVED ____T____T____T___ EXISTING UNDERGROUND TELECOMMUNICATION

EXISTING WATER EXISTING GAS EXISTING UNDERGROUND ELECTRIC ____E___ EXISTING OVERHEAD UTILITY

PROPOSED SANITARY SEWER

PROPOSED WATER -----PG------PROPOSED GAS PROPOSED UNDERGROUND ELECTRIC

PROPOSED UNDERGROUND **TELECOMMUNICATION** PROPOSED UNDERGROUND COMBINED ELECTRIC & TELECOMMUNICATION

EXISTING CATCHBASIN **EXISTING DRAIN MANHOLE** EXISTING SEWER MANHOLE EXISTING WATER VALVE EXISTING HYDRANT

EXISTING ELECTRIC MANHOLE **EXISTING TELEPHONE MANHOLE** PROPOSED SEWER MANHOLE PROPOSED WATER VALVE PROPOSED HYDRANT PROPOSED GAS VALVE

PROPOSED ELECTRIC MANHOLE

PROPOSED LIGHT POLE BASE

GRAPHIC SCALE

North End Mixed Use Development

Two International Group

Russell Street & Deer Street Portsmouth, NH

MARK DATE DESCRIPTION

T5037-00

January 4, 2022

AS SHOWN

T5037-002-C-DSGN.DWG

CHECKED: APPROVED: GENERAL NOTES

SCALE:


PROJECT NO:


DRAWN BY:


DATF:


G-100

AND LEGEND









PROJECT APPLICANT: PORT HARBOR LAND, LLC
1000 MARKET STREET, BUILDING ONE

PORTSMOUTH, NH 03801
PROJECT NAME: PROPOSED MIXED USE DEVELOPMENT PROJECT

PROJECT NAME: PROPOSED MIXED USE DEVELOPMENT PROJECT MAP / LOT : MAP 118 / LOT 28
PROJECT ADDRESS: RUSSELL STREET & DEER STREET MAP 124 / LOT 12
PORTSMOUTH, NH 03801 MAP 125 / LOT 21

PROJECT LATITUDE: 43°-04'-43" N
PROJECT LONGITUDE: 70°-45'-41" W

PROJECT DESCRIPTION

THE PROJECT CONSISTS OF THE CONSTRUCTION OF AN OFFICE BUILDING AND TWO MIXED USE RESIDENTIAL BUILDINGS WITH ASSOCIATED SITE IMPROVEMENTS.

DISTURBED AREA

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 2.1 ACRES.

SOIL CHARACTERISTICS

BASED ON THE USCS WEB SOIL SURVEY THE SOILS ON SITE CONSIST OF URBAN LAND WHICH IS EXCESSIVELY DRAINED SOILS WITH A HYDROLOGIC SOIL GROUP RATING OF A.

NAME OF RECEIVING WATERS

THE STORMWATER RUNOFF FROM THE SITE WILL BE DISCHARGED VIA A CLOSED DRAINAGE SYSTEM TO THE CITY OF PORTSMOUTH'S CLOSED DRAINAGE SYSTEM WHICH ULTIMATELY FLOWS TO NORTH MILL POND THEN TO THE PISCATAQUA RIVER.

CONSTRUCTION SEQUENCE OF MAJOR ACTIVITIES:

CUT AND CLEAR TREES.

- 2. CONSTRUCT TEMPORARY AND PERMANENT SEDIMENT, EROSION AND DETENTION CONTROL FACILITIES. EROSION, SEDIMENT AND DETENTION MEASURES SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OPERATIONS THAT WILL INFLUENCE STORMWATER RUNOFF SUCH AS:
- NEW CONSTRUCTION
- CONTROL OF DUST
- CONTROL OF DUST
 CONSTRUCTION DURING LATE WINTER AND EARLY SPRING
 ALL PERMANENT DITCHES, SWALES, DETENTION, RETENTION AND SEDIMENTATION BASINS TO BE

STABILIZED USING THE VEGETATIVE AND NON-STRUCTURAL BMPS PRIOR TO DIRECTING RUNOFF

- TO THEM.
 CLEAR AND DISPOSE OF DEBRIS.
- 5. CONSTRUCT TEMPORARY CULVERTS AND DIVERSION CHANNELS AS REQUIRED.
- 6. GRADE AND GRAVEL ROADWAYS AND PARKING AREAS ALL ROADS AND PARKING AREA SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
- 7. BEGIN PERMANENT AND TEMPORARY SEEDING AND MULCHING. ALL CUT AND FILL SLOPES SHALL
 BE SEEDED AND MULCHED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE
- BE SEEDED AND MULCHED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.

 8. DAILY, OR AS REQUIRED, CONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, PERIMETER
- EROSION CONTROL MEASURES, SEDIMENT TRAPS, ETC., MULCH AND SEED AS REQUIRED.
 9. SEDIMENT TRAPS AND/OR BASINS SHALL BE USED AS NECESSARY TO CONTAIN RUNOFF UNTIL SOILS ARE STABILIZED.
- 10. FINISH PAVING ALL ROADWAYS AND PARKING LOTS.
- 11. INSPECT AND MAINTAIN ALL EROSION AND SEDIMENT CONTROL MEASURES.
- 12. COMPLETE PERMANENT SEEDING AND LANDSCAPING.
- 13. REMOVE TRAPPED SEDIMENTS FROM COLLECTOR DEVICES AS APPROPRIATE AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES.

SPECIAL CONSTRUCTION NOTES:

THE CONSTRUCTION SEQUENCE MUST LIMIT THE DURATION AND AREA OF DISTURBANCE.
 THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF

RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

- ALL EROSION CONTROL MEASURES AND PRACTICES SHALL CONFORM TO THE "NEW HAMPSHIRE STORMWATER MANUAL VOLUME 3: EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION"
- 2. PRIOR TO ANY WORK OR SOIL DISTURBANCE, CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR EROSION CONTROL MEASURES AS REQUIRED IN THE PROJECT MANUAL.
- 3. CONTRACTOR SHALL INSTALL TEMPORARY EROSION CONTROL BARRIERS, INCLUDING HAY BALES, SILT FENCES, MULCH BERMS, SILT SACKS AND SILT SOCKS AS SHOWN IN THESE DRAWINGS AS THE FIRST ORDER OF WORK.
- 4. SILT SACK INLET PROTECTION SHALL BE INSTALLED IN ALL EXISTING AND PROPOSED CATCH BASIN INLETS WITHIN THE WORK LIMITS AND BE MAINTAINED FOR THE DURATION OF THE
- 5. PERIMETER CONTROLS INCLUDING SILT FENCES, MULCH BERM, SILT SOCK, AND/OR HAY BALE BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT UNTIL NON-PAVED AREAS HAVE BEEN STABILIZED.
- 5. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION.
- 7. ALL DISTURBED AREAS NOT OTHERWISE BEING TREATED SHALL RECEIVE 6" LOAM, SEED AND
- FERTILIZER.

 8. INSPECT ALL INLET PROTECTION AND PERIMETER CONTROLS WEEKLY AND AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE
- EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS 1/3 THE FILTER HEIGHT.

 9. CONSTRUCT EROSION CONTROL BLANKETS ON ALL SLOPES STEEPER THAN 3:1.

STABILIZATION:

- AN AREA SHALL BE CONSIDERED STABLE WHEN ONE OF THE FOLLOWING HAS OCCURRED:
- A. BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED;
 B. A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED;
- C. A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN
- INSTALLED;
 D. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.;
- E. IN AREAS TO BE PAVED, "STABLE" MEANS THAT BASE COURSE GRAVELS MEETING THE REQUIREMENTS OF NHDOT STANDARD FOR ROAD AND BRIDGE CONSTRUCTION, 2016, ITEM 304.2 HAVE BEEN INSTALLED.
- . WINTER STABILIZATION PRACTICES:
- A. ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS;
- B. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR
- THE DESIGN FLOW CONDITIONS;

 C. AFTER OCTOBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOW AFTER EACH STORM EVENT;
- STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES, AND DISTURBED AREAS, WHERE
 CONSTRUCTION ACTIVITY SHALL NOT OCCUR FOR MORE THAN TWENTY-ONE (21) CALENDAR DAYS
 BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR
 TEMPORARILY CEASED IN THAT AREA. STABILIZATION MEASURES TO BE USED INCLUDE:

 A. ALL WASTE
- A. TEMPORARY SEEDING;
- B. MULCHING.4. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
- WHEN CONSTRUCTION ACTIVITY PERMANENTLY OR TEMPORARILY CEASES WITHIN 100 FEET OF NEARBY SURFACE WATERS OR DELINEATED WETLANDS, THE AREA SHALL BE STABILIZED WITHIN SEVEN (7) DAYS OR PRIOR TO A RAIN EVENT. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN AN THESE AREAS, SILT FENCES, MULCH BERMS, HAY BALE BARRIERS AND ANY
- EARTH/DIKES SHALL BE REMOVED ONCE PERMANENT MEASURES ARE ESTABLISHED. DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STABILIZED CHANNELS WHERE POSSIBLE. SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILT FENCES, MULCH BERMS, HAY BALE BARRIERS, OR SILT SOCKS. ALL STORM DRAIN BASIN INLETS SHALL BE PROVIDED WITH FLARED END SECTIONS AND TRASH RACKS. THE SITE SHALL BE STABILIZED FOR THE WINTER BY OCTOBER 15.

DUST CONTROL:

- I. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST THROUGHOUT THE CONSTRUCTION $\,$ 1 $\,$ PERIOD.
- DUST CONTROL METHODS SHALL INCLUDE, BUT BE NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY
- DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ABUTTING AREAS.

STOCKPILES:

- 1. LOCATE STOCKPILES A MINIMUM OF 50 FEET AWAY FROM CATCH BASINS, SWALES, AND CULVERTS.
- 2. ALL STOCKPILES SHOULD BE SURROUNDED WITH TEMPORARY EROSION CONTROL MEASURES
- PRIOR TO THE ONSET OF PRECIPITATION.

 3. PERIMETER BARRIERS SHOULD BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE
- INTEGRITY OF THE BARRIER SHOULD BE INSPECTED AT THE END OF EACH WORKING DAY.

 4. PROTECT ALL STOCKPILES FROM STORMWATER RUN-OFF USING TEMPORARY EROSION CONTROL MEASURES SUCH AS BERMS, SILT SOCK, OR OTHER APPROVED PRACTICE TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.

OFF SITE VEHICLE TRACKING

THE CONTRACTOR SHALL CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE(S) PRIOR TO ANY EXCAVATION ACTIVITIES.

VEGETATION:

1. TEMPORARY GRASS COVER: A. SEEDBED PREPARATION:

- a. APPLY FERTILIZER AT THE RATE OF 600 POUNDS PER ACRE OF 10-10-10. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF THREE (3) TONS PER ACRE;
- B. SEEDING:
 - a. UTILIZE ANNUAL RYE GRASS AT A RATE OF 40 LBS/ACRE;b. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SO
 - b. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF TWO (2) INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED;
 - c. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). HYDROSEEDINGS, WHICH INCLUDE MULCH, MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING;

C. MAINTENANCE:

a. TEMPORARY SEEDING SHALL BE PERIODICALLY INSPECTED. AT A MINIMUM, 95% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND OTHER TEMPORARY MEASURES USED IN THE INTERIM (MULCH, FILTER BARRIERS, CHECK DAMS, ETC.).

VEGETATIVE PRACTICE:

- A. FOR PERMANENT MEASURES AND PLANTINGS:
 a. LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF
- THREE (3) TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5;
 FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 800 POUNDS PER ACRE OF 10-20-20 FERTILIZER;
- c. SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN, AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE REQUIRED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4-1/2 POUNDS AND 5-1/2 POUNDS PER INCH OF WIDTH;
- d. SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH;
- e. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AS INDICATED ABOVE;
 f. THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED,
 WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY
 AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED,
 AND ALL NOXIOUS WEEDS REMOVED;
- g. THE CONTRACTOR SHALL PROTECT AND MAINTAIN THE SEEDED AREAS UNTIL ACCEPTED;
 h. A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE
- A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREM

 APPLIED AT THE INDICATED RATE:

 SEED MIX

 APPLICATION RATE

CREEPING RED FESCUE

TALL FESCUE

20 LBS/ACRE
20 LBS/ACRE

REDTOP 2 LBS/ACRE
IN NO CASE SHALL THE WEED CONTENT EXCEED ONE (1) PERCENT BY WEIGHT. ALL SEED
SHALL COMPLY WITH STATE AND FEDERAL SEED LAWS. SEEDING SHALL BE DONE NO
LATER THAN SEPTEMBER 15. IN NO CASE SHALL SEEDING TAKE PLACE OVER SNOW.

DORMANT SEEDING (SEPTEMBER 15 TO FIRST SNOWFALL):
 A. FOLLOW PERMANENT MEASURES SLOPE, LIME, FERTILIZER AND GRADING REQUIREMENTS.
 APPLY SEED MIXTURE AT TWICE THE INDICATED RATE. APPLY MULCH AS INDICATED FOR

CONCRETE WASHOUT AREA:

PERMANENT MEASURES.

- 1. THE FOLLOWING ARE THE ONLY NON-STORMWATER DISCHARGES ALLOWED. ALL OTHER
- NON-STORMWATER DISCHARGES ARE PROHIBITED ON SITE:

 A. THE CONCRETE DELIVERY TRUCKS SHALL, WHENEVER POSSIBLE, USE WASHOUT FACILITIES AT THEIR OWN PLANT OR DISPATCH FACILITY;
- B. IF IT IS NECESSARY, SITE CONTRACTOR SHALL DESIGNATE SPECIFIC WASHOUT AREAS AND DESIGN FACILITIES TO HANDLE ANTICIPATED WASHOUT WATER;
- C. CONTRACTOR SHALL LOCATE WASHOUT AREAS AT LEAST 150 FEET AWAY FROM STORM DRAINS, SWALES AND SURFACE WATERS OR DELINEATED WETLANDS;
 D. INSPECT WASHOUT FACILITIES DAILY TO DETECT LEAKS OR TEARS AND TO IDENTIFY WHEN

ALLOWABLE NON-STORMWATER DISCHARGES:

MATERIALS NEED TO BE REMOVED.

- 1. FIRE-FIGHTING ACTIVITIES;
- 2. FIRE HYDRANT FLUSHING;
- 3. WATER USED TO WASH VEHICLES WHERE DETERGENTS ARE NOT USED;
- 4. WATER USED TO CONTROL DUST;
- POTABLE WATER INCLUDING UNCONTAMINATED WATER LINE FLUSHING;
 ROUTINE EXTERNAL BUILDING WASH DOWN WHERE DETERGENTS ARE NOT USED;
- PAVEMENT WASH WATERS WHERE DETERGENTS ARE NOT USED;
 UNCONTAMINATED AIR CONDITIONING/COMPRESSOR CONDENSATION;
- UNCONTAMINATED GROUND WATER OR SPRING WATER;
 FOUNDATION OR FOOTING DRAINS WHICH ARE UNCONTAMINATED;
- 11. UNCONTAMINATED EXCAVATION DEWATERING;

12. LANDSCAPE IRRIGATION.

- WASTE MATERIAL:

 A. ALL WASTE MATERIALS SHALL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE SHALL BE DEPOSITED
- B. NO CONSTRUCTION WASTE MATERIALS SHALL BE BURIED ON SITE;C. ALL PERSONNEL SHALL BE INSTRUCTED REGARDING THE CORRECT PROCEDURE FOR WASTE
- DISPOSAL BY THE SUPERINTENDENT.

 2. HAZARDOUS WASTE:
- A. ALL HAZARDOUS WASTE MATERIALS SHALL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER;B. SITE PERSONNEL SHALL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTENDENT.
- A. ALL SANITARY WASTE SHALL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

SPILL PREVENTION:

- CONTRACTOR SHALL BE FAMILIAR WITH SPILL PREVENTION MEASURES REQUIRED BY LOCAL, STATE AND FEDERAL AGENCIES. AT A MINIMUM, CONTRACTOR SHALL FOLLOW THE BEST MANAGEMENT SPILL PREVENTION PRACTICES OUTLINED BELOW.
- 2. THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT SHALL BE USED TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING
- CONSTRUCTION TO STORMWATER RUNOFF:

 A. GOOD HOUSEKEEPING THE FOLLOWING GOOD HOUSEKEEPING PRACTICE SHALL BE
 - FOLLOWED ON SITE DURING CONSTRUCTION:

 a. ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB SHALL BE STORED ON SITE;
 - b. ALL REGULATED MATERIALS STORED ON SITE SHALL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR PROPER (ORIGINAL IF POSSIBLE) CONTAINERS AND, IF POSSIBLE,
 - UNDER A ROOF OR OTHER ENCLOSURE, ON AN IMPERVIOUS SURFACE;
 c. MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL SHALL BE FOLLOWED;
 - d. THE SITE SUPERINTENDENT SHALL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS;
 - e. SUBSTANCES SHALL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER;
 - f. WHENEVER POSSIBLE ALL OF A PRODUCT SHALL BE USED UP BEFORE DISPOSING OF THE
 - CONTAINER.
 g. THE TRAINING OF ON-SITE EMPLOYEES AND THE ON-SITE POSTING OF RELEASE
 RESPONSE INFORMATION DESCRIBING WHAT TO DO IN THE EVENT OF A SPILL OF
- B. HAZARDOUS PRODUCTS THE FOLLOWING PRACTICES SHALL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
- ASSOCIATED WITH HAZARDOUS MATERIALS:

 a. PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT
- b. ORIGINAL LABELS AND MATERIAL SAFETY DATA SHALL BE RETAINED FOR IMPORTANT PRODUCT INFORMATION;
- c. SURPLUS PRODUCT THAT MUST BE DISPOSED OF SHALL BE DISCARDED ACCORDING TO THE MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL.
- C. PRODUCT SPECIFIC PRACTICES THE FOLLOWING PRODUCT SPECIFIC PRACTICES SHALL BE FOLLOWED ON SITE:
- a. PETROLEUM PRODUCTS:
- i. ALL ON SITE VEHICLES SHALL BE MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO REDUCE LEAKAGE;
 ii. PETROLEUM PRODUCTS SHALL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE SHALL BE APPLIED
- ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.

 iii. SECURE FUEL STORAGE AREAS AGAINST UNAUTHORIZED ENTRY;
- iv. INSPECT FUEL STORAGE AREAS WEEKLY;

REGULATED SUBSTANCES.

- v. WHEREVER POSSIBLE, KEEP REGULATED CONTAINERS THAT ARE STORED OUTSIDE MORE THAN 50 FEET FROM SURFACE WATER AND STORM DRAINS, 75 FEET FROM PRIVATE
- WELLS, AND 400 FEET FROM PUBLIC WELLS; vi. COVER REGULATED CONTAINERS IN OUTSIDE STORAGE AREAS;
- vii. SECONDARY CONTAINMENT IS REQUIRED FOR CONTAINERS CONTAINING REGULATED SUBSTANCES STORED OUTSIDE, EXCEPT FOR ON PREMISE USE HEATING FUEL TANKS, OR ABOVEGROUND OR UNDERGROUND STORAGE TANKS OTHERWISE REGULATED.
- viii. THE FUEL HANDLING REQUIREMENTS SHALL INCLUDE:

 (1) EXCEPT WHEN IN USE, KEEP CONTAINERS CONTAINING REGULATED SUBSTANCES
 - CLOSED AND SEALED;
 - (2) PLACE DRIP PANS UNDER SPIGOTS, VALVES, AND PUMPS;(3) HAVE SPILL CONTROL AND CONTAINMENT EQUIPMENT READILY AVAILABLE IN
 - (4) USE FUNNELS AND DRIP PANS WHEN TRANSFERRING REGULATED SUBSTANCES;
 (5) PERFORM TRANSFERS OF REGULATED SUBSTANCES OVER AN IMPERVIOUS
- SURFACE.

 ix. FUELING AND MAINTENANCE OF EXCAVATION, EARTHMOVING AND OTHER
 CONSTRUCTION RELATED EQUIPMENT SHALL COMPLY WITH THE REGULATIONS OF THE
 NEW HAMPSHIRE DEPARTMENT OF ENVIRONMENTAL SERVICES THESE REQUIREMENTS
 ARE SUMMARIZED IN WD-DWGB-22-6 BEST MANAGEMENT PRACTICES FOR FUELING AND
 MAINTENANCE OF EXCAVATION AND EARTHMOVING EQUIPMENT, OR ITS SUCCESSOR
- DOCUMENT.
 HTTPS://www.des.nh.gov/organization/commissioner/pip/factsheets/dwgb/documents/dwgb-22-6.pdf
 b. FERTILIZERS:
- i. FERTILIZERS USED SHALL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS;
 ii. ONCE APPLIED FERTILIZER SHALL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO
- STORMWATER;
 ii. STORAGE SHALL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER SHALL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.
- c. PAINTS:i. ALL CONTAINERS SHALL BE TIGHTLY SEALED AND STORED WHEN NOT REQUIRED FOR
- ii. EXCESS PAINT SHALL NOT BE DISCHARGED TO THE STORM SEWER SYSTEM;iii. EXCESS PAINT SHALL BE DISPOSED OF PROPERLY ACCORDING TO MANUFACTURER'S INSTRUCTIONS OR STATE AND LOCAL REGULATIONS.
- D. SPILL CONTROL PRACTICES IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION, THE FOLLOWING PRACTICES SHALL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP:
 - a. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP SHALL BE CLEARLY POSTED AND SITE PERSONNEL SHALL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES;
 b. MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP SHALL BE KEPT IN THE
 - MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP SHALL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS SHALL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS, RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE;
- c. ALL SPILLS SHALL BE CLEANED UP IMMEDIATELY AFTER DISCOVERY;
- i. THE SPILL AREA SHALL BE KEPT WELL VENTILATED AND PERSONNEL SHALL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A
- HAZARDOUS SUBSTANCE;
 e. SPILLS OF TOXIC OR HAZARDOUS MATERIAL SHALL BE REPORTED TO THE APPROPRIATE LOCAL, STATE OR FEDERAL AGENCIES AS REQUIRED;
- f. THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS SHALL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.

 E. VEHICLE FUELING AND MAINTENANCE PRACTICE:
- a. CONTRACTOR SHALL MAKE AN EFFORT TO PERFORM EQUIPMENT/VEHICLE FUELING AND MAINTENANCE AT AN OFF-SITE FACILITY;
 b. CONTRACTOR SHALL PROVIDE AN ON-SITE FUELING AND MAINTENANCE AREA THAT IS
- CLEAN AND DRY;
- c. IF POSSIBLE THE CONTRACTOR SHALL KEEP AREA COVERED;d. CONTRACTOR SHALL KEEP A SPILL KIT AT THE FUELING AND MAINTENANCE AREA;
- e. CONTRACTOR SHALL REGULARLY INSPECT VEHICLES FOR LEAKS AND DAMAGE;
 f. CONTRACTOR SHALL USE DRIP PANS, DRIP CLOTHS, OR ABSORBENT PADS WHEN REPLACING SPENT FLUID.

EROSION CONTROL OBSERVATIONS AND MAINTENANCE PRACTICES

1. THIS PROJECT EXCEEDS ONE (1) ACRE OF DISTURBANCE AND THUS REQUIRES A SWPPP. THE SWPPP SHALL BE PREPARED BY THE CONTRACTOR. THE CONTRACTOR SHALL BE FAMILIAR WITH THE SWPPP AND KEEP AN UPDATED COPY OF THE SWPPP ONSITE AT ALL TIMES.

2. THE FOLLOWING REPRESENTS THE GENERAL OBSERVATION AND REPORTING PRACTICES THAT

- SHALL BE FOLLOWED AS PART OF THIS PROJECT:


 A. OBSERVATIONS OF THE PROJECT FOR COMPLIANCE WITH THE SWPPP SHALL BE MADE BY THE CONTRACTOR AT LEAST ONCE A WEEK OR WITHIN 24 HOURS OF A STORM 0.25 INCHES OR
- B. AN OBSERVATION REPORT SHALL BE MADE AFTER EACH OBSERVATION AND DISTRIBUTED TO THE ENGINEER, THE OWNER, AND THE CONTRACTOR;
 C. A REPRESENTATIVE OF THE SITE CONTRACTOR, SHALL BE RESPONSIBLE FOR MAINTENANCE
- AND REPAIR ACTIVITIES;
 D. IF A REPAIR IS NECESSARY, IT SHALL BE INITIATED WITHIN 24 HOURS OF REPORT.

FLOW— **−**FLOW ~PERFORATED RISER DIKE, IF **PLAN VIEW** IF USING PIPE NECESSARY, WEIR OR OUTLET TO DIVERT EMBANKMENT IF FLOW INTO USING STONE **TRAP** -EXCAVATION FOR **OUTLET OR PIPE** REQUIRED STORAGE OUTLET 3:1 MAX. SLOPE **SECTION VIEW** SIDE SLOPES TO BE STABILIZED

1. THE TRAP SHALL BE INSTALLED AS CLOSE TO THE DISTURBED AREA AS POSSIBLE.


- 2. THE MAXIMUM CONTRIBUTING AREA TO A SINGLE TRAP SHALL BE LESS THAN 5 ACRES.
- THE MINIMUM VOLUME OF THE TRAP SHALL BE 3,600 CUBIC FEET OF STORAGE FOR EACH ACRE OF DRAINAGE AREA.
 TRAP OUTLET SHALL BE MINIMUM OF ONE FOOT BELOW THE CREST OF THE
- 5. TRAP SHALL DISCHARGE TO A STABILIZED AREA.
- 6. TRAP SHALL BE CLEANED WHEN 50 PERCENT OF THE ORIGINAL VOLUME IS FILLED.
- MATERIALS REMOVED FROM THE TRAP SHALL BE PROPERLY DISPOSED OF AND STABILIZED.
 SEDIMENT TRAPS MUST BE USED AS NEEDED TO CONTAIN RUNOFF UNTIL SOILS ARE STABILIZED.

SEDIMENT TRAP



NOTES: 1. SILT SOCK SHALL BE SILT SOXX BY FILTREXX OR APPROVED EQUAL 2. INSTALL SILT SOCK IN ACCORDANCE WITH...

SILT SOCK NO SCALE



1. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OF SEDIMENT FROM THE SITE. WHEN WASHING IS REQUIRED, IT SHALL BE DONE SO RUNOFF DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING STORM DRAINS, DITCHES, OR WATERWAYS

STABILIZED CONSTRUCTION EXIT

NO SCALE

North End Mixed Use Development

| Two | Internationa | Group

Russell Street &

Portsmouth, NH

Deer Street

E D C B A

APPROVED: -EROSION CONTROL NOTES

AND DETAILS SHEET

January 4, 202

AS SHOWN

T5037-002-C-DTLS.DWG

SCALE:

MARK DATE DESCRIPTION


PROJECT NO


DATF:

C-501

Plotted On:Jan 04, 2022 Tighe & Bond: J:\T\T503


5037 Two Internation





- PAVEMENT MARKINGS TO BE INSTALLED IN LOCATIONS AS SHOWN ON SITE
- STRIPING SHALL BE CONSTRUCTED USING WHITE THERMO PLASTIC, REFLECTERIZED PAVEMENT MARKING MATERIAL MEETING THE REQUIREMENTS OF ASTM D 4505

STOP BAR AND LEGEND



0" TOLERANCE.

- 1. DETECTABLE WARNING SURFACE SHALL BE 2' X 3' CAST IRON PANEL SET IN
- 2. DETECTABLE WARNING SURFACE SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

CAST IRON DETECTABLE WARNING SURFACE NO SCALE

→ 5.0% MAX SLOPE IN

STRIPING SHALL BE CONSTRUCTED USING

WHITE THERMO PLASTIC, REFLECTERIZED


REQUIREMENTS OF ASTM D 4505

CROSSWALK STRIPING

NO SCALE

PAVEMENT MARKING MATERIAL MEETING THE

TRAVEL DIRECTION



NHDOT ITEM No. 304.2 NHDOT ITEM No. 304.3 (GRAVEL) (CRUSHED GRAVEL) SIEVE SIZE % PASSING SIEVE SIZE % PASSING 25-70 95-100 55-85 #200 0-12 27-52 HOT BITUMINOUS CONCRETE-#200 0-12 NHDOT SECTION 401 3" NOMINAL NHDOT SECTION 401 4" NOMINAL 1" OF 3/8" SUPERPAVE WEARING COURSE 1-1/2" OF 3/8" SUPERPAVE WEARING COURSE 2" OF 3/4" SUPERPAVE BASE COURSE 2-1/2" OF 3/4" SUPERPAVE BASE COURSE 4" CRUSHED-12" CRUSHED-**GRAVEL BASE GRAVEL BASE** (NHDOT ITEM (NHDOT ITEM No. 304.3) No. 304.3) 8" GRAVEL-12" GRAVEL GRANULAR FILL SUBBASE SUBBASE (NHDOT ITEM (NHDOT ITEM No. 304.2) No. 304.2) ĆOMPÁČTĘĎ SUBGRÁDE NOTES: 1. SEE SITE PLAN FOR PAVEMENT WIDTH AND LOCATION. 2. SEE GRADING, DRAINAGE AND EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.

1" (1:3) PORTLAND—

COURSE ALONG

BACK OF CURB

— 2' SAWCUT → 1

6" REVEAL

VERTICAL

BRICK SIDEWALK SHALL BE INSTALLED AS DETAILED AND PER CITY OF PORTSMOUTH REQUIREMENTS/SPECIFICATIONS AND SHALL

2. CITY STANDARD BRICK SHALL BE TRADITIONAL EDGE, PATHWAY, FULL RANGE 2.25"X4"X8" PAVER, BY PINE HALL BRICK, INC. BRICK

CONCRETE WASHOUT AREA NO SCALE

INCLUDE A CONTINUOUS APPROVED PAVER EDGE RESTRAINT SYSTEM AT ALL LOCATIONS NOT ADJACENT TO CURB OR BUILDINGS.

GRANITE CURB

(SEE DETAIL)

FINAL WEARING-

COURSE PAVEMENT

SAND MIX BED

CEMENT / COURSE

SINGLE ROW HEADER-

- 1. SEE SITE PLAN FOR PAVEMENT WIDTH AND LOCATION.
- 2. SEE GRADING, DRAINAGE AND EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.

NHDOT ITEM No. 304.2

(GRAVEL)

SIEVE SIZE % PASSING

#200

HOT BITUMINOUS CONCRETE—

25-70

GRANULAR FILL

ĆOMPÁČTĘĎ SUBGRÁDE

NHDOT ITEM No. 304.3

(CRUSHED GRAVEL)

#200

% PASSING

95-100


55-85

27-52

- 3. A TACK COAT SHALL BE PLACED ON TOP OF BINDER COURSE PAVEMENT
- PRIOR TO PLACING WEARING COURSE. 4. REFER TO CITY SPECIFICATIONS FOR ASPHALT MIX DESIGN.

CITY RIGHT-OF-WAY PAVEMENT SECTION

NO SCALE



- 1. SEE SITE PLAN(S) FOR LIMITS OF VERTICAL GRANITE CURB (VGC).
- 2. ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.
- 3. MINIMUM LENGTH OF STRAIGHT CURB STONES = 3'

CURB TIP-DOWN-

5" THICK -


CONCRETE

- 4. MAXIMUM LENGTH OF STRAIGHT CURB STONES = 10' 5. MAXIMUM LENGTH OF STRAIGHT CURB STONES LAID ON CURVES (SEE TABLE).
- 6. ALL RADII 20 FEET AND SMALLER SHALL BE CONSTRUCTED USING CURVED SECTIONS.


NO SCALE

7. JOINTS BETWEEN STONES SHALL HAVE A MAXIMUM SPACING OF 1/2" AND SHALL BE MORTARED.

VERTICAL GRANITE CURB



-RAMP TIP DOWN MAXIMUM SLOPE 1:12 6' CURB--BACK OF TIP-DOWN SIDEWALK STDEWALK SLOPE -11:20 (MAX.) MATCH PAVEMENT FINISH GRADE. 0" TOLERANCE. CURB TYPE AS 6' CURB SPECIFIED ON TIP-DOWN **CAST IRON RADIUS** DRAWINGS TYPE DETECTABLE -6" (MAX.) REVEAL WARNING SURFACE <u>PLAN A</u> (SEE DETAIL)



6' TIP DOWN → 5'-0" MIN. → 6' TIP DOWN →

SECTION B-B

12:1 MAX.

- NOTES:
 1. RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICANS WITH DISABILITIES ACT AND LOCAL AND STATE REQUIREMENTS.
- 2. A 6" COMPACTED CRUSHED GRAVEL BASE (NHDOT ITEM No. 304.3) SHALL BE PROVIDED BENEATH RAMPS.
- 3. DETECTABLE WARNING PANEL SHALL BE CAST IRON SET IN CONCRETE (SEE DETAIL.)
- 4. PROVIDE DETECTABLE WARNING SURFACES ANYTIME THAT A CURB RAMP, BLENDED TRANSITION, OR LANDING CONNECTS TO A
- 5. LOCATE THE DETECTABLE WARNING SURFACES AT THE BACK OF THE CURB ALONG THE EDGE OF THE LANDING.
- 6. THE MAXIMUM RUNNING SLOPE OF ANY SIDEWALK CURB RAMP IS 12:1, THE MAXIMUM CROSS SLOPE IS 2%. THE SLOPE OF THE LANDING SHALL NOT EXCEED 2% IN ANY DIRECTION.
- 7. TRANSITIONS SHALL BE FLUSH AND FREE OF ABRUPT CHANGES. ROADWAY SHOULDER SLOPES ADJOINING SIDEWALK CURB RAMPS
- SHALL BE A MAXIMUM OF 5% (FULL WIDTH) FOR A DISTANCE OF 2 FT. FROM THE ROADWAY CURBLINE. 8. THE BOTTOM OF THE SIDEWALK CURB RAMP OR LANDING, EXCLUSIVE OF THE FLARED SIDES, SHALL BE WHOLLY CONTAINED
- WITHIN THE CROSSWALK MARKINGS. 9. DETECTABLE WARNING PANELS SHALL BE A MINIMUM OF 2 FEET IN DEPTH. THE ROWS OF TRUNCATED DOMES SHALL BE ALIGNED
- PERPENDICULAR TO THE GRADE BREAK BETWEEN THE RAMP, BLENDED TRANSITION, OR LANDING AND THE STREET. 10. THE TEXTURE OF THE DETECTABLE WARNING FEATURE MUST CONTRAST VISUALLY WITH THE SURROUNDING SURFACES (EITHER LIGHT-ON-DARK OR DARK-ON-LIGHT).

CONCRETE WHEELCHAIR ACCESSIBLE RAMP

NO SCALE

North End Mixed Use Development

CURB REVEAL

-CURB TIP-DOWN

" REVEAL

SIDEWALK FLUSH

6" COMPACTED CRUSHED GRAVEL,

OR OTHER APPROVED MATERIAL

AT SPECIFIED DEPTH

WITH PAVEMENT

Two International Group

Russell Street & Deer Street Portsmouth, NH

E			
D			
С			
В			
Α			
1ARK	DATE	DESCRIPTION	
PROJECT NO:			T5037-002

DATF: January 4, 202 T5037-002-C-DTLS.DWG DRAWN BY: CHECKED: APPROVED:

DETAILS SHEET

SCALE: AS SHOWN

C-502

WHITE BACKGROUND 1. CONTAINMENT MUST BE STRUCTURALLY SIGN SHALL BE PLACED IN

CONTAINMENT

SEASONAL HIGH

GROUNDWATER TABLE

TYPICAL SECTION

3. A TACK COAT SHALL BE PLACED ON TOP OF BINDER COURSE PAVEMENT

ON-SITE PAVEMENT SECTION

NO SCALE

4. REFER TO CITY SPECIFICATIONS FOR ASPHALT MIX DESIGN.

-CITY STANDARD BRICK

(SEE NOTE #2)

-SINGLE ROW

STRETCHER

COURSE

BUILDING

VERTICAL GRANITE CURB

-SINGLE ROW HEADER

COURSE ALONG BACK

PAVEMENT

OF CURB

SIDEWALK PLAN VIEW

VARIES

}}

—6" MIN DEPTH

AROUND

AGGREGATE ALL

PRIOR TO PLACING WEARING COURSE.

SOUND AND LEAK FREE AND CONTAIN ALL LIQUID WASTES.


2. CONTAINMENT DEVICES MUST BE OF SUFFICIENT QUANTITY OR VOLUME TO COMPLETELY CONTAIN THE LIQUID WASTES GENERATED.

3. WASHOUT MUST BE CLEANED OR NEW FACILITIES CONSTRUCTED AND READY TO

USE ONCE WASHOUT IS 75% FULL. 4. WASHOUT AREA(S) SHALL BE INSTALLED IN A LOCATION EASILY ACCESSIBLE BY CONCRETE TRUCKS.

5. ONE OR MORE AREAS MAY BE INSTALLED ON THE CONSTRUCTION SITE AND MAY BE RELOCATED AS CONSTRUCTION

PROGRESSES. 6. AT LEAST WEEKLY REMOVE ACCUMULATION OF SAND AND AGGREGATE AND DISPOSE OF PROPERLY.



-POLYETHYLENE

LINER (SEE

DETAIL)

TOP OF GRATE

20" O.D.

|-----

RISER

._____

─3/4" CRUSHED STONE


BEDDING

SECTION A-A

SEE DETAIL A-

BASE

POLYETHYLENE




1. ALL PAINT SHALL BE FAST DRYING TRAFFIC PAINT, MEETING THE REOUIREMENTS OF AASHTO M248-TYPE F. PAINT SHALL BE APPLIED AS SPECIFIED BY MANUFACTURER.

REQUIREMENTS OF THE AMERICAN W/DISABILITIES ACT.

ACCESSIBLE PARKING STALL

NO SCALE


2. SYMBOLS & PARKING STALLS SHALL CONFORM TO THE



1. SYMBOL SHALL BE CONSTRUCTED IN ALL ACCESSIBLE SPACES USING WHITE THERMOPLASTIC, REFLECTORIZED PAVEMENT PARKING

MATERAL MEETING THE REQUIREMENTS OF ASTM D 4505. 2. SYMBOL SHALL BE CONSTRUCTED TO THE LATEST ADA, STATE AND LOCAL REQUIREMENTS.

> **ACCESSIBLE SYMBOL** NO SCALE



Tighe&Bond



MATCH EXISTING PAVEMENT—

EXCAVATED TRENCH-(SEE TRENCH SECTION)

EXISTING PAVEMENT

TYPE AND THICKNESS

(6" MINIMUM)

MINIMUM

(TYP.)

1. ALL CATCH BASIN OUTLETS TO HAVE "ELIMINATOR" OIL AND FLOATING DEBRIS TRAP MANUFACTURED BY KLEANSTREAM (NO EQUAL)

TOP OF DEBRIS TRAP

-MATCH EXISTING BASE

COURSES MIN. 6" CRUSHED

GRAVEL BASE & 12" GRAVEL

EXISTING PAVEMENT

EXISTING BASE COURSE

-LIMIT OF

TRENCH

EXCAVATED

-LEAVE EXISTING

BASE COURSE

UNDISTURBED

PAVEMENT SAW

-CUT WITH

(UNDISTURBED)

-SAW CUT EDGE, CLEAN AND

IMMEDIATELY PRIOR TO

COAT WITH RS-1 EMULSION

CONSTRUCTING NEW PAVEMENT.

2. INSTALL DEBRIS TRAP TIGHT TO INSIDE OF STRUCTURE. 3. 1/4" HOLE SHALL BE DRILLED IN

NO SCALE

"ELIMINATOR" OIL **FLOATING DEBRIS TRAP**



Two International Group

Russell Street & Deer Street Portsmouth, NH

Е			
D			
С			
В			
Α			
MARK	DATE	DESCRIPTION	
PROJE	CT NO:		T5037-002

DATF: January 4, 202 T5037-002-C-DTLS.DWG DRAWN BY:

CHECKED: APPROVED:

DETAILS SHEET

SCALE: AS SHOWN

C-503

ROADWAY TRENCH PATCH NO SCALE

MINIMUM


(TYP.)

<u>PLAN</u>

DPW PRIOR TO COMMENCING WORK.

COORDINATE AND OBTAIN APPROVAL FOR ALL TRENCHING AND

PATCHING WITHIN CITY RIGHT OF WAY WITH CITY OF PORTSMOUTH



- AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
- THE TONGUE AND THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL
- CONSTRUCT CRUSHED STONE BEDDING AND BACKFILL UNDER (6" MINIMUM THICKNESS)
- PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING.
- THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS. 10. ALL STRUCTURES WITH MULTIPLE PIPES SHALL HAVE A MINIMUM OF 12" OF INSIDE SURFACE BETWEEN
- NO HOLES CLOSER THAN 3" TO JOINTS.

4' DIAMETER CATCHBASIN

-MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A (MINIMUM HEIGHT) WORD "DRAIN" SHALL GRADE RINGS OR CLAY BRICKS, FRAME

- PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN
- HOLES, NO MORE THAN 75% OF A HORIZNTAL CROSS SECTION SHALL BE HOLES, AND THERE SHALL BE

4' DIAMETER DRAIN MANHOLE

NO SCALE

(TONGUE AND GROOVE JOINT) ALL SECTIONS SHALL BE CONCRETE CLASS AA(4000 psi) CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQ.IN. PER LINEAR FT. IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL. THE TONGUE AND GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQ. IN. PER LINEAR FT. RISERS OF 1', 2', 3' & 4' CAN BE USED TO REACH DESIRED DEPTH. THE STRUCTURES SHALL BE DESIGNED FOR H20 LOADING. FITTING FRAME TO GRADE MAY BE DONE WITH PREFABRICATED ADJUSTMENT RINGS OR CLAY BRICKS (2 COURSES MAX.). CONE SECTIONS MAY BE EITHER CONCENTRIC OR ECCENTRIC, OR FLAT SLAB TOPS MAY BE USED WHERE PIPE WOULD OTHERWISE ENTER INTO THE CONE SECTION OF THE STRUCTURE AND WHERE PERMITTED. PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING OUTSIDE EDGES OF PIPES SHALL PROJECT NO MORE THAN 3" BEYOND INSIDE WALL OF STRUCTURE 10. PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS. 11. THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT. 12. "ELIMINATOR" OIL/WATER SEPARATOR SHALL BE INSTALLED TIGHT TO INSIDE OF CATCHBASIN. NO SCALE

SECTION B-B

FLAT SLAB TOP

<u>PLAN</u>

2 1/8" —

SEE NOTE

NO. 6

SEE NOTE-

KOR-N-SEAL

BOOT

HOLE CAST—

TO PLAN

ALL OUTLETS


"ELIMINATOR"


OIL/WATER


SEPARATOR

(OR EQUAL)

TO HAVE







3. PLACE CLASS AA CONCRETE TO 2" BELOW THE TOP OF THE GRATE ELEVATION (SUBSIDIARY TO DRAINAGE

BEFORE PLACING CONCRETE (EXCEPT AS SHOWN WHEN USED WITH 3-FLANGE FRAME AND CURB).

8. SEE NHDOT DR-04, "DI-DB, UNDERDRAIN FLUSHING BASIN AND POLYETHYLENE LINER DETAILS", FOR

9. CATCHBASINS WITHIN CITY RIGHT OF WAY SHALL HAVE A POLYETHYLENE LINER

TRIM POLYETHYLENE SHEET A MAXIMUM OF 4" OUTSIDE THE FLANGE ON THE FRAME FOR THE CATCH BASIN

6. THE CENTER OF THE GRATE & FRAME MAY BE SHIFTED A MAXIMUM OF 6" FROM THE CENTER OF THE DOWNSPOUT

POLYETHYLENE LINER

NO SCALE

FRAME AND POLYETHYLENE SHEET.


4. USE ON DRAINAGE STRUCTURES 4' MIN. DIAMETER ONLY.

7. PLACED ONLY IN DRAINAGE STRUCTURES IN PAVEMENT.

STRUCTURE).

IN ANY DIRECTION.


ADDITIONAL INFORMATION.




SLIP RESISTANT SURFACE 1-1/2" FLAT FACE GOTHIC FLUSH (4) BOLT SLOTS 1" - WIDE ON 36" TO 30 STAINLESS STEEL CAM LOCK MPIC® MULTI-TOOL **PICKBAR** - T-GASKET -Ø33-3/4"-**SECTION A-A**

- 1. MANHOLE FRAME AND COVER SHALL BE 32" HINGED ERGO XL
- 2. ALL DIMENSIONS ARE NOMINAL.
- 3. FRAMES USING NARROWER DIMENSIONS FOR THICKNESS ARE ALLOWED PROVIDED:
- A. THE FRAMES MEET OR EXCEED THE SPECIFIED LOAD RATING. B. THE INTERIOR PERIMETER (SEAT AREA) DIMENSIONS OF THE
- FRAMES REMAIN THE SAME TO ALLOW CONTINUED USE OF EXISTING GRATES/COVERS AS THE EXISTING FRAMES ALLOW, WITHOUT SHIMS OR OTHER MODIFICATIONS OR ACCOMMODATIONS.
- C. ALL OTHER PERTINENT REQUIREMENTS OF THE SPECIFICATIONS ARE MET.
- 4. LABEL TYPE OF MANHOLE WITH 3" HIGH LETTERS IN HE CENTER

DRAIN MANHOLE FRAME & COVER



STORM DRAIN TRENCH NO SCALE




NOTES:
1. DIMENSIONS SHOWN REPRESENT TYPICAL REQUIREMENTS. MANHOLE LOCATIONS AND REQUIREMENTS SHALL BE COORDINATED WITH EVERSOURCE PRIOR TO CONSTRUCTION 2. CONCRETE MINIMUM STRENGTH - 4,000

PSI @ 28 DAYS 3. STEEL REINFORCEMENT - ASTM A615, GRADE 60

4. PAD MEETS OR EXCEEDS EVERSOURCE SPECIFICATIONS

3-PHASE TRANSFORMER PAD NO SCALE

HYDRANT— NOTE: 1. HYDRANT TO BE KENNEDY TYPE K-81, RIGHT OPEN (NO EQUAL). COORDINATE -VALVE BOX -THRUST BLOCK WITH CITY OF PORTSMOUTH WATER 15" (SEE DETAIL) DEPARTMENT AND CITY OF PORTSMOUTH FIRE DEPARTMENT. 2. PAINT HYDRANT IN ACCORDANCE WITH CITY STANDARD SPECIFICATIONS AFTER INSTALLATION AND TESTING. WATER MAIN 12" CRUSHED STONE 6" MIN. -THRUST BLOCK (SEE DETAIL) 6" MJ GATE VALVE-CRUSHED STONE--HYDRANT DRAIN 15"x15"x4" CONCRETE BASE-TO BE PLUGGED -DRAIN PIT - 3' DIA. x 2' FIRE HYDRANT BELOW HYDRANT NO SCALE




1. REFER TO ELECTRICAL PLANS FOR WIRING DETAILS.

- CONCRETE: 4000 PSI, AIR ENTRAINED STEEL: 60 KSI
- 3. LIGHT POLE FOUNDATIONS SHALL BE PLACED PRIOR TO INSTALLATION OF BRICK PAVERS.
- 4. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL, TO INCLUDE PERFORMANCE SPECIFICATIONS,
- CALCULATIONS AND NH LICENSED STRUCTURAL ENGINEER'S STAMP FOR LIGHT POLE FOUNDATION. STANDARD BASE SHALL BE CONSTRUCTED UNLESS THERE IS CONFLICT WITH THE EXISTING DUCT BANK.
- SPREAD FOOTING BASE SHALL BE USED IN LIEU OF STANDARD BASE IN LOCATIONS WHERE TOP OF DUCT BANK ELEVATION WILL CONFLICT WITH STANDARD POLE BASE DEPTH. CONTRACTOR SHALL VERIFY LOCATIONS WHERE SPREAD FOOTINGS ARE REQUIRED PRIOR TO CONSTRUCTION. SEE NOTE#4 FOR SUBMITTAL REQUIREMENTS.

HISTORIC LIGHT FIXTURE BASE

NO SCALE




North End Mixed Use Development

Tighe&Bond

Two International Group


Russell Street & Deer Street Portsmouth, NH





DETAILS SHEET


SCALE: AS SHOWN


C-504











THRUST BLOCKING DETAIL

NO SCALE

-INSIDE FACE

OF MANHOLE

PIPE

PIPE TO MANHOLE JOINTS

NOTES:

W/MORTAR

—ANODIZED ALUMINUM

-KOR-N-SEAL BOOT

LEAST 75% OF THE JOINT CAVITY.

MANUFACTURERS' WRITTEN INSTRUCTIONS.

KOR-N-SEAL JOINT

SLEEVE OR EQUAL

-STAINLESS

STEEL CLAMP

ASPHALT IMPREGNATED-

USING A DOUBLE ROW ELASTOMERIC OR MASTIC-LIKE GASKET.

2. PIPE TO MANHOLE JOINTS SHALL BE PER CITY OF PORTSMOUTH STANDARD.

POLYURETHANE

POLYTITE

(OR EQUAL)

1. HORIZONTAL JOINTS BETWEEN THE SECTIONS OF PRECAST CONCRETE BARRELS SHALL BE

3. FOR BITUMASTIC TYPE JOINTS THE AMOUNT OF SEALANT SHALL BE SUFFICIENT TO FILL AT

4. ALL GASKETS, SEALANTS, MORTAR, ETC. SHALL BE INSTALLED IN ACCORDANCE WITH

MANHOLE JOINTS

NO SCALE

PER CITY OF PORTSMOUTH DPW STANDARD AND SHALL BE SEALED FOR WATERTIGHTNESS

GASKET 1-/2" x 2"

INTERNAL CLAMP

WATER MAIN, SIZE VARIES			UNDISTURBED MATERIAL						
(TYP.)		20	REACTION	PIPE SIZE					
7 ~ //>//		= - -	TYPE	4"	6"	8"	10"	12"	
		SUF	A 90°	0.89	2.19	3.82	11.14	17.24	
		PRESSURE	B 180°	0.65	1.55	2.78	8.38	12.00	
			C 45°	0.48	1.19	2.12	6.02	9.32	
		TEST	D 22-1/2°	0.25	0.60	1.06	3.08	4.74	
			E 11-1/4°	0.13	0.30	0.54	1.54	2.38	
	NOT NOT								
CONCRETE—/	~ 1.0	POL	JR THRUST BL	OCKS AGA	JINST UND	ISTURBEC) MATERTA	J. WHFRF	

TRENCH WALL HAS BEEN DISTURBED, EXCAVATE LOOSE MATERIAL AND EXTEND THRUST BLOCK TO UNDISTURBED MATERIAL. NO JOINTS SHALL BE COVERED WITH CONCRETE.

SQUARE FEET OF CONCRETE THRUST BLOCKING BEARING ON

- 2. ON BENDS AND TEES, EXTEND THRUST BLOCKS FULL LENGTH OF 5 3. PLACE BOARD IN FRONT OF ALL PLUGS BEFORE POURING THRUST
- BLOCKS. 4. WHERE M.J. PIPE IS USED, M.J. PLUG WITH RETAINER GLAND MAY BE
- SUBSTITUTED FOR END BLOCKINGS. 5. INSTALLATION AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE WITH CITY OF PORTSMOUTH WATER DEPARTMENT STANDARDS.

NOTE 3)

BITUMASTIC

HORIZONTAL JOINTS

—APPROVED PREFORMED

O-RING

BITUMASTIC SEALANT (SEE

-RUBBER-LIKE

O-RING SET

IN RECESS


RUBBER-LIKE

ROLL-N-LOK

(OR EQUAL)

GASKET ROLLS

OUT OF RECESS




1. STEEL REINFORCEMENT SHALL CONFORM

-ADJUST TO GRADE WITH NOT MORE

LOAM PAVED AREA | AREA -SEE TYPICAL CROSS SECTIONS (SHEET R-4) 6" COMPACTED— LOAM AND SEED >PAVEMENT CROSS -SUBBASE / COMPACTED-SECTIONS GRANULAR FILL 3" (MIN.) —2 - 1-1/2" STREET LIGHTING CONDUIT -2 - 3" CABLE CONDUITS **BURIED CABLE** SAFETY RIBBON 9 - 5" ELECTRICAL 2" (MIN.) CONDUITS —2 - 3" TELEPHONE CONDUITS UNDISTURBED SOIL-2" MIN. 8" MIN.\ 3" MIN. -SAND BEDDING (SEE NOTE 8)

- NUMBER, MATERIAL, AND SIZE OF UTILITY CONDUITS TO BE DETERMINED BY LOCAL UTILITY OR AS SHOWN ON ELECTRICAL DRAWINGS. CONTRACTOR TO PROVIDE ONE SPARE CONDUIT FOR EACH UTILITY TO BUILDING.
- DIMENSIONS SHOWN REPRESENT OWNERS MINIMUM REQUIREMENTS. ACTUAL DIMENSIONS MAY BE GREATER BASED ON UTILITY COMPANY STANDARDS, BUT SHALL NOT BE LESS THAN THOSE SHOWN.
- NO CONDUIT RUN SHALL EXCEED 360 DEGREES IN TOTAL BENDS. A SUITABLE PULLING STRING, CAPABLE OF 200 POUNDS OF PULL, MUST BE INSTALLED IN THE CONDUIT BEFORE UTILITY COMPANY IS NOTIFIED TO INSTALL CABLE. THE STRING SHOULD BE BLOWN INTO THE
- CONDUIT AFTER THE RUN IS ASSEMBLED TO AVOID BONDING THE STRING TO THE CONDUIT. UTILITY COMPANY MUST BE GIVEN THE OPPORTUNITY TO INSPECT THE CONDUIT PRIOR TO BACKFILL. THE CONTRACTOR IS RESPONSIBLE FOR ALL REPAIRS SHOULD THE UTILITY COMPANY BE UNABLE TO
- INSTALL ITS CABLE IN A SUITABLE MANNER. ALL CONDUIT INSTALLATIONS MUST CONFORM TO THE CURRENT EDITION OF THE NATIONAL ELECTRIC SAFETY CODE, STATE AND LOCAL CODES AND ORDINANCES, AND, WHERE APPLICABLE, THE NATIONAL
- ALL 90° SWEEPS WILL BE MADE USING RIGID GALVANIZED STEEL. SWEEPS WITH A 36 TO 48 INCH
- SAND BEDDING TO BE REPLACED WITH CONCRETE ENCASEMENT WHERE COVER IS LESS THAN 3 FEET, WHEN LOCATED BELOW PAVEMENT, OR WHERE SHOWN ON THE UTILITIES PLAN.

ELECTRICAL AND COMMUNICATION CONDUIT NO SCALE



Deer Street Portsmouth, NH

MARK DATE DESCRIPTION PROJECT NO: DATE: January 4, 2022 T5037-002-C-DTLS.DWG DRAWN BY: CHECKED: APPROVED:

North End

Mixed Use

International

Russell Street &

Two

Group

Development

DETAILS SHEET

SCALE: AS SHOWN C-505

1. INVERT AND SHELF TO BE PLACED AFTER EACH LEAKAGE TEST.

2. CARE SHALL BE TAKEN TO INSURE THAT THE BRICK INVERT IS A SMOOTH CONTINUATION OF THE SEWER INVERT.

3. INVERT BRICKS SHALL BE LAID ON EDGE.

4. TWO (2) COATS OF BITUMINOUS WATERPROOF COATING SHALL BE APPLIED TO ENTIRE EXTERIOR OF MANHOLE.


5. FRAMES AND COVERS: MANHOLE FRAMES AND COVERS WITHIN CITY RIGHT OF WAY SHALL BE CITY STANDARD HINGE COVERS MANUFACTURED BY EJ. FRAMES AND COVERS WILL BE PURCHASED FROM THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS. ALL OTHER MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A 30-INCH CLEAR OPENING. A 3-INCH (MINIMUM HEIGHT) WORD "SEWER" SHALL BE PLAINLY CAST INTO THE CENTER OF EACH COVER.


TYPICAL SECTION


6. HORIZONTAL JOINTS SHALL BE SEALED FOR WATER TIGHTNESS USING A DOUBLE ROW OF ELASTOMERIC OR MASTIC-LIKE SEALANT. 7. BARREL AND CONE SECTIONS SHALL BE PRECAST REINFORCED CONCRETE DESIGNED FOR H20 LOADING, AND CONFORMING TO ASTM C478-06.

SEWER MANHOLE

NO SCALE








NORTH END MIXED USE DEVELOPMENT RUSSELL STREET & DEER STREET PORTSMOUTH, NEW HAMPSHIRE


FIRE TRUCK TURNING EXHIBIT



Portsmouth Fire Truck Overall Length Overall Width Overall Body Height Min Body Ground Clearance Track Width Lock-to-lock time Max Steering Angle (Virtual)


47.830ft 8.500ft 10.432ft 0.862ft 8.000ft 6.00s 38.00°

VEHICLE WHEEL BASE VEHICLE OVERHANG VEHICLE WHEEL BASE (REVERSE) VEHICLE OVERHANG (REVERSE)




January 4, 2022 T5037-002-C-DSGN.dwg

SITE PLAN




GROUND FLOOR PLAN



PRECEDENT IMAGES - FACADE















PRECEDENT IMAGES - LOCAL PORTSMOUTH
















PRECEDENT IMAGES - COMMUNITY SPACE





