GENERAL INFORMATION

OWNER

MAP 162 LOT 16 RANDI & JEFF COLLINS 77 MEREDITH WAY PORTSMOUTH, NH 03801

APPLICANT

774-278-8676

RANDI & JEFF COLLINS 77 MEREDITH WAY PORTSMOUTH, NH 03801 774-278-8676

RESOURCE LIST

PLANNING/ZONING DEPARTMENT
1 JUNKINS AVENUE
PORTSMOUTH, NH 03801
603-610-7216
NICK CRACKNELL, PRINCIPAL PLANNER
PUBLIC WORKS

600 PEVERLY HILL ROAD
PORTSMOUTH, STATE 03801
603-472-1530
DAVE DEFOSSES, CONSTRUCTION TECHNICAL
SUPERVISOR

POLICE DEPARTMENT
3 JUNKINS AVENUE
PORTSMOUTH, NH 03801
603-427-1510

FIRE DEPARTMENT
170 COURT STREET
PORTSMOUTH, NH 03801
603-427-1515


ASSOCIATED PROFESSIONALS

ATTORNEY
BOSEN & ASSOCIATES
266 MIDDLE STREET
PORTSMOUTH, NH 03801
603-427-5500
CHRISTOPHER P. MULLIGAN, ESQUIRE

PROPOSED 2 LOT SUBDIVISION

77 MEREDITH WAY
PORTSMOUTH, NEW HAMPSHIRE

JULY 1, 2022 LAST REVISED JULY 21, 2022



PROGRESS
PRINT
date: 07/21/2022

1	7/21/2022	REVISED PER TAC COMMENTS JK	C JCC
REV	DA TE	DESCRIPTION DF	? CK

INDEX OF SHEETS

	MDEX OF SHEETS
SHEET	SHEET TITLE
C-00	COVER
C-01	NOTES & LEGEND
S-01	EXISTING CONDITIONS PLAN
S-02	SUBDIVISION PLAN
C-02	SITE PREPARATION & DEMOLITION PLAN
C-03	SITE LAYOUT PLAN
C-04	GRADING & DRAINAGE PLAN
C-05	UTILITY PLAN
C-06	ROAD PLAN AND PROFILE
C-07	DETAILS

PERMITS/APPROVALS

	-		
	NUMBER	APPROVED	EXPIRES
CITY PLANNING BOARD SUBDIVISION APPROVAL	-	_	_
CITY ZONING BOARD VARIANCE REQUEST (ARTICLE 5 — SECTION 10.521)	LU-22-61	2022/06/22	2024/06/22

VARIANCE GRANTED

ON JUNE 22, 2022 THE CITY OF PORTSMOUTH ZONING BOARD OF ADJUSTMENT GRANTED RELIEF FROM THE FOLLOWING SECTION OF THE CITY OF PORTSMOUTH ZONING ORDINANCE:

ARTICLE 5 SECTION 10.521 — MINIMUM CONTINUOUS LOT FRONTAGE:

TO ALLOW THE CONTINUOUS STREET FRONTAGE TO BE 73.99' FOR PROPOSED LOT A & 31.61' FOR PROPOSED LOT B, WHERE 100' IS REQUIRED AND 31.7' EXISTS.

OWNER'S SIGNATURE

THE PROPERTY WILL BE DEVELOPED IN ACCORDANCE WITH THIS PLAN AND THE ORDINANCES OF THE CITY OF PORTSMOUTH, NEW HAMPSHIRE.

OWNER OR AUTHORIZED AGENT DATE

SITE DEVELOPMENT PLANS

TAX MAP 162 LOT 16

COVER

PROPOSED 2 LOT SUBDIVISION 77 MEREDITH WAY

OWNED BY

RANDI & JEFF COLLINS
PREPARED FOR

RANDI & JEFF COLLINS

SCALE: AS SHOWN

JULY 1, 2022



Structural Engineers
Traffic Engineers
Land Surveyors
Landscape Architects
Scientists

Phone (603) 431-2222 Fax (603) 431-0910 www.tfmoran.com

Portsmouth, NH 03801

| 170 Commerce Way, Suite 102


Copyright 2022 ©TFMoran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of TFMoran, Inc.

This plan is not effective unless signed by a duly authorized officer of



THESE PLANS ARE PERMIT DRAWINGS ONLY AND HAVE NOT BEEN DETAILED FOR CONSTRUCTION OR BIDDING.



GENERAL NOTES

- 1. THESE PLANS ARE PERMIT DRAWINGS ONLY AND HAVE NOT BEEN DETAILED FOR CONSTRUCTION OR BIDDING.
- 2. THESE PLANS WERE PREPARED UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER. TFMORAN, INC. ASSUMES NO LIABILITY AS A RESULT OF ANY CHANGES OR NON-CONFORMANCE WITH THESE PLANS EXCEPT UPON THE WRITTEN APPROVAL OF THE
- 3. THE SITE LAYOUT PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF
- 4. ALL IMPROVEMENTS SHOWN ON THE SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE CITY PLANNING BOARD.
- 5. ALL WORK SHALL CONFORM TO THE APPLICABLE REGULATIONS AND STANDARDS OF THE CITY OF PORTSMOUTH, AND SHALL BE BUILT IN A WORKMANLIKE MANNER IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS, ALL WORK TO CONFORM TO CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS STANDARD SPECIFICATIONS. ALL WORK WITHIN THE RIGHT-OF-WAY OF THE CITY AND/OR STATE SHALL COMPLY WITH APPLICABLE STANDARDS. COORDINATE ALL WORK WITHIN THE RIGHT-OF-WAY WITH APPROPRIATE CITY, COUNTY, AND/OR STATE AGENCY.
- 6. THE SITE CONTRACTOR SHALL ENSURE THAT ALL WORK IS PERFORMED IN ACCORDANCE WITH APPLICABLE SECTIONS OF ENV-WQ 1500. THE SITE CONTRACTOR SHALL NOTIFY THE ENGINEER IN ADVANCE OF CONSTRUCTION OF EACH STORMWATER FACILITY TO COORDINATE REQUIRED INSPECTIONS. THE CONTRACTOR SHALL TAKE PROGRESS PHOTOS DURING CONSTRUCTION OF ALL STORMWATER DRAINAGE COMPONENTS AND SEND TO THE ENGINEER.
- 7. SEE EXISTING CONDITIONS PLAN FOR THE HORIZONTAL AND VERTICAL DATUM.
- 8. SEE EXISTING CONDITIONS PLAN FOR BENCHMARK INFORMATION. VERIFY TBM ELEVATIONS PRIOR TO CONSTRUCTION.
- 9. CONTACT EASEMENT OWNERS PRIOR TO COMMENCING ANY WORK WITHIN THE EASEMENTS.
- IN THE FIELD. 11. SITE WORK SHALL BE CONSTRUCTED FROM A COMPLETE SET OF PLANS, NOT ALL FEATURES ARE DETAILED ON EVERY PLAN. THE ENGINEER IS TO BE NOTIFIED OF ANY CONFLICT WITHIN

10. PRIOR TO COMMENCING ANY SITE WORK, ALL LIMITS OF WORK SHALL BE CLEARLY MARKED

- 12. TFMORAN, INC. ASSUMES NO LIABILITY FOR WORK PERFORMED WITHOUT AN ACCEPTABLE
- PROGRAM OF TESTING AND INSPECTION AS APPROVED BY THE ENGINEER OF RECORD. 13. TEMPORARY FENCING SHALL BE PROVIDED AND COVERED WITH A FABRIC MATERIAL TO CONTROL DUST MITIGATION.
- 14. ALL DEMOLITION SHALL INSURE MINIMUM INTERFERENCE WITH ROADS, STREETS, WALKWAYS, AND ANY OTHER ADJACENT OPERATING FACILITIES. PRIOR WRITTEN PERMISSION FROM THE OWNER/DEVELOPER AND LOCAL PERMITTING AUTHORITY IS REQUIRED IF CLOSURE/OBSTRUCTIONS TO ROADS, STREET, WALKWAYS, AND OTHERS IS DEEMED
- 15. REFER TO ARCHITECTURAL PLANS FOR LAYOUT OF BUILDING FOUNDATIONS AND CONCRETE ELEMENTS WHICH ABUT THE BUILDING SUCH AS STAIRS, SIDEWALKS, LOADING DOCK RAMPS, PADS, AND COMPACTOR PADS. DO NOT USE SITE PLANS FOR LAYOUT OF FOUNDATIONS.
- 16. IN THE EVENT OF A CONFLICT BETWEEN PLANS, SPECIFICATIONS, AND DETAILS, THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY FOR CLARIFICATION.

NECESSARY. CONTRACTOR TO PROVIDE ALTERNATE ROUTES AROUND

CLOSURES/OBSTRUCTIONS PER LOCAL/STATE/FEDERAL REGULATIONS.

- 17. IF CONDITIONS AT THE SITE ARE DIFFERENT THAN SHOWN ON THE PLANS, THE ENGINEER SHALL BE NOTIFIED PRIOR TO PROCEEDING WITH THE AFFECTED WORK.
- 18. CONTRACTOR'S GENERAL RESPONSIBILITIES:
- A. BID AND PERFORM THE WORK IN ACCORDANCE WITH ALL LOCAL, STATE, AND NATIONAL CODES, SPECIFICATIONS, REGULATIONS, AND STANDARDS AND CONDITIONS OF ALL PROJECT-SPECIFIC PERMITS AND APPROVALS AS LISTED ON THE COVER SHEET TO THESE PLANS OR OTHERWISE REQUIRED.
- B. NOTIFY ENGINEER IN WRITING OF ANY DISCREPANCIES OF PROPOSED LAYOUT AND/OR EXISTING FEATURES.
- C. EMPLOY A LICENSED SURVEYOR TO DETERMINE ALL LINES AND GRADES AND LAYOUT OF SITE ELEMENTS AND BUILDINGS.
- D. THE CONTRACTOR SHALL BE RESPONSIBLE TO BECOME FAMILIAR WITH THE SITE AND ALL SURROUNDING CONDITIONS. THE CONTRACTOR SHALL ADVISE THE APPROPRIATE AUTHORITY OF INTENTIONS AT LEAST 48 HOURS IN ADVANCE.
- E. TAKE APPROPRIATE MEASURES TO REDUCE, TO THE FULLEST EXTENT POSSIBLE, NOISE, DUST, AND UNSIGHTLY DEBRIS. CONSTRUCTION ACTIVITIES SHALL BE CARRIED OUT BETWEEN THE HOURS OF 7:00 AM AND 9:00 PM. MONDAY THROUGH FRIDAY IN ACCORDANCE WITH THE APPLICABLE MUNICIPAL ORDINANCES AND REGULATIONS OF THE CITY OF PORTSMOUTH, NEW HAMPSHIRE.
- F. MAINTAIN EMERGENCY ACCESS TO ALL AREAS AFFECTED BY WORK AT ALL TIMES.
- G. IN ACCORDANCE WITH RSA 430:53 AND AGR 3800, THE CONTRACTOR SHALL NOT TRANSPORT INVASIVE SPECIES OFF THE PROPERTY, AND SHALL DISPOSE OF INVASIVE SPECIES ON-SITE IN A LEGAL MANNER.
- H. COORDINATE WITH ALL UTILITY COMPANIES AND CONTACT DIGSAFE (811 OR 888-344-7233) AT LEAST 72 HOURS PRIOR TO ANY EXCAVATION.
- I. PROTECT NEW AND EXISTING BURIED UTILITIES DURING INSTALLATION OF ALL SITE ELEMENTS. DAMAGED UTILITIES SHALL BE REPAIRED OR REPLACED AT NO ADDITIONAL
- J. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MEANS AND METHODS OF CONSTRUCTION AND FOR CONDITIONS AT THE SITE. THESE PLANS, PREPARED BY TFMORAN, INC., DO NOT EXTEND TO OR INCLUDE SYSTEMS PERTAINING TO THE SAFETY OF THE CONSTRUCTION CONTRACTOR OR THEIR EMPLOYEES, AGENTS, OR REPRESENTATIVES IN THE PERFORMANCE OF THE WORK. THE SEAL OF THE SURVEYOR OR ENGINEER HEREON DOES NOT EXTEND TO ANY SUCH SAFETY SYSTEMS THAT MAY NOW OR HEREAFTER BE INCORPORATED INTO THESE PLANS. THE CONSTRUCTION CONTRACTOR SHALL PREPARE OR OBTAIN THE APPROPRIATE SAFETY SYSTEMS WHICH MAY BE REQUIRED BY THE US OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) AND/OR LOCAL REGULATIONS.
- K. WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS. THE CONTRACTOR SHALL USE CAUTION WHEN SCALING REPRODUCED PLANS. IN CASE OF CONFLICT BETWEEN THIS PLAN SET AND ANY OTHER DRAWING AND/OR SPECIFICATION, THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY FOR CLARIFICATIONS.
- L. VERIFY LAYOUT OF PROPOSED BUILDING FOUNDATIONS WITH ARCHITECT AND THAT PROPOSED FOUNDATION MEETS PROPERTY LINE AND/OR WETLAND SETBACKS PRIOR TO COMMENCING ANY FOUNDATION CONSTRUCTION.
- M. PROVIDE AN AS-BUILT PLAN AT THE COMPLETION OF THE PROJECT TO THE PLANNING DIRECTOR AND PER CITY REGULATIONS.
- N. IF ANY DEVIATIONS FROM THE APPROVED PLANS AND SPECIFICATIONS HAVE BEEN MADE, THE SITE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS STAMPED BY A LICENSED SURVEYOR OR QUALIFIED ENGINEER ALONG WITH A LETTER STAMPED BY A QUALIFIED ENGINEER DESCRIBING ALL SUCH DEVIATIONS. AND BEAR ALL COSTS FOR PREPARING AND FILING ANY NEW PERMITS OR PERMIT AMENDMENTS THAT MAY BE REQUIRED.
- O. AT COMPLETION OF CONSTRUCTION, THE SITE CONTRACTOR SHALL PROVIDE A LETTER CERTIFYING THAT THE PROJECT WAS COMPLETED IN ACCORDANCE WITH THE APPROVED PLANS AND SPECIFICATIONS, AND A LETTER STAMPED BY A QUALIFIED ENGINEER THAT THEY HAVE OBSERVED ALL UNDERGROUND DETENTION SYSTEMS, INFILTRATION SYSTEMS, OR FILTERING SYSTEMS PRIOR TO BACKFILL, AND THAT SUCH SYSTEMS CONFORM TO

GRADING & DRAINAGE NOTES

- 1. THE CONTRACTOR SHALL ENSURE THAT ALL WORK IS PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF NHDES ENV-WQ 1500 AS APPLICABLE.
- 2. THE CONTRACTOR SHALL COORDINATE WITH THE OWNER TO SUBMIT AN eNOI AT LEAST 14
- DAYS IN ADVANCE OF ANY EARTHWORK ACTIVITIES AT THE SITE.
- 3. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CHECK THE ACCURACY OF THE TOPOGRAPHY AND REPORT ANY DISCREPANCIES TO THE ENGINEER PRIOR TO ANY EARTHWORK BEING PERFORMED ON THE SITE. NO CLAIM FOR EXTRA WORK WILL BE CONSIDERED FOR PAYMENT AFTER EARTHWORK HAS COMMENCED.
- 4. THE CONTRACTOR SHALL REFER TO THE GEOTECHNICAL REPORT FOR INFORMATION ABOUT SOIL AND GROUNDWATER CONDITIONS. THE CONTRACTOR SHALL FOLLOW THE GEOTECHNICAL ENGINEER'S RECOMMENDED METHODS TO ADDRESS ANY SOIL AND GROUNDWATER ISSUES THAT ARE FOUND ON SITE, INCLUDING AND NOT LIMITED TO DEWATERING METHODS, PERIMETER DRAINS AND TIE INTO STORMWATER MANAGEMENT SYSTEM, ETC.
- 5. COORDINATE WITH GEOTECHNICAL/STRUCTURAL PLANS FOR SITE PREPARATION AND OTHER BUILDING INFORMATION.
- COORDINATE WITH ARCHITECTURAL PLANS FOR DETAILED GRADING AT BUILDING, AND SIZE AND LOCATION OF ALL BUILDING SERVICES.
- 7. COORDINATE WITH MECHANICAL AND PLUMBING PLANS FOR ROOF DRAIN INFORMATION.
- 8. LIMITS OF WORK ARE SHOWN AS APPROXIMATE. THE CONTRACTOR SHALL COORDINATE ALL WORK TO PROVIDE SMOOTH TRANSITIONS. THIS INCLUDES GRADING, PAVEMENT, CURBING, SIDEWALKS, AND ALIGNMENTS.
- 9. THE CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE BUILDING ENTRANCE, RAMPS, AND LOADING
- 10. THE SITE SHALL BE GRADED SO ALL FINISHED PAVEMENT HAS POSITIVE DRAINAGE AND SHALL NOT POND WATER DEEPER THAN 1/4" FOR A PERIOD OF MORE THAN 15 MINUTES AFTER FLOODING.
- 11. ALL ELEVATIONS SHOWN AT CURB ARE TO THE BOTTOM OF CURB UNLESS OTHERWISE NOTED. CURBS HAVE A 6" REVEAL UNLESS OTHERWISE NOTED.
- 12. ALL SIDEWALK AND OTHER CURB REVEALS SHALL BE 6" WITH A TOLERANCE OF PLUS OR MINUS 3/8". WHERE SIDEWALK IS TO BE FLUSH, THE PAVEMENT REVEAL SHALL BE 1/4" WITH A TOLERANCE OF 1/8".
- 13. THE FINISHED GRADE AT BOTTOM OF ALL ACCESSIBLE RAMPS SHALL BE FLUSH WITH PAVEMENT WITH A TOLERANCE OF PLUS OR MINUS 1/4".
- 14. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE PRIOR TO INSTALLATION OF FINISHED PAVEMENT.
- 15. ROAD AND DRAINAGE CONSTRUCTION SHALL CONFORM TO THE TYPICAL SECTIONS AND DETAILS SHOWN ON THE PLANS AND SHALL MEET LOCAL STANDARDS AND THE REQUIREMENTS OF THE LATEST NHDOT STANDARD SPECIFICATIONS FOR ROADS AND BRIDGE CONSTRUCTION AND THE NHDOT STANDARD STRUCTURE DRAWINGS UNLESS OTHERWISE
- 16. STORMWATER DRAINAGE SYSTEM SHALL BE CONSTRUCTED TO LINE AND GRADE AS SHOWN ON THE PLANS. CONSTRUCTION METHODS SHALL CONFORM TO NHDOT STANDARD SPECIFICATIONS, SECTION 603. CATCH BASINS AND DRAIN MANHOLES SHALL CONFORM TO SECTION 604. ALL CATCH BASIN GRATES SHALL BE TYPE B AND CONFORM TO NHDOT STANDARDS AND SPECIFICATIONS UNLESS OTHERWISE NOTED.
- 17. NO FILL SHALL BE PLACED IN ANY WETLAND AREA.
- 18. ALL EXCAVATIONS SHALL BE THOROUGHLY SECURED ON A DAILY BASIS BY THE CONTRACTOR AT THE COMPLETION OF CONSTRUCTION OPERATIONS IN THE IMMEDIATE AREA.
- 19. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED, FERTILIZER, AND MULCH.
- 20. DENSITY REQUIREMENTS: MINIMUM DENSITY* LOCATION

90%

BELOW PAVED OR CONCRETE AREAS 95% 95%

TRENCH BEDDING MATERIAL AND SAND BLANKET BACKFILL BELOW LOAM AND SEED AREAS

*ALL PERCENTAGES OF COMPACTION SHALL BE OF THE MAXIMUM DRY DENSITY AT THE OPTIMUM MOISTURE CONTENT AS DETERMINED AND CONTROLLED IN ACCORDANCE WITH ASTM D-1557, METHOD C. FIELD DENSITY TESTS SHALL BE MADE IN ACCORDANCE WITH ASTM D-1556 OR ASTM D-6938.

date: 07/21/2022

REVISED PER TAC COMMENTS

DESCRIPTION

1 7/21/2022

REV DATE

UTILITY NOTES

- 1. LENGTH OF PIPE IS FOR CONVENIENCE ONLY. ACTUAL PIPE LENGTH SHALL BE DETERMINED
- 2. ALL PROPOSED UTILITY WORK, INCLUDING MATERIAL, INSTALLATION, TERMINATION, EXCAVATION, BEDDING, BACKFILL, COMPACTION, TESTING, CONNECTIONS, AND CONSTRUCTION SHALL BE COORDINATED WITH AND COMPLETED IN ACCORDANCE WITH THE APPROPRIATE REQUIREMENTS, CODES, AND STANDARDS OF ALL CORRESPONDING UTILITY ENTITIES AND SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION, SIZE, AND ELEVATION OF ALL EXISTING UTILITIES, SHOWN OR NOT SHOWN ON THESE PLANS, PRIOR TO THE START OF ANY CONSTRUCTION. THE ENGINEER SHALL BE NOTIFIED IN WRITING OF ANY UTILITIES FOUND INTERFERING WITH THE PROPOSED CONSTRUCTION AND APPROPRIATE REMEDIAL ACTION BE AGREED TO BY THE ENGINEER BEFORE PROCEEDING WITH THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT "DIGSAFE" (811) AT LEAST 72 HOURS BEFORE DIGGING.
- 4. COORDINATE ALL WORK ADJACENT TO PROPOSED BUILDINGS WITH ARCHITECTURAL BUILDING DRAWINGS. CONFIRM UTILITY PENETRATIONS AND INVERT ELEVATIONS ARE COORDINATED PRIOR TO INSTALLATION.
- 5. THE CONTRACTOR SHALL CONTACT ALL UTILITY COMPANIES OWNING UTILITIES, EITHER OVERHEAD OR UNDERGROUND, WITHIN THE CONSTRUCTION AREA AND SHALL COORDINATE AS NECESSARY WITH THE UTILITY COMPANIES OF SAID UTILITIES. THE PROTECTION OR RELOCATION OF UTILITIES IS ULTIMATELY THE RESPONSIBILITY OF THE CONTRACTOR.
- 6. THE EXACT LOCATION OF NEW UTILITY CONNECTIONS SHALL BE DETERMINED BY THE CONTRACTOR IN COORDINATION WITH UTILITY COMPANY, COUNTY AGENCY, AND/OR PRIVATE
- 7. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES, AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER THE UTILITY INSTALLATION COMPLETE AND
- 8. ALL UTILITY COMPANIES REQUIRE INDIVIDUAL CONDUITS. CONTRACTOR TO COORDINATE WITH TELEPHONE, CABLE, AND ELECTRIC COMPANIES REGARDING NUMBER, SIZE, AND TYPE OF CONDUITS REQUIRED PRIOR TO INSTALLATION OF ANY CONDUIT.
- 9. SANITARY SEWER SHALL BE CONSTRUCTED TO THE STANDARDS AND SPECIFICATIONS AS SHOWN ON THESE PLANS. ALL SEWER MAINS AND FITTINGS SHALL BE PVC AND SHALL CONFORM TO ASTM F 679 (SDR 35 MINIMUM). FORCE MAINS AND FITTINGS SHALL CONFORM TO NH CODE OF ADMINISTRATIVE RULES ENV-WQ 700. ALL SEWER CONSTRUCTION SHALL BE IN ACCORDANCE WITH NH CODE OF ADMINISTRATIVE RULES ENV-WQ 700. SANITARY MANHOLES SHALL CONFORM TO NHDES WATER DIVISION WASTEWATER ENGINEERING BUREAU STANDARDS AND SPECIFICATIONS SHOWN HEREON.
- 10. ON-SITE WATER DISTRIBUTION SHALL BE TO CITY OF PORTSMOUTH STANDARDS AND SPECIFICATIONS. WATER MAINS SHALL HAVE A MINIMUM OF 5.5' COVER. WHERE WATER PIPES CROSS SEWER LINES A MINIMUM OF 18" VERTICAL SEPARATION BETWEEN THE TWO OUTSIDE PIPE WALLS SHALL BE OBSERVED. HORIZONTAL SEPARATION BETWEEN WATER AND SEWER SHALL BE 10' MINIMUM. WHERE A SANITARY LINE CROSSES A WATER LINE, SEWER LINE MUST BE CONSTRUCTED OF FORCE MAIN MATERIALS (PER ENV-WQ 704.08) FROM BUILDING OR MANHOLE TO MANHOLE, OR SUBSTITUTE RUBBER-GASKETED PRESSURE PIPE FOR THE SAME DISTANCE. WHEN SANITARY LINES PASS BELOW WATER LINES, LAY PIPE SO THAT NO JOINT IN THE SANITARY LINE WILL BE CLOSER THAN 6' HORIZONTALLY TO THE
- 11. THRUST BLOCKS SHALL BE PROVIDED AT ALL LOCATIONS WHERE WATER LINE CHANGES DIRECTIONS OR CONNECTS TO ANOTHER WATER LINE.
- 12. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR CONDUIT AND WIRING TO ALL SIGNS AND LIGHTS. CONDUIT TO BE A MINIMUM OF 24" BELOW FINISH GRADE.
- 13. ALL PROPOSED UTILITIES SHALL BE UNDERGROUND. ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES.
- 14. THE CONTRACTOR SHALL ARRANGE AND PAY FOR ALL INSPECTIONS. TESTING, AND RELATED SERVICES AND SUBMIT COPIES OF ACCEPTANCE TO THE OWNER, UNLESS OTHERWISE
- 15. PROVIDE PERMANENT PAVEMENT REPAIR FOR ALL UTILITY TRENCHES IN EXISTING ROAD OR PAVEMENT TO REMAIN. SAW CUT TRENCH, PAVEMENT, AND GRANULAR BASE THICKNESS TO

MATCH EXISTING PAVEMENT. OBTAIN ALL PERMITS REQUIRED FOR TRENCHING.

- 16. UNLESS OTHERWISE SPECIFIED, ALL UNDERGROUND STRUCTURES, PIPES, CHAMBERS, ETC. SHALL BE COVERED WITH A MINIMUM OF 18" OF COMPACTED SOIL BEFORE EXPOSURE TO
- 17. THE PROPERTY WILL BE SERVICED BY THE FOLLOWING:

DRAINAGE PRIVATE SEWER MUNICIPA

INDICATED

WATER MUNICIPAL NOT AVAILABLE GAS

ELECTRIC **EVERSOURCE** CONSOLIDATED COMMUNICATIONS FKA FAIRPOINT COMMUNICATIONS TELEPHONE

COMCAST

CABLE

SITE DEVELOPMENT PLANS

TAX MAP 162 LOT 16

NOTES & LEGEND PROPOSED 2 LOT SUBDIVISION 77 MEREDITH WAY

OWNED BY


RANDI & JEFF COLLINS PREPARED FOR

RANDI & JEFF COLLINS

SCALE: NTS

Seacoast Division

JULY 1, 2022



ivil Engineers Structural Engineers affic Engineers ind Surveyors andscape Architects cientists

Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.tfmoran.com

DR BMK FB 47442-00 CK CRR CADFILE 47442-00_NOTES & LEGEND

C - 01

| 170 Commerce Way, Suite 102

48 Constitution Drive, Bedford, N.H. 03110 All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of TFMoran, Inc.

BUII DING

CONCRETE

COORDINAT

DIAMETER

ELEVATION

BOTTOM OF SLOPE

BOTTOM OF WALL

BEST MANAGEMENT PRACTICE

This plan is not effective unless signed by a duly authorized officer of FMoran, Inc.

Copyright 2022 ©TFMoran, Inc.

BLDG

BMP

BW

CONC

COORD

ELEV

NTS NOT TO SCALE

LSA

MAX

N/F

LENGTH

MAXIMUM

MINIMUM

LINEAR FEET

LANDSCAPE AREA

NOW OR FORMERLY

NEW HAMPSHIRE FISH & GAME

REMOVE AND RESET REM RFMOVF RET RETAIN RIM ELEVATION RIM ROW RIGHT OF WAY SLOPE SQUARE FEET SW SIDEWALK

TOP OF CURB

TOP OF WALL

UNDERGROUND

ACCESSIBLE WHEELCHAIR RAMP

TEST PIT

TYPICAL

WITH

TYP

UG

WCR

TEMPORARY BENCHMARK

DIP DMH F&C F&G FES GT HDPE НН HWHYD HYDRANT OCS

SMH


SOS


FLARED END SECTION GREASE TRAP HANDHOLE HEADWALL LIGHT POLE PVC POLYVINYL CHLORIDE PIPE RCP RD

OUTLET CONTROL STRUCTURE REINFORCED CONCRETE PIPE ROOF DRAIN SEWER MANHOLE SEDIMENT OIL SEPARATOR TAPPING SLEEVE, VALVE, AND BOX LITILITY POLE


DUCTILE IRON PIPE DRAIN MANHOLF FRAME AND COVER FRAME AND GRATE HIGH DENSITY POLYETHYLENE PIPE


THE APPROVED PLANS AND SPECIFICATIONS.





1.1 21 2022 - 2.465m





SITE DATA

OWNER OF RECORD OF MAP 162 LOT 16: RANDI & JEFF COLLINS 77 MEREDITH WAY, PORTSMOUTH, NH 03801

DEED REFERENCE TO PARCEL IS BK 6274 PG 1666

AREA OF PARCEL = $22,463\pm$ SF OR $0.5157\pm$ ACRES

GENERAL RESIDENCE A (GRA) EXISTING USE: 1 LOT, SINGLE FAMILY DWELLING UNIT PROPOSED USE: 2 LOTS, 2 SINGLE FAMILY DWELLING UNITS

THE PURPOSE OF THIS PLAN IS TO DEPICT TWO PROPOSED SING FAMILY DWELLING UNITS WITH ACCESS ALONG MEREDITH WAY. ASSOCIATED IMPROVEMENTS INCLUDE AND ARE NOT LIMITED TO ACCESS, GRADING, STORMWATER MANAGEMENT SYSTEMS, UTILITIES.

DIMENSIONAL REQUIREMENTS (CURRENT ZONING)

		REQUIRED:	PROVIDED: LOT A:	LOT B:
	MINIMUM LOT DIMENSIONS: LOT AREA LOT FRONTAGE DEPTH	7,500 SF 100 FT 70 FT	11,198 SF 73.99 FT 151.4 FT	11,265 SF 31.61 FT 152.1 FT
	MINIMUM YARD DIMENSIONS: FRONT SIDE REAR	15 FT 10 FT 20 FT	22.0 FT 10.2 FT 69.0 FT	17.1 FT 16.2 FT 74.9 FT
	MAXIMUM STRUCTURE DIMENSIONS: SLOPED ROOF FLAT ROOF ROOF APPURTENANCE HEIGHT BUILDING LOT COVERAGE	35 FT 30 FT 8 FT 25% (MAX)	<35 FT NA >8 FT 21.4%	<35 FT NA >8 FT 18.0%
		15 FT 10 FT 20 FT	15 FT 10 FT 20 FT	15 FT 10 FT 20 FT
	MINIMUM OPEN SPACE	30%	70.4%	68.5%
PAR	KING REQUIREMENTS			
	PARKING SPACES 1.3 SPACES/UNIT	2 SPACES	2 SPACES	2 SPACES

NOTES

- 1. SEE NOTES ON SHEET C-01.
- 2. ALL DIMENSIONS ARE TO THE FACE OF CURB UNLESS NOTED OTHERWISE.
- 3. LIGHTING, SIGNAGE, LANDSCAPING, AND SCREENING SHALL MEET THE REQUIREMENTS OF THE PORTSMOUTH ZONING ORDINANCE AND SITE PLAN REGULATIONS.
- 4. SNOW SHALL NOT BE STOCKPILED IN STORMWATER BMP'S, WETLAND BUFFERS, OR WETLANDS. SEE SNOW STORAGE LOCATIONS. IN THE EVENT THAT THE SNOW STORAGE AREAS PROVIDED ON THE SITE ARE COMPLETELY UTILIZED, EXCESS SNOW SHALL BE TRANSPORTED OFF SITE FOR DISPOSAL IN ACCORDANCE WITH NHDES REGULATION. IF SNOW IS STORED WITHIN PARKING AREA, KEEP CATCH BASINS CLEAR.
- 5. ALL CONDITIONS ON THIS PLAN SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO REQUIREMENTS OF THE SITE PLAN REVIEW REGULATIONS.
- 6. THIS SITE PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.
- 7. ALL IMPROVEMENTS SHOWN ON THIS SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE PORTSMOUTH PLANNING DIRECTOR.



SITE DEVELOPMENT PLANS

TAX MAP 162 LOT 16

SITE LAYOUT PLAN PROPOSED 2 LOT SUBDIVISION 77 MEREDITH WAY

OWNED BY

RANDI & JEFF COLLINS

PREPARED FOR


RANDI & JEFF COLLINS 1"=20' (11"X17")

JULY 1, 2022



Civil Engineers Structural Engineers Traffic Engineers Land Surveyors Landscape Architects | 170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.tfmoran.com

47442-00 DR BMK FB - CK CRR CADFILE 47442-00_SITE LAYOUT C - 03



- 1. SEE NOTES ON SHEET C-01.
- 2. ALL DOORS AND GARAGE ENTRANCES SHALL BE AT FINISHED FLOOR ELEVATION UNLESS OTHERWISE
- 3. PROPOSED SPOT GRADES ARE PROVIDED TO THE NEAREST 0.05. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE FINISHED GRADES MEET ADA STANDARDS FOR WHEEL CHAIR RAMPS, HANDICAP SPACES AND ACCESS AISLES, CROSSWALKS, SIDEWALKS, ETC.
- 4. ALL ELEVATIONS SHOWN AT CURB ARE TO THE BOTTOM OF CURB UNLESS OTHERWISE NOTED. CURBS HAVE A 6" REVEAL UNLESS OTHERWISE NOTED.
- 5. LENGTH OF PIPE IS FOR CONVENIENCE ONLY. ACTUAL PIPE LENGTH SHALL BE DETERMINED IN THE
- 7. ALL PROPOSED DRAINAGE PIPES SHALL BE 12" AND HDPE, UNLESS OTHERWISE NOTED ON THE
- 8. DRAINAGE PIPES WITH LESS THAN 3' COVER SHALL BE INSULATED (SEE UTILITY TRENCH DETAIL) AND DRAINAGE CATCH BASINS WITH LESS THAN 3.5' OF COVER OVER INVERTS SHALL USE SLAB
- TOP CATCH BASIN (SEE DETAILS).
- 9. THE CONTRACTOR SHALL REFER TO THE GEOTECHNICAL REPORT AND ARCHITECTURAL PLANS FOR SUBDRAINAGE SYSTEMS FOR THE BUILDING FOUNDATION. SUBDRAINAGE MUST DAYLIGHT OR TIE INTO THE STORMAR MANAGEMENT SYSTEM. COORDINATE SUBDRAINAGE SYSMTEM DESIGN WITH THE ENGINEER OF RECORD. TEST DIT & INICII TRATIONI TEST

TEST PIT & INFILTRATION TEST					
ВМР	P TEST APPROX BOTTOM TEST PIT # GROUND OF POND PIT				
		ELEV	ELEV	ELEV	DEPTH (MIN)
RAIN GARDEN #1	2	35.75	35.25	35	5
RAIN GARDEN #2	1	35.00	34.25	33.50	4'

1. ALL TEST PITS ARE TO BE TESTED FOR INFILTRATION RATES AT THE GIVEN INFILTRATION

- ELEVATIONS.

 2. TEST PITS ARE TO BE TESTED FOR INFILIRATION RATES AT THE GIVEN INFILIRATION
 ELEVATIONS.

 2. TEST PITS ARE TO BE EXCAVATED UNTIL SEASONAL HIGH WATER TABLE OR THE LOCATION OF
 LEDGE IS ENCOUNTERED. TEST PIT DEPTHS LISTED ARE MINIMUM DEPTHS. IF SEASONAL HIGH WATER
- OR LEDGE ARE ENCOUNTERED, THE TEST PIT CAN BE STOPPED.
- 3. INFILTRATION TESTS ARE FOR INFILTRATION ONLY. THEY CAN BE DISCONTINUED IF SEASONAL HIGH WATER OR LEDGE IS ENCOUNTERED WITHIN THE TESTING RANGE FOR THE INFILTRATION.
- 4. INFILTRATION TESTS SHALL BE PERFORMED ACCORDING TO ENV-WQ 1504.14 (e) [AoT STANDARDS].

SOIL LEGEND (PER NRCS WEB SOIL SURVEY)			
SYMBOL	DESCRIPTION	HYDROLOGIC SOIL GROUP	
799	URBAN LAND — CANTON COMPLEX, 3—5% SLOPES	А	



SITE DEVELOPMENT PLANS

TAX MAP 162 LOT 16

GRADING & DRAINAGE PLAN PROPOSED 2 LOT SUBDIVISION

77 MEREDITH WAY OWNED BY

RANDI & JEFF COLLINS

PREPARED FOR

RANDI & JEFF COLLINS

1"=20' (11"X17")


JULY 1, 2022




Structural Engineers Land Surveyors Landscape Architects

| 170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.tfmoran.com

47442-00 CK CRR CADFILE 47442-00_GRADING & DRAINAGE C - 04





1+00

1+13

date: 07/21/2022

1"=20' (11"X17") SCALE: 1'=10' (22'X34')

JULY 1, 2022 Seacoast Division

| 170 Commerce Way, Suite 102 Structural Engineers Portsmouth, NH 03801 Traffic Engineers Phone (603) 431-2222 Land Surveyors

OWNED BY RANDI & JEFF COLLINS

PREPARED FOR RANDI & JEFF COLLINS


Fax (603) 431-0910 Landscape Architects www.tfmoran.com

Copyright 2022 ©TFMoran, Inc. 48 Constitution Drive, Bedford, N.H. 03110 All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of TFMoran, Inc. This plan is not effective unless signed by a duly authorized officer of TFMoran, Inc.




0+00

MEREDITH WAY



DR CK REV DATE DESCRIPTION

C - 06




SEE SPECIFICATIONS FOR SOCK SIZE AND COMPOST FILL REQUIREMENTS.


SILT SOCK SHALL BE INSPECTED PERIODICALLY AND AFTER ALL STORM EVENTS, AND REPAIR OR REPLACEMENT SHALL BE PERFORMED AS NEEDED.

SILT SOCK

COMPOST MATERIAL SHALL BE DISPERSED ON SITE, AS DETERMINED BY THE ENGINEER.

NOT TO SCALE





NOTES:

- 1. INSTALL PER MANUFACTURER'S SPECIFICATIONS.
- 2. INSPECTION SHOULD OCCUR FOLLOWING ANY RAIN EVENT $> \frac{1}{2}$ EMPTY THE SEDIMENT BAG PER MANUFACTURER'S SPECIFICATIONS. 4. REMOVED CAKED ON SILT FROM SEDIMENT BAG AND FLUSH WITH MEDIUM
- SPRAY WITH OPTIMAL FILTRATION. 5. REPLACE BAG IF TORN OR PUNCTURED TO $> \frac{1}{2}$ " DIAMETER ON LOWER
- HALF OF BAG.

FLEXSTORM CATCH-IT FILTERS

> ALL PRODUCTS MANUFACTURED BY INLET & PIPE PROTECTION, INC. A DIVISION OF ADS, INC. WWW.INLETFILTERS.COM

(866) 287-8655 INFO@INLETFILTERS.COM

INLET PROTECTION


NOT TO SCALE

FXISTING OR 4 TIMES THE CIRCUMFERENCE OF THE LARGEST PAVEMENT CONSTRUCTION VEHICLE TIRE, WHICHEVER IS GREATER EXISTING GROUND 3"-6" STONE 12"MIN MOUNTABLE BERM (OPTIONAL) FILTER CLOTH-PROFILE (SPUN BOUND 1135 MIRAFI 600X OR EQUIVALENT) 10' MIN. — 3"−6" STONE —— PLAN VIEW

- 1. FILTER CLOTH WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE SURFACE.
- 2. WATER ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED ACROSS THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
- 3. MAINTENANCE THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY.
- 4. WASHING WHEELS SHALL BE CLEANED TO REMOVE SEDIMENT PRIOR TO ENTRANCE ONTO PUBLIC RIGHTS-OF-WAY. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
- 5. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN STORM EVENT.

STABILIZED CONSTRUCTION **ENTRANCE**

NOT TO SCALE




1. FOR TOP INSULATION, USE 2" THICK OF 2"X2"X8" RIGID STYROFOAM INSULATION (1 LAYER IF LESS THAN 5' COVER, 2 LAYERS IF GREATER THAN 5' COVER BUT LESS THAN 6' COVER). FOR SIDE INSULATION, USE 2" THICK OF 2"X2"X8" RIGID STYROFOAM INSULATION EXTENDING TO A MINIMUM DEPTH OF 5'.

2. TRACER WIRE SPECIFIED FOR NON-METALLIC WATER LINES SHALL BE INSTALLED BELOW AND TO THE SIDE OF THE PIPE AND PER THE MANUFACTURER REQUIREMENTS. TRACER WIRE PRODUCT SHALL BE SELECTED FOR OPEN CUT INSTALLATION TECHNIQUE. 3. IN LOCATIONS WITH EXISTING FILL SOILS, THE EXISTING SUBGRADE SOILS AT THE BOTTOM OF THE TRENCH SHALL BE OVER-EXCAVATED 2' DEEP AND RECOMPACTED IN 12" LIFTS TO 95% MAXIMUM DENSITY.

UTILITY TRENCH

OR SEWER, WATER, AND STORM DRAIN LINES

NOT TO SCALE





NOTES

- 1. ELECTRIC SERVICE INSTALLATION AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE IN ACCORDANCE WITH FEDERAL, STATE AND
- 2. COMMUNICATION SERVICE INSTALLATION SHALL MEET ALL
- CONSTRUCTION REQUIREMENTS. 3. ACTUAL NUMBER OF CONDUITS TO BE DETERMINED BY RESPECTIVE
- 4. VERIFY INSTALLATION REQUIREMENTS WITH RESPECTIVE COMPANIES.

NOT TO SCALE

ELECTRIC/COMMUNICATIONS CONDUIT





*NOTE: >1.0' SEPARATION FROM BOTTOM OF FILTER LAYER TO ESHWT. RAIN GARDEN #2 IS NOT BEING ANALYZED FOR INFILTRATION."

RAIN GARDEN DETAIL

NOT TO SCALE

NOTE: SEE PLANS FOR BED, BERM AND OVERFLOW ELEVATIONS * SEE UNDERGROUND STORAGE DETAIL FOR PLACEMENT OF UNDERDRAIN FOR RAIN GARDEN #2


RAIN GARDEN CONSTRUCTION

- 1. CLEAR AND GRUB THE AREA WHERE THE RAIN GARDEN AREAS ARE TO BE LOCATED. STOCKPILE LOAM FOR REUSE ON SLOPES.
- 2. GRADE RAIN GARDEN AREAS ACCORDING TO PLAN AND DETAILS. SIDE SLOPES SHALL HAVE 4" LOAM AND SEED AND A SLOPE NOT TO EXCEED 3:1. BOTTOM OF RAIN GARDEN AREAS TO BE CONSTRUCTED WITH MANUFACTURED SOIL (SEE RAIN GARDEN CONSTRUCTION DETAIL).
- 3. BOTTOM OF THE RAIN GARDEN TO BE SEEDED WITH A CONSERVATION SEED MIX THAT MEETS NH STATE STANDARDS.
- 4. SOIL SPECIFICATION TO CONFORM TO THE LATEST UNH STORMWATER CENTER BIORETENTION SOIL SPECIFICATIONS. A COPY OF THE 2017 UNHSC BIORETENTION SPECIFICATION ARE INCLUDED IN THE STORMWATER OPERATION AND MAINTENANCE MANUAL.
- 5. THE CONTRACTOR SHALL TAKE MEASURES TO PREVENT EQUIPMENT & VEHICLE TRAFFIC FROM DRIVING IN THE AREA OF THE PROPOSED RAIN GARDEN AREA DURING CONSTRUCTION.

RAIN GARDEN MAINTENANCE

MAINTENANCE SCHEDULE TO BEGIN AFTER CONSTRUCTION IS FINISHED AND BASIN STABILIZATION IS COMPLETE.

1. CONTRACTOR AND LAND OWNERS TO PERFORM SCHEDULED MAINTENANCE ON THE RAIN GARDENS IN ACCORDANCE WITH THE STORMWATER OPERATION AND MAINTENANCE



STANDARD DUTY PAVEMENT

- 1. SEE GRADING & EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.
- 2. PROVIDE CLEAN BUTT TO EXISTING PAVEMENT- USE TACK COAT. A TACK COAT SHALL ALSO BE PLACED BETWEEN GRAVEL COURSE AND SUCCESSIVE LAYERS OF BITUMINOUS CONCRETE. SPECIFICALLY, A TACK COAT SHALL BE PLACED ATOP THE BINDER COURSE PAVEMENT PRIOR TO PLACING THE WEARING COURSE.
- 3. REMOVE ALL LOAM AND/OR YIELDING MATERIAL BELOW PAVEMENT
- 4. BITUMINOUS MATERIALS SHALL CONFORM TO NHDOT SPECIFICATION SECTION 401.
- 5. BITUMINOUS CONCRETE SHALL BE COMPACTED TO AT LEAST 92.5% OF THEORETICAL MAXIMUM DENSITY AS DETERMINED BY ASTM D2041 OR AASHTO T209. PLACEMENT TEMPERATURES OF BITUMINOUS CONCRETE MIXES, IN GENERAL, RANGE BETWEEN 270 AND 310 DEGREES FAHRENHEIT.
- 6. PAVEMENT BASE COURSE AGGREGATE SHALL CONFORM TO NHDOT SPECIFICATION SECTION 304, ITEM 304.3 AND COMPACTED TO A MINIMUM OF 95% OF MODIFIED PROCTOR MAXIMUM DRY DENSITY.
- 7. PAVEMENT SUBBASE COURSE AGGREGATE AND AGGREGATE FOR SUBGRADE REPAIR AREAS SHALL BE SUITABLE FOR USE AS STRUCTURAL FILL AND BE PROOF ROLLED AND COMPACTED TO 95% MODIFIED PROCTOR MAXIMUM DRY DENSITY.
- 8. THE EXPOSED SOIL SUBGRADE SHOULD BE PROOF ROLLED PRIOR TO THE PLACEMENT OF SUBBASE GRAVEL, AND SOFT AREAS SHOULD BE REPAIRED AND REPLACED.
- 9. ALL PARKING SPACES SHALL BE STANDARD DUTY. ALL OTHER LOCATIONS SHALL BE HEAVY DUTY.

PAVEMENT SECTIONS NOT TO SCALE



1 7/21/2022 SHEET ADDED TO PLAN SET REV DATE **DESCRIPTION** DR CK

SITE DEVELOPMENT PLANS

TAX MAP 162 LOT 16

DETAILS

PROPOSED 2 LOT SUBDIVISION 77 MEREDITH WAY

OWNED BY

RANDI & JEFF COLLINS PREPARED FOR

RANDI & JEFF COLLINS

HEAVY DUTY PAVEMENT

1"=20' (11"X17") SCALE: NTBO' (22"X34") JULY 1, 2022

Seacoast Division | 170 Commerce Way, Suite 102 ivil Engineers Structural Engineers Portsmouth, NH 03801 raffic Engineers Phone (603) 431-2222 and Surveyors Fax (603) 431-0910 andscape Architects cientists www.tfmoran.com 47442-00 CK CRR CADFILE C - 0747442-00_DETAILS

Copyright 2022 ©TFMoran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of TFMoran, Inc.

This plan is not effective unless signed by a duly authorized officer of FMoran, Inc.

