Transmittal

Date:			Job Number				
Project Name:							
To:							
-							
-							
We are sending t	these by						
US Mail		l	FedEx		UPS		
Hand Deliver			Courier		Other		
We are sending yo	bu						
Attached		Under separate cover via			the following items		
Shop drawings	s Prin	nts/Plans	Samples	Specifications	Change Order	Other	
Number Date	Сору	Descriptio	n				
			•				

These are transmitted as checked below:

	For your use	Approved as submitted	Resubmit
	As requested	Approved as noted	Submit
	For review and comment	Returned for corrections	Return
	Copies for approval	Copies for distribution	Corrected prints
_			
Copy t	0:	Signed:	

Phone:



City of Portsmouth, New Hampshire

Site Plan Application Checklist

This site plan application checklist is a tool designed to assist the applicant in the planning process and for preparing the application for Planning Board review. The checklist is required to be completed and uploaded to the Site Plan application in the City's online permitting system. A preapplication conference with a member of the planning department is strongly encouraged as additional project information may be required depending on the size and scope. The applicant is cautioned that this checklist is only a guide and is not intended to be a complete list of all site plan review requirements. Please refer to the Site Plan review regulations for full details.

Applicant Responsibilities (Section 2.5.2): Applicable fees are due upon application submittal along with required attachments. The application shall be complete as submitted and provide adequate information for evaluation of the proposed site development. <u>Waiver requests must be submitted in writing with appropriate justification</u>.

Name of Applicant: _____Kimley Horn & Associates, Inc. ___ Date Submitted: May 23, 2022

Application # (in City's online permitting): LU-22-35

Site Address: 333 Borthwick Ave., Portsmouth, NH 03801 Map: 240 Lot: 2-1

	Application Requirements					
N	Required Items for Submittal	Item Location (e.g. Page or Plan Sheet/Note #)	Waiver Requested			
Ŋ	Complete <u>application</u> form submitted via the City's web-based permitting program (2.5.2.1 (2.5.2.3A)	LU-22-35	N/A			
Ø	All application documents, plans, supporting documentation and other materials uploaded to the application form in viewpoint in digital Portable Document Format (PDF). One hard copy of all plans and materials shall be submitted to the Planning Department by the published deadline. (2.5.2.8)	ATTACHED	N/A			

	Site Plan Review Application Required Information						
Ø	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested				
Ø	Statement that lists and describes "green" building components and systems. (2.5.3.1B)	N/A					
Ø	Existing and proposed gross floor area and dimensions of all buildings and statement of uses and floor area for each floor. (2.5.3.1C)	COVER SHEET C0.00 SITE DATA TABLE	N/A				
Ø	Tax map and lot number, and current zoning of all parcels under Site Plan Review. (2.5.3.1D)	COVER SHEET C0.00 SITE DATA TABLE	N/A				

	Site Plan Review Application Required Info	ormation	
$\mathbf{\Sigma}$	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
Ø	Owner's name, address, telephone number, and signature. Name, address, and telephone number of applicant if different from owner. (2.5.3.1E)	COVER SHEET C0.00	N/A
	Names and addresses (including Tax Map and Lot number and zoning districts) of all direct abutting property owners (including properties located across abutting streets) and holders of existing conservation, preservation or agricultural preservation restrictions affecting the subject property. (2.5.3.1F)	Existing Conditions Plan	N/A
M	Names, addresses and telephone numbers of all professionals involved in the site plan design. (2.5.3.1G)	COVER SHEET C0.00	N/A
A	List of reference plans. (2.5.3.1H)	COVER SHEET C0.00	N/A
$\mathbf{\Sigma}$	List of names and contact information of all public or private utilities servicing the site. (2.5.3.1)	COVER SHEET C0.00	N/A

	Site Plan Specifications		
Ŋ	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
Ŋ	Full size plans shall not be larger than 22 inches by 34 inches with match lines as required, unless approved by the Planning Director (2.5.4.1A)	Required on all plan sheets	N/A
Ø	Scale: Not less than 1 inch = 60 feet and a graphic bar scale shall be included on all plans. (2.5.4.1B)	Required on all plan sheets	N/A
Ø	GIS data should be referenced to the coordinate system New Hampshire State Plane, NAD83 (1996), with units in feet. (2.5.4.1C)	SHEETS C0.02 (SURVEY BY OTHERS), C1.00 & C4.00, C401 NOTES	N/A
Ø	Plans shall be drawn to scale and stamped by a NH licensed civil engineer. (2.5.4.1D)	Required on all plan sheets	N/A
Ø	Wetlands shall be delineated by a NH certified wetlands scientist and so stamped. (2.5.4.1E)	C1.00, C4.00, C401	N/A
Ŋ	Title (name of development project), north point, scale, legend. (2.5.4.2A)	Required on all plan sheets	N/A
Ø	Date plans first submitted, date and explanation of revisions. (2.5.4.2B)	Required on all plan sheets	N/A
Ŋ	Individual plan sheet title that clearly describes the information that is displayed. (2.5.4.2C)	Required on all plan sheets	N/A
Ŋ	Source and date of data displayed on the plan. (2.5.4.2D)	Required on all plan sheets	N/A

Site Plan Application Checklist/December 2020

	Site Plan Specifications – Required Exhibits	s and Data	
\mathbf{N}	Required Items for Submittal	Item Location	Waiver
		(e.g. Page/line or Plan Sheet/Note #)	Requested
R	1. Existing Conditions: (2.5.4.3A)		
	 Surveyed plan of site showing existing natural and built features; 	SITE SURVEY BY OTHERS	
	 Existing building footprints and gross floor area; 	C1.00 & COVER SHEET (DATA TABLE)	
	• Existing parking areas and number of parking spaces provided;	C0.00 & C4.01 PARKING TABLE	
	Zoning district boundaries;	C1.00 EXISTING CONDITIONS PLAN	
	 Existing, required, and proposed dimensional zoning requirements including building and open space coverage, yards 	C1.00, C4.00, C4.01, DATA TABLE ON C0.00	
	 and/or setbacks, and dwelling units per acre; Existing impervious and disturbed areas; 	IMPERVIOUS AREA ON POND EXHIBIT LOD ON SITE DATA TABLE: C0.00 & C4.01	
	 Limits and type of existing vegetation; 	L1.00, C1.00, C0.02 (SURVEY), C2.00	
	 Wetland delineation, wetland function and value assessment (including vernal pools); 	WETLAND EXHIBIT, C1.00, C4.00, & C4.01	
	• SFHA, 100-year flood elevation line and BFE data, as required.	N/A - C1.00 & C4.00	
M	2. Buildings and Structures: (2.5.4.3B)		
	 Plan view: Use, size, dimensions, footings, overhangs, 1st fl. elevation; 	ARCH. PLANS A1.01B, A1.02A, A2.01, SITE PLAN - C4.01 & GRADING PLAN C5.00	
	 Elevations: Height, massing, placement, materials, lighting, façade treatments; 	ELEVATIONS & FACADE: A2.01	
	Total Floor Area;	FLOOR AREA: C0.00 SITE DATA TABLE	
	Number of Usable Floors;	ARCH. PLANS A1.01B, A1.02A, A2.01	
	 Gross floor area by floor and use. 	FLOOR AREA: C0.00 SITE DATA TABLE	
	3. Access and Circulation: (2.5.4.3C)		
	 Location/width of access ways within site; 		
	 Location of curbing, right of ways, edge of pavement and sidewalks; 		
	 Location, type, size and design of traffic signing (pavement markings); 	SITE LAYOUT C4.01;	
	 Names/layout of existing abutting streets; 	EXISTING FACILITY	
	 Driveway curb cuts for abutting prop. and public roads; 		
	 If subdivision; Names of all roads, right of way lines and easements noted; 		
	• AASHTO truck turning templates, description of minimum vehicle allowed being a WB-50 (unless otherwise approved by TAC).		
\mathbf{N}	4. Parking and Loading: (2.5.4.3D)		
	 Location of off street parking/loading areas, landscaped areas/buffers; 	SITE LAYOUT C4.01 SITE DATA TABLE	
	 Parking Calculations (# required and the # provided). 	& PARKING TABLE	
\mathbf{N}	5. Water Infrastructure: (2.5.4.3E)		
	 Size, type and location of water mains, shut-offs, hydrants & Engineering data; 	SITE UTILITY PLAN C6.00; INTERNALLY	
	 Location of wells and monitoring wells (include protective radii). 	FED	
\mathbf{V}	6. Sewer Infrastructure: (2.5.4.3F)	SITE UTILITY PLAN	
	 Size, type and location of sanitary sewage facilities & Engineering data, including any onsite temporary facilities during construction period. 	C6.00; TIE INTO EXST	

Ø	 7. Utilities: (2.5.4.3G) The size, type and location of all above & below ground utilities; 	SITE UTILITY PLAN
	Size type and location of generator pads, transformers and other fixtures.	C6.00
$\mathbf{\nabla}$	8. Solid Waste Facilities: (2.5.4.3H)	N/A
	• The size, type and location of solid waste facilities.	N/A; EXISTING
	 9. Storm water Management: (2.5.4.3I) The location, elevation and layout of all storm-water drainage. The location of onsite snow storage areas and/or proposed offsite snow removal provisions. Location and containment measures for any salt storage facilities Location of proposed temporary and permanent material storage locations and distance from wetlands, water bodies, and 	GRADING & DRAINAGE SHEET C5.00
	stormwater structures.	
	 10. Outdoor Lighting: (2.5.4.3J) Type and placement of all lighting (exterior of building, parking lot and any other areas of the site) and photometric plan. 	N/A
Ŋ	 Indicate where dark sky friendly lighting measures have been implemented. (10.1) 	N/A
	 12. Landscaping: (2.5.4.3K) Identify all undisturbed area, existing vegetation and that which is to be retained; Location of any irrigation system and water source. 	LANDSCAPE PLAN - L100; EXISITNG IRRIGATION SYSTEM TO BE EXTENDED
Ø	 13. Contours and Elevation: (2.5.4.3L) Existing/Proposed contours (2 foot minimum) and finished grade elevations. 	Grading and Drainage Plan Sheet C500
M	 14. Open Space: (2.5.4.3M) Type, extent and location of all existing/proposed open space. 	C0.00 & C4.01 & DRAINAGE AREA MAP
Ŋ	 All easements, deed restrictions and non-public rights of ways. (2.5.4.3N) 	C1.00 & C4.00
N	 16. Character/Civic District (All following information shall be included): (2.5.4.3P) Applicable Building Height (10.5A21.20 & 10.5A43.30); Applicable Special Requirements (10.5A21.30); Proposed building form/type (10.5A43); Proposed community space (10.5A46). 	SITE DATA TABLE C0.00 & C4.01
	 17. Special Flood Hazard Areas (2.5.4.3Q) The proposed development is consistent with the need to minimize flood damage; All public utilities and facilities are located and construction to minimize or eliminate flood damage; Adequate drainage is provided so as to reduce exposure to flood hazards. 	GRADING & DRAINAGE C5.00 UTILITY PLAN C6.00

	Other Required Information						
Ŋ	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested				
Ŋ	Traffic Impact Study or Trip Generation Report, as required. (3.2.1-2)	N/A					
Ø	Indicate where Low Impact Development Design practices have been incorporated. (7.1)	ATTACHED STORMWATER MANAGEMENT PLAN					
$\mathbf{\Sigma}$	Indicate whether the proposed development is located in a wellhead protection or aquifer protection area. Such determination shall be approved by the Director of the Dept. of Public Works. (7.3.1)	N/A					
Q	Stormwater Management and Erosion Control Plan. (7.4)	C3.00, C3.01, C3.02 & STORMWATER MANAGEMENT PLAN					
N	Inspection and Maintenance Plan (7.6.5)	ATTACHED					

Final Site Plan Approval Required Information					
Ŋ	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested		
	All local approvals, permits, easements and licenses required, including but not limited to: • Waivers; • Driveway permits; • Special exceptions; • Variances granted; • Easements; • Licenses. (2.5.3.2A)	LU-22-35: AWAITING CONDITIONAL APPROVAL LETTER FROM CONSERVATION COMMITTEE FROM 5/11/22 MEETING. BOA BUILDING SETBACK VARIANCE APPROVAL ATTACHED			
	 Exhibits, data, reports or studies that may have been required as part of the approval process, including but not limited to: Calculations relating to stormwater runoff; Information on composition and quantity of water demand and wastewater generated; Information on air, water or land pollutants to be discharged, including standards, quantity, treatment and/or controls; Estimates of traffic generation and counts pre- and post-construction; Estimates of noise generation; A Stormwater Management and Erosion Control Plan; Endangered species and archaeological / historical studies; Wetland and water body (coastal and inland) delineations; Environmental impact studies. 	ATTACHED			
Ŋ	A document from each of the required private utility service providers indicating approval of the proposed site plan and indicating an ability to provide all required private utilities to the site. (2.5.3.2D)	N/A; EXISTING BUILDING			

Site Plan Application Checklist/December 2020

	Final Site Plan Approval Required Info	rmation	
A	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
Ŋ	A list of any required state and federal permit applications required for the project and the status of same. (2.5.3.2E)	N/A	
Ŋ	A note shall be provided on the Site Plan stating: "All conditions on this Plan shall remain in effect in perpetuity pursuant to the requirements of the Site Plan Review Regulations." (2.5.4.2E)	SITE LAYOUT C4.01 NOTE #14	N/A
Ŋ	For site plans that involve land designated as "Special Flood Hazard Areas" (SFHA) by the National Flood Insurance Program (NFIP) confirmation that all necessary permits have been received from those governmental agencies from which approval is required by Federal or State law, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334. (2.5.4.2F)	N/A	
	 Plan sheets submitted for recording shall include the following notes: a. "This Site Plan shall be recorded in the Rockingham County Registry of Deeds." b. "All improvements shown on this Site Plan shall be constructed and maintained in accordance with the Plan by the property owner and all future property owners. No changes shall be made to this Site Plan without the express approval of the Portsmouth Planning Director." (2.13.3) 	SITE LAYOUT C4.01 NOTE #15	N/A
	(2.15.3)		
Appli	cant's Signature: Matthew trunky Date:	5/24/2022	

Page **6** of **6**

February 22, 2022 *Updated May 5, 2022*

City of Portsmouth

RE: Portsmouth Regional Hospital – Radiation Oncology Project Narrative

The existing Portsmouth Regional Hospital is located at 333 Borthwick Ave, Portsmouth, NH 03801 (Map 240, Lot 2-1). The medical campus is located on the east side of Blue Star Turnpike (I-95), the west side of Borthwick Avenue, and can be accessed via multiple entrances from Borthwick Avenue. The scope of the proposed Radiation Oncology project consists of internal renovations, and a 1-story building addition located on the southeast corner of the existing hospital building.

The proposed footprint of the building addition is approximately ±8,700 square feet. The proposed sitework is anticipated to consist of asphalt, concrete, utility, landscape, and drive-under canopy demolition where the current patient discharge canopy and associated drive are located as well as removal of existing sidewalk and landscaping located along the south side of the existing hospital building. Site improvements are anticipated to consist of the new building addition, new drive-under canopy and associated drive, sidewalk connectivity, new granite curb, new mobile imaging pad, and associated new utilities/ utility relocations.

A portion of the project scope is located adjacent to and partially within a previously man-made stormwater management area which is now delineated as a city jurisdictional inland wetland and has an associated 100-ft wetland buffer, in which a portion of the site improvements will occur. A small amount of disturbance to the actual wetland is being proposed. Refer to the attached wetland exhibit. Please note, the overall wetland data has been calculated with older drawings by others. Only the wetland adjacent to this project was delineated and flagged by Gove Environmental Services, Inc., and surveyed by James Verra and Associates, Inc. Refer to attached letter and site survey.

Wetlands and 100-foot buffer, Overall Site

- Subject Parcel: Map 240, Lot2-1 (±20.87 ac)
- Total wetland area onsite: approximately ±2.7 acres
- Total area of 100-foot wetland buffer onsite: approximately ±8.4 acres

Wetland and 100-foot buffer, Proposed Impact

- Area of inland wetland to be disturbed:
 - Permanent (due to proposed building location): ±200 square feet (sf)
 - Temporary (due to construction of proposed building and utility relocations, but will be planted back as wetlands): ±4,400 square feet (sf)
 - Total disturbance: ±4,600 square feet (sf)
- Area of 100-ft wetland buffer to be disturbed:
 - o Permanent: ±13,200 sf
 - Temporary: ±4,300 sf

The drainage area to the existing man-made stormwater management area/ inland wetland that is located within the proposed project area (**Pond 1**) was analyzed utilizing provided site surveys as well as previous design drawings for the medical campus. It appears a portion of the southeastern parking lot drains to another existing man-made stormwater management area/ inland wetland that is located along the north side of Borthwick Avenue (**Pond 2**). Pond 2 drains to Pond 1 via a 21" RCP pipe. The drainage area to the Pond 2 remains the same as the current existing condition.

The drainage area to the Pond 1 also remains relatively the same as existing conditions as a portion of the existing hospital building roof will continue to drain to Pond 1, new roof for the proposed building addition is located where existing sidewalks and drives are currently located, and some existing pavement is being removed to allow Pond 1 to expand to provide additional pond volume to attempt to offset any pond volume lost due to the proposed project. The existing 24" RCP pipe outfall from Pond 1 remains in place. Refer to the attached drainage area exhibit.

Existing pond volume: ±54,190 cubic feet (cf)

Proposed pond volume: ±56,265 cubic feet (cf)

A HydroCAD stormwater model was utilized to analyze both the pre-developed and postdeveloped conditions, and the following results were generated for Type III, 24-hour storm events:

	CN	2-yr (cfs)	10-yr (cfs)	25-yr (cfs)	50-yr (cfs)	100-yr (cfs)
Pre-developed:	92	9.1	14.2	17.7	19.9	21.9
Post-Developed:	92	8.8	13.6	17.1	19.3	21.5

Total drainage area to Pond 1: +/-4.2 acres

Per the table above, the stormwater discharge for the post-developed conditions from the revised Pond 1 are slightly less than the pre-developed conditions.

Please refer to the photos below, and attached supporting documentation. If you have any questions or need more information, please feel free to reach me by email (<u>chris.akers@kimley-horn.com</u>) or by phone at 615-476-4764.

Sincerely, Chris Akers, Project Manager

Page 3

Photographs	Observations
<image/>	Southern portion of hospital campus with subject wetland (image taken from internal front drive).
Photographs	Observations
<image/>	East elevation of hospital building where Radiation Oncology addition is proposed (image taken from internal front drive). Construction activity from current ICU Med/ Surg Stepdown project.

Page 4


<image/>	Southern portion of hospital campus with subject wetland (image taken from internal ambulance/ ED drive).
<section-header></section-header>	Observations Existing brick canopy at Patient Discharge to be removed. Construction activity from current ICU Med/ Surg Stepdown project.

Page 5



Details

Property		Ownership	Valuation	
Location Map-Lot Vision Account N	333 BORTHWICK AVE 0240-0002-0001 Jumber 35555	Owner HCA HEALTH SVC OF NH INC D/B/A PRH 32902 C/O DUCHARME MCMILLEN & ASSOC AddressPO BOX 80610, INDIANAPOLIS, IN 46280	Total Last Sale Book/Page	\$86,709,000 \$0 on 2784/1340
Land Parcel Area (AC)	20.87	Zoning Zoning OR		





February 21, 2022

Kimley-Horn and Associates, Inc. 10 Lea Avenue, Suite 400 Nashville, TN 37210

404 Wyman Street, Suite 385 Waltham, MA 02451

RE: Agent Authorization

To Whom It May Concern:

Be advised that I am the Chief Executive Officer of the Portsmouth Regional Hospital located at 333 Borthwick Ave, Portsmouth, NH 03801. I am an authorized agent to the owners of HCA Health Services of New Hampshire, Inc. dba Portsmouth Regional Hospital. As the authorized agent, I hereby authorize and empower:

Kimley-Horn and Associates, Inc. to act as agent/ representative to communicate and submit required information as necessary in obtaining site-related approvals and permits for the proposed Radiation Oncology Addition project located at 333 Borthwick Ave, Portsmouth, NH 03801.

۲

Owner's Signature Dean M. Carucci, CEO

333 Borthwick Avenue Portsmouth, NH 03801 Phone: 436-5110 1-800-685-8282 www.portsmouthhospital.com

SITE CIVIL PLANS FOR PORTSMOUTH REGIONAL HOSPITAL **RADIATION ONCOLOGY ADDITION** 333 BORTHWICK AVENUE, PORTSMOUTH, NH 03801

SITE DATA	FABLE	
OWNER OF RECORD		ERVICES OF NH PRH 32902
SITE ADDRESS		HWICK AVE, ITH, NH 03801
SITE AREA	± 20.	.87 AC
DISTURBANCE LIMITS W/ THIS PROJECT	± 0.	.7 AC
TAX MAP & LOT	TAX MAP	240, LOT 2-1
ZONING	OR - OFFIC	E RESEARCH
SETBACKS	REQUIRED	PROPOSED
FRONT YARD SETBACK	50'-0"	±40'
REAR YARD SETBACK	50'-0"	±157'
SIDE YARD SETBACK	75'-0"	±71' * (EXISTING)
MIN. OPEN SPACE ON A LOT	30%	±38.3%
MAX BUILDING COVERAGE	30%	± 20.1%
BUILDING DA	TA	
	EXISTING	PROPOSED ADDITION
HOSPITAL BEDS	233	0
HOSPITAL/ MOB FLOOR PLATE	±173,916 SF	± 8,700 SF
HOSPITAL GROSS AREA	±427,495 SF	± 8,870 SF
MEDICAL OFFICE BUILDING GROSS AREA (ATTACHED TO HOSPITAL BUILDING)	±46,665 SF	0 SF
BUILDING HEIGHT	± 65'-4"	± 14'-8"

PARKING SUMMARY						
	EXISTING	DEMOLISHED	PROPOSED	NET RESULT		
ONSITE STANDARD SPACES	754	11	2	745		
ONSITE ACCESSIBLE (INCLUDING VAN ACCESSIBLE)	29	4	6	31		
OFFSITE STANDARD SPACES*	0	0	490	490		
OFFSITE ACCESSIBLE (INCLUDING VAN ACCESSIBLE)*	0	0	11	11		
TOTAL				1277		


*PER SATELLITE PARKING LOT DRAWINGS PREPARED BY TIGHE & BOND

REFERENCE PLANS

- "LOT LINE REVISION PLAN FOR PORTSMOUTH HOSPITAL OFFICE BUILDING ASSOCIATION, ISLINGTON WOOD, LLC AND HCA REALTY INC. (TAX MAP 234, LOTS 7-4A & 7-4B) (TAX MAP 240, LOT 2-2) BORTHWICK AVENUE EXTENSION PORTSMOUTH. NEW HAMPSHIRE DATED JAN 13, 2006 PREPARED BY DOUCET SURVEY, INC., R.C.R.D.
- PLAN #D-33642 "TOPOGRAPHIC PLAN" AT PORTSMOUTH REGIONAL HOSPITAL FOR HCA HEALTH SERVICES OF NH, INC. DATED OCTOBER 10, 2007 BY DOUCET SURVEY.
- "SIDEWALK SITE PLAN" FOR PORTSMOUTH REGIONAL HOSPITAL FOR HCA HEALTH SERVICES OF NH, INC. DATED OCTOBER 22, 2003 BY MILLETTE, SPRAGUE & COLWELL
- "SITE PLAN" FOR PORTSMOUTH REGIONAL HOSPITAL FOR HCA HEALTH SERVICES OF NH, INC. DATED AUGUST 19, 2002 BY MILLETTE, SPRAGUE & COLWELL SHEET 2 OF 3.
- JURISDICTIONAL WETLANDS WERE DELINEATED BY NHSC, INC. ON SEPTEMBER 25, 2007 IN ACCORDANCE WITH THE 1987 CORPS OF ENGINEERS WETLANDS DELINEATION MANUAL, AS REQUIRED BY THE NH DES WETLANDS BUREAU.
- **"TOPOGRAPHIC WORKSEET OF THE POWERLINES BY ISLINGTON &** BORTHWICK AVE." PREPARED BY EASTERN TOPOGRAPHIC FOR DOUCET SURVEY, DATED SEPT 25, 2007.
- "PORTSMOUTH REGIONAL HOSPITAL PHASE 1 ADDITIONS AND RENOVATIONS" BY APPLEDORE ENGINEERING, INC., DATED APRIL 1.2008.
- JURISDICTIONAL WETLANDS DELINEATION BY GOVE
- ENVIRONMENTAL SERVICES, INC. DATED OCTOBER 2019. TOPOGRAPHIC SURVEY BY JAMES VERRA & ASSOCIATES, INC.
- DATED 10/2019). SHEETS C-2 AND C-2A OF "PORTSMOUTH HOSPITAL EXPANSION" BY APPLEDORE ENGINEERING, DATED 8/4/11. "REVISED TO ADD REAR PARKING"

Know what's **below Call** before you dig

TECHNICAL ADVISORY COMMITTEE: MAY 23, 2022



SHEET NUMBER
C0.00
C0.01
C0.02
C1.00
C2.00
C3.00
C3.01
C3.02
C4.00
C4.01
C5.00
C6.00
C7.00
C7.01
L1.00

PROJECT DESIGN TEAM

ARCHITECT

GOULD TURNER GROUP, P.C. 615 3RD AVENUE SOUTH, SUITE 700 NASHVILLE, TN 37210 PHONE: (615) 254-1500 CONTACT: CHRIS DUMONT, AIA

SURVEY

JAMES VERRA & ASSOCIATES, INC. 101 SHATTUCK WAY, SUITE 8 NEWINGTON, NH 03801 PHONE: (603) 436-3557 CONTACT: JIM VERRA, LLS

CIVIL ENGINEER

KIMLEY-HORN AND ASSOCIATES, INC. 404 WYMAN STREET, SUITE 385 WALTHAM, MA 02451 PHONE: (781) 328-0676 CONTACT: MATTHEW HAMBY

ENVIRONMENTAL

GOVE ENVIRONMENTAL SERVICES, INC 8 CONTINENTAL DR, UNIT H EXTER, NH 03833 PHONE: (603) 778-0654 CONTACT: BRENDEN WALDEN

UTILITY CONTACTS

WATER/ SANITARY SEWER

PORTSMOUTH DEPT OF PUBLIC WORKS MIKE JENKINS 680 PEVERLY HILL ROAD PORTSMOUTH, NH 03801 PHONE: (603) 427-1530

NORTHERN UTILITIES, INC. JEFF INGLISH 325 WEST ROAD PORTSMOUTH, NH 03801 PHONE (603) 436-0310

TELEPHONE/ CABLE CONSOLIDATED COMMUNICATIONS 1575 GREENLOAD ROAD GREENLAND, NH 03840 PHONE: (800) 240-5019

M,P,E & T CONSULTANTS

I.C. THOMASSON ASSOCIATES, INC 2950 KRAFT DRIVE, SUITE 500 NASHVILLE, TN 37204 PHONE: (615) 346-3400 CONTACT: BOYD JOHNSON

STRUCTURAL ENGINEER

STANLEY D. LINDSEY & ASSOCIATES, LTD. 750 OLD HICKORY BLVD, BLD 1, SUITE 175 BRENTWOOD, TN 37027 PHONE: (615) 320-1735 CONTACT: MARK HILNER

ELECTRIC

PUBLIC SERVICES OF NH/ EVERSOURCE WAYNE BROOKS 1700 LAFAYETTE ROAD PORTSMOUTH, NH 03801 PHONE:(800) 662-7764

NATURAL GAS

Sheet List Table							
	SHEET TITLE						
	COVER SHEET						
	GENERAL NOTES						
	SURVEY BY OTHERS						
	EXISTING CONDITIONS - OVERALL						
	SITE DEMOLITION PLAN						
	EROSION CONTROL PLAN - PHASE 1						
	EROSION CONTROL PLAN - PHASE 2						
	EROSION CONTROL DETAILS						
	SITE LAYOUT - OVERALL						
	SITE LAYOUT - ENLARGEMENT						
	GRADING & DRAINAGE PLAN						
	SITE UTILITY PLAN						
	SITE DETAILS						
	SITE DETAILS						
	LANDSCAPE PLAN						

TION JAMES SCHALL No. 15914 0 0 7 0 7 7 0 DESIGNED BY: ZCN DRAWN BY: ZCN CHECKED BY: MEH 05/23/202 DATE: KIMLEY-HORN PROJECT NO. 118252004 COVER SHEET C0.00

CONTRACTOR RESPONSIBILITIES:

- PRIOR TO CONSTRUCTION THE CONTRACTOR SHALL BE RESPONSIBLE FOR:
- THE CONTRACTOR SHALL VERIFY ALL PROPOSED AND EXISTING CONDITIONS INCLUDING Α. UTILITIES (INVERTS, CONNECTIONS, MATERIALS, ETC.) AND DIMENSIONS WITHIN THE LIMITS OF WORK PRIOR TO THE START OF CONSTRUCTION.
- REFER TO ARCHITECTURAL DRAWINGS FOR DETAILED BUILDING INFORMATION. Β.
- THE CONTRACTOR IS RESPONSIBLE FOR ALL NOTIFICATIONS AND LIAISONS WITH UTILITY C. COMPANIES DURING THE PROCESS OF LOCATING, RELOCATING, AND TYING INTO PUBLIC UTILITIES.
- PRIOR TO COMMENCING LAND DISTURBANCE ACTIVITY, THE LIMITS OF LAND D. DISTURBANCE SHALL BE CLEARLY AND ACCURATELY DEMARCATED WITH STAKES, RIBBONS, OR OTHER APPROPRIATE MEANS. THE LOCATION AND EXTENT OF ALL AUTHORIZED LAND DISTURBANCE SHALL OCCUR INSIDE THE APPROVED LIMITS INDICATED ON THE APPROVED PLANS.
- 2. DURING CONSTRUCTION:
 - THE CONTRACTOR SHALL BE RESPONSIBLE FOR DEVIATIONS FROM THESE PLANS AND Α. SPECIFICATIONS WITHOUT PRIOR WRITTEN CONSENT OF THE ENGINEER MAY CAUSE THE WORK TO BE UNACCEPTABLE.
 - R THE CONTRACTOR SHALL USE MATERIALS AND EMPLOY CONSTRUCTION METHODS IN ORDER TO COMPLY WITH THE DRAWINGS AND SPECIFICATIONS. WHERE A CONFLICT OCCURS, THE STRICTEST DESIGN SHALL GOVERN. THE ENGINEER'S REVIEW OF SHOP DRAWINGS, PRODUCT DATA, ETC., DOES NOT RELIEVE THE CONTRACTOR FROM COMPLYING WITH THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL INFORM THE ENGINEER IN WRITING OF ANY SPECIFIC DEVIATIONS AND OBTAIN ENGINEER'S WRITTEN APPROVAL OF THE SPECIFIC DEVIATION.
 - C. IT IS SOLELY THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL APPLICABLE SAFETY CODES AND REGULATIONS DURING ALL PHASES OF CONSTRUCTION.
 - ALL CONSTRUCTION MUST CONFORM TO THE STANDARDS, SPECIFICATIONS, AND CODES D. OF THE GOVERNING MUNICIPALITIES.
 - CONSTRUCTION SHALL MEET ALL CURRENT STANDARDS SET FORTH IN THE AMERICANS F WITH DISABILITIES ACT.
 - F. IF THE CONTRACTOR DAMAGES ANY EXISTING UTILITIES DURING CONSTRUCTION, HE SHALL, AT HIS OWN EXPENSE, REPLACE OR REPAIR THE UTILITIES TO ORIGINAL CONDITION AND QUALITY AS APPROVED BY THE OWNER AND REPRESENTATIVE OF THE APPROPRIATE UTILITY COMPANY.
 - G. SUFFICIENT BARRICADES, LIGHTS, SIGNS, AND OTHER TRAFFIC CONTROL METHODS IN ACCORDANCE WITH GOVERNING ORDINANCES MAY BE NECESSARY FOR THE PROTECTION AND SAFETY OF THE PUBLIC. SAID CONTROL DEVICES SHALL BE PER THE MANUAL OF TRAFFIC CONTROL DEVICES, M.U.T.C.D., CURRENT EDITION, AND SHALL BE PROVIDED AND MAINTAINED THROUGHOUT CONSTRUCTION.
 - TRAFFIC CONTROLS AND OTHER WARNING DEVICES SHALL BE INSTALLED PRIOR TO THE н COMMENCEMENT OF ANY WORK ON CITY, COUNTY, OR NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION ROADS. THEY SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION AND SHALL REMAIN IN PLACE UNTIL THE CONCLUSION OF ALL WORK.
 - ALL WARNING DEVICES SHALL BE EITHER TYPE I BARRICADES OR DRUMS WITH WARNING LIGHTS ON EVERY OTHER DEVICE. THEY SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), CURRENT EDITION, AND PORTSMOUTH STANDARDS FOR COLOR, SIZE, REFLECTIVITY, HEIGHT, AND PLACEMENT
 - FIRE DEPARTMENT ACCESS SHALL BE MAINTAINED AT ALL TIMES.
 - Κ. CONTRACTOR SHALL SHORE AND BRACE ALL EARTH, FORMS, CONCRETE, STEEL, WOOD, AND MASONRY TO RESIST GRAVITY, EARTH, WIND, THERMAL, CONSTRUCTION, AND MISCELLANEOUS LOADS DURING CONSTRUCTION.
 - ON-SITE BURIAL OF DEBRIS IS PROHIBITED.
 - M. UNLESS OTHERWISE NOTED THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF ALL FABRICATED MATERIALS TO THE ENGINEER. DESIGN DOCUMENTS SHALL NOT BE REPRODUCED AS SHOP DRAWINGS.
 - IN CASE OF UNFORESEEN CONSTRUCTION COMPLICATIONS OR DISCREPANCIES, THE N CONTRACTOR IS TO IMMEDIATELY NOTIFY THE ENGINEER IN WRITING.
 - Ο. ALL REQUIRED TESTING REPORTS SHALL BE AVAILABLE AT THE JOB SITE.
 - Ρ. AS-BUILT DRAWINGS OF ROADWAYS, STORM DRAINS, SANITARY SEWER AND WATER LINES, FIELD APPROVAL BY THE ENGINEER, AND ALL APPLICABLE BONDS ARE REQUIRED PRIOR TO FINAL ACCEPTANCE BY THE OWNER.
 - Q. CONTRACTOR SHALL MAINTAIN CONTINUOUS UTILITY SERVICE TO ALL EXISTING BUILDINGS THROUGHOUT CONSTRUCTION UNLESS APPROVAL FOR SERVICE INTERRUPTION IS OBTAINED FROM THE OWNERS IN ADVANCE.
 - THE CONTRACTOR SHALL VERIFY EXISTING CONDITIONS TO ENSURE THAT THE NEW R WORK SHALL FIT INTO THE EXISTING SITE IN THE MANNER INTENDED AND AS SHOWN ON THE DRAWINGS. SHOULD ANY CONDITIONS EXIST THAT ARE CONTRARY TO THOSE SHOWN ON THE DRAWINGS, THE CONTRACTOR SHALL NOTIFY THE OWNER'S REPRESENTATIVE PRIOR TO PERFORMING ANY WORK IN THE AREA INVOLVING DIFFERENCES. NOTIFICATION SHALL BE IN THE FORM OF A DRAWING OR SKETCH INDICATING FIELD MEASUREMENTS AND NOTES RELATING TO THE AREA.
 - ANY FOREIGN ITEM FOUND DURING CONSTRUCTION IS THE PROPERTY OF THE OWNER S THIS INCLUDES, BUT IS NOT LIMITED TO, PRECIOUS METALS, COINS, PAPER CURRENCY, ARTIFACTS AND ANTIQUITIES.
 - т THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE DONE TO THE PREMISES OR ADJACENT PREMISES, OR INJURIES TO THE PUBLIC DURING THE CONSTRUCTION OF THE WORK, WHETHER CAUSED BY HIMSELF, HIS SUBCONTRACTORS, OR THE CARELESSNESS OF ANY OF HIS EMPLOYEES.
 - U. THE CONTRACTOR SHALL FURNISH, INSTALL AND MAINTAIN ALL NECESSARY TEMPORARY WORKS FOR THE PROTECTION OF THE WORK AND THE PUBLIC, INCLUDING BARRICADES, WARNING SIGNS, LIGHTS, ETC.
 - V THE CONTRACTOR ACKNOWLEDGES & AGREES THAT THE WORK IS ENTIRELY AT HIS RISK UNTIL SITE IS ACCEPTED, AND HE WILL BE HELD RESPONSIBLE FOR ITS SAFETY BY THE OWNER. THE CONTRACTOR WILL INDEMNIFY THE OWNER & OWNER'S REPRESENTATIVE FROM LIABILITY AT THE SITE THROUGHOUT THE CONSTRUCTION PROCESS.
 - W. THE CONTRACTOR SHALL GIVE ALL NECESSARY NOTICES AND OBTAIN ALL PERMITS AND PAY ALL LEGAL FEES. HE SHALL ALSO COMPLY WITH ALL CITY, COUNTY AND STATE BUILDING LAWS, ORDINANCES OR REGULATIONS RELATING TO BUILDING SIDEWALKS, STREETS, BLASTING, PUBLIC INFRASTRUCTURE, STORMWATER REGULATIONS, ETC.
 - THE CONTRACTOR IS TO CHECK AND VERIFY ALL MEASUREMENTS, LEVELS, ETC. BEFORE ORDERING MATERIALS AND PROCEEDING WITH THE WORK, AND IS TO BE RESPONSIBLE FOR THE SAME.

CONTRACTOR RESPONSIBILITIES (CONT.):

- Y. THE CONTRACTOR WILL BE HELD RESPONSIBLE FOR THE DAMAGE OR LOSS OF ANY REFERENCE POINTS AND HUBS DURING THE CONSTRUCTION OF HIS WORK, AND SHALL BEAR THE COST OF REPLACING SAME.
- Z. CARE SHALL BE TAKEN TO PROTECT ANY UTILITIES, TREES, ETC. WHICH ARE TO REMAIN AND NOT TO BE DISTURBED BY THE CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGES TO SUCH PROPERTY.

DEMOLITION INFORMATION:

NOTIFICATIONS

THE CONTRACTOR SHALL NOTIFY THE OWNER AND CITY INSPECTOR(S) 24 HOURS PRIOR TO ANY DEMOLITION OR CONSTRUCTION.

- DISPOSAL GUIDELINES:
- ONLY ITEMS SPECIFICALLY NOTED TO BE DEMOLISHED SHALL BE REMOVED FROM THE Α. SITE.
- REMOVE EXISTING PAVED AREAS AS SHOWN INCLUDING DRIVEWAYS, SIDEWALKS, PARKING AREAS, SERVICE AREAS, EQUIPMENT PADS, AND ALL MISCELLANEOUS PAVING.
- ALL DEBRIS RESULTING FROM DEMOLITION SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY BY THE CONTRACTOR IN ACCORDANCE WITH LOCAL STATE AND FEDERAL REGULATIONS. BACKFILL ALL TRENCHES AND EXCAVATIONS RESULTING FROM DEMOLITION.
- ALL DEMOLISHED MATERIAL BECOMES THE PROPERTY OF THE CONTRACTOR UNLESS D OTHERWISE NOTED.
- TREE PROTECTION GUIDELINES:

PROTECT ALL EXISTING TREES NOTED "TO REMAIN" AND ALL ITEMS TO BE TURNED OVER TO THE OWNER DURING DEMOLITION. TAKE ALL NECESSARY PRECAUTIONS AND PROTECTIVE MEASURES. ANY EXISTING ITEMS TO BE TURNED OVER TO THE OWNER WHICH ARE DAMAGED DURING DEMOLITION SHALL BE REPAIRED AT NO ADDITIONAL COST TO THE OWNER. TREES WHICH ARE DAMAGED WILL BE REPLACED OR REIMBURSED AT A RATE TO BE DETERMINED BY THE OWNER.

UTILITIES:

3.

- A. PRIOR TO REMOVING OR ABANDONING ANY UTILITY THE CONTRACTOR SHALL VERIFY THAT NO UPSTREAM SERVICE WILL BE TERMINATED. THE CONTRACTOR SHALL INFORM THE ENGINEER IN WRITING OF ANY TERMINATION NOT SHOWN ON THE PLANS.
- ALL ABANDONED WATER LINES, STORM SEWER PIPE, SANITARY SEWER PIPES, GAS Β. LINES, OR ANY OTHER ABANDONED UNDERGROUND UTILITY SHALL BE ABANDONED IN PLACE UNLESS NOTED OTHERWISE.

SITE INFORMATION:

1. THE FOLLOWING ARE APPLICABLE TO ALL CIVIL DOCUMENTS:

- A. WHERE A DETAIL SECTION, TYPICAL SECTION, OR A NOTE IS SHOWN FOR ONE CONDITION, IT SHALL APPLY FOR ALL LIKE OR SIMILAR CONDITIONS, UNLESS OTHERWISE NOTED ON THE PLANS.
- EXISTING AND PROPOSED CONTOURS ARE AT ONE (1) FOOT INTERVALS.
- ALL DIMENSIONS ARE TO FACE OF CURB UNLESS OTHERWISE NOTED.
- ALL PIPE LENGTHS SPECIFIED IN THESE PLANS ARE THE HORIZONTAL DISTANCE AND D ARE SHOWN FOR REFERENE ONLY. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE ACTUAL LENGTHS BASED ON PROPOSED PIPE SLOPE.
- PIPE LENGTHS IN PLANS ARE MEASURED FROM CENTER OF STRUCTURE TO CENTER OF STRUCTURE UNLESS OTHERWISE NOTED.

EROSION AND SEDIMENT CONTROL INFORMATION:

1. COMPREHENSIVE:

- THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION AND SEDIMENT CONTROL MEASURES AND PRACTICES PRIOR TO OR CONCURRENT WITH LAND-DISTURBING ACTIVITIES.
- PROVISIONS TO PREVENT EROSION OF SOIL FROM THE SITE SHALL BE AT A MINIMUM IN В CONFORMANCE WITH THE REQUIREMENTS OF THE NEW HAMPSHIRE EROSION AND SEDIMENT CONTROL HANDBOOKS. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.
- C. FAILURE TO INSTALL, OPERATE, OR MAINTAIN ALL EROSION CONTROL MEASURES WILL RESULT IN ALL CONSTRUCTION BEING STOPPED ON THE JOB SITE UNTIL SUCH MEASURES ARE CORRECTED BACK TO THE STANDARDS SPECIFIED IN THE NEW HAMPSHIRE EROSION AND SEDIMENT CONTROL HANDBOOKS, CURRENT EDITION.
- D. EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.
- F EROSION CONTROL DEVICES SHALL BE INSTALLED PRIOR TO LAND DISTURBANCE. THE LOCATION OF SOME OF THE EROSION CONTROL DEVICES MAY HAVE TO BE ALTERED FROM THAT SHOWN ON THE APPROVED PLANS IF DRAINAGE PATTERNS DURING CONSTRUCTION ARE DIFFERENT FROM THE FINAL PROPOSED DRAINAGE PATTERNS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ACCOMPLISH EROSION CONTROL FOR ALL DRAINAGE PATTERNS CREATED AT VARIOUS STAGES DURING CONSTRUCTION. ANY DIFFICULTY IN CONTROLLING EROSION DURING ANY PHASE OF CONSTRUCTION SHALL BE REPORTED TO THE ENGINEER IMMEDIATELY.
- F THE CONSTRUCTION OF THE SITE WILL COMMENCE WITH THE INSTALLATION OF EROSION CONTROL MEASURES SUFFICIENT TO CONTROL SEDIMENT DEPOSITS AND EROSION. ALL SEDIMENT CONTROL WILL BE MAINTAINED UNTIL ALL UPSTREAM GROUND WITHIN THE CONSTRUCTION AREA HAS BEEN COMPLETELY STABILIZED WITH PERMANENT VEGETATION AND ALL ROADS/DRIVEWAYS HAVE BEEN PAVED.
- CONSTRUCTION EXITS SHALL BE CONSTRUCTED AT EACH POINT OF ENTRY OR EXIT G. FROM THE SITE AND SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOW OF MUD ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH STONE AS CONDITIONS DEMAND, REPAIR, AND/OR CLEANOUT OF ANY STRUCTURES USED TO TRAP SEDIMENT. ALL MATERIALS SPILLED, DROPPED, WASHED, OR TRACKED FROM VEHICLES OFF SITE ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY. ACCESS POINTS PROTECTED WITH A CONSTRUCTION EXIT SHALL BE OTHERWISE BARRICADED UNTIL THE SITE IS STABILIZED.

CONCRETE INFORMATION (SITE WORK ONLY):

PRODUCT CRITERIA

- A. UNLESS OTHERWISE NOTED CEMENT SHALL BE TYPE I OR III CONFORMING TO ASTM C150. AGGREGATES SHALL BE NORMAL WEIGHT CONFORMING TO ASTM C33.
- CONCRETE SHALL CONFORM TO ACI BUILDING CODE (318-89). UNLESS NOTED В CONCRETE SHALL BE NORMAL WEIGHT AND HAVE A 28 DAY COMPRESSIVE STRENGTH OF 3,500 P.S.I.
- SLUMP SHALL BE 3" TO 5" FOR REGULAR MIX. LARGER SLUMP SHALL BE PERMITTED WITH WATER REDUCING ADMIXTURES AND WRITTEN CONSENT OF THE ENGINEER.
- THE RELATIONSHIP BETWEEN MAXIMUM AGGREGATE SIZE TO MINIMUM AMOUNT OF D. CEMENT IN CONCRETE PAVEMENT (LB. PER C.Y. OR MIX) SHALL BE AS FOLLOWS: 1" - 520, 3/4" - 540, 1/2" - 590, 3/8" - 610.

2. CURING CRITERIA:

- Α. CONCRETE CURING SHALL COMPLY WITH ACI 308. CURING PROCESS SHALL START IMMEDIATELY FOLLOWING INITIAL SET. CURING SHALL BE BY CURING COMPOUND.
- CONCRETE EXPOSED TO THE WEATHER SHALL BE AIR-ENTRAINED IN ACCORDANCE Β. WITH ACI 318-89 TABLE 4.1.1. NORMAL WEIGHT CONCRETE SLABS SHALL HAVE AIR CONTENT IN ACCORDANCE WITH ACI 302.IR-89 TABLE 5.2.7A.
- C. HOT WEATHER CONCRETING SHALL COMPLY WITH ACI 305. NO CONCRETE ABOVE 90 DEGREES FAHRENHEIT SHALL BE POURED. LOWER CONCRETE TEMPERATURE BY COOLING WATER AND AGGREGATE. FORMS, STEEL, AND SUBGRADE SHALL BE SPRINKLED WITH COLD WATER. AFTER FINISHING CONCRETE USE LIGHT FOG SPRAY UNTIL CURING COMPOUND IS USED.
- D. COLD WEATHER CONCRETING SHALL COMPLY WITH ACI 306. SPECIAL MATERIAL PROCEDURES SHALL BE PROVIDED DURING PLACING AND CURING OF CONCRETE BELOW 40 DEGREES FAHRENHEIT.
- CURING, HOT, AND COLD WEATHER CONCRETING PROCEDURES ARE ONLY GIVEN AS A F GUIDE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PREVENT CONCRETE DAMAGE AND CRACKS. DAMAGED OR CRACKED CONCRETE WILL NOT BE ACCEPTED.

REINFORCING STEEL INFORMATION (SITE WORK ONLY):

PRODUCT CRITERIA

- REINFORCING STEEL SHALL CONFORM TO ASTM A-615, GRADE 60 AND GRADE 40 FOR #3 Α. AND SMALLER BARS. MINIMUM LAP 48" DIAMETER.
- WELDED WIRE FABRIC SHALL CONFORM TO ASTM A-185, MINIMUM LAP SHALL BE 8". R
- REINFORCING THAT IS WELDED SHALL BE WELDABLE TYPE AND CONFORM TO ASTM C. A-706

PAVEMENT INFORMATION:

- 1. PAVEMENT:
 - ALL MATERIALS, EQUIPMENT, METHODS OF CONSTRUCTION, AND WORKMANSHIP SHALL Α. CONFORM TO THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION. NHDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.
 - SEE PAVEMENT DETAILS ON CONSTRUCTION DOCUMENTS FOR SPECIFIC DESIGN INFORMATION AND REQUIREMENTS.
 - ALL CURB AND GUTTER TO BE 24" AND CONSTRUCTED OF 3000 P.S.I. CONCRETE UNLESS OTHERWISE NOTED.
- SIGNING AND STRIPING:
- SIGNING AND STRIPING TO BE PROVIDED BY THE CONTRACTOR ACCORDING TO THE DRAWINGS AND SPECIFICATIONS.
- B. ALL STRIPING TO BE THERMOPLASTIC UNLESS OTHERWISE NOTED.

STORM SEWER NOTES:

- REINFORCED CONCRETE PIPE SHALL BE RCP CLASS III UNLESS OTHERWISE NOTED WITH BELL-AND-SPIGOT AND GASKETED JOINTS WITH ASTM C 443 RUBBER GASKETS.
- 2. FILL HEIGHTS OVER 13' REQUIRE CLASS IV RCP STORM PIPE.
- 3. STORM INLETS SHALL BE PRECAST IN ACCORDANCE WITH PORTSMOUTH PUBLIC WORKS SPECIFICATIONS WHICH MEET OR EXCEED ASTM C 478.
- 4. ALL MANHOLE FRAMES AND COVERS ARE TO BE PER PORTSMOUTH PUBLIC WORKS STANDARD DETAIL FOR DIMENSIONS AND MATERIALS AND AS BELOW IF NOT OTHERWISE INDICATED. FERROUS; 24-INCH (610-MM) ID BY 7- TO 9-INCH (175- TO 225-MM) RISER WITH 4-INCH- (102-MM-) MINIMUM WIDTH FLANGE AND 26-INCH- (660-MM-) DIAMETER COVER. INCLUDE INDENTED TOP DESIGN WITH LETTERING CAST INTO COVER, USING WORDING EQUIVALENT TO "STORM SEWER."
- 5. MATERIAL: GRAY IRON ASTM A48 CLASS 30 UNLESS OTHERWISE INDICATED.
- ALL HDPE PIPE SHALL BE CORRUGATED HIGH DENSITY POLYETHYLENE SMOOTH INTERIOR PIPE. HDPE PIPE SHALL CONFORM TO ASTM D3350 WITH SOIL TIGHT JOINTS.
- 7. ALL HDPE SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS AND AASHTO SECTION 30.
- 8. CONTRACTOR TO PROVIDE AND INSTALL MANUFACTURER RECOMMENDED FITTINGS ON RCP CONNECTIONS TO HDPE STRUCTURES.
- 9. REFER TO PIPE CHART FOR CASTING TYPES. INSTALL REDUCERS AS NECESSARY PER MANUFACTURER'S SPECIFICATIONS TO ACCOMMODATE LARGER INLET SIZES.
- 10. FOLLOW CONSTRUCTION PLANS AND MANUFACTURER DETAILS, SPECIFICATIONS, AND INSTALLATION INSTRUCTION AS INCLUDED WITHIN THE PLANS AND PROVIDED BY MANUFACTURER FOR THE INSTALLATION OF WATER QUALITY AND DETENTION SYSTEMS.
- 11. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR ALL STORM SEWER PIPE, STRUCTURES, WATER QUALITY STRUCTURES, AND DETENTION STRUCTURES FOR ENGINEER AND OWNER APPROVAL PRIOR TO ORDERING MATERIALS.

CLEARING AND GRUBBING:

- ON THE PLANS. Β.
- C.

- F

GRADING NOTES:

- Α.
- R
- С RECOMMENDATIONS.
- D.
- LISTED IN THE BID DOCUMENTS.

G

- TESTS AS REQUIRED.
- SITE.
- ACTION TAKEN.
- Κ.
- М CONTRACTOR.
- PART OF THIS SPECIFICATION:

- SIEVE.
- STANDARD EFFORT
- MM) DROP.

PROVIDE POSITIVE DRAINAGE AWAY FROM BUILDINGS AT ALL LOCATIONS UNLESS Ο. OTHERWISE NOTED.

SHALL APPLY.

Q.

A. DO NOT EXCEED CLEARING AND GRUBBING LIMITS OF CONSTRUCTION LINES INDICATED

ALL AREAS OUTSIDE THE LIMITS OF CONSTRUCTION LINE SHALL NOT BE CROSSED BY HEAVY EQUIPMENT OR USED FOR STORING HEAVY EQUIPMENT OR MATERIALS.

NO EQUIPMENT SHALL BE STORED UNDER THE DRIP LINE OF TREES TO REMAIN.

DO NOT FALL ANY TREES OR PUSH PILES OF DEBRIS AGAINST ANY TREES TO REMAIN.

REMOVE ALL STUMPS, ROCKS, ASPHALT & CONCRETE DEBRIS, ETC. AND DISPOSE OFF SITE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

CONTACT ALL UTILITY AUTHORITIES WHO HAVE LINES WITHIN THE CLEARING AND GRUBBING LIMITS BEFORE STARTING WORK

ALL EROSION CONTROL SEDIMENT BARRIERS, SILT FENCES, AND TREE PROTECTION DEVICES SHALL BE INSTALLED PRIOR TO STARTING CLEARING AND GRUBBING.

AFTER STAKING IS COMPLETED. TREES WITHIN GRADING LIMITS TO BE SAVED WILL BE IDENTIFIED BY THE OWNER'S REPRESENTATIVE. FIELD CHANGES TO GRADING PLANS SHALL BE MADE FOR SMOOTH TRANSITION OF GRADES AROUND ALL TREES WHICH REQUITE TREE WELLS WITHIN THE GRADING LIMITS.

G. ALL CLEARING SHALL BE LIMITED TO AREAS TO BE GRADED WITHIN 15 CALENDAR DAYS.

TOPSOIL SHALL BE STORED ON SITE IN LOCATIONS APPROVED BY THE OWNER'S REPRESENTATIVE. DRAINAGE SHALL ROUT AROUND THESE TOPSOIL STOCKPILES FOR THE DURATION OF THE GRADING OPERATIONS. EROSION CONTROL MEASURES SHALL PREVENT THE LOSS OF TOPSOIL MATERIAL.

UNSUITABLE SOILS SHALL BE UNIFORMLY SPREAD ACROSS NON-STRUCTURAL FILL AREAS AND COVERED WITH TOPSOIL AND SEEDED.

FILL AREA SHALL BE PROOF-ROLLED WITH RUBBER-TIRED EQUIPMENT WITH A MINIMUM WEIGHT OF FIFTEEN TONS PRIOR TO BEGINNING FILL OPERATION. AREAS WHICH ARE SOFT OR UNSTABLE SHALL BE UNDERCUT UNTIL STABLE SOILS ARE FOUND. RE-COMPACTION OF THESE SOILS SHALL BE PER GEOTECHNICAL ENGINEER

CUT AREA SHALL BE PROOF-ROLLED AFTER FINAL SUBGRADE IS ACHIEVED IN THE SAME MANNER AS FILLED AREAS. SOFT OR UNSTABLE SOILS SHALL BE SCARIFIED TO A DEPTH OF 12" AND RE-COMPACTED PER GEOTECHNICAL ENGINEER RECOMMENDATIONS.

ALL GRADING SHALL BE COMPLETED TO THE LEVEL INDICATED BY THE SCOPE OF WORK

ELEVATIONS SHOWN ON THE PLANS IS THE FINISH GRADE ELEVATION.

GRADING SHALL BE SEQUENCED SO THAT BASE STONE IS PLACED WITHIN 10 CALENDAR DAYS PF ACHIEVING OPTIMUM SUBGRADE COMPACTION.

SOILS TESTING LABORATORY/ SOILS ENGINEER. CONTRACTOR WILL EMPLOY A QUALIFIED SOILS TESTING LABORATORY/ ENGINEER TO OBSERVE THIS WORK AND MAKE

HAVE EARTH BORROW FILL, AGGREGATE, AND TOPSOIL, AND STRUCTURAL FILL TESTED AND APPROVED BY DESIGNATED TESTING LABORATORY BEFORE MOVING IT TO THE JOB

CONTRACTOR SHALL OBSERVE PROOF-ROLLING OF AREAS WHERE BUILDING AND PAVING WILL BE LOCATED TO DETERMINE ADEQUACY OF SOIL COMPACTION AND IN-PLACE SOILS. OTHER AREAS WILL BE INSPECTED BY SOILS ENGINEER TO DETERMINE ADEQUACY IN THOSE AREAS. IF SOILS ARE NOT ADEQUATE TO BEAR WEIGHTS THAT WILL BE IMPOSED, TESTING LABORATORY WILL OBSERVE AND REPORT CORRECTIVE

TEST IN-PLACE SOIL AND FILLED AND COMPACTED AREAS. IF THESE ARE NOT ADEQUATE TO BEAR WEIGHTS IMPOSED, TESTING LABORATORY WILL ADVICE THE OWNER'S REPRESENTATIVE OF THEIR RECOMMENDATIONS. HE WILL DIRECT ANY CORRECTIVE MEASURES THAT ARE NECESSARY.

SOILS COMPACTION TESTING OF IN-PLACE AND FILLED AND COMPACTED AREAS WILL BE PERFORMED BY TESTING LABORATORY IN ACCORDANCE WITH THEIR REQUIREMENTS.

THE SOILS ENGINEER'S AND TESTING LABORATORY'S FEES WILL BE PAID BY THE

APPLICABLE SPECIFICATIONS FOR COMPACTED FILL: THE FOLLOWING CURRENT AMERICAN SOCIETY OF TESTING MATERIALS (ASTM) STANDARDS ARE HEREBY MADE

 D421-58, DRY PREPARATION OF SOIL SAMPLES FOR GRAIN-SIZE ANALYSIS AND DETERMINATION OF SOIL CONSTANTS. D422-63, STANDARD METHOD OF PARTICLE SIZE ANALYSIS OF SOILS.

• D1140-54, METHOD OF TEST FOR AMOUNT OF MATERIAL IN SOILS FINER THAN NO.200

 D698, METHOD FOR LABORATORY COMPACTION CHARACTERISTICS OF SOIL USING D1557-78, STANDARD TEST METHODS FOR MOISTURE-DENSITY RELATIONS OF SOILS


AND SOIL-AGGREGATE MIXTURES USING 10 LB. (4.54-KG) RAMMER AND 18-INCH (457


CONTRACTOR SHALL REVIEW THE SITE SPECIFIC GEOTECHNICAL REPORT PRIOR TO COMMENCING WITH GRADING OPERATIONS. WHERE CONFLICTS BETWEEN THE GRADING NOTES AND GEOTECHNICAL REPORT EXIST, THE MORE STRINGENT REQUIREMENT


CONTRACTOR IS RESPONSIBLE FOR DOCUMENTING WITH LOAD TICKETS, PHOTOGRAPHS, LOG BOOK, VIDEO RECORDING AND OTHER MEANS AS NECESSARY TO VERIFY THE INSTALLATION OF STORMWATER BEST MANAGEMENT PRACTICES REQUIRED BY THE LOCAL MUNICIPALITY AND JURISDICTION. AS-BUILT TOPOGRAPHY AND UTILITY PLANS HAVING BEEN PREPARED BY A QUALIFIED LAND SURVEYOR ARE REQUIRED TO BE SUBMITTED TO KIMLEY-HORN AT THE CONCLUSION OF THE PROJECT FOR VERIFICATION OF DESIGN INTENT. ANY MODIFICATIONS TO THE GRADING AND UTILITY SYSTEMS REQUIRED, NOT PREVIOUSLY APPROVED BY THE OWNER AND ENGINEER ARE THE RESPONSIBILITY OF THE CONTRACTOR.

 $\widehat{\boldsymbol{\mathbf{x}}}$

Ζ Ο Ζ Ο Δш C A sh Ш ע ⊲ $\sim \sim$ Ο _ Ω Οz S Ο ŽΣ S 0 M \square Ο







LINE BEARING <u>3</u> N 41°56'56" W 10.00 15 N 87°57'24" W 895.13 L16 N 41°56'56" W 229.05

HCA HEALTH SERVICES OF NEW HAMPSHIRE, INC

BRICK COLUMN COVERED FNTRANC

APPROXIMATE

SEWER

LOCATION

BORTHWICK AVENUE

TBM "A"

LARGE SURVEY NAIL

SET IN UTILITY POLE PSNH 317/3

ELEV=26.73

ACCESS

COVER

#333 MULTI LEVEL BRICK CONCRET

"S"

"Т"

6" METAL OUTLET

15" RCP

VA PUBLIC WAY

ТВМ "В

18" ACP

SMH DPW#519

 $\overline{\ }$ SEWER DETAIL

160 FEET

40 METERS

CUT X ON

ELEV=28.37

OP FLANGE BOLT

ELEV.=27.70

TRANSFORMER ON CONC. PAD

28.80

22.15

SEWER

DETAIL

SMH DPW#5482

\SMH DPW#5483

SMH DPW#5481

SEE NOTE 8

TBM "L

LARGE SURVEY NAIL

SET IN UTILITY POLE

PSNH 37

1.0' ABOVE GRADE ELEV=29.03

320.79

NOTES:

- OWNER OF RECORD. ..HCA HEALTH SERVICES OF NH., D/B/A PRH 32902 C/O DUCHARME MCMILLEN & ASSOCIATES .PO BOX 80610, INDIANAPOLIS, IN 46280 ADDRESS. DEED REFERENCE. .2784/1340 TAX SHEET / LOT .. .240-02-01 ..846,664 S.F 19.44 ACRES PARCEL AREA ...
- .OFFICE/RESEARCH (OR) ZONED: 2. MINIMUM LOT AREA.. 3 ACRÉS

FRONT YARD SETBACK 50' REAR YARD SETBACK......50'

- 3. THE RELATIVE ERROR OF CLOSURE WAS LESS THAN 1 FOOT IN 15,000 FEET.
- 4. THE LOCATION OF ALL UNDERGROUND UTILITIES SHOWN HEREON ARE APPROXIMATE AND ARE BASED UPON THE FIELD LOCATION OF ALL VISIBLE STRUCTURES (IE CATCH BASINS, MANHOLES, WATER GATES ETC.) AND INFORMATION COMPILED FROM PLANS PROVIDED BY UTILITY COMPANIES AND GOVERNMENTAL AGENCIES. ALL CONTRACTORS SHOULD NOTIFY, IN WRITING, SAID AGENCIES PRIOR TO ANY EXCAVATION WORK AND CALL DIG-SAFE @ 1-888-DIG-SAFE
- 5. HORIZONTAL DATUM: NAD 1983 ESTABLISHED BY SURVEY GRADE GPS OBSERVATION AND NGS "OPUS" SOLUTION. REFERENCE FRAME: NAD83 (2011)(EPOCH: 2010.0000), US SURVEY FOOT. VERTICAL DATUM: NAVD 1988. PRIMARY BENCHMARK: CITY OF PORTSMOUTH "ALBA"
- 6. ENGINEER OR CONTRACTOR TO VERIFY SITE BENCHMARKS BY LEVELING BETWEEN 2 BENCHMARKS PRIOR TO THE ESTABLISHMENT OF ANY GRADES OR ELEVATIONS. DISCREPANCIES ARE TO BE REPORTED TO JAMES VERRA AND ASSOCIATES. INC..
- 7. THE PARCEL SHOWN HEREON LIES WITHIN ZONE X (AREAS OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN) AS IDENTIFIED ON FLOOD INSURANCE RATE MAP. ROCKINGHAM COUNTY, NEW HAMPSHIRE, MAP NUMBER 33015C0260E, EFFECTIVE DATE MAY 17, 2005 BY THE FEDERAL EMERGENCY MANAGEMENT AGENCY.
- 8. LIMIT OF 300' EVERSOURCE ELECTRIC EASEMENT.
- 9. BRICK GENERATOR ENCLOSURE. TOP OF CONCRETE ELEV.=27.20
- 10. THE DELINEATION OF THE WETLANDS SHOWN HEREON WAS BY BRENDEN WALDEN NEW HAMPSHIRE CERTIFIED WETLAND SCIENTIST #297, GOVE ENVIRONMENTAL SERVICES, LLC., 8 CONTINENTAL DRIVE, UNIT H, EXETER, NH 03833.
- 11. THE SUBSURFACE UTILITIES SHOWN HEREON WERE IDENTIFIED BY WADE HANSEN, GROUND PENETRATING RADAR SYSTEMS, INC., 5217 MONROE STREET, SUITE A, TOLEDO, OHIO 43623.
- 12. AN EXISTING UNITIL GAS LINE SOUTHWESTERLY OF THE HOSIPTAL IN THE VICINITY OF THE LIBERTY MUTUAL PARCEL & A 6" CLDI WATER LINE IN THE SAME AREA WERE NOT FIELD LOCATED BY GROUND PENETRATING RADAR SYSTEMS, INC.


REFERENCE PLANS:

- 1. GAS LINE AS-BUILT EASEMENT AND CONSERVATION PLAN, PREPARED FOR HOSPITAL CORPROATION OF AMERICA, PORTSMOUTH, NH, DATED 10/31/85. RCRD PLAN #D-15830.
- 2. SCHILLER S/S-OCEAN ROAD S/S, 115 KV TRANSMISSION LINE #U181, MILE 4, PLANR-6775-A, DATED 7/10/2009, BY NORTHEAST UTILITIES, NOT RECORDED.
- 3 SUBDIVISION OF LAND. FRANETAL REALTY TRUST COMPAMY. OPTIONED TO LIBERTY MUTUAL INSURANCE COMPANY, PORTSMOUTH, NEW HAMPSHIRE, REVISED TO 2/19/71 RCRD PLAN #2190.


PURSUANT TO RSA 676:18,III AND RSA 672:14


I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN.


James Verra	11-19-2019
JAMES VERRA	DATE




	· · · · · · · · · · · · · · · · · · ·					
0	11-08-2019	FOR REVIEW	& COMM	ENT		JV
REV. NO.	DATE	DESCRIP	TION			APPR'D
	POR	TED EXISTING (333 BORTHWI SMOUTH, NI SESSOR'S PARCE for	CK EW	AVEN HAM	UE (PSHI	RE
	ICA HE	CALTH SERVICES	OF	NEW	HAMPS	HIRE
		RRA and ASSOCIA	TES	INC	DATE:	11-19-2019
JAI	WES VE	101 SHATTUCK WAY	IES,	<i>INC.</i>	JOB NO:	23834
		SUITE 8 NEWINGTON, N.H., 03801-7876			SCALE: 1" =	40'
		603-436-3557			DWG NAME:	23834
_	GTD PROJECT JV	GTD GTD DRAWN BY			PLAN NO:	23834
		©2019 by JAMES VERRA and ASSOCIATE			SHEET:	1 of 1










Drawing name: K:\NSH_LDEV\118252004 - portsmouth - cancer center - 2021\4-CADD\plansheets\C3.00 EROSION CONTROL PLAN.dwg C3.00 EROSION CONTROL PLAN - PHASE 1 May 23, 2022 1:36pm by: Zack.Newman













SITE DATA TABLE					PAVEMENT LEGEND				
OWNER OF RECORD	HCA HEALTH S INC D/B/A				DESCRIPTION	DET #/ SHT #			
SITE ADDRESS 333 BORTHWICK AVE, PORTSMOUTH, NH 03801			SIDEWALK CONCRETE	1 / C7.00		ONSITE STANDARI	O SPACES		
SITE AREA	± 20	.87 AC						ONSITE ACCESSIB	LE (INCLUDING VAN AC
DISTURBANCE LIMITS W/ THIS PROJECT	± 0 TAX MAP	.7 AC 240, LO [:]	Т 2-1		ASPHALT PAVEMENT	2 / C7.00		OFFSITE STANDAR	D SPACES*
ZONING	OR - OFFIC	1		► ► ► ►	CONCRETE PAVEMENT	3 / C7.00		OFFSITE ACCESSI	BLE (INCLUDING VAN A
SETBACKS	REQUIRED 50'-0"	 	POSED				-	TOTAL	
REAR YARD SETBACK	50'-0"		:157'		MOBILE IMAGING CONCRETE PAD	4 / C7.00	4	*PER SATELLITE PA	RKING LOT DRAWINGS
SIDE YARD SETBACK	75'-0"	±71'*	(EXISTING)		SPECIALITY SIDEWALK PAVEMENT	NOTE THIS SHEET			
MIN. OPEN SPACE ON A LOT	30% 30%		88.3% 20.1%]]		
BUILDING COVERAGE		Ţ,	20.1%						
	EXISTING		POSED	OF SCOFIELD LIT	RETE SURFACE WITH MEDIUM BROOM FII THOCHROME COLOR HARDENER, COLOR SEAL CURED, COLORED SURFACE WITH S	TO BE SELECTED			
HOSPITAL BEDS	233		0	SCOFIELD CURE SURFACES AND	SEAL-VOC MATTE FINISH CLEAR SEALAN APPLY MATERIALS PER MANUFACTURER	T. PREPARE			
HOSPITAL/ MOB FLOOR PLATE	±173,916 SF	± 8,	700 SF	SPECIFICATIONS	5. 				
HOSPITAL GROSS AREA	±427,495 SF	± 8,	870 SF					ĒOb	
MEDICAL OFFICE BUILDING GROSS AREA (ATTACHED TO HOSPITAL BUILDING)	±46,665 SF	() SF					30	0' EVERSOURCE ELECT
	± 65'-4"	±	14'-8"						100' WE
SITE LAYOUT NOTES									F
1. INSTALL CONCRETE JOINTS WHER AND DETAILS. ALIGN ON WALLS, B									
EVENLY SPACE BETWEEN ELEMEN PROVIDE EXPANSION JOINTS BET	VEEN CONCRETE	E							
PAVEMENT AND ALL VERTICAL ELE CURBS, ETC.). 2. ALL RADIUS ARE 3' UNLESS OTHEF	, , , , , , , , , , , , , , , , , , ,				V 17				+ · · ·
 LAYOUT ALL CURVES SMOOTHLY A CHANGES AT TANGENT POINTS. ALL DIMENSIONS ARE TO THE FAC 					V				
 ALL DIMENSIONS ARE TO THE FAC OTHERWISE NOTED. LAYOUT ALL ELEMENTS IN FIELD A 		:55		62.0	275				
OWNER'S REPRESENTATIVE FOR A BEGINNING ANY CONSTRUCTION. 6. CONTRACTOR TO TAKE ALL PRECA				62 (\downarrow · \downarrow · · ·		d	
AND AVOID SITE UTILITIES. ALL UT SHOWN ON DRAWING. VERIFY LOC	ILITIES ARE NOT			W "40	IL98 S			4	
CONSIDER SUCH WHEN ESTIMATIN 7. ALL LANDSCAPE ISLANDS SHALL E	E MOUNDED WIT	н						5	
TOPSOIL 4" ABOVE THE CURB LINE POSITIVE DRAINAGE. 8. ALL PAVEMENT MARKINGS AND SI		E			V V	¥ ¥		5	
INSTALLED PER THE MANUAL ON U CONTROL DEVICES, LATEST EDITIO 9. ALL PAVEMENT MARKINGS ON-SIT	ON.			. //:	A VIII	V N			
OTHERWISE NOTED. 10. SAW CUT LINES SHALL BE DONE IN	A STRAIGHT NE	AT			V				2'
LINE A MINIMUM OF 18" FROM THE PAVEMENT. 11. IF DURING CONSTRUCTION ACTIVI									5'
OF THE PRESENCE OF STATE AND PROTECTED PLANT AND/OR ANIMA	FEDERALLY							☆	
DISCOVERED, WORK SHALL COME STOP AND CITY OF PORTSMOUTH WITHIN TWO WORKING DAYS OF T	SHALL BE NOTIF	IED				- int	×''		
ANIMAL SPECIES FOUND ON THE S 12. PRIOR TO THE START OF THE CLEAR	SITE.	'N			\succ			R10	
GRUBBING, OR ANY SOIL DISTURB PORTSMOUTH STORMWATER MGM FOR A POTENTIAL SOIL EROSION A	/IT. AT (603) 427-1	530							
CONTROL, PRE-INSPECTION MEET 13. THE CONTRACTOR MUST PROVIDE	'ING. E A DEWATERING	i						RIO	
PLAN, IF APPLICABLE, TO CITY OF BUILDING AND SITE DEVELOPMEN 610-7243 FOR REVIEW PRIOR TO T	T DIVISION AT (60)3)		1					RIU R3
CONTROL MEASURES PRE-INSPEC 14. ALL CONDITIONS ON THIS PLAN SH	TION MEETING. IALL REMAIN IN								RIL
EFFECT IN PERPETUITY PURSUAN REQUIREMENTS OF THE SITE PLAN REGULATIONS.			/			NCRETE SIDEWALK		R3'	
15. RECORDING NOTE: • THIS SITE PLAN SHALL BE				/ /	FLI FLI	USH CONDITION, TY DETAIL 3/ C7	'	ò) s	
ROCKINGHAM COUNTY RE ALL IMPROVEMENTS SHO PLAN SHALL BE CONSTRU	WN ON THIS SITE ICTED AND	Ξ					6	John Walter	
MAINTAINED IN ACCORDA BY THE PROPERTY OWNE SHALL BE MADE TO THIS S	RS. NO CHANGE	S					8	F # 19	5
THE EXPRESS APPROVAL PORTSMOUTH PLANNING	OF THE DIRECTOR.					D CONCRETE			
16. TOPOGRAPHY AND EXISTING CON SURVEY PERFORMED BY JAMES V INC. ON 10/2019.						E GTOLT, TTT 1, ETAIL 6/ C7.01			FLAG TO R
17. FLOOD HAZARD ZONE: ZONE X (OL ANNUAL CHANCE FLOODPLAIN) PE			/))	ito de la companya de	A r		EXIS" GENE
#33015C0260F, DATED 01/29/2021. 18. HORIZONTAL DATUM IS BASED ON 19. VERTICAL DATUM BASED ON NAVE	NAD 1983.				\$	× ····	F F		TO R
20. JURISDICTIONAL WETLANDS DELIN ENVIRONMENTAL SERVICES, INC. 1	NEATED BY GOVE				PROPOSED ACCESSIBLE			Service of the servic	
2019 IN ACCORDANCE WITH: 2012 CORPS OF ENGINEE DELINEATIONS MANUAL, 1	RS WETLANDS				Ψ PARKING, TYP.; DETAIL 11/ C7.00	is the second se			R30'
ERDC/ EL TR-12-1. FIELD INDICATORS FOR IE	ENTIFYING HYDE	RIC			(P).			ő	**
SOILS IN NEW ENGLAND, Y 2019. • US ARMY CORPS OF ENGL	VERSION 4, APRII	L			07		5 // 🌣		Bar Bar Fri
WETLAND PLAN LIS, 2018. CLASSIFICATION OF WETL	ANDS AND			/	EXISTING TREE TO REMAIN				₩ ^N 30' F F F F
DEEPWATER HABITATS O MANUAL FWS/ OBS-79/31 (21. UNDERGROUND ELECTRIC, WATER	F THE U.S USFW (1979).								
21. UNDERGROUND ELECTRIC, WATER LOCATIONS BASED ON SURFACE M INC ON 10/2019.								EXISTING TREE	F F F F F F F F F F F F F F F F F F F
			∬ /	300' EVERSOU				OPOSED ACCESSIB	
							PA	RKING SIGN (TYP.); TAIL 12/ C7.00	Service of the servic
							v		
							1	Fig. Str. Tree	
	/			lt.		Ň	EXISTING S AND DRIVE	DEWALK, CURB, TO REMAIN	
					11/				





GRADING NOTES

- ELEVATIONS OF EXISTING UTILITIES AT CONNECTION POINTS PRIOR TO GRADING OR INSTALLATION OF ANY PROPOSED UTILITIES. DISCREPANCIES ARE FOUND
- BY LOCAL INSPECTOR.
- GRADE, WILL BE ESTABLISHED TO TEMPORARY VEGETATION. MULCH, TEMPORARY VEGETATION OR PERMANENT VEGETATION SHALL BE COMPLETED ON ALL EXPOSED AREAS WITHIN 14 DAYS AFTER PERMANENT VEGETATION UPON COMPLETION.
- UNIFORMLY SPREAD OVER SEEDED AREA WITHIN 24 HOURS OF SEEDING. IF UNABLE TO ACCOMPLISH, MULCH SHALL BE USED AS A STEEPER THAN 2.5:1 AND WITH A HEIGHT OF TEN FEET OR GREATER BUFFERS, SHALL BE STABILIZED WITH THE APPROPRIATE EROSION CONTROL MATTING OR BLANKETS.
- ROAD OR STREET.
- MUST CALL FOR AN INSPECTION TO OBTAIN A PERMIT TO GRADE. YOUR SCHEDULE.
- ACCORDING TO LOCAL AND STATE REQUIREMENTS AND AS STIPULATED IN THE STORMWATER POLLUTION PREVENTION PLAN. EACH DEVICE IS TO BE MAINTAINED OR REPLACED IF SEDIMENT ACCUMULATION HAS REACHED ONE HALF THE CAPACITY OF THE DEVICE. ADDITIONAL DEVICES MAY BE NECESSARY AS THE PROJECT PROGRESSES AND NEW CHANNELS HAVE DEVELOPED.


- ACTIVITIES.
- THIS CONTRACT. REFER TO LANDSCAPING PLANS FOR AREAS TO
- PLANS AND EROSION CONTROL PLANS
- LAWN AREAS.
- BEST MANAGEMENT PRACTICES, AND/OR OTHER WATER QUALITY MANAGEMENT FACILITIES SHALL BE PROVIDED AND MAINTAINED AT ALL TIMES DURING CONSTRUCTION. DAMAGES TO ADJACENT PROPERTY AND/OR THE CONSTRUCTION SITE CAUSED BY THE CONTRACTOR'S OR PROPERTY OWNER'S FAILURE TO PROVIDE AND MAINTAIN ADEQUATE DRAINAGE AND EROSION/SEDIMENT CONTROL FOR THE CONSTRUCTION AREA SHALL BE THE RESPONSIBILITY OF THE PROPERTY OWNER AND/OR CONTRACTOR.
- CALL--811 OR 1-800-752-6007
- RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT RESULT FROM THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY UNDERGROUND UTILITIES TO REMAIN.









Drawing name: K:\NSH_LDEV\118252004 - portsmouth - cancer center - 2021\4-CADD\plansheets\C7.00 SITE DETAILS.dwg C7.00 SITE DETAILS May 23, 2022 1:49pm by: Zack.Newman



Drawing name: K:\NSH_LDEV\118252004 - portsmouth - cancer center - 2021\4-CADD\plansheets\C7.00 SITE DETAILS.dwg C7.01 SITE DETAILS May 23, 2022 1:49pm by: Zack.Newman











	DIMENSION NOTES
1.	CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS. WHERE THERE IS A QUESTION REGARDING DIMENSIONS, CONSULT THE ARCHITECT BEFORE PROCEEDING. DO NOT SCALE DRAWINGS.
2.	REFER TO LARGE SCALE PLANS FOR ADDITIONAL DIMENSIONS.
3.	ALL INTERIOR WALL DIMENSIONS ARE FROM OUTSIDE FACE OF GYPSUM BOARD TO OUTSIDE FACE OF GYPSUM BOARD OR TO CENTERLINE OF COLUMN UNLESS NOTED OTHERWISE.
4.	UNLESS INDICATED OTHERWISE, ALL INTERIOR WALLS ARE 4 7/8" THICK AND ARE CONSTRUCTED OF 5/8" GYPSUM BOARD ON EACH SIDE OF 3 5/8" METAL STUDS.
5.	CORRIDOR WIDTHS GIVEN ARE THE MINIMUM CLEAR DIMENSIONS.
6.	REFER TO ANSI/ADA DETAILS FOR ACCESSIBLE DOOR CLEARANCE REQUIREMENTS. DOORS SHALL BE MOUNTED 6 INCHES FROM FINISH FACE OF WALL TO HINGE SIDE OF FRAME, UNLESS NOTED OTHERWISE.REFER TO DETAIL 1/6.01.
7.	THE DIMENSIONS PROVIDED REFLECT INFORMATION INDICATED IN THE ORIGINAL CONTRACT DOCUMENTS FURNISHED BY THE OWNER AND HAVE NOT BEEN FIELD CHECKED OR OTHERWISE VERIFIED. IT IS INTENDED THAT THE NEW CONSCTRUCTION BE ALIGN WITH THE EXISTING BUILDING AS SHOWN. NEW WINDOWS SHALL ALIGN WITHEXISTING WINDOWS BELOW. NEW ARCHITECTURAL ELEMENTS SHALL ALIGN WITH EXISTING ELEMENTS AS SHOWN, ETC. THE CONTRACTOR SHALL DETERMINE THE ACTUAL CONDITIONS AND ADVISE THE ARCHITECT IF ADJUSTMENTS ARE NECESSARY.
8.	CONTRACTOR SHALL "3D LASER SCAN" THE PORTION OF THE EXISTING HOSPITAL WHERE WORK IS INDICATED TO DETERMINE THE ACTUAL DIMENSIONS OF THE BUILDING WITH THE LEVEL OF ACCURACY REQUIRED FOR THE PROPER FABRICATION OF THE WALL PANELS AND ALIGNMENT OF WINDOWS AND OTHER ELEMENTS.

DIMENSIONED 1st FLOOR - PART A










<u>KEYNOTES:</u>

- REMOVE AND SALVAGE ACT AND/OR SUSPENSION GRID TO SUPPORT MEP SCOPE OF WORK SEE MEP DRAWINGS FOR ADDITIONAL INFORMATION
- REMOVE AND SALVAGE ACOUSTICAL CEILING TILE AND/OR SUSPENSION GRID FOR APPROXIMATELY 80-FEET TO SUPPORT ELECTRICAL SCOPE OF WORK. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.


	GENERAL FLOOR PLAN NOTES
1.	REFER TO A0.00 FOR ADDITIONAL GENERAL NOTES.
2.	SEE SHEET A4.01 FOR PARTITION TYPES AND DETAILS.
3.	MECHANICAL AND/OR ELECTRICAL PORTIONS OF THE WORK MAY REQUIRE WO FLOOR BELOW OR IN SPACES ADJACENT TO THE WORK. THE SCOPE OF PROJECT WORK NECESSARY TO ACCESS THESE AREAS AND TO REPAIR OR REPLACE ANY FI FLOORS, WALLS, CEILINGS OR OTHER ITEMS DAMAGED OBTAINING SUCH ACCE
4.	WHEN PENETRATING FLOOR SLAB OR REMOVING MECHANICAL, PLUMBING, ELE AND LOW VOLTAGE FROM FLOOR, SEAL PENETRATION WITH A TESTED FIRE PRO ASSEMBLY WITH A RATING EQUAL TO THE SURROUNDING CONSTRUCTION.
5.	REFER TO SOUND TRANSMISSION PLANS FOR SOUND BATT LOCATIONS AND RE RATINGS REQUIRED.
6.	REFER TO FINISH AND FURNITURE PLANS FOR TACK BOARD/MARKER BOARD/CLO LOCATIONS. PROVIDE NECESSARY BLOCKING FOR THESE ITEMS, WHICH SHALL AND INSTALLED BY CONTRACTOR, & FOR ITEMS PROVIDED BY OTHERS.
7.	SEE FINISH PLANS FOR CORNER GUARD, HANDRAIL AND DOOR GUARD LOCATI
8.	PROVIDE FIRE RETARDANT WOOD BLOCKING AS REQUIRED BY PROJECT CONDI-
9.	O.F.E OWNER FURNISHED EQUIPMENT INSTALLED BY THE CONTRACTOR, VEN OWNER. REFER TO THE O.F.E. BROCHURE TO DETERMINE THE PARTY RESPONSIB INSTALLATION. OWNER TO PURCHASE AND DELIVER ALL NEW EQUIPMENT TO T CONTRACTOR SHALL COORDINATE DELIVERY SCHEDULE WITH OWNER. CONTR SHALL PROVIDE MECHANICAL, PLUMBING AND ELECTRICAL CONNECTIONS REQ ALL EQUIPMENT IN THE O.F.E BROCHURE.
10.	SEE SPECIFICATIONS FOR SPECIFIC LEVEL OF FINISH AND PREPARATION REQUIRE EACH SURFACE.
11.	THE OWNER SHALL FURNISH AND THE CONTRACTOR SHALL COORDINATE AND INSTALL THE FOLLOWING:
	 A. AT EACH SINK/LAVATORY LOCATION, ONE SOAP DISPENSER UNLESS NOTED VERIFY LOCATIONS WITH OWNER'S REPRESENTATIVE. B. AT EACH PATIENT CARE, UTILITY AND WORK AREA ONE SHARPS DISPOSAL UDISPENSER AND HAND GEL DISPENSER, AS DIRECTED BY THE OWNER'S REPRESENTED BY THE BY AND BY THE BY AND BY
12.	WALL MOUNTED SINKS AND LAVATORIES SHALL BE MOUNTED SO THAT THE CE THE SINK IS 1'-3" MIN. TO FACE OF ADJACENT FIXED EQUIPMENT, SIDE WALL, CA ETC.
13.	CLINICAL SINKS SHALL BE MOUNTED SO THAT THE CENTERLINE OF THE SINK IS


3. CLINICAL SINKS SHALL BE MOUNTED SO THAT THE CENTERLINE OF THE SINK IS 1'-6" MIN. TO THE FACE OF THE ADJACENT FIXED EQUIPMENT, SIDE WALL, CASEWORK, ETC.


			PARTITION LEGEND	- SEE SHEE
			TWO HOUR RATED FIRE & SMOKE BARRIER - SHAFTWALL	2S
		2	TWO HOUR RATED FIRE & SMOKE BARRIER	_2FS
		3	TWO HOUR RATED FIRE BARRIER	2F
		4	ONE HOUR RATED FIRE & SMOKE BARRIER - SHAFTWALL	<u>15</u>
		5	ONE HOUR RATED FIRE & SMOKE BARRIER	1FS
		6	ONE HOUR RATED FIRE BARRIER	
		7	ONE HOUR RATED FIRE BARRIER - (INCIDENTAL_USE/HAZARDOUS AREA)	
	LOWEST PRIORITY	8	SMOKE PARTITION	NS
			PARTITION TO CEILING - STUDS TO DECK, STOP GYPSUM BOARD 4" ABOVE CEILING.	





NOTED 1ST FLOOR PLAN PART A













GOVE ENVIRONMENTAL SERVICES, INC.

October 15, 2019

Portsmouth Regional Hospital

Subject: Wetland Delineation Report Portsmouth Regional Hospital 333 Borthwick Ave, Portsmouth, NH

Dear Chris Akers,

Per your request, this letter is to verify that Gove Environmental Services, Inc., performed a site inspection to identify wetlands at Portsmouth Regional Hospital, 333 Borthwick Ave, Portsmouth, NH. Wetlands were evaluated utilizing the following standards:

- 1. US Army Corps of Engineers Regional Supplement to the Corps of Engineers Wetland Delineation Manual: Northcentral and Northeast Region, Technical Report ERDC/EL TR-12-1 (January 2012).
- 2. Field Indicators for Identifying Hydric Soils in New England Version 4, April 2019. New England Hydric Soils Technical Committee.
- 3. US Army Corps of Engineers National Wetland Plant List, 2018.
- 4. Classification of Wetlands and Deepwater Habitats of the United States. USFW Manual FWS/OBS-79/31 (1979).

Brenden Walden performed the site inspection on 9/17/19. During the site inspection, two areas of wetland were identified on the Site. The wetland areas were demarcated with a series of pink "Wetland Delineation" flagging consecutively labeled:

1 Start – 15 Stop & A1-A22

The attached sketch plan depicts the general location of the flag series, which were used to identify the resource areas in the field. A general description of the wetlands is also provided

The wetland demarcated by the 1 Start - 15 Stop series of flags, delineated a drainage area dominated by emergent vegetation, hydric soils on the wetland border consisted of NE-S1 & HTM-S hydric soil classifications, soil saturation and water staining were also observed. Bordering upland area consisted developed area and impervious surface.


The wetland demarcated by the A1-A22 series of flags, delineated the wetland boundary for a detention basin vegetated with emergent vegetation. The wetland boundary consisted of NE-S with areas of HTM-S. Bordering upland areas consist of maintained lawn areas and impervious surface from surrounding development.

This concludes the wetland delineation report. If I can be of further assistance, please feel free to contact me at (603) 778-0644.

Sincerely,


Brenden Walden Business Manager & Wetland Scientist Gove Environmental Services, Inc.


Enc. Wetland Delineation Sketch





8 Continental Dr Unit H, Exeter, NH 03833-7507 Ph (603) 778 0644 / Fax (603) 778 0654 www.gesinc.biz info@gesinc.biz











Stormwater Management

Long-Term Maintenance & Operation Plan

Portsmouth Regional Medical Center South Stormwater Wetland Pond

333 Borthwick Avenue Portsmouth, NH

May 23, 2022

Prepared by: Kimley-Horn and Associates, Inc. 404 Wyman St, Ste 385 Waltham, MA 02451

Kimley **»Horn**

Summary

This document describes the stormwater system components of the development and outlines the inspection and maintenance required to ensure the efficacy of the on-site stormwater system.

Description of Stormwater System Components

There is an existing stormwater wetland pond along the south side of the existing hospital facility that detains stormwater runoff from pavement areas and building roof that is captured in a system of pipes and routed to the stormwater wetland pond. The existing stormwater wetland pond is denoted in Exhibit A.

Maintenance Inspections of Stormwater Sensitive Areas

The owner is responsible for the maintenance of the property and adhering to the maintenance guidelines of this agreement as noted below. A major storm event is defined as any storm event which causes local flooding or where there are fallen trees or large tree limbs, debris, or road obstructions as a result of the event.

Maintenance Operations for Stormwater Wetland Pond

- Spot Reseeding. Inspectors should look for bare or eroding areas in the contributing drainage area or around the wetland stormwater pond and make sure they are immediately stabilized with conservation seed mix.
- Remove and replace dead plants. Since up to 10% of the plant stock may die off in the first year, construction contracts should include a care and replacement warranty to ensure that vegetation is properly established and survives during the first growing season following construction. The typical thresholds below which replacement is required are 85% survival of plant material and 100% survival of trees.
- Check for sediment buildup at curb cuts, gravel diaphragms or pavement edges that prevents flow from getting into the bed, and check for other signs of bypassing.
- Check for any winter- or salt-killed vegetation, and replace it with hardier native wetland species.
- Note presence of accumulated sand, sediment and/ or trash and remove it.
- Inspect stormwater wetland pond side slopes for evidence of any rill or gully erosion, and repair it.
- Check the stormwater wetland pond for evidence of excessive ponding, dead plants or concentrated flows, and take appropriate remedial action.
- Check inflow points for clogging, and remove any sediment.
- Look for any bare soil or sediment sources in the contributing drainage area, and stabilize them immediately.
- Check for clogged or slow-draining soil, a crust formed on the top layer, or other causes of insufficient filtering time, and restore proper filtration characteristics

Checklists, which further indicate what should be evaluated during inspections, are included with this document.

Routine and Non-Routine Maintenance Tasks

Maintenance of the stormwater wetland pond should be integrated into routine landscape maintenance tasks. If landscaping contractors will be expected to perform maintenance, their contracts should contain specifics on unique stormwater wetland pond landscaping needs, such as maintaining elevation differences needed for ponding, sediment and trash removal, and no use of fertilizers and pesticides.

Pollutant Disposal

All trash and pollutants should be removed from the site and deposited in a permitted landfill. Deposited sediment can be used in gardens or landscaped areas but should be applied in thin layers and not stock piled in a location where it could erode any further. Leaves and other organic materials can be deposited or composted.

Responsible Party

The responsible party for the inspection and maintenance of the stormwater wetland pond:

Portsmouth Regional Hospital 333 Borthwick Avenue Portsmouth, New Hampshire 03801

South Stormwater Wetland Pond Area										
		Conditi	ion							
Maintenance Item	Good	Marginal	Poor	N/A [*]	Comment					
General Inspection										
Access to the site is adequately maintained for inspection and maintenance.										
Area is clean (trash, debris, grass clippings, etc. removed).										
Inle	et/Outle	et Structures	1							
Drainage ways (overland flow or pipes) to the practice are free of trash, debris, large branches, etc.										
Area around the inlet structure is maintained and trimmings are removed.										
No evidence of gullies, rills, or excessive erosion around the inlet structure.										
	Main Tr	eatment	I	1						
Wetland area is free of trash, debris, and sediment.										
Vegetation within and around practice is maintained per landscaping plan. Any trimmings are removed.										
Plants seem to be healthy and in good condition. Comment on condition of plants.										
	Res	sults								
Overall condition of Wetland Area										
Ac	ditional	Comments								
Notes: [*] If a specific maintenance item was not checked, please check N/A and explain why in the appropriate										
comment box.										



CITY OF PORTSMOUTH

Planning Department 1 Junkins Avenue Portsmouth, New Hampshire 03801 (603) 610-7216

ZONING BOARD OF ADJUSTMENT

April 28, 2022

HCA Health Services of NH, Inc. dba Portsmouth Regional Hospital PO BOX 80610 Indianapolis, IN 46280

RE: Board of Adjustment Request for Property Located at 333 Borthwick Avenue (LU-22-35)

Dear Owner:

The Zoning Board of Adjustment, at its regularly scheduled meeting of **Tuesday, April 26, 2022**, considered your application for building an addition on the existing hospital which requires the following: 1) A Variance from Section 10.531 to allow a 40' front yard where 50' is required. Said property is shown on Assessor Map 240, Lot 2-1 and lies within the Office Research District. As a result of said consideration, the Board voted to **grant** the request as presented and advertised.

The Board's decision may be appealed up to thirty (30) days after the vote. Any action taken by the applicant pursuant to the Board's decision during this appeal period shall be at the applicant's risk. Please contact the Planning Department for more details about the appeals process.

Approvals may also be required from other City Commissions or Boards. Once all required approvals have been received, applicant is responsible for applying for and securing a building permit from the Inspection Department prior to starting any project work.

This approval shall expire unless a building permit is issued within a period of two (2) years from the date granted unless an extension is granted in accordance with Section 10.236 of the Zoning Ordinance.

The minutes and audio recording of this meeting are available by contacting the Planning Department.

Very truly yours,


Partt

Arthur Parrott, Chairman of the Zoning Board of Adjustment

cc: Shanti Wolph, Chief Building Inspector

Rosann Maurice-Lentz, City Assessor

Chris Akers, Project Manager, Kimley-Horn



Hydrograph Return Period Recap Hydraflow Hydrographs Extension for Autodesk® Civil 3D® by Autodesk, Inc. v2020.4

lyd. No.	Hydrograph type	Inflow				Hydrograph Description					
0.	(origin)	hyd(s)	1-yr	2-yr	3-yr	5-yr	10-yr	25-yr	50-yr	100-yr	Description
1	SCS Runoff			16.61		23.20	28.61	36.05	41.44	47.34	PRE-DEVELOPMENT RUNOFF
2	SCS Runoff			16.61		23.20	28.61	36.05	41.44	47.34	POST-DEVELOPMENT RUNOFF
3	Reservoir	1		9.051		10.72	14.18	17.71	19.92	21.93	PRE-DEVELOPMENT
4	Reservoir	2		8.827		10.59	13.57	17.12	19.33	21.45	POST-DEVELOPMENT


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	16.61	2	716	35,198				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	16.61	2	716	35,198				POST-DEVELOPMENT RUNOFF
3	Reservoir	9.051	2	722	33,767	1	22.45	9,429	PRE-DEVELOPMENT
4	Reservoir	8.827	2	722	33,767	2	22.41	9,733	POST-DEVELOPMENT
PO		G.gpw			Return F	Period: 2 Ye	ear	Thursday,	05 / 5 / 2022

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type Storm frequency	= SCS Runoff = 2 yrs	Peak discharge Time to peak	= 16.61 cfs = 716 min
Time interval	= 2 min	Hyd. volume	= 35,198 cuft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 3.33 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180



3


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	23.20	2	716	50,272				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	23.20	2	716	50,272				POST-DEVELOPMENT RUNOFF
3	Reservoir	10.72	2	722	48,841	1	22.91	13,320	PRE-DEVELOPMENT
4	Reservoir	10.59	2	724	48,841	2	22.80	13,648	POST-DEVELOPMENT
PO		G.gpw	1	1	Return F	⊥ Period: 5 Ye) ear	Thursday,	 05 / 5 / 2022

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type Storm frequency	= SCS Runoff = 5 yrs	Peak discharge Time to peak	= 23.20 cfs = 716 min
Time interval	= 2 min	Hyd. volume	= 50,272 cuft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 4.43 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180




Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	28.61	2	716	62,900				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	28.61	2	716	62,900				POST-DEVELOPMENT RUNOFF
3	Reservoir	14.18	2	722	61,470	1	23.21	16,336	PRE-DEVELOPMENT
4	Reservoir	13.57	2	722	61,469	2	23.15	16,866	POST-DEVELOPMENT
POND EXISTING.gpw					Return I	Period: 10 `	 Year	Thursday,	05 / 5 / 2022

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type	= SCS Runoff	Peak discharge	= 28.61 cfs
Storm frequency	= 10 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 62,900 cuft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 5.34 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180



7


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	36.05	2	716	80,516				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	36.05	2	716	80,516				POST-DEVELOPMENT RUNOFF
3	Reservoir	17.71	2	722	79,085	1	23.60	20,589	PRE-DEVELOPMENT
4	Reservoir	17.12	2	722	79,085	2	23.53	21,204	POST-DEVELOPMENT
PO	ND EXISTIN	G.gpw			Return F	Period: 25 \	/ear	Thursday,	05 / 5 / 2022

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type	= SCS Runoff	Peak discharge	= 36.05 cfs
Storm frequency	= 25 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 80,516 cuft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 6.60 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180



9


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	41.44	2	716	93,438				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	41.44	2	716	93,438				POST-DEVELOPMENT RUNOFF
3	Reservoir	19.92	2	722	92,008	1	23.88	23,729	PRE-DEVELOPMENT
4	Reservoir	19.33	2	722	92,007	2	23.80	24,417	POST-DEVELOPMENT
PO	ND EXISTIN	G.gpw			Return F	Period: 50 \	/ear	Thursday,	05 / 5 / 2022

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type Storm frequency Time interval Drainage area Basin Slope	 SCS Runoff 50 yrs 2 min 4.180 ac 0.0 % 	Peak discharge Time to peak Hyd. volume Curve number Hydraulic length	 = 41.44 cfs = 716 min = 93,438 cuft = 92* = 0 ft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 7.52 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180



11


Hyd. No.	Hydrograph type (origin)	Peak flow (cfs)	Time interval (min)	Time to Peak (min)	Hyd. volume (cuft)	Inflow hyd(s)	Maximum elevation (ft)	Total strge used (cuft)	Hydrograph Description
1	SCS Runoff	47.34	2	716	107,662				PRE-DEVELOPMENT RUNOFF
2	SCS Runoff	47.34	2	716	107,662				POST-DEVELOPMENT RUNOFF
3	Reservoir	21.93	2	722	106,232	1	24.17	27,298	PRE-DEVELOPMENT
4	Reservoir	21.45	2	722	106,231	2	24.10	28,058	POST-DEVELOPMENT
POND EXISTING.gpw				Return F	Return Period: 100 Year			Thursday, 05 / 5 / 2022	

Hyd. No. 2

POST-DEVELOPMENT RUNOFF

Hydrograph type	= SCS Runoff	Peak discharge	= 47.34 cfs
Storm frequency	= 100 yrs	Time to peak	= 716 min
Time interval	= 2 min	Hyd. volume	= 107,662 cuft
Drainage area	= 4.180 ac	Curve number	= 92*
Basin Slope	= 0.0 %	Hydraulic length	= 0 ft
Tc method	= TR55	Time of conc. (Tc)	= 5.00 min
Total precip.	= 8.53 in	Distribution	= Type II
Storm duration	= 24 hrs	Shape factor	= 484

* Composite (Area/CN) = [(0.910 x 98) + (1.320 x 79) + (1.950 x 98)] / 4.180



13