

**AMBIT ENGINEERING, INC.** CIVIL ENGINEERS AND LAND SURVEYORS

200 Griffin Road, Unit 3, Portsmouth, NH 03801  
Phone (603) 430-9282 Fax 436-2315

9 January 2020

Dexter Legg, Planning Board Chair  
City of Portsmouth  
1 Junkins Avenue, Portsmouth, NH 03801

**RE: Request for Conditional Use Permit Approval at 60 Penhallow Street, Brick Market; Tax Map 107, Lot 27**

Dear Mr. Legg and Planning Board Members:

On behalf of Mark McNabb and Dagny Taggart, LLC we hereby submit this letter as an application for **Conditional Use Permit Approval at 60 Penhallow Street** for the Brick Market Project at 60 Penhallow Street. The application proposes to construct a 17,200 square foot building on a parcel of land (Tax Map 107; Lot 27) which is in the Character District 4 (CD4) Zone. The Portsmouth Zoning Ordinance allows a maximum building footprint of 15,000 square feet on any given parcel in the CD4 Zone, absent any development incentives. The Ordinance does allow, under Section 10.5A43.43, for a building footprint to be enlarged to a maximum of 20,000 square feet if at least 30% of the development area is assigned and improved as community space.

This proposal seeks the expanded footprint area mentioned above utilizing the dedication of 30% of the development area of the project to community space. The location as well as the types of community space submitted in this application are shown on the Plan titled "Brick Market Master Plan Community Space", and consist of Wide Pedestrian Sidewalks, Pedestrian Alleys, a Plaza, and Pocket Parks. Please note that in this application there is no proposed ground floor parking. The site redevelopment offers an excellent opportunity to link the McIntire Building site with Market Square by creating community space, open to the public, across properties owned by the applicant. We believe the benefits to the public and the city justify the granting of the minor increase to the building footprint. This application coincides with our application for Site Plan Review. Please see the submitted Plan Set and Supporting Material for Site Plan Approval for additional details regarding the site development; as well as the aforementioned Community Space Plan. We look forward to your review of this submission, and request approval of the Conditional Use Application Permit Application as hereby submitted.

Sincerely,

*John Chagnon*

John R. Chagnon, PE  
CC: Mark McNabb, Tracy Kozak, Robbi Woodburn, FX Bruton



# SITE REDEVELOPMENT BRICK MARKET 60 PENHALLOW STREET PORTSMOUTH, NEW HAMPSHIRE SITE PERMIT PLANS

**OWNER:**  
DAGNY TAGGART, LLC  
**APPLICANT:**  
MCNABB PROPERTIES, LTD  
30 PENHALLOW ST, STE 300 EAST  
PORTSMOUTH, NH 03801  
(603) 427-0725

**CIVIL ENGINEER & LAND SURVEYOR:**

AMBIT ENGINEERING, INC.  
200 GRIFFIN ROAD, UNIT 3  
PORTSMOUTH, N.H. 03801  
Tel. (603) 430-9282  
Fax (603) 436-2315

**STRUCTURAL ENGINEER:**

JSN ASSOCIATES, LLC  
1 AUTUMN STREET  
PORTSMOUTH NH, 03801  
TEL.(603) 433-8639

**MEP & FIRE PROTECTION:**

PETERSEN ENGINEERING  
127 PARROTT AVENUE  
PORTSMOUTH NH, 03801  
TEL.(603) 436-4233

**LIGHTING DESIGNER:**

J&M LIGHTING DESIGN, INC.  
PO BOX 4 WOODLAND AVENUE  
KENNEBUNKPORT ME, 04046-1659  
TEL.(207) 967-5223

**ATTORNEY:**  
FX BRUTON  
BRUTON & BERUBE, PLLC  
601 CENTRAL AVENUE  
DOVER, NH 03820  
(603) 749-4529

**LANDSCAPE ARCHITECT:**

WOODBURN & COMPANY  
103 KENT PLACE  
NEWMARKET, NH 03857  
TEL. (603) 659-5949  
FAX (603) 659-5939

**ARCHITECT:**

JSA ARCHITECTS  
273 CORPORATE DRIVE  
SUITE 100  
PORTSMOUTH NH 03801  
TEL. (603) 436-2551  
FAX (603) 436-6973




**GEOTECHNICAL ENGINEER:**

GSI  
18 COTE AVENUE #11  
GOFFSTOWN NH 03045  
TEL. (603) 624-2722

**PERMIT LIST:**  
PORTSMOUTH HDC: APPROVED 11-13-19  
PORTSMOUTH SITE REVIEW: PENDING  
PORTSMOUTH CONDITIONAL USE PERMIT: PENDING

**LEGEND:**

EXISTING	PROPOSED	
---	---	PROPERTY LINE
---	---	SETBACK
S	S	SEWER PIPE
SL	SL	SEWER LATERAL
G	G	GAS LINE
D	D	STORM DRAIN
W	W	WATER LINE
WS	WS	WATER SERVICE
UGE	UGE	UNDERGROUND ELECTRIC
OHW	OHW	OVERHEAD ELECTRIC/WIRES
---	UD	FOUNDATION DRAIN
---	---	EDGE OF PAVEMENT (EP)
100	100	CONTOUR
97x3	98x0	SPOT ELEVATION
⊙	⊙	UTILITY POLE
⊙	⊙	WALL MOUNTED EXTERIOR LIGHTS
⊙	⊙	TRANSFORMER ON CONCRETE PAD
⊙	⊙	ELECTRIC HANDHOLD
⊙	⊙	SHUT OFFS (WATER/GAS)
⊙	⊙	GATE VALVE
⊙	⊙	HYDRANT
⊙	⊙	CATCH BASIN
⊙	⊙	SEWER MANHOLE
⊙	⊙	DRAIN MANHOLE
⊙	⊙	TELEPHONE MANHOLE
⊙	⊙	PARKING SPACE COUNT
⊙	⊙	PARKING METER
LSA	LSA	LANDSCAPED AREA
TBD	TBD	TO BE DETERMINED
CI	CI	CAST IRON PIPE
COP	COP	COPPER PIPE
DI	DI	DUCTILE IRON PIPE
PVC	PVC	POLYVINYL CHLORIDE PIPE
RCP	RCP	REINFORCED CONCRETE PIPE
AC	AC	ASBESTOS CEMENT PIPE
VC	VC	VITRIFIED CLAY PIPE
EP	EP	EDGE OF PAVEMENT
EL	EL	ELEVATION
FF	FF	FINISHED FLOOR
INV	INV	INVERT
S =	S =	SLOPE FT/FT
TBM	TBM	TEMPORARY BENCH MARK
TYP	TYP	TYPICAL



**INDEX OF SHEETS**

DWG. No.	Description
-	STANDARD BOUNDARY SURVEY
-	EASEMENT PLAN
-	PROPOSED EASEMENT PLAN
-	MASTER PLAN - EXISTING CONDITIONS
-	MASTER PLAN - COMMUNITY SPACE
C1	EXISTING CONDITIONS PLAN
C2	DEMOLITION PLAN
C3	SITE LAYOUT PLAN
L1-L4	LANDSCAPE PLANS
LM	LANDSCAPE MATERIALS
C4	UTILITY PLAN
C5	GRADING & DRAINAGE PLAN
P1	DANIEL STREET OFFSITE IMPROVEMENTS
P2	PENHALLOW STREET OFFSITE IMPROVEMENTS
D1-D4	DETAILS
-	ARCHITECTURAL PLANS AND ELEVATION
-	ARCHITECTURAL PARKING PLANS
-	LIGHTING PLANS

**UTILITY CONTACTS**

**ELECTRIC:**  
EVERSOURCE  
1700 LAFAYETTE ROAD  
PORTSMOUTH, N.H. 03801  
Tel. (603) 436-7708, Ext. 555.5678  
ATTN: MICHAEL BUSBY, P.E. (MANAGER)

**NATURAL GAS:**  
UNITIL  
325 WEST ROAD  
PORTSMOUTH, N.H. 03801  
Tel. (603) 294-5144  
ATTN: DAVE BEAULIEU

**CABLE:**  
COMCAST  
155 COMMERCE WAY  
PORTSMOUTH, N.H. 03801  
Tel. (603) 679-5695 (X1037)  
ATTN: MIKE COLLINS

**SEWER & WATER:**  
PORTSMOUTH DEPARTMENT OF PUBLIC WORKS  
680 PEVERLY HILL ROAD  
PORTSMOUTH, N.H. 03801  
Tel. (603) 427-1530  
ATTN: JIM TOW

**COMMUNICATIONS:**  
FAIRPOINT COMMUNICATIONS  
JOE CONSIDINE  
1575 GREENLAND ROAD  
GREENLAND, N.H. 03840  
Tel. (603) 427-5525

**PORTSMOUTH APPROVAL CONDITIONS NOTE:**  
ALL CONDITIONS ON THIS PLAN SET SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO THE REQUIREMENTS OF THE CITY OF PORTSMOUTH SITE PLAN REVIEW REGULATIONS.

APPROVED BY THE PORTSMOUTH PLANNING BOARD


CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_

**SITE PERMIT PLANS  
BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

PLAN SET SUBMITTAL DATE: 8 JANUARY 2020





LOCATION MAP SCALE 1"=300'

LEGEND:

- N/F NOW OR FORMERLY
- RP RECORD OF PROBATE
- RCD ROCKINGHAM COUNTY
- 21 REGISTRY OF DEEDS
- MAP 11 / LOT 21
- BOUNDARY
- SETBACK
- RAILROAD SPIKE FOUND
- IRON ROD/PIPE FOUND
- DRILL HOLE FOUND
- STONE/CONCRETE BOUND FOUND
- RAILROAD SPIKE SET
- IRON ROD SET
- DRILL HOLE SET
- GRANITE BOUND SET
- SEWER LINE
- GAS LINE
- STORM DRAIN
- WATER LINE
- UNDERGROUND ELECTRIC
- OVERHEAD ELECTRIC/WIRES
- CONTOUR
- SPOT ELEVATION
- EDGE OF PAVEMENT (EP)
- WOODS / TREE LINE
- UTILITY POLE (w/ GUY)
- GAS SHUT OFF
- WATER SHUT OFF/CURB STOP
- GATE VALVE
- HYDRANT
- METER (GAS, WATER, ELECTRIC)
- CATCH BASIN
- TELEPHONE MANHOLE
- SEWER MANHOLE
- DRAIN MANHOLE
- AIR CONDITIONER UNIT
- SIGNS
- AC ASBESTOS CEMENT PIPE
- CI CAST IRON PIPE
- CMP CORRUGATED METAL PIPE
- CMU CONCRETE MASONRY UNIT
- COP COPPER PIPE
- DI DUCTILE IRON PIPE
- PVC POLYVINYL CHLORIDE PIPE
- RCP REINFORCED CONCRETE PIPE
- VC VITRIFIED CLAY PIPE
- EL ELEVATION
- EP EDGE OF PAVEMENT
- F.F. FINISHED FLOOR
- INV. INVERT
- TBM TEMPORARY BENCHMARK
- TYP. TYPICAL
- VGC/SGC VERTICAL/SLOPED GRANITE CURB
- CCB CAPE COD BERM
- LSA LANDSCAPED AREA


PLAN REFERENCES:

- 1) PLAN OF LAND FOR INDIAN HEAD BANK OF PORTSMOUTH, DANIEL & PENHALLOW STREETS, PORTSMOUTH, NH. PREPARED BY TOWN PLANNING AND ENGINEERING ASSOC. INC. DATED JUNE 10, 1977, FINAL REVISION DATE AUGUST 30, 1978. R.C.R.D. PLAN C-8101.
- 2) PLAN OF LAND FOR INDIAN HEAD BANK OF PORTSMOUTH, DANIEL & PENHALLOW STREETS, COUNTY OF ROCKINGHAM, PORTSMOUTH, NEW HAMPSHIRE. PREPARED BY TOWN PLANNING AND ENGINEERING ASSOC., INC. R.C.R.D. PLAN C-7121.
- 3) LAND IN PORTSMOUTH COUNTY OF ROCKINGHAM TO CITY OF PORTSMOUTH, PORTSMOUTH, NH. PREPARED BY JOHN W. DURGIN, FILE NUMBER NO. 555 PLAN NO 7171. R.C.R.D. PLAN #01878.
- 4) SUBDIVISION OF LAND PORTSMOUTH, NH FOR SUSAN PETRIE-CLEMONS. PREPARED BY JOHN W. DURGIN ASSOCIATES, INC. DATED AUGUST 13, 1981. R.C.R.D. PLAN C-11434.
- 5) AS BUILT PLAN FOR INDIAN HEAD BANK OF PORTSMOUTH, PLEASANT STREET, PORTSMOUTH, N.H. COUNTY OF ROCKINGHAM PREPARED BY TOWN PLANNING AND ENGINEERING ASSOC. INC. DATED JANUARY 29, 1980. FINAL REVISION DATE FEBRUARY 19, 1980. NOT RECORDED.
- 6) PLAN OF LAND OF PORTSMOUTH TRUST CO., MARKET SQUARE, PORTSMOUTH N.H. PREPARED BY JOHN W. DURGIN CIVIL ENGINEERS, FILE NO. 555 PLAN NO. 6427, DATED JULY 1937. R.C.R.D. PLAN #02644.
- 7) PLAN OF PROPERTIES ON STATE AND PLEASANT STS., PORTSMOUTH, NH. OWNED BY FREDERICK GARDNER AND PISCATAQUA BANK. PREPARED BY WILLIAM A. GROVER CIVIL ENGINEER. DATED SEPT 10, 1919. R.C.R.D. PLAN #0249.
- 8) WATER LINE EASEMENT, 28 PENHALLOW STREET, PORTSMOUTH, NH. DATED OCTOBER 13, 1989. NOT RECORDED.
- 9) LOT CONSOLIDATION, PORTSMOUTH N.H. FOR AMERICAN BANK DESIGN. PREPARED BY DURGIN-SCHOFIELD ASSOCIATES. DATED APRIL 20, 1988. FINAL REVISION MAY 17, 1988. R.C.R.D. PLAN D-18233.
- 10) SUBDIVISION PLAN OF LAND 22 AND 26 MARKET SQUARE, PORTSMOUTH, NEW HAMPSHIRE, COUNTY OF ROCKINGHAM AS PREPARED FOR / OWNER OF RECORD JAMES A. SHANLEY P.O. BOX 1380 PORTSMOUTH, N.H. 03801. PREPARED BY CIVILWORKS, INC. DATED FEBRUARY 15, 1989. R.C.R.D. PLAN D-19371.
- 11) CONDOMINIUM SITE PLAN OF LAND, 22-26 MARKET SQUARE, PORTSMOUTH, NEW HAMPSHIRE, COUNTY OF ROCKINGHAM, AS PREPARED FOR / OWNER OF RECORD LBJ PROPERTIES, LLC 1818 HIGHWAY 395 MINDEN, NV 89423. PREPARED BY CIVILWORKS, INC. DATED AUGUST 3, 2007, FINAL REVISION MARCH 6, 2009. R.C.R.D. PLAN D-36050.
- 12) PROPOSED EASEMENT PLAN MAP U-7 - LOT 42 FOR COVENTRY ASSETS, LTD, 30 PENHALLOW STREET, PORTSMOUTH N.H. COUNTY OF ROCKINGHAM. PREPARED BY AMBIT ENGINEERING, INC. DATED OCTOBER 2000. R.C.R.D. PLAN C-28714.
- 13) EASEMENT RELEASE PLAN MAP U-7 - LOT 42 FOR COVENTRY ASSETS, LTD, 30 PENHALLOW STREET, PORTSMOUTH N.H. COUNTY OF ROCKINGHAM. PREPARED BY AMBIT ENGINEERING, INC. DATED DECEMBER 2000, FINAL REVISION DECEMBER 20, 2000. R.C.R.D. PLAN C-28681.
- 14) TAX MAP 107 LOT 29 BOUNDARY PLAN OWNER: BNG PROPERTIES, INC. PREPARED FOR: TUSCAN BRANDS LOCATED AT: 14 MARKET SQUARE, PLEASANT STREET & DANIEL STREET, PORTSMOUTH, NEW HAMPSHIRE. PREPARED BY S&H LAND SERVICES, LLC. DATED JANUARY 2, 2019. R.C.R.D. PLAN D-41249.
- 15) PLAN OF LAND TAX MAP 107 LOTS 39, 40 AND 41, PROPERTY OF HELEN S. BROUSSEAU GST EXEMPT TRUST AND HELEN S. BROUSSEAU REVOCABLE TRUST OF 2000, 12 PENHALLOW, 191 & 195 STATE STREET, COUNTY OF ROCKINGHAM, PORTSMOUTH NEW HAMPSHIRE. PREPARED BY MSC CIVIL ENGINEERS & LAND SURVEYORS, INC. DATED DECEMBER 12, 2007, FINAL REVISION JANUARY 8, 2008. R.C.R.D. PLAN D-35246.
- 16) CONDOMINIUM SITE PLAN TAX MAP 107 LOTS 39, 40 AND 41, PROPERTY OF HELEN S. BROUSSEAU GST EXEMPT TRUST AND HELEN S. BROUSSEAU REVOCABLE TRUST OF 2000, 12 PENHALLOW, 191 & 195 STATE STREET, COUNTY OF ROCKINGHAM, PORTSMOUTH NEW HAMPSHIRE. PREPARED BY MSC CIVIL ENGINEERS & LAND SURVEYORS, INC. DATED JANUARY 31, 2008, FINAL REVISION JUNE 19, 2008. R.C.R.D. PLAN D-335541.
- 17) PLAN OF A LOT OF LAND IN PORTSMOUTH BELONGING TO JONATHAN M. TREDICK, PORTSMOUTH, NH. PREPARED BY ALFRED M. HOYT, SURVEYOR DATED JULY 1, 1864. R.C.R.D. PLAN #0019.
- 18) SUBDIVISION PLAN FOR LI JUNE CHEN AND SHIANG TA CHEN, 54 DANIEL ST, PORTSMOUTH, NEW HAMPSHIRE, COUNTY OF ROCKINGHAM. PREPARED BY AMBIT SURVEY, DATED NOVEMBER 1998. R.C.R.D. PLAN D-27033.
- 19) EASEMENT PLAN OF LAND 26 MARKET SQUARE, PORTSMOUTH, AS PREPARED FOR JAMES A. SHANLEY PO BOX 1380 PORTSMOUTH, NH 03801. PREPARED BY CIVILWORKS, INC. DATED SEPTEMBER 10, 1993. R.C.R.D. PLAN B-22525.
- 20) DIVISION PLAN, ESTATE OF JOTHAM ODIORNE. c.1774 RP 4093.

**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

NOTES:


- 1) PARCELS ARE SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOTS 27 & 31.
- 2) OWNER OF RECORD:  
DAGNY TAGGART, LLC  
30 PENHALLOW STREET, SUITE 300 EAST  
PORTSMOUTH, NH 03801  
5990/1701 (LOT 31) & 5990/1703 (LOT 27)  
C-7121, C-8101, & D-41408
- 3) PARCELS ARE NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259E. EFFECTIVE DATE MAY 17, 2005.
- 4) EXISTING LOT AREAS:  
  
MAP 107 LOT 27  
23,279 S.F.  
0.5344 ACRES  
  
MAP 107 LOT 31  
8,867 S.F.  
0.2036 ACRES
- 5) ASSESSOR'S MAP 107 LOT 27 IS LOCATED IN THE CHARACTER DISTRICT 4 (CD4) ZONING DISTRICT. ASSESSOR'S MAP 107 LOT 31 IS LOCATED IN THE CHARACTER DISTRICT 5 (CD5) ZONING DISTRICT. BOTH PARCELS ARE LOCATED WITHIN THE DOWNTOWN OVERLAY DISTRICT AND THE HISTORIC DISTRICT.
- 6) DIMENSIONAL REQUIREMENTS:  
SEE ZONING ORDINANCE
- 7) THE PURPOSE OF THIS PLAN IS TO SHOW THE RESULT OF A STANDARD BOUNDARY SURVEY OF ASSESSOR'S MAP 107 LOTS 27 & 31 IN THE CITY OF PORTSMOUTH.
- 8) SEE SHEET 2 OF 2 FOR EASEMENTS, RESTRICTIONS, AND ENCUMBRANCES.
- 9) NOT ALL UTILITIES SHOWN HEREON.



I CERTIFY THAT THIS PLAN WAS PREPARED UNDER MY DIRECT SUPERVISION, THAT IT IS THE RESULT OF A FIELD SURVEY BY THIS OFFICE AND HAS AN ACCURACY OF THE CLOSED TRAVERSE THAT EXCEEDS THE PRECISION OF 1:15,000.

I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN.

PAUL A. DOBBERSTEIN, LLS #1000  
DATE 11/18/2019



LENGTH TABLE

LINE	BEARING	DISTANCE
L1	S89°30'55"E	9.00'
L2	S89°25'37"W	4.33'
L3	N89°52'12"W	0.76'
L4	S03°04'06"W	17.95'
L5	N88°22'54"W	17.56'

NO.	DESCRIPTION	DATE
4	ISSUED WITH 60 PENHALLOW	11/18/19
3	MISCELLANEOUS REVISIONS	10/7/19
2	ISSUED WITH TAC SUBMISSION	7/15/19
1	MONUMENTS SET	4/3/19
0	ISSUED FOR COMMENT	3/27/19

STANDARD BOUNDARY SURVEY  
TAX MAP 107 -  
LOTS 27 & 31

LAND OF:  
**DAGNY TAGGART, LLC**  
PROPERTY LOCATED AT:  
3 PLEASANT STREET &  
60 PENHALLOW STREET  
CITY OF PORTSMOUTH  
COUNTY OF ROCKINGHAM  
STATE OF NEW HAMPSHIRE





**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors


200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

**NOTES:**

- 1) PARCELS ARE SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOTS 27 & 31.
- 2) OWNER OF RECORD:  
DAGNY TAGGART, LLC  
30 PENHALLOW STREET, SUITE 300 EAST  
PORTSMOUTH, NH 03801  
5990/1701 (LOT 31) & 5990/1703 (LOT 27)  
C-7121, C-8101, & D-41408
- 3) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259E. EFFECTIVE DATE MAY 17, 2005.
- 4) EXISTING LOT AREAS:  
  
MAP 107 LOT 27  
23,279 S.F.  
0.5344 ACRES  
  
MAP 107 LOT 31  
8,867 S.F.  
0.2036 ACRES
- 5) ASSESSOR'S MAP 107 LOT 27 IS LOCATED IN THE CHARACTER DISTRICT 4 (CD4) ZONING DISTRICT. ASSESSOR'S MAP 107 LOT 31 IS LOCATED IN THE CHARACTER DISTRICT 5 (CD5) ZONING DISTRICT. BOTH PARCELS ARE LOCATED WITHIN THE DOWNTOWN OVERLAY DISTRICT AND THE HISTORIC DISTRICT.
- 6) DIMENSIONAL REQUIREMENTS:  
SEE ZONING ORDINANCE
- 7) THE PURPOSE OF THIS PLAN IS TO SHOW THE EASEMENTS ASSOCIATED WITH A STANDARD BOUNDARY SURVEY OF ASSESSOR'S MAP 107 LOTS 27 & 31 IN THE CITY OF PORTSMOUTH. ALSO SHOWN IS A PROPOSED EASEMENT RESTRICTING BUILDING CONSTRUCTION ON ASSESSOR'S MAP 107 LOTS 27 & 42.
- 8) ASSESSOR'S MAP 107 LOTS 27 & 42 WILL BE BURDENED BY A POTENTIAL NO BUILD AREA; SUBJECT TO FINAL DESIGN APPROVAL BY THE PORTSMOUTH BUILDING INSPECTOR'S OFFICE FOR ANY BUILDING CONSTRUCTION ON ASSESSOR'S MAP 107 LOT 31. OWNER SHALL REVIEW APPLICABLE IBC CODES RELATIVE TO THE OPENINGS IN THE 30 PENHALLOW STREET BUILDING AND DESIGN ACCORDINGLY TO COMPLY.

NO.	DESCRIPTION	DATE
4	ISSUED WITH 60 PENHALLOW	11/18/19
3	MISCELLANEOUS REVISIONS	10/7/19
2	ADD BUILDING EASEMENT	7/15/19
1	REVISE PER COMMENTS	3/28/19
0	ISSUED FOR COMMENT	3/27/19


**EASEMENT PLAN**  
**TAX MAP 107 -**  
**LOTS 27 & 31**  
LAND OF:  
**DAGNY TAGGART, LLC**  
PROPERTY LOCATED AT:  
**3 PLEASANT STREET &**  
**60 PENHALLOW STREET**  
CITY OF PORTSMOUTH  
COUNTY OF ROCKINGHAM  
STATE OF NEW HAMPSHIRE



**LOCATION MAP**


**LEGEND:**

- |                 |                              |
|-----------------|------------------------------|
| N/F             | NOW OR FORMERLY              |
| RP              | RECORD OF PROBATE            |
| RCRD            | ROCKINGHAM COUNTY            |
|                 | REGISTRY OF DEEDS            |
| 11/27           | MAP 11 / LOT 21              |
| <b>BOUNDARY</b> |                              |
| ---             | SETBACK                      |
| ○               | RAILROAD SPIKE FOUND         |
| ○               | IRON ROD/PIPE FOUND          |
| ○               | DRILL HOLE FOUND             |
| ○               | STONE/CONCRETE BOUND FOUND   |
| ○               | RAILROAD SPIKE SET           |
| ○               | IRON ROD SET                 |
| ○               | DRILL HOLE SET               |
| ○               | GRANITE BOUND SET            |
| ---             | SEWER LINE                   |
| ---             | GAS LINE                     |
| ---             | STORM DRAIN                  |
| ---             | WATER LINE                   |
| ---             | UNDERGROUND ELECTRIC         |
| ---             | OVERHEAD ELECTRIC/WIRES      |
| ---             | CONTOUR                      |
| ---             | SPOT ELEVATION               |
| ---             | EDGE OF PAVEMENT (EP)        |
| ---             | WOODS / TREE LINE            |
| ---             | UTILITY POLE (w/ GUY)        |
| ---             | GAS SHUT OFF                 |
| ---             | WATER SHUT OFF/CURB STOP     |
| ---             | GATE VALVE                   |
| ---             | HYDRANT                      |
| ---             | METER (GAS, WATER, ELECTRIC) |
| ---             | CATCH BASIN                  |
| ---             | TELEPHONE MANHOLE            |
| ---             | SEWER MANHOLE                |
| ---             | DRAIN MANHOLE                |
| ---             | AIR CONDITIONER UNIT         |
| ---             | SIGNS                        |
| AC              | ASBESTOS CEMENT PIPE         |
| CI              | CAST IRON PIPE               |
| CMP             | CORRUGATED METAL PIPE        |
| CMU             | CONCRETE MASONRY UNIT        |
| COP             | COPPER PIPE                  |
| DI              | DUCTILE IRON PIPE            |
| PVC             | POLYVINYL CHLORIDE PIPE      |
| RCP             | REINFORCED CONCRETE PIPE     |
| VC              | VITRIFIED CLAY PIPE          |
| EL              | ELEVATION                    |
| EP              | EDGE OF PAVEMENT             |
| F.F.            | FINISHED FLOOR               |
| INV.            | INVERT                       |
| TBM             | TEMPORARY BENCHMARK          |
| TYP.            | TYPICAL                      |
| VGC/SGC         | VERTICAL/SLOPED GRANITE CURB |
| CCB             | CAPE COD BERM                |
| LSA             | LANDSCAPED AREA              |




I CERTIFY THAT THIS PLAN WAS PREPARED UNDER MY DIRECT SUPERVISION, THAT IT IS THE RESULT OF A FIELD SURVEY BY THIS OFFICE AND HAS AN ACCURACY OF THE CLOSED TRAVERSE THAT EXCEEDS THE PRECISION OF 1:15,000.


I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE, AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN.



PAUL A. DOBBERSTEIN, L.L.S. #1000  
DATE 11/18/2019







LOCATION MAP SCALE 1"=300'

LEGEND:

- N/F NOW OR FORMERLY
- RP RECORD OF PROBATE
- RCRD ROCKINGHAM COUNTY
- 11/27 REGISTRY OF DEEDS
- MAP 11 / LOT 21
- BOUNDARY
- - - SETBACK
- RAILROAD SPIKE FOUND
- IRON ROD/PIPE FOUND
- DRILL HOLE FOUND
- STONE/CONCRETE
- BOUND FOUND
- RAILROAD SPIKE SET
- IRON ROD SET
- DRILL HOLE SET
- GRANITE BOUND SET

**PLAN REFERENCES:**  
 1) STANDARD BOUNDARY SURVEY TAX MAP 107 - LOTS 27 & 31, PREPARED FOR: McNABB PROPERTIES, LTD., LAND OF: JARBEL REALTY, LLC, PROPERTY LOCATED AT: 3 PLEASANT STREET & 0 DANIEL STREET, CITY OF PORTSMOUTH, COUNTY OF ROCKINGHAM, STATE OF NEW HAMPSHIRE. PREPARED BY AMBIT ENGINEERING, INC. DATED MARCH 2019, FINAL REVISION DATE APRIL 3, 2019. R.C.R.D. PLAN D-41408.  
 2) SEE PLAN REFERENCE 1 FOR ADDITIONAL PLAN REFERENCES.

DANIEL STREET

107/28  
 N/F  
 LCB PROPERTIES, LLC &  
 LBJ PROPERTIES, LLC  
 144 W. BRIGHAM ROAD, SUITE 5  
 ST. GEORGE, UT 84790  
 5621/2624

107/30  
 N/F  
 MARKET SQUARE CONDOMINIUM  
 5046/568  
 D-19371 & D-36050

107/31  
 N/F  
 DAGNY TAGGART, LLC  
 30 PENHALLOW STREET  
 SUITE 300 E  
 PORTSMOUTH, NH 03801  
 5990/1701  
 C7121, C8101, &  
 D-41408

LENGTH TABLE


LINE	BEARING	DISTANCE
L1	S89°30'55"E	9.00'
L2	S89°25'37"W	4.33'

107/27

I CERTIFY THAT THIS PLAN WAS PREPARED UNDER MY DIRECT SUPERVISION, THAT IT IS THE RESULT OF A FIELD SURVEY BY THIS OFFICE AND HAS AN ACCURACY OF THE CLOSED TRAVERSE THAT EXCEEDS THE PRECISION OF 1:15,000.

I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN.

PAUL A. DOBBERSTEIN, LLS #1000  
 DATE 1/9/2020



2000  
 C-28714  
 MAGNETIC  
 N  
 R.C.R.D. PLAN


**AMBIT ENGINEERING, INC.**  
 Civil Engineers & Land Surveyors  
 200 Griffin Road - Unit 3  
 Portsmouth, N.H. 03801-7114  
 Tel (603) 430-9282  
 Fax (603) 436-2315

- NOTES:**
- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOT 27.
  - 2) OWNER OF RECORD:  
 DAGNY TAGGART, LLC  
 30 PENHALLOW STREET, SUITE 300 EAST  
 PORTSMOUTH, NH 03801  
 5990/1703  
 C-7121, C-8101, & D-41408
  - 3) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259E. EFFECTIVE DATE MAY 17, 2005.
  - 4) EXISTING LOT AREA:  
 23,279 S.F.  
 0.5344 ACRES
  - 5) THE PURPOSE OF THIS PLAN IS TO SHOW THE LOCATION OF PROPOSED EASEMENTS FOR ROOF OVERHANGS OF A PROPOSED BUILDING ON ASSESSOR'S MAP 107 LOT 27 IN THE CITY OF PORTSMOUTH. EASEMENTS TO BE GRANTED ARE WITHIN THE RIGHTS-OF-WAY OF DANIEL STREET AND PENHALLOW STREET.

NO.	DESCRIPTION	DATE
1	TITLE, EASEMENT NOTES	1/8/19
0	ISSUED FOR COMMENT	12/23/19

**PROPOSED EASEMENT PLAN**  
**TAX MAP 107 - LOT 27**  
 OVER RIGHTS-OF-WAY OF:  
**DANIEL STREET &**  
**PENHALLOW STREET**  
 OWNER:  
**CITY OF PORTSMOUTH**  
 FOR BENEFIT OF:  
**DAGNY TAGGART, LLC**  
 PROPERTY LOCATED AT:  
 60 PENHALLOW STREET  
 CITY OF PORTSMOUTH  
 COUNTY OF ROCKINGHAM  
 STATE OF NEW HAMPSHIRE








**NOTES:**

- 1) PARCELS ARE SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOTS 27, 31 & 42.
- 2) OWNERS OF RECORD:
  - 107/27 & 31  
 DAGNY TAGGART, LLC  
 30 PENHALLOW STREET, SUITE 300 EAST  
 PORTSMOUTH, NH 03801  
 5990/701 (LOT 31) & 5990/1703 (LOT 27)  
 C-7121, C-8101, & D-4140B
  - 107/42  
 COVENTRY ASSETS, LTD  
 30 PENHALLOW STREET, SUITE 300 E  
 PORTSMOUTH, NH 03801  
 3067/2440 (LOT 42)  
 C-28681 & C-28714
- 3) PARCELS ARE NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259E. EFFECTIVE DATE MAY 17, 2005.
- 4) EXISTING LOT AREAS:
  - MAP 107 LOT 27  
 23,279 S.F.  
 0.5344 ACRES
  - MAP 107 LOT 31  
 8,867 S.F.  
 0.2036 ACRES
  - MAP 107 LOT 42  
 17,111 S.F.  
 0.3928 ACRES
- 5) ASSESSOR'S MAP 107 LOTS 27 & 42 ARE LOCATED IN THE CHARACTER DISTRICT 4 (CD4) ZONING DISTRICT. ASSESSOR'S MAP 107 LOT 31 IS LOCATED IN THE CHARACTER DISTRICT 5 (CD5) ZONING DISTRICT. PARCELS ARE LOCATED WITHIN THE DOWNTOWN OVERLAY DISTRICT AND THE HISTORIC DISTRICT.
- 6) DIMENSIONAL REQUIREMENTS:  
 SEE ZONING ORDINANCE

NO.	DESCRIPTION	DATE
2	ISSUED FOR APPROVAL	11/18/19
1	UPDATED FOR 60 PENHALLOW	10/7/19
0	ISSUED FOR COMMENT	7/25/19
REVISIONS		

**MASTER PLAN  
 EXISTING CONDITIONS  
 TAX MAP 107  
 LOTS 27, 31 & 42  
 BRICK MARKET  
 PROPERTY LOCATED AT:  
 3 PLEASANT STREET  
 30 PENHALLOW STREET  
 60 PENHALLOW STREET  
 CITY OF PORTSMOUTH  
 COUNTY OF ROCKINGHAM  
 STATE OF NEW HAMPSHIRE**

2000  
 MAGNETIC  
 N  
 R.C.R.D. PLAN  
 C-28714




08/01/2019 09:30:00 AM: D:\Projects\2019\107\107.dwg, User: JCHAGNON, Plot Date: 11/18/2019 11:25:54 AM











LOCATION MAP

SCALE 1"=300'



LENGTH TABLE

LINE	BEARING	DISTANCE
L1	S89°30'55\"E	9.00'
L2	S89°25'37\"W	4.33'




**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

- NOTES:**
- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOT 27.
  - 2) OWNER OF RECORD:  
DAGNY TAGGART, LLC  
30 PENHALLOW STREET, SUITE 300 EAST  
PORTSMOUTH, NH 03801
  - 3) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0259E. EFFECTIVE DATE MAY 17, 2005.
  - 4) LOT AREA:  
23,279 S.F.  
0.5344 ACRES
  - 5) ASSESSOR'S MAP 107 LOT 27 IS LOCATED IN THE CHARACTER DISTRICT 4 (CD4) ZONING DISTRICT, DOWNTOWN OVERLAY DISTRICT (DOD), AND THE HISTORIC DISTRICT (HDC).
  - 6) DIMENSIONAL REQUIREMENTS:  
SEE ZONING ORDINANCE
  - 7) THE PURPOSE OF THIS PLAN IS TO SHOW THE EXISTING CONDITIONS OF ASSESSOR'S MAP 107 LOT 31 IN THE CITY OF PORTSMOUTH.
  - 8) VERTICAL DATUM: MEAN SEA LEVEL NAVD 88  
BENCHMARK: NGS  
PID 000 289 (V-31 USGS 1943)  
ELEVATION: 29.19

**BRICK MARKET**  
**60 PENHALLOW STREET**  
**PORTSMOUTH, N.H.**


NO.	DESCRIPTION	DATE
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19



SCALE: 1"=10'      OCTOBER 2019

EXISTING CONDITIONS  
PLAN


**C1**





**DEMOLITION NOTES**

- A) THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR THE DESIGNER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE UTILITIES AND ANTICIPATE CONFLICTS. CONTRACTOR SHALL REPAIR EXISTING UTILITIES DAMAGED BY THEIR WORK AND RELOCATE EXISTING UTILITIES THAT ARE REQUIRED TO BE RELOCATED PRIOR TO COMMENCING ANY WORK IN THE IMPACTED AREA OF THE PROJECT.
- B) ALL MATERIALS SCHEDULED TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTORS UNLESS OTHERWISE SPECIFIED. THE CONTRACTOR SHALL DISPOSE OF ALL MATERIALS OFF-SITE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCES AND CODES. THE CONTRACTOR SHALL COORDINATE REMOVAL, RELOCATION, DISPOSAL, OR SALVAGE OF UTILITIES WITH THE OWNER AND APPROPRIATE UTILITY COMPANY.
- C) ANY EXISTING WORK OR PROPERTY DAMAGED OR DISRUPTED BY CONSTRUCTION/ DEMOLITION ACTIVITIES SHALL BE REPLACED OR REPAIRED TO THE ORIGINAL EXISTING CONDITIONS BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
- D) THE CONTRACTOR SHALL VERIFY LOCATION OF ALL EXISTING UTILITIES AND CALL DIG SAFE AT LEAST 72 HOURS PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
- E) SAWCUT AND REMOVE PAVEMENT ONE FOOT OFF PROPOSED EDGE OF PAVEMENT OR EXISTING CURB LINE IN AREAS WHERE PAVEMENT TO BE REMOVED ABUTS EXISTING PAVEMENT OR CONCRETE TO REMAIN.
- F) IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE THEMSELVES WITH THE CONDITIONS OF ALL THE PERMIT APPROVALS.
- G) THE CONTRACTOR SHALL OBTAIN AND PAY FOR ADDITIONAL CONSTRUCTION PERMITS, NOTICES AND FEES NECESSARY TO COMPLETE THE WORK AND ARRANGE FOR AND PAY FOR ANY INSPECTIONS AND APPROVALS FROM THE AUTHORITIES HAVING JURISDICTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY ADDITIONAL AND OFF-SITE DISPOSAL OF MATERIALS REQUIRED TO COMPLETE THE WORK.
- H) THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL EXISTING STRUCTURES, CONCRETE, UTILITIES, VEGETATION, PAVEMENT, AND CONTAMINATED SOIL WITHIN THE WORK LIMITS SHOWN UNLESS SPECIFICALLY IDENTIFIED TO REMAIN. ANY EXISTING MONITORING WELLS IN THE PROJECT AREA IDENTIFIED DURING THE CONSTRUCTION AND NOT CALLED OUT ON THE PLANS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER TO COORDINATE MONITORING WELL REMOVAL AND/OR RELOCATION WITH NHDES AND OTHER AUTHORITY WITH JURISDICTION PRIOR TO CONSTRUCTION.
- I) ALL WORK WITHIN THE CITY OF PORTSMOUTH RIGHT OF WAY SHALL BE COORDINATED WITH THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS (DPW).
- J) CONTRACTOR SHALL PROTECT ALL PROPERTY MONUMENTATION THROUGHOUT DEMOLITION AND CONSTRUCTION OPERATIONS. SHOULD ANY MONUMENTATION BE DISTURBED, THE CONTRACTOR SHALL EMPLOY A NH LICENSED LAND SURVEYOR TO REPLACE THEM.
- K) PROVIDE INLET PROTECTION BARRIERS AT ALL CATCH BASINS WITHIN CONSTRUCTION LIMITS AND IMMEDIATELY OFF-SITE TO BE MAINTAIN FOR THE DURATION OF THE PROJECT. INLET PROTECTION BARRIERS SHALL BE HIGH FLOW SILT SACK BY ACF ENVIRONMENTAL OR APPROVED EQUAL. INSPECT BARRIERS WEEKLY AND AFTER EACH RAIN OF 0.25 INCHES OR GREATER. CONTRACTOR SHALL COMPLETE A MAINTENANCE INSPECTION REPORT AFTER EACH INSPECTION. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF WARRANTED OR FABRIC BECOMES CLOGGED. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO THE START OF ANY CLEARING OR DEMOLITION ACTIVITIES.
- L) THE CONTRACTOR SHALL PAY ALL COSTS NECESSARY FOR TEMPORARY PARTITIONING, BARRICADING, FENCING, SECURITY AND SAFELY DEVICES REQUIRED FOR THE MAINTENANCE OF A CLEAN AND SAFE CONSTRUCTION SITE.
- M) ANY CONTAMINATED MATERIAL REMOVED DURING THE COURSE OF THE WORK WILL REQUIRE HANDLING IN ACCORDANCE WITH NHDES REGULATIONS. CONTRACTOR SHALL HAVE A HEALTH AND SAFETY PLAN IN PLACE, AND COMPLY WITH ALL APPLICABLE PERMITS, APPROVALS, AUTHORIZATIONS, AND REGULATIONS




**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

- NOTES:**
- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS. DIG SAFE TICKETS EXPIRE IN 30 DAYS.
  - 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
  - 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).

**BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
2	LIGHTING NOTE	12/23/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19




SCALE: 1"=10'      OCTOBER 2019

**DEMOLITION PLAN      C2**

APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_



I:\JOBSS\IN 3000\IN 3039\2019 Survey and Site Development\Plans & Specs\Site\3039 Existing Conditions 2019.dwg, C2 DEMO 60 PENHALLOW







**UTILITY NOTES:**


- 1) SEE EXISTING CONDITIONS PLAN FOR BENCHMARK INFORMATION.
- 2) COORDINATE ALL UTILITY WORK WITH APPROPRIATE UTILITY.
- 3) SEE GRADING AND DRAINAGE PLAN FOR PROPOSED GRADING AND EROSION CONTROL MEASURES.
- 4) ALL WATER MAIN INSTALLATIONS SHALL BE CLASS 52, POLYWRAPPED, CEMENT LINED DUCTILE IRON PIPE.
- 5) ALL WATERMAIN INSTALLATIONS SHALL BE PRESSURE TESTED AND CHLORINATED AFTER CONSTRUCTION AND BEFORE ACTIVATING THE SYSTEM. CONTRACTOR SHALL COORDINATE WITH THE CITY OF PORTSMOUTH.
- 6) ALL SEWER PIPE SHALL BE PVC SDR 35 UNLESS OTHERWISE STATED.
- 7) ALL WORK WITHIN CITY R.O.W. SHALL BE COORDINATED WITH CITY OF PORTSMOUTH.
- 8) CONTRACTOR SHALL MAINTAIN UTILITY SERVICES TO ADJACENT PROPERTIES THROUGHOUT CONSTRUCTION.
- 9) ANY CONNECTION TO EXISTING WATERMAIN SHALL BE CONSTRUCTED BY THE CITY OF PORTSMOUTH.
- 10) EXISTING UTILITIES TO BE REMOVED SHALL BE CAPPED AT THE MAIN AND MEET THE DEPARTMENT OF PUBLIC WORKS STANDARDS FOR CAPPING OF WATER AND SEWER SERVICES.
- 11) ALL ELECTRICAL MATERIAL WORKMANSHIP SHALL CONFORM TO THE NATIONAL ELECTRIC CODE, LATEST EDITION, AND ALL APPLICABLE STATE AND LOCAL CODES.
- 12) THE EXACT LOCATION OF NEW UTILITY SERVICES AND CONNECTIONS SHALL BE COORDINATED WITH BUILDING DRAWINGS AND UTILITY COMPANIES.
- 13) ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
- 14) ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES TO FACILITATE PULLING CABLES.
- 15) THE CONTRACTOR SHALL OBTAIN, PAY FOR, AND COMPLY WITH ALL REQUIRED PERMITS, ARRANGE FOR ALL INSPECTIONS, AND SUBMIT COPIES OF ACCEPTANCE CERTIFICATED TO THE OWNER PRIOR TO THE COMPLETION OF PROJECT.
- 16) THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED IN THESE DRAWINGS TO RENDER INSTALLATION OF UTILITIES COMPLETE AND OPERATIONAL.
- 17) CONTRACTOR SHALL PROVIDE EXCAVATION, BEDDING, BACKFILL AND COMPACTION FOR NATURAL GAS SERVICES.
- 18) A 10-FOOT MINIMUM EDGE TO EDGE HORIZONTAL SEPARATION SHALL BE PROVIDED BETWEEN ALL WATER AND SANITARY SEWER LINES. AN 18-INCH MINIMUM OUTSIDE TO OUTSIDE VERTICAL SEPARATION SHALL BE PROVIDED AT ALL WATER/SANITARY SEWER CROSSINGS WATER ABOVE SEWER.
- 19) SAWCUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN.
- 20) GATE VALVES, FITTINGS, ETC. SHALL MEET THE REQUIREMENTS OF THE CITY OF PORTSMOUTH.
- 21) COORDINATE TESTING OF SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH.
- 22) ALL SEWER PIPES WITH LESS THAN 6' COVER SHALL BE INSULATED.
- 23) CONTRACTOR SHALL COORDINATE ALL ELECTRIC WORK INCLUDING BUT NOT LIMITED TO: CONDUIT CONSTRUCTION, MANHOLE CONSTRUCTION, UTILITY POLE CONSTRUCTION, OVERHEAD WIRE RELOCATION, AND TRANSFORMER CONSTRUCTION WITH POWER COMPANY.
- 24) CONTRACTOR SHALL PHASE UTILITY CONSTRUCTION, PARTICULARLY WATER MAIN AND GAS MAIN CONSTRUCTION AS TO MAINTAIN CONTINUOUS SERVICE TO ADJACENT PROPERTIES. CONTRACTOR SHALL COORDINATE TEMPORARY SERVICES TO ADJACENTERS WITH UTILITY COMPANY AND AFFECTED ADJACENT.
- 25) SITE LIGHTING SPECIFICATIONS, CONDUIT LAYOUT AND CIRCUITRY FOR PROPOSED SITE LIGHTING AND SIGN ILLUMINATION SHALL BE PROVIDED BY THE PROJECT ELECTRICAL ENGINEER IN COORDINATION WITH THE SITE CIVIL ENGINEER.
- 26) CONTRACTOR SHALL CONSTRUCT ALL UTILITIES AND DRAINS TO WITHIN 10' OF THE FOUNDATION WALLS AND CONNECT THESE TO SERVICE STUBS FROM THE BUILDING.
- 27) THE CONTRACTOR SHALL INSTALL THE SEWER LINE AND MANHOLE IN CONSULTATION AND COORDINATION WITH DEPARTMENT OF PUBLIC WORKS.



**AMBIT ENGINEERING, INC.**  
 Civil Engineers & Land Surveyors  
 200 Griffin Road - Unit 3  
 Portsmouth, N.H. 03801-7114  
 Tel (603) 430-9282  
 Fax (603) 436-2315

**NOTES:**

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION." (NHDES DECEMBER 2008).
- 4) INSTALL CATCH BASIN INLET PROTECTION ON ALL EXISTING AND PROPOSED CATCH BASINS IN THE PROJECT VICINITY UNTIL CONSTRUCTION IS COMPLETED AND THE SITE IS STABILIZED.
- 5) ALL WATER MAIN AND SANITARY SEWER WORK SHALL MEET THE STANDARDS OF THE NEW HAMPSHIRE STATE PLUMBING CODE AND CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS.
- 6) UTILITY AS-BUILTS SHALL BE SUBMITTED TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS UPON COMPLETION OF THE PROJECT.
- 7) EVERSOURCE WORK ORDER #3107781
- 8) PROPOSED SEWER FLOW:  
 1ST FLOOR RESTAURANT: 3,600 GPD  
 OFFICE SPACE:  
 141,526 SF / (2.5 GPD X 100 SF) = 1,038 GPD  
 TOTAL PROPOSED FLOW = 4,638 GPD
- 9) THE APPLICANT SHALL HAVE A COMMUNICATIONS SITE SURVEY CONDUCTED BY A MOTOROLA COMMUNICATIONS CARRIER APPROVED BY THE PORTSMOUTH'S COMMUNICATIONS DIVISION. THE RADIO COMMUNICATIONS CARRIER MUST BE FAMILIAR AND CONVERSANT WITH THE PORTSMOUTH POLICE AND FIRE RADIO SYSTEMS CONFIGURATION. IF THE SITE SURVEY INDICATES THAT IT IS NECESSARY TO INSTALL A SIGNAL REPEATER EITHER ON OR NEAR THE PROPOSED PROJECT, THOSE COSTS SHALL BE THE RESPONSIBILITY OF THE PROPERTY OWNER. THE PROPERTY OWNER WILL BE REQUIRED TO MAINTAIN ANY INSTALLED EQUIPMENT. THE PROPERTY OWNER SHALL BE RESPONSIBLE TO PAY FOR THE SITE SURVEY WHETHER OR NOT THE SURVEY INDICATES THAT EQUIPMENT IS NECESSARY. THE OWNER SHALL COORDINATE WITH THE SUPERVISOR OF RADIO COMMUNICATIONS FOR PORTSMOUTH. THE SURVEY SHALL BE COMPLETED AND ANY REQUIRED EQUIPMENT INSTALLED, TESTED, AND ACCEPTED PRIOR TO THE ISSUANCE OF A CERTIFICATE OF OCCUPANCY.
- 10) ANY HISTORIC SERVICES ENCOUNTERED DURING UTILITY WORK SHALL BE ABANDONED PER THE REQUIREMENTS OF THE PORTSMOUTH DEPARTMENT OF PUBLIC WORKS.




**107/27**

**BRICK MARKET**  
 60 PENHALLOW STREET  
 PROPOSED  
 4 STORY BUILDING  
 17,200 SF FOOTPRINT  
 (INCLUDING PLINTHS)  
 FF 28.5

2000  
 MAGNETIC  
 R.C.R.D. PLAN  
 C-28714


**BRICK MARKET**  
 60 PENHALLOW STREET  
 PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
4	GREASE TRAP, TRANSFORMERS	1/8/20
3	NOTE 10, UTILITIES	12/23/19
2	ISSUED FOR DESIGN REVIEW	12/2/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19



APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_



SCALE: 1"=10" MAY 2019

UTILITY PLAN **C4**





**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors


200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

**NOTES:**

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- 4) CITY SHALL BE NOTIFIED IF THERE ARE ANY CONFLICTS WITH PROPOSED DRAINAGE PIPES UNCOVERED DURING CONSTRUCTION. REVIEW AND APPROVAL OF REMEDIES, BY THE CITY, REQUIRED.

**DRAIN STRUCTURE TABLE**

STRUCTURE	RIM ELEV.	INV. ELEV. IN INV. ELEV. OUT	DOWNSTREAM STRUCTURE
PIPE			
DMH 5961	28.52	21.87 6" CLAY 22.07 6" CLAY 24.19 6" CLAY 22.37 6" CLAY 23.12 15" HDPE	DMH 5962
15" HDPE	L = 16 LF, S = 0.0213 ft./ft.		
CB 5964	27.76	24.43 12" HDPE	DMH 5962
12" HDPE	L = 2 LF, S = 0.10 ft./ft.		
DMH 5962	27.99	24.23 12" HDPE 22.78 15" HDPE 23.35 12" HDPE 22.79 18" HDPE	DMH 5963
18" HDPE	L = 68 LF, S = 0.0209 ft./ft.		
CB 5966	27.05	23± 6" DRAIN 23.62 12" HDPE	DMH 5963
12" HDPE	L = 2 LF, S = 0.075 ft./ft.		
DMH 5963	27.10	23.47 12" HDPE 21.37 18" HDPE 21.28 12" HDPE 21.12 18" HDPE	DMH 5958
18" HDPE	L = 83 LF, S = 0.0143 ft./ft.		
DMH 5958	26.29	22.59 12" HDPE 19.93 18" HDPE 22.17 12" HDPE 19.91 18" HDPE	DMH 5957 NOT FOUND
18" HDPE	L = ?, S = ?		
CB 4265	27.30	24.14 12" RCP	CB 4267
12" RCP	L = 62 LF, S = 0.005 ft./ft.		
CB 4266	27.34	24.14 12" RCP	CB 4267
12" RCP	L = 24 LF, S = 0.0125 ft./ft.		
CB 4267	26.84	23.82 12" RCP 23.84 12" RCP 23.49 12" HDPE	CB 5966



107/27

2000  
MAGNETIC  
R.C.R.D. PLAN  
C-28714

TRENCH DRAIN BY  
WWW.IRONAGEGRATES.COM  
ELEVATION 28.4 @ FOUNTAIN  
VARIES @ BENCH

15 LF - 1/2" GALVANIZED  
SLOTTED DRAIN  
WWW.SLOTDRAINSYSTEMS.COM

PDH 5  
RIM = 28.35  
INV. IN = 23.9 RD  
INV. IN = 23.9 TD  
INV. OUT = 23.8 18"  
146 LF-18" HDPE  
S = 0.01375 ft./ft.

14 LF - 1/2" GALVANIZED  
SLOTTED DRAIN  
WWW.SLOTDRAINSYSTEMS.COM

23 LF - 1/2" GALVANIZED  
SLOTTED DRAIN  
WWW.SLOTDRAINSYSTEMS.COM

ROOF DRAIN  
56 LF-8" HDPE  
S = 0.01 ft./ft.

ROOF DRAIN  
6 LF-8" HDPE  
S = 0.01 ft./ft.

CONNECT EXISTING  
DOWNSPOUT  
(TYP.)


ROOF DRAIN  
25 LF-8" HDPE  
S = 0.01 ft./ft.

ROOF DRAIN  
21 LF-8" HDPE  
S = 0.01 ft./ft.

ROOF DRAIN  
21 LF-8" HDPE  
S = 0.01 ft./ft.


APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_



**BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
3	DRAIN PIPE SIZE	12/23/19
2	ISSUED FOR DESIGN REVIEW	12/21/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19



SCALE: 1"=10' MAY 2019

**GRADING AND DRAINAGE  
PLAN** **C5**



# Landscape Notes

- Design is based on drawings by Ambit Engineering dated November 18, 2019 and may require adjustment due to actual field conditions.
- The contractor shall follow best management practices during construction and shall take all means necessary to stabilize and protect the site from erosion.
- Erosion Control shall be in place prior to construction.
- The Contractor shall verify layout and grades and inform the Landscape Architect or Client's Representative of any discrepancies or changes in layout and/or grade relationships prior to construction.
- It is the contractor's responsibility to verify drawings provided are to the correct scale prior to any bid, estimate or installation. A graphic scale bar has been provided on each sheet for this purpose. If it is determined that the scale of the drawing is incorrect, the landscape architect will provide a set of drawings at the correct scale, at the request of the contractor.
- Trees to Remain within the construction zone shall be protected from damage for the duration of the project by snow fence or other suitable means of protection to be approved by Landscape Architect or Client's Representative. Snow fence shall be located at the drip line at a minimum and shall include any and all surface roots. Do not fill or mulch on the trunk flare. Do not disturb roots. In order to protect the integrity of the roots, branches, trunk and bark of the tree(s) no vehicles or construction equipment shall drive or park in or on the area within the drip line(s) of the tree(s). Do not store any refuse or construction materials or portalets within the tree protection area.
- This plan is for review purposes only, NOT for Construction. Construction Documents will be provided upon request.
- Location, support, protection, and restoration of all existing utilities and appurtenances shall be the responsibility of the Contractor.
- The Contractor shall verify exact location and elevation of all utilities with the respective utility owners prior to construction. Call DIGSAFE at 1-888-344-7233.
- The Contractor shall procure any required permits prior to construction.
- Prior to any landscape construction activities Contractor shall test all existing loam and loam from off-site intended to be used for lawns and plant beds using a thorough sampling throughout the supply. Soil testing shall indicate levels of pH, nitrates, macro and micro nutrients, texture, soluble salts, and organic matter. Contractor shall provide Landscape Architect with test results and recommendations from the testing facility along with soil amendment plans as necessary for the proposed plantings to thrive. All loam to be used on site shall be amended as approved by the Landscape Architect prior to placement.
- Contractor shall notify landscape architect or owner's representative immediately if at any point during demolition or construction a site condition is discovered which may negatively impact the completed project. This includes, but is not limited to, unforeseen drainage problems, unknown subsurface conditions, and discrepancies between the plan and the site. If a contractor is aware of a potential issue, and does not bring it to the attention of the landscape architect or owner's representative immediately, they may be responsible for the labor and materials associated with correcting the problem.
- The Contractor shall furnish and plant all plants shown on the drawings and listed thereon. All plants shall be nursery-grown under climatic conditions similar to those in the locality of the project. Plants shall conform to the botanical names and standards of size, culture, and quality for the highest grades and standards as adopted by the American Association of Nurserymen, Inc. in the *American Standard of Nursery Stock*, American Standards Institute, Inc. 230 Southern Building, Washington, D.C. 20005.
- A complete list of plants, including a schedule of sizes, quantities, and other requirements is shown on the drawings. In the event that quantity discrepancies or material omissions occur in the plant materials list, the planting plans shall govern.
- All plants shall be legibly tagged with proper botanical name.
- The Contractor shall guarantee all plants for not less than one year from time of acceptance.
- Owner or Owner's Representative will inspect plants upon delivery for conformity to Specification requirements. Such approval shall not affect the right of inspection and rejection during or after the progress of the work. The Owner reserves the right to inspect and/or select all trees at the place of growth and reserves the right to approve a representative sample of each type of shrub, herbaceous perennial, annual, and ground cover at the place of growth. Such sample will serve as a minimum standard for all plants of the same species used in this work.
- No substitutions of plants may be made without prior approval of the Owner or the Owner's Representative for any reason.
- All landscaping shall be provided with either of the following:
  - An underground sprinkling system
  - An outside hose attachment within 150 feet
- If an automatic irrigation system is installed, all irrigation valve boxes shall be located within planting bed areas.
- The contractor is responsible for all plant material from the time their work commences until final acceptance. This includes but is not limited to maintaining all plants in good condition, the security of the plant material once delivered to the site, and watering of plants. Plants shall be appropriately watered prior to, during and after planting. It is the contractor's responsibility to provide water from off site, should it not be available on site.
- All disturbed areas will be dressed with 6" of topsoil and planted as noted on the plans or seeded except plant beds. Plant beds shall be prepared to a depth of 12" with 75% loam and 25% compost.
- Trees, ground cover, and shrub beds shall be mulched to a depth of 2" with one-year-old, well-composted, shredded native bark not longer than 4" in length and 3/4" in width, free of woodchips and sawdust. Mulch for ferns and herbaceous perennials shall be no longer than 1" in length. Trees in lawn areas shall be mulched in a 5' diameter min. saucer. Color of mulch shall be black.
- In no case shall mulch touch the stem of a plant nor shall mulch ever be more than 3" thick total (including previously applied mulch) over the root ball of any plant.
- Secondary lateral branches of deciduous trees overhanging vehicular and pedestrian travel ways shall be pruned up to a height of 6' to allow clear and safe passage of vehicles and pedestrians under tree canopy.
- Snow shall be removed from the site.
- Landscape Architect is not responsible for the means and methods of the contractor.

# City of Portsmouth Notes

- The property owner and all future property owners shall be responsible for the maintenance, repair and replacement of all required screening and landscape materials.
- All required plant materials shall be tended and maintained in a healthy growing condition, replaced when necessary, and kept free of refuse and debris. All required fences and walls shall be maintained in good repair.
- The property owner shall be responsible to remove and replace dead or diseased plant materials immediately with the same type, size and quantity of plant materials as originally installed, unless alternative plantings are requested, justified and approved by the Planning Board or Planning Director.

# Plant List


## Plant List

### SHRUBS

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Cham	<i>Chamaecyparis obtusa</i> 'Gracilis'	Gracilis Falsecypress	6	7-8' ht	B&B Matched Specimen
Hs	<i>Hibiscus syriacus</i> 'Ardens'	Ardens Rose-of-Sharon	1	6-7' ht	B&B Full
Ig	<i>Ilex glabra</i> 'Shamrock'	Shamrock Inkberry	13	5 gal	Full
ImB	<i>Ilex meserve</i> 'Blue Maid'	Blue Maid Holly	1	6-7' ht	B&B Full
Leu	<i>Leucothoe fontanesiana</i> 'Silver Run'	Silver Run Leucothoe	9	3 gal	
Md	<i>Microbiota decussata</i>	Russian Cypress	9	5 gal	
Rhs	<i>Rhododendron</i> 'Scintillation'	Scintillation Rhododendron	6	2.5-3' ht	B&B

### PERENNIALS, GROUNDCOVERS, VINES AND ANNUALS

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Ast	<i>Astilbe</i> 'Fanal'	Rubryed Astilbe	15	1 gal	
Cal	<i>Calamagrostis acutifolia</i> 'Karl Foerster'	Feather Reed Grass	14	3 gal	
Hak	<i>Hakonechloa macra</i> 'Aureola'	Golden Japanese Forest Grass	3	1 gal	
Nep	<i>Nepeta faassenii</i> x 'Six Hills Giant'	Lavender blue Catmint	6	1 gal	



### PAVING MATERIALS LIST

MATERIAL	FINISH	DIMENSIONS	NOTES	
Bluestone Banding	Select Bluestone	Thermal	3' W x 3'+/- L x 4" thick	Custom radius pieces (see plans). Contractor to provide shop drawings. Select stone for greenish blue color tones, without weeds or spalling.
Granite Paving	Deer Isle Granite	Thermal	2' W x 3' L x 4" thick	
Granite Edging in Plaza	Wausau Granite	Thermal	4" W x 4" L x 4" thick	
Granite Edging in Sidewalk	To match existing	To match existing	Thickness to match brick	Length and width dimensions vary, see plan.
Brick	Clay paving brick			Specification TBD


**woodburn & company**  
LANDSCAPE ARCHITECTURE  
103 Kent Place  
Newmarket, New Hampshire  
Phone: 603.659.5949

**Brick Market**  
**60 PENHALLOW LANDSCAPE PLAN**  
Portsmouth, New Hampshire

Drawn By: VM  
Checked By: RW  
Scale: 1" = 10' - 0"  
Date: November 18, 2019  
Revisions:  
November 26, 2019  
January 8, 2020

**L-1**  
Sheet 1 of 5





**Plant List**

**TREES**

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Mag	<i>Magnolia loebneri</i> Leonard Messel	Leonard Messel Magnolia	1	8-10' Ht	B&B

**SHRUBS**



Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Box	<i>Buxus microphylla</i> 'Winter Gem'	Winter Gem Boxwood	6	3 gal	
Enk	<i>Enkianthus campanulatus</i>	Redvein Enkianthus	1	7-8' ht	Multi-stem tree form, B&B
Hy	<i>Hydrangea arborescens</i> 'Incrediball'	Incrediball Hydrangea	13	5 gal	
RhS	<i>Rhododendron</i> 'Scintillation'	Scintillation Rhododendron	7	2.5-3' ht	B&B
Tax	<i>Taxus media</i> 'Tauntorii'	Taunton Yew	5	2.5-3' ht	B&B

**PERENNIALS, GROUNDCOVERS, VINES and ANNUALS**

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
An	<i>Anemone</i> 'September Charm'	Japanese Anemone	20	1 gal	
Cal	<i>Calamagrostis acutifolia</i> 'Karl Foerster'	Feather Reed Grass	11	1 gal	
H1	<i>Hosta</i> 'Bold Ribbons'	Bold Ribbons Hosta	4	1 gal	
Hak	<i>Hakonechloa macra</i> 'Aureola'	Golden Japanese Forest Grass	8	1 gal	


**PAVING MATERIALS LIST**

	MATERIAL	FINISH	DIMENSIONS	NOTES
Bluestone Banding	Select Bluestone	Thermal	3' W x 3'+/- L x 4" thick	Custom radius pieces (see plans). Contractor to provide shop drawings. Select stone for greenish blue color tones, without weeds or spalling.
Granite Paving	Deer Isle Granite	Thermal	2' W x 3' L x 4" thick	
Granite Edging in Plaza	Wausau Granite	Thermal	4" W x 4" L x 4" thick	
Granite Edging in Sidewalk	To match existing	To match existing	Thickness to match brick	Length and width dimensions vary, see plan.
Brick	Clay paving brick			Specification TBD





Drawn By: VM  
Checked By: RW  
Scale: 1" = 10' - 0"  
Date: November 26, 2019  
Revisions:  
December 20, 2019  
January 8, 2020








**A Fountain Section**  
 Scale: 1/2"=1'-0"




**B Fountain Plan**  
 Scale: 1/2"=1'-0"



**C Mural Wall Section**  
 Scale: 3/4"=1'-0"




**D Paving Enlargement**  
 Scale: 1/2"=1'-0"




**PAVING MATERIALS LIST**

	MATERIAL	FINISH	DIMENSIONS	NOTES
Bluestone Banding	Select Bluestone	Thermal	3' W x 3'+/- L x 4" thick	Custom radius pieces (see plans). Contractor to provide shop drawings. Select stone for greenish blue color tones, without reeds or spalling.
Granite Paving	Deer Isle Granite	Thermal	2' W x 3' L x 4" thick	
Granite Edging in Plaza	Wausau Granite	Thermal	4" W x 4" L x 4" thick	
Granite Edging in Sidewalk	To match existing	To match existing	Thickness to match brick	Length and width dimensions vary, see plan.
Brick	Clay paving brick			Specification TBD






**A Bench Elevation**  
 Scale: 1/4"=1'-0"



**B Bench Plan**  
 Scale: 1/4"=1'-0"



**C Bench Section**  
 Scale: 3/4"=1'-0"






*Granite Edging - Wausau Granite*



*Granite Paving - Deer Isle Granite*



*Bluestone Paving*




*Tree Planters - 3'x3'x3'*



*Streetlife Round Podium Isle*



*Streetlife Solid Curved Bench - sits on top of Deer Isle granite wall (instead of metal legs as shown)*




*Granite Fountain*

*Wausau Red Granite*

*Deer Isle Granite*

*Bluestone*




*Mural Wall - 6' or 8' tall (see plan), Deer Isle granite base, posts to match wood on building*



*30 Penhallow Pocket Park - flush brick walkway with planters, leading to seating area*




*Trash Receptacle - Victor Stanley S-4524 in bronze*



*Example of existing flush brick sidewalk on Sheafe Street*








**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
300 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

**NOTES:**

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- 4) CITY SHALL BE NOTIFIED IF THERE ARE ANY CONFLICTS WITH PROPOSED DRAINAGE PIPES UNCOVERED DURING CONSTRUCTION. REVIEW AND APPROVAL OF REMEDIES, BY THE CITY, REQUIRED.
- 5) ANY HISTORIC SERVICES ENCOUNTERED DURING UTILITY WORK SHALL BE ABANDONED PER THE REQUIREMENTS OF THE PORTSMOUTH DEPARTMENT OF PUBLIC WORKS.
- 6) TEST PITS ARE REQUIRED TO VALIDATE THE DESIGN SHOWN HEREON. IT IS LIKELY THAT THERE WILL BE IMPACTS TO THE TELEPHONE DUCT SYSTEM CURRENTLY IN THE CITY STREETS. WORK WITH CONSOLIDATED COMMUNICATION TO RELOCATE IMPACTED DUCTS AS NEEDED.




APPROVED BY THE PORTSMOUTH PLANNING BOARD



**BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
1	ADDED NOTE 6	1/8/20
0	ISSUED FOR COMMENT	12/23/19




SCALE: 1"=20' MAY 2019

**DANIEL STREET  
OFFSITE IMPROVEMENTS** **P1**

J:\\_0055\N\_3000\N\_3039\2019 Site Development 60 Penhallow Plans & Specs\She\_3039 SITE 60 PENHALLOW.dwg, P1 DANIEL STREET

CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_






**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors

200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315


**NOTES:**

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
- 4) COORDINATE ALL WORK WITH EVERSOURCE - UTILIZING FINAL APPROVED PLANS



**BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
1	TRANSFORMERS	1/8/20
0	ISSUED FOR COMMENT	12/23/19




SCALE: 1"=20' DECEMBER 2019

**PENHALLOW STREET  
OFFSITE IMPROVEMENTS**

**P2**

APPROVED BY THE PORTSMOUTH PLANNING BOARD

CHAIRMAN \_\_\_\_\_ DATE \_\_\_\_\_



I:\JOBSS\IN 3000\IN 3039\2019 Site Development 60 Penhallow\Plans & Specs\Site\3039 SITE 60 PENHALLOW.dwg, P2 PENHALLOW STREET



# EROSION CONTROL NOTES

## CONSTRUCTION SEQUENCE

DO NOT BEGIN CONSTRUCTION UNTIL ALL LOCAL, STATE AND FEDERAL PERMITS HAVE BEEN APPLIED FOR AND RECEIVED.

THE CONTRACTOR SHALL OBTAIN AN NPDES PHASE II STORMWATER PERMIT AND SUBMIT A NOTICE OF INTENT (N.O.I) BEFORE BEGINNING CONSTRUCTION AND SHALL HAVE ON SITE A STORMWATER POLLUTION PREVENTION PLAN (S.W.P.P.P.) AVAILABLE FOR INSPECTION BY THE PERMITTING AUTHORITY DURING THE CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CARRYING OUT THE S.W.P.P.P. AND INSPECTING AND MAINTAINING ALL BMP'S CALLED FOR BY THE PLAN. THE CONTRACTOR SHALL SUBMIT A NOTICE OF TERMINATION (N.O.T.) FORM TO THE REGIONAL EPA OFFICE WITHIN 30 DAYS OF FINAL STABILIZATION OF THE ENTIRE SITE OR TURNING OVER CONTROL OF THE SITE TO ANOTHER OPERATOR.

INSTALL PERIMETER CONTROLS, I.E., SILT/SOXX, FODS AND CATCH BASIN PROTECTION AROUND THE LIMITS OF DISTURBANCE BEFORE ANY CONSTRUCTION. THE USE OF HAYBALES IS NOT ALLOWED.

REMOVE DEBRIS AND RUBBISH AS REQUIRED. DEMOLISH BUILDINGS AND OTHER IMPROVEMENTS AS SHOWN ON THE PLANS.

CUT AND CAP IMPACTED UTILITIES AS DIRECTED BY UTILITY PROVIDERS.

CONSTRUCT OFF SITE UTILITY IMPROVEMENTS NECESSARY TO CONSTRUCT BUILDING.

CONSTRUCT FOUNDATION

LAYOUT AND INSTALL ALL BURIED UTILITIES AND SERVICES UP TO THE PROPOSED BUILDING FOUNDATION. CAP AND MARK TERMINATIONS OR LOG SWING TIES.

BEGIN BUILDING CONSTRUCTION.

CONNECT UTILITIES AS NEEDED.

PLACE BASE MATERIALS IN WALKWAYS AND PROTECT.

CONTINUE BUILDING CONSTRUCTION.

PLANT LANDSCAPING IN AREAS OUT OF WAY OF BUILDING CONSTRUCTION. CONSTRUCT OTHER SITE IMPROVEMENTS.

AFTER BUILDINGS ARE COMPLETED, FINISH ALL REMAINING WORK.

REMOVE TRAPPED SEDIMENTS FROM COLLECTION DEVICES AS APPROPRIATE, AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES UPON COMPLETION OF FINAL STABILIZATION OF THE SITE.

## GENERAL CONSTRUCTION NOTES

THE EROSION CONTROL PROCEDURES SHALL CONFORM TO SECTION 645 OF THE "STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION" OF THE NHDOT, AND "STORM WATER MANAGEMENT AND EROSION AND SEDIMENT CONTROL HANDBOOK FOR URBAN AND DEVELOPING AREAS IN NEW HAMPSHIRE". THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

DURING CONSTRUCTION AND THEREAFTER, EROSION CONTROL MEASURES ARE TO BE IMPLEMENTED AS NOTED. THE SMALLEST PRACTICAL AREA OF LAND SHOULD BE EXPOSED AT ANY ONE TIME DURING DEVELOPMENT. NO DISTURBED AREA SHALL BE LEFT UNSTABILIZED FOR MORE THAN 45 DAYS.

ANY DISTURBED AREAS WHICH ARE TO BE LEFT TEMPORARILY, AND WHICH WILL BE REGRADED LATER DURING CONSTRUCTION SHALL BE MACHINE HAY MULCHED AND SEEDED WITH RYE GRASS TO PREVENT EROSION.

DUST CONTROL: IF TEMPORARY STABILIZATION PRACTICES, SUCH AS TEMPORARY VEGETATION AND MULCHING, DO NOT ADEQUATELY REDUCE DUST GENERATION, APPLICATION OF WATER OR CALCIUM CHLORIDE SHALL BE APPLIED IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES.

SILT FENCES AND SILT/SOXX SHALL BE PERIODICALLY INSPECTED DURING THE LIFE OF THE PROJECT AND AFTER EACH STORM. ALL DAMAGED SILT FENCES AND SILT/SOXX SHALL BE REPAIRED. SEDIMENT DEPOSITS SHALL PERIODICALLY BE REMOVED AND DISPOSED IN A SECURED LOCATION.

AVOID THE USE OF FUTURE OPEN SPACES ( LOAM AND SEED AREAS ) WHEREVER POSSIBLE DURING CONSTRUCTION. CONSTRUCTION TRAFFIC SHALL USE THE ROADBEDS OF FUTURE ACCESS DRIVES AND PARKING AREAS.

ADDITIONAL TOPSOIL REQUIRED FOR THE ESTABLISHMENT OF VEGETATION SHALL BE STOCKPILED IN AMOUNTS NECESSARY TO COMPLETE FINISHED GRADING OF ALL EXPOSED AREAS--CONSTRUCT SILT FENCE OR SILT/SOXX AROUND TOPSOIL STOCKPILE.

AREAS TO BE FILLED SHALL BE CLEARED, GRUBBED AND STRIPPED OF TOPSOIL TO REMOVE TREES, VEGETATION, ROOTS OR OTHER OBJECTIONABLE MATERIAL. STUMPS SHALL BE DISPOSED OF IN AN APPROVED FACILITY.

ALL FILLS SHALL BE PLACED AND COMPACTED TO REDUCE EROSION, SLIPPAGE, SETTLEMENT, SUBSIDENCE OR OTHER RELATED PROBLEMS.

ALL NON-STRUCTURAL, SITE-FILL SHALL BE PLACED AND COMPACTED TO 90% MODIFIED PROCTOR DENSITY IN LAYERS NOT EXCEEDING 18 INCHES IN THICKNESS UNLESS OTHERWISE NOTED.

FROZEN MATERIAL OR SOFT, MUCKY OR HIGHLY COMPRESSIBLE MATERIAL, TRASH, WOODY DEBRIS, LEAVES, BRUSH OR ANY DELETERIOUS MATTER SHALL NOT BE INCORPORATED INTO FILLS.

FILL MATERIAL SHALL NOT BE PLACED ON FROZEN FOUNDATION SUBGRADE.

DURING CONSTRUCTION AND UNTIL ALL DEVELOPED AREAS ARE FULLY STABILIZED, ALL EROSION CONTROL MEASURES SHALL BE INSPECTED WEEKLY AND AFTER EACH ONE HALF INCH OF RAINFALL.

THE CONTRACTOR SHALL MODIFY OR ADD EROSION CONTROL MEASURES AS NECESSARY TO ACCOMMODATE PROJECT CONSTRUCTION.

ALL ROADWAYS AND PARKING AREAS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. ALL CUT AND FILL SLOPES SHALL BE SEEDED/LOAMED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.

AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:  
 - BASE COURSE GRAVELS HAVE BEEN INSTALLED ON AREAS TO BE PAVED  
 - A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED  
 - A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED  
 - EROSION CONTROL BLANKETS HAVE BEEN INSTALLED

## VEGETATIVE PRACTICE

FOR PERMANENT MEASURES AND PLANTINGS:

LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF 2 TONS PER ACRE.

FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 500 POUNDS PER ACRE OF 10-20-20 FERTILIZER.

SEED SHALL BE SOWN AT THE RATES SHOWN IN THE TABLE BELOW. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AT A RATE OF 1.5 TO 2 TONS PER ACRE, AND SHALL BE HELD IN PLACE USING APPROPRIATE TECHNIQUES FROM THE EROSION AND SEDIMENT CONTROL HANDBOOK.

THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED SHALL BE RESEED, AND ALL NOXIOUS WEEDS REMOVED.

A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE:

GENERAL COVER	PROPORTION	SEEDING RATE
CREEPING RED FESCUE	50%	100 LBS/ACRE
KENTUCKY BLUEGRASS	50%	

SLOPE SEED (USED ON ALL SLOPES GREATER THAN OR EQUAL TO 3:1)

CREEPING RED FESCUE	42%	
TALL FESCUE	42%	48 LBS/ACRE
BIRDSFOOT TREFLOIL	16%	

IN NO CASE SHALL THE WEED CONTENT EXCEED ONE PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH APPLICABLE STATE AND FEDERAL SEED LAWS.

FOR TEMPORARY PROTECTION OF DISTURBED AREAS:  
 MULCHING AND SEEDED SHALL BE APPLIED AT THE FOLLOWING RATES:  
 PERENNIAL RYE: 0.7 LBS/1,000 S.F.  
 MULCH: 1.5 TONS/ACRE

## MAINTENANCE AND PROTECTION

THE CONTRACTOR SHALL MAINTAIN ALL LOAM & SEED AREAS UNTIL FINAL ACCEPTANCE AT THE COMPLETION OF THE CONTRACT. MAINTENANCE SHALL INCLUDE WATERING, WEEDING, REMOVAL OF STONES AND OTHER FOREIGN OBJECTS OVER 1/2 INCHES IN DIAMETER WHICH MAY APPEAR AND THE FIRST TWO (2) CUTTINGS OF GRASS NO CLOSER THEN TEN (10) DAYS APART. THE FIRST CUTTING SHALL BE ACCOMPLISHED WHEN THE GRASS IS FROM 2 1/2 TO 3 INCHES HIGH. ALL BARE AND DEAD SPOTS WHICH BECOME APPARENT SHALL BE PROPERLY PREPARED, LIMED AND FERTILIZED, AND RESEED, BY THE CONTRACTOR AT HIS EXPENSE AS MANY TIMES AS NECESSARY TO SECURE GOOD GROWTH. THE ENTIRE AREA SHALL BE MAINTAINED, WATERED AND CUT UNTIL ACCEPTANCE OF THE LAWN BY THE OWNER'S REPRESENTATIVE.

THE CONTRACTOR SHALL TAKE WHATEVER MEASURES ARE NECESSARY TO PROTECT THE GRASS WHILE IT IS DEVELOPING.

TO BE ACCEPTABLE, SEEDED AREAS SHALL CONSIST OF A UNIFORM STAND OF AT LEAST 90 PERCENT ESTABLISHED PERMANENT GRASS SPECIES, WITH UNIFORM COUNT OF AT LEAST 100 PLANTS PER SQUARE FOOT.

SEEDED AREAS WILL BE FERTILIZED AND RESEED AS NECESSARY TO INSURE VEGETATIVE ESTABLISHMENT.

THE SWALES WILL BE CHECKED WEEKLY AND REPAIRED WHEN NECESSARY UNTIL ADEQUATE VEGETATION IS ESTABLISHED.

THE SILT FENCE OR SILT/SOXX BARRIER SHALL BE CHECKED AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL.


SILT FENCING AND SILT/SOXX SHALL BE REMOVED ONCE VEGETATION IS ESTABLISHED, AND DISTURBED AREAS RESULTING FROM SILT FENCE AND SILT/SOXX REMOVAL SHALL BE PERMANENTLY SEEDED.

## WINTER NOTES

ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.



ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.

AFTER NOVEMBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3.



- NOTES:
1. ALL MATERIAL TO MEET FILTREXX SPECIFICATIONS.
  2. FILTREXX SYSTEM SHALL BE INSTALLED BY A CERTIFIED FILTREXX INSTALLER.
  3. THE CONTRACTOR SHALL MAINTAIN THE COMPOST FILTRATION SYSTEM IN A FUNCTIONAL CONDITION AT ALL TIMES. IT WILL BE ROUTINELY INSPECTED AND REPAIRED WHEN REQUIRED.
  4. SILT/SOXX DEPICTED IS FOR MINIMUM SLOPES, GREATER SLOPES MAY REQUIRE ADDITIONAL PLACEMENTS.
  5. THE COMPOST FILTER MATERIAL WILL BE DISPERSED ON SITE WHEN NO LONGER REQUIRED, AS DETERMINED BY THE ENGINEER.

## A FILTREXX® SILT/SOXX™ FILTRATION SYSTEM (IF NEEDED) NTS




## MAINTENANCE

1. MUD AND SOIL PARTICLES WILL EVENTUALLY CLOG THE VOIDS IN THE GRAVEL AND THE EFFECTIVENESS OF THE GRAVEL PAD WILL NOT BE SATISFACTORY. WHEN THIS OCCURS, THE PAD SHOULD BE TOP DRESSED WITH NEW STONE. COMPLETE REPLACEMENT OF THE PAD MAY BE NECESSARY WHEN THE PAD BECOMES COMPLETELY CLOGGED.
2. IF WASHING FACILITIES ARE USED, THE SEDIMENT TRAPS SHOULD BE CLEANED OUT AS OFTEN AS NECESSARY TO ASSURE THAT ADEQUATE TRAPPING EFFICIENCY AND STORAGE VOLUME IS AVAILABLE. VEGETATIVE FILTER STRIPS SHOULD BE MAINTAINED TO INSURE A VIGOROUS STAND OF VEGETATION AT ALL TIMES.


## CONSTRUCTION SPECIFICATIONS

1. STONE FOR A STABILIZED CONSTRUCTION ENTRANCE SHALL BE 1 TO 2 INCH STONE.
2. THE LENGTH OF THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 50 FEET, EXCEPT FOR A SINGLE RESIDENTIAL LOT WHERE A 30 FOOT MINIMUM LENGTH WOULD APPLY.
3. THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6 INCHES.
4. THE WIDTH OF THE ENTRANCE SHALL NOT BE LESS THAN THE FULL WIDTH OF THE ENTRANCE WHERE INGRESS OR EGRESS OCCURS OR 10 FEET, WHICHEVER IS GREATER. GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE. FILTER CLOTH IS NOT REQUIRED FOR A SINGLE FAMILY RESIDENCE LOT.
6. ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION ENTRANCE SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERM WITH 5:1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, WASHED, OR TRACKED ONTO PUBLIC RIGHT-OF-WAY MUST BE REMOVED PROMPTLY.
8. WHEELS SHALL BE CLEANED TO REMOVE MUD PRIOR TO ENTRANCE ONTO PUBLIC RIGHT-OF-WAY, WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH STONE WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.



## B STABILIZED CONSTRUCTION ENTRANCE (IF NEEDED) NTS



LENGTH (L) & WIDTH (W) AS REQUIRED TO FIT NHDOT TYPE GRATE & FRAME.



## C CATCH BASIN INLET BASKET (IF NEEDED) NTS



- NOTES:
1. CONCRETE SHALL BE 4,000 P.S.I. AFTER 28 DAYS.
  2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQ. IN. PER LINEAR FT. IN ALL SECTIONS & SHALL BE PLACED IN THE CENTER THIRD OF WALL.
  3. THE TONGUE OR THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQ. IN. PER LINEAR FT.
  4. EACH CASTING TO HAVE LIFTING HOLES CAST IN.
  5. OUTLET HOOD SHALL BE A "SNOUT" BY BEST MANAGEMENT PRODUCTS, INC. OR APPROVED EQUAL. SIZING AND INSTALLATION PER MANUFACTURER'S RECOMMENDATIONS.

## D CATCH BASIN w/ OIL-DEBRIS HOOD (IF NEEDED) NTS

**AMBIT ENGINEERING, INC.**  
 Civil Engineers & Land Surveyors  
 200 Griffin Road - Unit 3  
 Portsmouth, N.H. 03801-7114  
 Tel (603) 430-9282  
 Fax (603) 436-2315

## NOTES:

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).

## BRICK MARKET 60 PENHALLOW STREET PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
2	DETAIL D	12/23/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19




SCALE: AS SHOWN  
 OCTOBER 2019

## DETAILS D1



**NOTES:**




- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).



**BRICK PAVEMENT NOTES**


- SCOPE OF WORK:**
- 1) THE WORK SHALL CONSIST OF CONSTRUCTING/RECONSTRUCTING THE SUB-BASE AND CONSTRUCTING A NEW BRICK SIDEWALK AS DIRECTED IN THE FIELD BY THE ENGINEER AND COORDINATED WITH PORTSMOUTH DPW.
  - 2) REVEAL SHALL BE COORDINATED WITH PORTSMOUTH DPW.
- METHODS OF CONSTRUCTION:**
- A) ALL LABOR AND MATERIALS SHALL CONFORM TO THE STATE OF NEW HAMPSHIRE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, SECTION 608, AND CITY OF PORTSMOUTH SPECIFICATIONS FOR NEW BRICK SIDEWALK, SECTION 6.
  - B) EXCAVATION FOR SIDEWALKS SHALL BE AT A DEPTH OF 10 INCHES BELOW FINISH GRADE. IN AREAS NOT BUTTING CURBING OR BUILDINGS, THE EXCAVATION SHALL BE 6 INCHES WIDER THAN THE FINISHED SIDEWALK WIDTH. AT ALL DRIVE CROSSINGS, THE DEPTH OF EXCAVATION SHALL BE INCREASED ACCORDINGLY. THE CONTRACTOR SHALL PROVIDE NEAT AND SQUARE CUTTING OF EXISTING ASPHALT ROAD SURFACE AS NEEDED. ALL UNSUITABLE MATERIAL SHALL BE REMOVED AND DISPOSED OF OFF-SITE AT THE CONTRACTOR'S OWN EXPENSE.
  - C) THE BASE MATERIAL SHALL CONSIST OF A MIXTURE OF STONES OR ROCK FRAGMENTS AND PARTICLES WITH 100% PASSING THE 3 INCH SIEVE, 95% TO 100% PASSING THE 2 INCH SIEVE, 55% TO 85% PASSING THE 1 INCH SIEVE, AND 27% TO 52% PASSING THE NO. 4 SIEVE. AT LEAST 50% OF THE MATERIALS RETAINED ON THE 1 INCH SIEVE SHALL HAVE A FRACTURED FACE. THE BASE MATERIAL SHALL BE THOROUGHLY COMPACTED TO THE DEPTH SPECIFIED OR DIRECTED. IN THE WAY OF ALL DRIVE CROSSINGS THE BASE WILL BE INCREASED TO A COMPACTED DEPTH OF 12 INCHES. GRAVEL REQUIREMENTS FOR RECONSTRUCTION WILL BE AS DIRECTED, BASED ON SITE CONDITIONS. THE WORK INCLUDES BACKING UP ANY AND ALL CURB BEING INSTALLED BY OTHERS ON BOTH SIDES.
  - D) THE CLAY BRICK PAVERS SHALL BE LAID IN A 1 INCH BED OF A SAND MIXTURE COMPRISED OF: 3 PARTS SAND MIXED WITH 1 PART PORTLAND CEMENT.
  - E) THE CONTRACTOR SHALL LAY THE BRICKS SO THAT APPROXIMATELY 4.5 BRICKS SHALL COVER ONE SQUARE FOOT.
  - F) THE SIDEWALK SHALL PITCH TOWARDS THE STREET AS SHOWN ON THE GRADING PLAN.
  - G) IN AREAS WHERE THE FRONT OF THE BRICK SIDEWALK IS NOT ADJACENT TO GRANITE CURBING, THE CONTRACTOR SHALL INSTALL EDGING TO HOLD THE BRICKS IN PLACE. SUCH EDGING SHALL BE INSTALLED PER THE MANUFACTURER'S RECOMMENDATIONS.
  - H) THE CONTRACTOR SHALL SUBMIT A SAMPLE OF THE BRICKS FOR APPROVAL BY THE CITY BEFORE BRICKS ARE INSTALLED.

**CONSTRUCTION NOTE:**  
 EXISTING GRANITE CURB DISTURBED BY CONSTRUCTION SHALL BE REUSED AND ANY MISSING CURB SHALL BE REPLACED WITH NEW CURB MATCHING EXISTING CURB SIZE. NO CURB LESS THAN 3' IN LENGTH WILL BE ALLOWED.




Radius	Max. length
22' - 28'	3'
29' - 35'	5'
36' - 42'	6'
43' - 49'	7'
50' - 56'	8'
57' - 60'	9'
over 60'	10'

MIN. LENGTH OF CURB STONES 3FT.  
 MAX. LENGTH OF CURB STONES 10FT.  
 Laid on curves SEE CHART  
 NOTE: ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATE LENGTH.



**BRICK MARKET**  
 60 PENHALLOW STREET  
 PORTSMOUTH, N.H.

NO.	DESCRIPTION	DATE
2	DETAILS E, F, I & K	12/23/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19



SCALE: AS SHOWN OCTOBER 2019


DETAILS **D2**



**NOTES:**  
1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION WITHIN 100 FEET OF UNDERGROUND UTILITIES. THE EXCAVATOR IS RESPONSIBLE TO MAINTAIN MARKS.

2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.

3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).




**GAS SERVICE TRENCH**  
NTS

**BRICK MARKET**  
**60 PENHALLOW STREET**  
**PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
2	DETAILS L, N, O, & P	12/23/19
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19

REVISIONS



SCALE: AS SHOWN      OCTOBER 2019

DETAILS      **D3**

**SEWER UTILITY GENERAL NOTES:**

- MINIMUM PIPE SIZE FOR COMMERCIAL SERVICE SHALL BE SIX INCHES.
- PIPE AND JOINT MATERIALS:
  - PLASTIC SEWER PIPE
    - PIPE AND FITTINGS SHALL CONFORM TO THE FOLLOWING ASTM STANDARDS:
 

ASTM STANDARDS	GENERIC PIPE MATERIAL	SIZES APPROVED
D3034	*PVC (SOLID WALL)	8" THROUGH 15" (SDR 35)
F679	PVC (SOLID WALL)	18" THROUGH 27" (T-1 & T-2)
F789	PVC (SOLID WALL)	4" THROUGH 18" (T-1 TO T-3)
F794	PVC (RIBBED WALL)	8" THROUGH 36"
AWWA C900	*PVC (SOLID WALL)	8" THROUGH 18"


      - POLYVINYL CHLORIDE
    - DUCTILE IRON PIPE, FITTINGS AND JOINTS.
      - DUCTILE IRON PIPE AND FITTINGS FOR SEWERS SHALL CONFORM TO THE FOLLOWING STANDARDS OF THE UNITED STATES OF AMERICA STANDARDS INSTITUTE:
        - THICKNESS DESIGN OF DUCTILE IRON PIPE AND WITH ASTM A-536 DUCTILE IRON CASTINGS.
        - DUCTILE IRON PIPE, CENTRIFUGALLY CAST IN METAL MOULDS OR SAND LINED MOULDS FOR SEWER APPLICATIONS.
      - JOINTS SHALL BE OF THE MECHANICAL OR PUSH ON TYPE. JOINTS AND GASKETS SHALL CONFORM TO:
        - RUBBER GASKET JOINTS FOR CAST IRON PRESSURE PIPE & FITTINGS.
    - DAMAGED PIPE SHALL BE REJECTED AND REMOVED FROM THE JOB SITE.
    - JOINTS SHALL BE DEPENDENT UPON A NEOPRENE OR ELASTOMERIC GASKET FOR WATER TIGHTNESS. ALL JOINTS SHALL BE PROPERLY MATCHED WITH THE PIPE MATERIALS USED. WHERE DIFFERING MATERIALS ARE TO BE CONNECTED, AS AT THE STREET SEWER WYE OR AT THE FOUNDATION WALL, APPROPRIATE MANUFACTURED ADAPTERS SHALL BE USED.
    - TEES AND WYES: WHERE A TEE OR WYE IS NOT AVAILABLE IN THE EXISTING STREET SEWER, AN APPROPRIATE CONNECTION SHALL BE MADE DEPENDING ON THE PIPE ENCOUNTERED, FOR PVC PIPE CUT IN A SANITARY TEE, FOR CLAY PIPE, USE INSERT-A-TEE OR CUT IN A SANITARY TEE. ALL WORK TO BE APPROVED BY GOVERNING BODY.
    - HOUSE SEWER INSTALLATION: THE PIPE SHALL BE HANDLED, PLACED AND JOINED IN ACCORDANCE WITH INSTALLATION GUIDES OF THE APPROPRIATE MANUFACTURER. IT SHALL BE CAREFULLY BEDDED ON A 4 INCH LAYER OF CRUSHED STONE AND/OR GRAVEL AS SPECIFIED IN NOTE 10. BEDDING AND REFILL FOR DEPTH OF 12 INCHES ABOVE THE TOP OF THE PIPE SHALL BE CAREFULLY AND THOROUGHLY TAMPED BY HAND OR WITH APPROPRIATE MECHANICAL DEVICES.
    - THE PIPE SHALL BE LAID AT A CONTINUOUS AND CONSTANT GRADE FROM THE STREET SEWER CONNECTION TO THE FOUNDATION AT A GRADE OF NOT LESS THAN 1/4 INCH PER FOOT. PIPE JOINTS MUST BE MADE UNDER DRY CONDITIONS. IF WATER IS PRESENT, ALL NECESSARY STEPS SHALL BE TAKEN TO DEWATER THE TRENCH.
    - TESTING: WHEN REQUIRED BY THE GOVERNING AUTHORITY, TESTING SHALL CONFORM TO ENV-WQ 704.07.
    - ILLEGAL CONNECTIONS: NOTHING BUT SANITARY WASTE FLOW FROM DWELLING TOILETS, SINKS, LAUNDRY ETC. SHALL BE PERMITTED. ROOF LEADS, FOOTING DRAINS, SUMP PUMPS OR OTHER SIMILAR CONNECTIONS CARRYING RAIN WATER, DRAINAGE OR GROUND WATER SHALL NOT BE PERMITTED.
    - WATER SERVICE SHALL NOT BE LAID IN SAME TRENCH AS SEWER SERVICE, UNLESS IT IS ON A SHELF 12" HIGHER, AND 18" APART.
    - BEDDING: SCREENED GRAVEL AND/OR CRUSHED STONE, FREE FROM CLAY, LOAM, ORGANIC MATTER AND MEETING ASTM C33 STONE SIZE NO. 67.
 

100% PASSING	1 INCH SCREEN
90%-100% PASSING	3/4 INCH SCREEN
20%-55% PASSING	3/8 INCH SCREEN
0%-10% PASSING	#4 SIEVE
0%-5% PASSING	#8 SIEVE


 WHERE ORDERED BY THE ENGINEER TO STABILIZE THE TRENCH BASE, GRADED SCREENED GRAVEL OR CRUSHED STONE 1/2 INCH TO 1-1/2 INCH SHALL BE USED.
  - LOCATION: THE LOCATION OF THE TEE OR WYE SHALL BE RECORDED AND FILED IN THE MUNICIPAL RECORDS. IN ADDITION, A FERROUS METAL ROD OR PIPE SHALL BE PLACED OVER THE TEE OR WYE AS DESCRIBED IN THE TYPICAL "CHIMNEY" DETAIL, TO AID IN LOCATING THE BURIED PIPE WITH A DIP NEEDLE OR PIPE FINDER.
  - CAST-IN-PLACE CONCRETE: SHALL CONFORM TO THE REQUIREMENTS FOR CLASS A (3000 PSI) CONCRETE OF THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS AS FOLLOWS:
 

CEMENT:	6.0 BAGS PER CUBIC YARD
WATER:	5.75 GALLONS PER BAG OF CEMENT
MAXIMUM AGGREGATE SIZE:	3/4 INCH
  - CHIMNEYS: IF VERTICAL DROP INTO SEWER IS GREATER THAN 4 FEET, A CHIMNEY SHALL BE CONSTRUCTED FOR THE HOUSE CONNECTION. CHIMNEY INSTALLATION AS RECOMMENDED BY THE PIPE MANUFACTURER MAY BE USED IF APPROVED BY THE ENGINEER.
  - BACKFILL UP TO SUBBASE GRAVEL SHALL BE WITH EXCAVATED SOIL FROM TRENCHING OPERATIONS. COMPACT IN 8" LIFTS WITH VIBRATORY PLATE COMPACTORS TO 90% OF MODIFIED PROCTOR DENSITY. IF FINE-GRAINED, COMPACT WITH POGO STICKS OR SHEEPSFOOT ROLLERS. PLACE NO LARGE ROCKS WITHIN 24" OF PIPE. TRENCHES THAT ARE NOT ADEQUATELY COMPACTED SHALL BE RE-EXCAVATED AND BACKFILLED UNDER THE SUPERVISION OF THE DESIGN ENGINEER OR GOVERNING BODY. UNSUITABLE BACKFILL MATERIAL INCLUDES CHUNKS OF PAVEMENT, TOPSOIL, ROCKS OVER 6" IN SIZE, MUCK, PEAT OR PIECES OF PAVEMENT.
  - THE CONTRACTOR IS SOLELY RESPONSIBLE FOR JOB-SITE SAFETY AND COMPLIANCE WITH GOVERNING REGULATIONS.
  - ORDERED EXCAVATION OF UNSUITABLE MATERIAL BELOW GRADE. REFILL WITH BEDDING MATERIAL FOR TRENCH WIDTH SEE TRENCH DETAIL.
  - SAND BLANKET: CLEAN SAND, FREE FROM ORGANIC MATTER, SO GRADED THAT 90% - 100% PASSES A 1/2 INCH SIEVE AND NOT MORE THAN 15% WILL PASS A #200 SIEVE. BLANKET MAY BE OMITTED FOR DUCTILE IRON AND REINFORCED CONCRETE PIPE PROVIDED THAT NO STONE LARGER THAN 2 INCHES IS IN CONTACT WITH THE PIPE.
  - BASE COURSE GRAVEL, IF ORDERED BY THE ENGINEER, SHALL MEET THE REQUIREMENTS OF DIVISION 300 OF THE LATEST EDITION OF THE: "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION OF THE STATE OF NEW HAMPSHIRE, DEPARTMENT OF TRANSPORTATION".
  - FOR CROSS COUNTRY CONSTRUCTION, BACKFILL OR FILL SHALL BE MOUND TO A HEIGHT OF 6 INCHES ABOVE THE ORIGINAL GROUND SURFACE.
  - IF FULL ENCASUREMENT IS UTILIZED, DEPTH OF CONCRETE BELOW PIPE SHALL BE 1/4 I.D. (4" MIN.) BLOCK SUPPORT SHALL BE SOLID CONCRETE BLOCKS.
  - CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
  - THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION.
  - THE PURPOSE OF THIS PLAN IS TO SHOW STANDARDS FOR SEWER CONSTRUCTION.
  - IF FULL ENCASUREMENT IS UTILIZED, DEPTH OF CONCRETE BELOW PIPE SHALL BE 1/4 I.D. (4" MIN.) BLOCK SUPPORT SHALL BE SOLID CONCRETE BLOCKS.
  - CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).
  - THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION.
  - THE PURPOSE OF THIS PLAN IS TO SHOW STANDARDS FOR SEWER CONSTRUCTION.
  - IF FULL ENCASUREMENT IS UTILIZED, DEPTH OF CONCRETE BELOW PIPE SHALL BE 1/4 I.D. (4" MIN.) BLOCK SUPPORT SHALL BE SOLID CONCRETE BLOCKS.


**TRENCH NOTES:**  
A) TRENCH BACKFILL: - IN PAVED AREAS, SUITABLE MATERIAL FOR TRENCH BACKFILL SHALL BE THE NATURAL MATERIAL EXCAVATED DURING CONSTRUCTION, BUT SHALL EXCLUDE DEBRIS, PIECES OF PAVEMENT, ORGANIC MATTER, TOP SOIL, ALL WET OR SOFT MUCK, PEAT OR CLAY, ALL EXCAVATED LEDGE MATERIAL, AND ALL ROCKS OVER SIX INCHES IN LARGEST DIMENSION, OR ANY MATERIALS DEEMED TO BE UNACCEPTABLE BY THE ENGINEER.  
- IN CROSS-COUNTRY CONSTRUCTION, SUITABLE MATERIAL SHALL BE AS DESCRIBED ABOVE, EXCEPT THAT THE ENGINEER MAY PERMIT THE USE OF TOP SOIL, LOAM, MUCK OR PEAT, IF HE IS SATISFIED THAT THE COMPLETED CONSTRUCTION WILL BE ENTIRELY STABLE.  
B) "W" = MAXIMUM ALLOWABLE TRENCH WIDTH TO A PLANE 12 INCHES ABOVE THE PIPE. FOR PIPES 15 INCHES NOMINAL DIAMETER OR LESS, W SHALL BE NO MORE THAN 36 INCHES. FOR PIPES GREATER THAN 15 INCHES NOMINAL DIAMETER, W SHALL BE 24 INCHES PLUS PIPE O.D..  
C) TRENCH SHEETING: IF REQUIRED, WHERE SHEETING IS PLACED ALONGSIDE THE PIPE AND EXTENDS BELOW MID-DIAMETER, IT SHALL BE CUT OFF AND LEFT IN PLACE TO AN ELEVATION NOT LESS THAN 1 FOOT ABOVE THE TOP OF THE PIPE. WHERE SHEETING IS ORDERED BY THE ENGINEER TO BE LEFT IN PLACE, IT SHALL BE CUT OFF AT LEAST 3 FEET BELOW FINISHED GRADE, BUT NOT LESS THAN 1 FOOT ABOVE THE TOP OF THE PIPE.  
D) MINIMUM PIPE COVER FOR UTILITY MAINS (UNLESS GOVERNED BY OTHER CODES):  
6' MINIMUM FOR SEWER (IN PAVEMENT)  
4' MINIMUM FOR SEWER (CROSS COUNTRY)  
3' MINIMUM FOR STORMWATER DRAINS  
5' MINIMUM FOR WATER MAINS  
E) ALL PAVEMENT CUTS SHALL BE REPAIRED BY THE INFRARED HEAT METHOD.




**TYPICAL PIPE TRENCH**  
NTS



**SEWER SERVICE**




**SEWER SERVICE CONNECTION**




**WATER CROSSING**


**NOTES:**  
1. ELECTRICAL INSTALLATION SHALL BE BY A LICENSED ELECTRICIAN.  
2. LIGHTS SHALL BE WIRED IN ACCORDANCE WITH NEC AND CITY OR PORTSMOUTH ORDINANCES  
3. AN ELECTRICAL PERMIT IS REQUIRED FOR ALL CONDUIT AND ELECTRICAL WORK.



**LIGHT POLE BASE DETAIL**




**BOLT PATTERN**




**LIGHT POLE DETAIL**

**L CITY STREET LIGHT**  
NTS



**TAPPING SLEEVE AND GATE**



**SEWER SERVICE CONNECTION**

**M C4 TAPPING SLEEVE AND GATE**  
INSTALL PER PORTSMOUTH REQUIREMENTS NTS

**P C4 SEWER SERVICE DETAILS**  
INSTALL PER PORTSMOUTH REQUIREMENTS NTS






**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 430-9282  
Fax (603) 436-2315

**NOTES:**

- 1) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
- 2) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
- 3) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).


**3 GRATES ARRAYED**




**IRON AGE DESIGNS**  
2104 SW 152nd St #4 TEL 206.276.0925  
Burien, WA 98166 FAX 206.257.0318  
www.ironagegrates.com

Argo 5"x20" Heel-Proof Trench Grate drawn by: CD  
scale: NTS  
drawing no. ARG.A.05x20 date: 01/01/09

- NOTES:**
1. Material: cast iron
  2. Natural finish
  3. Total thickness: 1 1/8"
  4. Fits drain channels manufactured by:  
ABT® PolyDrain®  
ACO™ KlassikDrain-K100/K100S  
MEADRAIN® 1000 Series
  5. No openings greater than 1/4"
  6. Due to casting inconsistencies, all dimensions are nominal.
  7. Weight: 11 lbs. per casting
- © 2009 Iron Age Designs




- GENERAL NOTES:**
- CONCRETE SPECIFICATIONS:**
- 1) 4000 PSI @ 28 DAYS.
  - 2) 4%-6% ENTRAINED AIR.
  - 3) TANK PENETRATIONS ARE INTEGRALLY CAST.
  - 4) ALL JOINTS SEALED WITH BUTYL RUBBER JOINT SEALANT.
- GREASE TRP INFORMATION:**
- 1) TANKS SHOULD BE PUMPED AS NEEDED.
  - 2) ACCESS COVERS SHOULD HAVE RISERS TO BRING COVER ACCESS TO GRADE.
  - 3) TANKS CAN BE VACUUM TESTED AT AN ADDITIONAL COST.




**Q** IRON AGE GRATE DETAIL  
**C3** WWW.IRONAGEGRATES.COM ARGO 5" X 20" HEEL PROOF TRENCH GRATE NTS  
(877)418-3568

**T** AMERICAN CONCRETE INDUSTRIES  
**C4** 1000 GALLON 2 COMP. GREASE TRAP NTS  
9,200 Lbs ITEM # 8827



**R** SLOT DRAIN DETAIL  
**C5** WWW.SLOTDRAINSYSTEMS.COM NTS  
(855)497-7508




**S** TRENCH DRAIN DETAIL  
**C5** AT FOUNTAIN AND BENCH NTS

**BRICK MARKET**  
**60 PENHALLOW STREET**  
**PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
1	ISSUED FOR APPROVAL	11/18/19
0	ISSUED FOR COMMENT	10/8/19

REVISIONS




SCALE: AS SHOWN OCTOBER 2019

DETAILS

**D4**



11/18/2019 2:13:00 PM: C:\Revit\Projects\2018\081.02\_60 Penhallow Street-CENTRAL\_edocof98.rvt



**1** FIRST FLOOR OVERALL PLAN  
1/8" = 1'-0"

GROSS SQUARE FOOTAGE	
NOTE: MEASURED TO 6" INTO EXTERIOR WALLS FROM INSIDE FACE	
ABOVE GRADE	
FIRST FLOOR	16,462
MECHANICAL MEZZANINE	724
SECOND FLOOR	16,669
THIRD FLOOR	16,130
FOURTH FLOOR	9,593
TOTAL	59,578
BELOW GRADE	
FIRST FLOOR	18,131
SECOND FLOOR	17,569
TOTAL	35,700
GRAND TOTAL (ABOVE AND BELOW TOTALS)	95,278
FOOTPRINT	
NOTE: MEASURED TO OUTSIDE FACE OF EXTERIOR WALLS	
FIRST FLOOR	17,197

**JSA**  
ARCHITECTS  
INTERIORS  
PLANNERS

273 CORPORATE DRIVE  
PORTSMOUTH, NH 03801  
T 603.436.2551  
F 603.436.6973  
www.jsainc.com

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale: 1/8" = 1'-0"  
Date: 11/18/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE

TAC SUBMISSION  
FIRST FLOOR  
PLAN

**A0.01**

COPYRIGHT © 2019









ARCHITECTS  
INTERIORS  
PLANNERS

273 CORPORATE DRIVE  
PORTSMOUTH, NH 03801  
T 603.436.2551  
F 603.436.6973  
www.jsainc.com

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale: 1/8" = 1'-0"  
Date: 11/18/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE


TAC SUBMISSION

PARKING LEVEL  
2 PLAN


A0.01B

COPYRIGHT © 2019

GROSS SQUARE FOOTAGE	
NOTE: MEASURED TO 6" INTO EXTERIOR WALLS FROM INSIDE FACE	
ABOVE GRADE	
FIRST FLOOR	16,462
MECHANICAL MEZZANINE	724
SECOND FLOOR	16,669
THIRD FLOOR	16,130
FOURTH FLOOR	9,593
TOTAL	59,578
BELOW GRADE	
FIRST FLOOR	18,131
SECOND FLOOR	17,569
TOTAL	35,700
GRAND TOTAL (ABOVE AND BELOW TOTALS)	95,278
FOOTPRINT	
NOTE: MEASURED TO OUTSIDE FACE OF EXTERIOR WALLS	
FIRST FLOOR	17,197



1 PARKING LEVEL 2 PLAN  
1/8" = 1'-0"



11/18/2019 1:59:56 PM: C:\Revit Projects 2018\POB1.02\_60 Penhallow Street-CENTRAL\_edocof89.rvt





ARCHITECTS  
INTERIORS  
PLANNERS

273 CORPORATE DRIVE  
PORTSMOUTH, NH 03801  
T 603.436.2551  
F 603.436.6973  
www.jsainc.com

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale: 1/8" = 1'-0"  
Date: 11/18/2019  
Project Number: P19081.02



REVISIONS		
NO.	DESCRIPTION	DATE

TAC SUBMISSION

ROOF PLAN

A0.02

COPYRIGHT © 2019



1 ROOF OVERALL PLAN  
1/8" = 1'-0"

11/18/2019 2:01:27 PM: C:\Revit\Projects\2018\PO81.02\_60 Penhallow Street-CENTRAL\_edocof98.rvt





1 NORTH ELEVATION - DANIEL STREET  
1/8" = 1'-0"



2 EAST ELEVATION - PENHALLOW STREET  
1/8" = 1'-0"

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES


Scale: 1/8" = 1'-0"  
Date: 11/18/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE


TAC SUBMISSION

EXTERIOR  
ELEVATIONS





1 SOUTH ELEVATION - PEDESTRIAN WAY  
1/8" = 1'-0"



2 WEST ELEVATION - PEDESTRIAN WAY  
1/8" = 1'-0"

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale: 1/8" = 1'-0"  
Date: 11/18/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE

TAC SUBMISSION

EXTERIOR  
ELEVATIONS



NOTE ; These Renderings include proposed off-site improvements that are not related to the Planning Board's approval and that would require separate City Council approval.



ARCHITECTS  
INTERIORS  
PLANNERS

273 CORPORATE DRIVE  
PORTSMOUTH, NH 03801  
T 603.436.2551  
F 603.436.6973  
www.jsainc.com

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale:  
Date: 11/18/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE

TAC SUBMISSION

TANGRAM  
RENDERINGS

A0.05

COPYRIGHT © 2019



NORTHEAST VIEW



NORTHWEST VIEW



SOUTHWEST VIEW



SOUTHEAST VIEW

11/18/2019 2:08:17 PM C:\Revit\Projects\2018\POB1\_02\_60 Penhallow Street-CENTRAL\_edocof99.rvt







DANIEL STREET

CITY STANDARD CORNBREAD STREET LAMP - field verify location

CITY STANDARD CORNBREAD STREET LAMP - field verify location



ARCHITECTS  
INTERIORS  
PLANNERS

273 CORPORATE DRIVE  
PORTSMOUTH, NH 03801  
T 603.436.2551  
F 603.436.6973  
www.jsainc.com

J & M Lighting Design Inc.  
PO Box 1959  
Kennebunkport, ME 04046  
207.967.5223

60 PENHALLOW STREET  
at BRICK MARKET

Penhallow Street  
Portsmouth, NH

DAGNY TAGGART LLC  
McNABB PROPERTIES

Scale: 3/32" = 1'-0"  
Date: 12/02/2019  
Project Number: P19081.02

REVISIONS		
NO.	DESCRIPTION	DATE

TAC SUBMISSION

PHOTOMETRIC  
PLAN

J & M LIGHTING DESIGN, INC.  
207-967-5223  
jmlight@comcast.com  
DEC 4 2019

BRICK MARKET  
DESIGN IDENTIFYING  
PROPOSED ILLUMINATION STUDY

A0.07-R1

COPYRIGHT © 2019

14 - 16 Market Square

visible decorative accent lights  
inside building windows at 2nd and  
3rd floor corner rooms

ILLUMINATION STUDY ASSUMES A FLAT HORIZONTAL PLANE  
ALL ILLUMINATION LEVELS ARE MAINTAINED WITH A 20% DEPRECIATION

CONTRIBUTION FROM CITY OWNED COBRA-HEADS OR CITY DECORATIVE  
LANTERN NOT INCLUDED IN ILLUMINANCE STUDY

CONTRIBUTION FROM HIDDEN BENCH AND PODIUM LIGHTS ARE  
NOT INCLUDED IN ILLUMINANCE STUDY

CONTRIBUTION FROM MURAL OR FOUNTAIN LIGHT ARE  
NOT INCLUDED IN ILLUMINANCE STUDY

CONTRIBUTION FROM INTERIOR BUILDING  
ILLUMINATION IS INCLUDED IN CALCULATIONS

CONTRIBUTION FROM TYPE JOW EMERGENCY LIGHTS AT EGRESS  
NOT INCLUDED IN CALCULATIONS

TYPE JCCS VERTICALLY MOUNTED ON DANIEL & PENHALLOW  
STREETS SIDE OF THE BUILDING ARE COLOR CHANGING  
LUMINOUS ELEMENTS RED, GREEN, BLUE AND WHITE ARE FOR  
EFFECT AND NOT CONTRIBUTING TO ILLUMINATION LEVELS ON THE GROUND

JBBS-123 L or R mounted under podium bench wash vertical face of wall  
source of light masked from patrons view

recess lights at entrance to garage  
are for reference values are not included  
in calculations


JBBS-LENGTH mounted under seat to wash vertical face  
of wall source of light masked from patrons view

(4) JBS-173 mounted under seat to wash vertical face of  
wall source of light masked from patrons view

Utility Area  
mural lights TBD feed from 60 Penhallow  
mural  
circuit

30 Penhallow Street

Brick



screen lights TBD

fountain lights TBD 2 circuits  
"fountain" circuit

flora lights TBD

flora lights TBD

JNC canterinary lights mounted 20' above grade

PLEASANT STREET

21 Pleasant Street

am Street



**AMBIT ENGINEERING, INC.** CIVIL ENGINEERS AND LAND SURVEYORS

200 Griffin Road, Unit 3, Portsmouth, NH 03801  
Phone (603) 430-9282 Fax 436-2315

9 January 2020

Dexter Legg, Planning Board Chair  
City of Portsmouth  
1 Junkins Avenue  
Portsmouth, NH 03801

**RE: Request for Site Plan Approval at 60 Penhallow Street, Brick Market; Tax Map 107, Lot 27**

Dear Mr. Legg and Planning Board Members:

On behalf of Mark McNabb and Dagny Taggart, LLC we hereby submit the attached Plan Set and Supporting Material for Planning Board Approval for the proposed building for the Brick Market Project at 60 Penhallow Street. The project includes proposed new construction of a 4 story commercial building to be known as 60 Penhallow Street with the associated required site improvements. The site is currently a surface parking lot at the corner of Penhallow and Daniel Streets, on the opposite corner of the McIntire Building.

The site redevelopment offers an excellent opportunity to link the McIntire Building site with Market Square by creating public access across the submitted and adjacent properties owned by the applicant and known as Tax Map 107, Lots 27, 31 and 35. The applicant is linking those properties in this application as a development area as allowed in the Portsmouth Ordinance under Section 10.5A43.33. Section 10.5A43.33 of the Ordinance allows for a development area not located in an incentive overlay district to be allowed an additional story in height if at least 20 % of the development area is assigned as community space. This project utilizes this incentive and dedicates 30% of the area as community space. Included in the application is a Plan titled "Brick Market Master Plan Community Space" which details the submitted community space.

The Board considered this project at a Conceptual Consultation on November 21, 2019. At the meeting comments we received, specifically in regards to the Community Space Plan. Those comments have been incorporated into this submission.

The following plans are included in our submission:

- Cover Sheet – This shows the Development Team, Legend, Site Location, and Site Zoning.
- Standard Boundary Survey Plan and Easement Plan – These plans show the existing property boundaries and property easements on the entire Community Development Area.



- Proposed Easement Plan – This plan shows the location of proposed roof overhangs where we are requesting an easement.
- Master Plan Exiting Conditions – This plan shows the existing features and boundary of the Development Area.
- Master Plan Community Space – This plan shows the 30 % of the Development Area that will be dedicated as Community Space.
- Existing Conditions Plan C1 – This plan shows the existing conditions on the property.
- Demolition Plan C2 – This plan shows site preparation for construction.
- Site Layout Plan C3 – This plan shows the proposed site development at 60 Penhallow in detail with the associated Zoning Calculations.
- Landscape Plans L1 - LM – These plans shows Site Landscape and Hardscape for the proposed development.
- Utility Plan C4 – This plan shows proposed site utilities.
- Grading and Drainage Plan C5 – This plan shows proposed site grading and drainage features. Based on the comments from the Planning Board at the Conceptual Consultation we reviewed possible flow mitigation options, given the increase to covered area. Understanding the desire to provide a site covered with appropriate urban useable space amenities (i.e. walkways and pedestrian areas) the increase is a part of the fabric of creating this Community Space. There is some space that has been re-dedicated to a Pocket Park and back to open (permeable) space.
- Offsite Improvements P1 and P2– These plans shows offsite improvements on Daniel Street and Penhallow Street. The offsite improvements are required for 2 purposes:
  - So as to bury the overhead power lines in the Daniel Street Corridor.
  - To provide improvements to the City’s Drainage in Daniel Street to offset the minor increase to impervious area on the site.
- Detail Sheets D1 to D4 – These plans show the associated construction details.
- Floor Plans and Elevations – These plan shows the proposed building Floor Levels and exterior elevations. The First and Second Parking Floor Plans show the two parking decks within the building that will provide underground parking to service the building. There is an included Rendering View.
- Lighting Plans – These plans show the proposed lighting design.

Also included herewith is the following Supplemental Information to assist in the review of the project: Façade Glazing Calculations, Green Building Statement, Easement Example Deeds, Example Trash Chutes, Lighting Cut Sheets, Eversource and Unitil Will Serve Letters, Drainage Analysis, and the Trip Generation Report.



The project received TAC Approval at the January 7, 2020 Technical Advisory Committee Meeting subject to stipulations. The stipulations, as well as our responses to the stipulations, are listed below:

- 1) The plans shall be updated to match the plans presented at the TAC meeting as “Transformer Location Alternative”. **Plans have been updated to show the Transformer Location presented and discussed at the TAC Committee meeting.**
- 2.) The drainage plan shall indicate test pits are required to validate the design. Plan shall note potential impacts to the telephone duct system currently in the road as well as any required work with Consolidated Communications to relocate ducts as needed. **Note 6 on Sheet P1 has been added to indicate the need for test pits as well as identify the possibility of potential impacts.**
- 3.) Copies of the draft easements for community space and any other easements for which the City will be a party need to be submitted for Planning Board review. **Draft Easements are submitted herewith.**
- 4.) The Community Space Plan shall be updated to reflect the proposed limits of the pocket park along 30 Penhallow Street as discussed at the TAC meeting. **The Community Space Plan and Landscape Plan L – 2 are consistent and show the aforementioned Pocket Park.**
- 5.) A rendering of the proposed entrance to the community space plaza from the Daniel Street side shall be provided including the proposed location of the transformers. **Please see the renderings submitted in the Site Plan Set.**

We look forward to your review of this submission, and request approval of the site plan as submitted.

Sincerely,

*John Chagnon*

John R. Chagnon, PE

CC: Mark McNabb, Tracy Kozak, Robbi Woodburn, FX Bruton





# City of Portsmouth, New Hampshire

## Site Plan Application Checklist

This site plan application checklist is a tool designed to assist the applicant in the planning process and for preparing the application for Planning Board review. A pre-application conference with a member of the planning department is strongly encouraged as additional project information may be required depending on the size and scope. The applicant is cautioned that this checklist is only a guide and is not intended to be a complete list of all site plan review requirements. Please refer to the Site Plan review regulations for full details.

**Applicant Responsibilities (Section 2.5.2):** Applicable fees are due upon application submittal along with required attachments. The application shall be complete as submitted and provide adequate information for evaluation of the proposed site development. Waiver requests must be submitted in writing with appropriate justification.

Name of Owner/Applicant: Dagny Taggart, LLC/McNabb Properties, LTD Date Submitted: 11/18/19

Phone Number: Applicant: 603-427-0725 E-mail: christine@mcnabbgroup.com

Site Address: 60 Penhallow Street Map: 107 Lot: 27

Zoning District: Character District 4 (CD4) Lot area: 23,279 sq. ft.

Application Requirements			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Fully executed and signed Application form. <b>(2.5.2.3)</b>		N/A
<input type="checkbox"/>	All application documents, plans, supporting documentation and other materials provided in digital Portable Document Format (PDF). <b>(2.5.2.8)</b>		N/A

Site Plan Review Application Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Statement that lists and describes "green" building components and systems. <b>(2.5.3.1A)</b>	See attached from JSA	
<input type="checkbox"/>	Gross floor area and dimensions of all buildings and statement of uses and floor area for each floor. <b>(2.5.3.1B)</b>	See Sheet C3	N/A
<input type="checkbox"/>	Tax map and lot number, and current zoning of all parcels under Site Plan Review. <b>(2.5.3.1C)</b>	See Sheet C1	N/A
<input type="checkbox"/>	Owner's name, address, telephone number, and signature. Name, address, and telephone number of applicant if different from owner. <b>(2.5.3.1D)</b>	See Cover Sheet	N/A



**Site Plan Review Application Required Information**

<input checked="" type="checkbox"/>	<b>Required Items for Submittal</b>	<b>Item Location (e.g. Page/line or Plan Sheet/Note #)</b>	<b>Waiver Requested</b>
<input type="checkbox"/>	Names and addresses (including Tax Map and Lot number and zoning districts) of all direct abutting property owners (including properties located across abutting streets) and holders of existing conservation, preservation or agricultural preservation restrictions affecting the subject property. <b>(2.5.3.1E)</b>	See Standard Boundary Survey	N/A
<input type="checkbox"/>	Names, addresses and telephone numbers of all professionals involved in the site plan design. <b>(2.5.3.1F)</b>	See Cover Sheet	N/A
<input type="checkbox"/>	List of reference plans. <b>(2.5.3.1G)</b>	See Standard Boundary Survey	N/A
<input type="checkbox"/>	List of names and contact information of all public or private utilities servicing the site. <b>(2.5.3.1H)</b>	See Cover Sheet	N/A

**Site Plan Specifications**

<input checked="" type="checkbox"/>	<b>Required Items for Submittal</b>	<b>Item Location (e.g. Page/line or Plan Sheet/Note #)</b>	<b>Waiver Requested</b>
<input type="checkbox"/>	Full size plans shall not be larger than 22 inches by 34 inches with match lines as required, unless approved by the Planning Director. Submittals shall be a minimum of 11 inches by 17 inches as specified by Planning Dept. staff. <b>(2.5.4.1A)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Scale: Not less than 1 inch = 60 feet and a graphic bar scale shall be included on all plans. <b>(2.5.4.1B)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	GIS data should be referenced to the coordinate system New Hampshire State Plane, NAD83 (1996), with units in feet. <b>(2.5.4.1C)</b>	N/A	N/A
<input type="checkbox"/>	Plans shall be drawn to scale. <b>(2.5.4.1D)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Plans shall be prepared and stamped by a NH licensed civil engineer. <b>(2.5.4.1D)</b>	PE 07651	N/A
<input type="checkbox"/>	Wetlands shall be delineated by a NH certified wetlands scientist and so stamped. <b>(2.5.4.1E)</b>	N/A	N/A
<input type="checkbox"/>	Title (name of development project), north point, scale, legend. <b>(2.5.4.2A)</b>	See Cover Sheet	N/A
<input type="checkbox"/>	Date plans first submitted, date and explanation of revisions. <b>(2.5.4.2B)</b>	See Revision Block	N/A
<input type="checkbox"/>	Individual plan sheet title that clearly describes the information that is displayed. <b>(2.5.4.2C)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Source and date of data displayed on the plan. <b>(2.5.4.2D)</b>	See Plan Notes	N/A



**Site Plan Specifications**

<input checked="" type="checkbox"/>	<b>Required Items for Submittal</b>	<b>Item Location (e.g. Page/line or Plan Sheet/Note #)</b>	<b>Waiver Requested</b>
<input type="checkbox"/>	A note shall be provided on the Site Plan stating: "All conditions on this Plan shall remain in effect in perpetuity pursuant to the requirements of the Site Plan Review Regulations." <b>(2.5.4.2E)</b>	See Cover Sheet, C3 Site Plan	N/A
<input type="checkbox"/>	Plan sheets submitted for recording shall include the following notes: a. "This Site Plan shall be recorded in the Rockingham County Registry of Deeds." b. "All improvements shown on this Site Plan shall be constructed and maintained in accordance with the Plan by the property owner and all future property owners. No changes shall be made to this Site Plan without the express approval of the Portsmouth Planning Director." <b>(2.13.3)</b>	See Sheet C3 Site Plan	N/A
<input type="checkbox"/>	Plan sheets showing landscaping and screening shall also include the following additional notes: a. "The property owner and all future property owners shall be responsible for the maintenance, repair and replacement of all required screening and landscape materials." b. "All required plant materials shall be tended and maintained in a healthy growing condition, replaced when necessary, and kept free of refuse and debris. All required fences and walls shall be maintained in good repair." c. "The property owner shall be responsible to remove and replace dead or diseased plant materials immediately with the same type, size and quantity of plant materials as originally installed, unless alternative plantings are requested, justified and approved by the Planning Board or Planning Director." <b>(2.13.4)</b>	See Sheet L1 & L2	N/A



**Site Plan Specifications – Required Exhibits and Data**

<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
	<b>1. Existing Conditions: (2.5.4.3A)</b>		
<input type="checkbox"/>	a. Surveyed plan of site showing existing natural and built features;	C1	
<input type="checkbox"/>	b. Zoning boundaries;	Cover Sheet	
<input type="checkbox"/>	c. Dimensional Regulations;	C3 Zoning Development	
<input type="checkbox"/>	d. Wetland delineation, wetland function and value assessment;	N/A	
<input type="checkbox"/>	e. SFHA, 100-year flood elevation line and BFE data.	Note 3, C1	
	<b>2. Buildings and Structures: (2.5.4.3B)</b>		
<input type="checkbox"/>	a. Plan view: Use, size, dimensions, footings, overhangs, 1st fl. elevation;	A0-1.0-1.2	
<input type="checkbox"/>	b. Elevations: Height, massing, placement, materials, lighting, façade treatments;	A0-1.0-1.2	
<input type="checkbox"/>	c. Total Floor Area;	A0-1.0-1.2	
<input type="checkbox"/>	d. Number of Usable Floors;	A0-1.0-1.2	
<input type="checkbox"/>	e. Gross floor area by floor and use.	A0-1.0-1.2	
	<b>3. Access and Circulation: (2.5.4.3C)</b>		
<input type="checkbox"/>	a. Location/width of access ways within site;	C3	
<input type="checkbox"/>	b. Location of curbing, right of ways, edge of pavement and sidewalks;	C3	
<input type="checkbox"/>	c. Location, type, size and design of traffic signing (pavement markings);	C3	
<input type="checkbox"/>	d. Names/layout of existing abutting streets;	Cover Sheet	
<input type="checkbox"/>	e. Driveway curb cuts for abutting prop. and public roads;	C3	
<input type="checkbox"/>	f. If subdivision; Names of all roads, right of way lines and easements noted;	N/A	
<input type="checkbox"/>	g. AASHTO truck turning templates, description of minimum vehicle allowed being a WB-50 (unless otherwise approved by TAC).	N/A	
	<b>4. Parking and Loading: (2.5.4.3D)</b>		
<input type="checkbox"/>	a. Location of off street parking/loading areas, landscaped areas/buffers;	C3, Floor Plans	
<input type="checkbox"/>	b. Parking Calculations (# required and the # provided).	N/A	
	<b>5. Water Infrastructure: (2.5.4.3E)</b>		
<input type="checkbox"/>	a. Size, type and location of water mains, shut-offs, hydrants & Engineering data;	C4	
<input type="checkbox"/>	b. Location of wells and monitoring wells (include protective radii).	N/A	
	<b>6. Sewer Infrastructure: (2.5.4.3F)</b>		
<input type="checkbox"/>	a. Size, type and location of sanitary sewage facilities & Engineering data.	C4	
	<b>7. Utilities: (2.5.4.3G)</b>		
<input type="checkbox"/>	a. The size, type and location of all above & below ground utilities;	C4	
<input type="checkbox"/>	b. Size type and location of generator pads, transformers and other fixtures.	C4	



**Site Plan Specifications – Required Exhibits and Data**

<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	<b>8. Solid Waste Facilities: (2.5.4.3H)</b>		
<input type="checkbox"/>	a. The size, type and location of solid waste facilities.	Architectural Plans	
<input type="checkbox"/>	<b>9. Storm water Management: (2.5.4.3I)</b>		
<input type="checkbox"/>	a. The location, elevation and layout of all storm-water drainage.	C5	
<input type="checkbox"/>	<b>10. Outdoor Lighting: (2.5.4.3J)</b>		
<input type="checkbox"/>	a. Type and placement of all lighting (exterior of building, parking lot and any other areas of the site) and; b. photometric plan.	Lighting Plans	
<input type="checkbox"/>	<b>11. Indicate where dark sky friendly lighting measures have been implemented. (10.1)</b>	Lighting Plans	
<input type="checkbox"/>	<b>12. Landscaping: (2.5.4.3K)</b>		
<input type="checkbox"/>	a. Identify all undisturbed area, existing vegetation and that which is to be retained;	L1	
<input type="checkbox"/>	b. Location of any irrigation system and water source.	L1	
<input type="checkbox"/>	<b>13. Contours and Elevation: (2.5.4.3L)</b>		
<input type="checkbox"/>	a. Existing/Proposed contours (2 foot minimum) and finished grade elevations.	C5	
<input type="checkbox"/>	<b>14. Open Space: (2.5.4.3M)</b>		
<input type="checkbox"/>	a. Type, extent and location of all existing/proposed open space.	C3 Community Space Plan	
<input type="checkbox"/>	<b>15. All easements, deed restrictions and non-public rights of ways. (2.5.4.3N)</b>	Easement Plan	
<input type="checkbox"/>	<b>16. Location of snow storage areas and/or off-site snow removal. (2.5.4.3O)</b>	Remove Offsite/C3 Note	
<input type="checkbox"/>	<b>17. Character/Civic District (All following information shall be included): (2.5.4.3Q)</b>		
<input type="checkbox"/>	a. Applicable Building Height (10.5A21.20 & 10.5A43.30);	C3	
<input type="checkbox"/>	b. Applicable Special Requirements (10.5A21.30);	C3	
<input type="checkbox"/>	c. Proposed building form/type (10.5A43);	C3	
<input type="checkbox"/>	d. Proposed community space (10.5A46).	Community Space Plan C3	



Other Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Traffic Impact Study or Trip Generation Report, as required. <i>(Four (4) hardcopies of the full study/report and Six (6) summaries to be submitted with the Site Plan Application) (3.2.1-2)</i>	GPI Report	
<input type="checkbox"/>	Indicate where Low Impact Development Design practices have been incorporated. <b>(7.1)</b>	C5	
<input type="checkbox"/>	Indicate whether the proposed development is located in a wellhead protection or aquifer protection area. Such determination shall be approved by the Director of the Dept. of Public Works. <b>(7.3.1)</b>	N/A	
<input type="checkbox"/>	Indicate where measures to minimize impervious surfaces have been implemented. <b>(7.4.3)</b>	N/A	
<input type="checkbox"/>	Calculation of the maximum effective impervious surface as a percentage of the site. <b>(7.4.3.2)</b>	C3	
<input type="checkbox"/>	Stormwater Management and Erosion Control Plan. <i>(Four (4) hardcopies of the full plan/report and Six (6) summaries to be submitted with the Site Plan Application) (7.4.4.1)</i>	Drainage Analysis	


Final Site Plan Approval Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	All local approvals, permits, easements and licenses required, including but not limited to: <ul style="list-style-type: none"> <li>a. Waivers;</li> <li>b. Driveway permits;</li> <li>c. Special exceptions;</li> <li>d. Variances granted;</li> <li>e. Easements;</li> <li>f. Licenses.</li> </ul> <b>(2.5.3.2A)</b>	Cover Sheet	
<input type="checkbox"/>	Exhibits, data, reports or studies that may have been required as part of the approval process, including but not limited to: <ul style="list-style-type: none"> <li>a. Calculations relating to stormwater runoff;</li> <li>b. Information on composition and quantity of water demand and wastewater generated;</li> <li>c. Information on air, water or land pollutants to be discharged, including standards, quantity, treatment and/or controls;</li> <li>d. Estimates of traffic generation and counts pre- and post-construction;</li> <li>e. Estimates of noise generation;</li> <li>f. A Stormwater Management and Erosion Control Plan;</li> <li>g. Endangered species and archaeological / historical studies;</li> <li>h. Wetland and water body (coastal and inland) delineations;</li> <li>i. Environmental impact studies.</li> </ul> <b>(2.5.3.2B)</b>	Drainage Analysis C4 C5  GPI Report  TBD Drainage Analysis N/A N/A N/A	



**Final Site Plan Approval Required Information**

<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	A document from each of the required private utility service providers indicating approval of the proposed site plan and indicating an ability to provide all required private utilities to the site. <b>(2.5.3.2D)</b>	Pending	
<input type="checkbox"/>	A list of any required state and federal permit applications required for the project and the status of same. <b>(2.5.3.2E)</b>	See Cover Sheet	

Applicant's Signature: \_\_\_\_\_



Date: \_\_\_\_\_

11-18-19



# Construction Cost Estimate

## Ambit Engineering

Date: November 18, 2019

Project: McNabb Properties - 60 Penhallow Street Job No: 3039

Location: 60 Penhallow Street, Portsmouth, NH

Scope: **Site Cost Estimate**

ITEM NO	DESCRIPTION	UNIT	AMOUNT	UNIT COST	TOTAL
1	6" PVC Sewer	LF	30	\$120.00	\$3,600.00
2	8" - 24" HDPE Drainage Pipe	LF	350	\$100.00	\$35,000.00
3	Slot Drains & Covers	LF	150	\$65.00	\$9,750.00
4	4' DMH	EA	2	\$4,000.00	\$8,000.00
5	Grease Trap	EA	1	\$4,000.00	\$4,000.00
6	Common Excavation	CY	17860	\$25.00	\$446,500.00
7	Miscellaneous Paving	TON	60	\$100.00	\$6,000.00
8	Bluestone	SF	840	\$80.00	\$67,200.00
9	Red Granite Edging	SF	320	\$65.00	\$20,800.00
10	Deer Isle Granite	SF	2700	\$55.00	\$148,500.00
11	Crushed Gravel / Base Preparation	CY	215	\$25.00	\$5,375.00
12	Fountain	LS	1	\$50,000.00	\$50,000.00
13	Brick Sidewalk	SY	150	\$96.00	\$14,400.00
14	Landscape Plantings	LS	1	\$75,000.00	\$75,000.00
15	Re-Set Curb	LF	300	\$60.00	\$18,000.00
16	Underground Electric / Conduit	LF	350	\$55.00	\$19,250.00
17	Transformers & Pole Relocation	EA	3	\$25,000.00	\$75,000.00
18	Seating Walls	LF	150	\$120.00	\$18,000.00
19	Mural Walls	LF	80	\$150.00	\$12,000.00
20	Water & Sprinkler Services	LF	120	\$180.00	\$21,600.00
21	Podium Bench	EA	1	\$12,000.00	\$12,000.00
22	Shoring	LF	560	\$35.00	\$19,600.00
23	Erosion Control	LS	1	\$2,500.00	\$2,500.00
	<b>TOTAL</b>				<b>\$1,092,075</b>

Note: This is an estimate of construction costs based upon various sources

### APPLICATION FEE:

**\$500 + (\$ 1,092,075 /1000 x \$5) + (28,600 / 1,000 x \$10)= \$ 6,246.38**





**60 Penhallow Street at Brick Market**

**Façade Glazing Analysis**

11/26/2019

Character District CD-4

**PENHALLOW STREET EAST**

Officefront façade type	
<b>FRONT - east façade, upper floors</b>	
wall area	3481 sf
glazed area	1158 sf
<b>% glazing</b>	<b>33.3%</b>
cd4 allowed	20%-50%

Gallery façade Type	
<b>FRONT - east façade, 1st floor</b>	
wall area (10' vertical)	1139 sf
glazed area	489 sf
<b>% glazing</b>	<b>42.9%</b>
cd4 allowed	20%-50%

**DANIEL STREET NORTH**

Officefront façade type	
<b>FRONT -north façade, upper floors</b>	
wall area	2594 sf
glazed area	1145 sf
<b>% glazing</b>	<b>44.1%</b>
cd4 allowed	20%-50%

Gallery façade Type	
<b>FRONT - north façade, 1st floor</b>	
wall area (10' vertical)	1478 sf
glazed area	578 sf
<b>% glazing</b>	<b>39.1%</b>
cd4 allowed	20%-50%





0 Daniel Street (60 Penhallow Street)

Site Plan Review 11-18-2019

## Green Building Statement

### WATER

- Protect water quality – Eliminate surface parking lot.
- Conserve Water -- Target 30% reduction in fixtures water use over building code, meeting EPACT 2005.

### ENERGY

- Conserve Energy -- Target 50% Energy Use Index (EUI) Reduction over code compliance (IECC2015) in each building. Use early energy modeling to analyze effective scenarios. Provide high performance thermal envelope. Achieve Energy Star certification and associated rebates. Use Heat Recovery for ventilation. Commission energy using systems. LED lighting throughout.
- Renewable Energy – Rooftop Solar Photovoltaic system for portion of building's energy needs.
- Building Performance -- Use industry tools to annually monitor and benchmark buildings. Train staff on proper building operation with comprehensive Facilities Staff Training and Systems Manuals.
- Reduce Low level ozone (smog) -- Provide safe and secure bicycle storage. Use only low-VOC products for construction and operation.

### MATERIALS & RESOURCES

- Minimize waste (during construction and operation)
- Use regional, renewable, low carbon footprint materials

### INDOOR ENVIRONMENTAL QUALITY

- Thermal comfort -- Meet ASHRAE 55 Thermal Comfort Code. Address thermal envelope per above. Provide multiple zones of heating and cooling in each apartment.
- Indoor air quality (before and during occupancy) -- MEET ASHRAE 62 Ventilation Code in all occupied spaces. MEET LEED IEQ credit requirements.
- Views / connection to outdoors -- Provide views to outdoors for every regularly occupied space.
- Daylighting -- Achieve Daylight Factor of 2% minimum for every regularly occupied space.
- Individual controls (light, heat etc...) -- Provide individual controls for temperature and lighting.



FRANCIS X. BRUTON, III  
CATHERINE A. BERUBE  
JOSHUA P. LANZETTA

OF COUNSEL  
JAMES H. SCHULTE

# Bruton & Berube, PLLC

ATTORNEYS AT LAW

601 Central Avenue  
Dover, NH 03820

TEL (603) 749-4529  
(603) 743-6300  
FAX (603) 343-2986

[www.brutonlaw.com](http://www.brutonlaw.com)

December 8, 2020

Juliet T.H. Walker, AICP  
Planning Director  
City of Portsmouth  
1 Junkins Avenue  
Portsmouth, NH 03801

**RE: 60 Penhallow Street, Portsmouth**


Dear Ms. Walker:

On behalf of Dagny Taggart, LLC, the owner of the property located at 60 Penhallow Street, Portsmouth, New Hampshire, identified as City of Portsmouth Tax Map 107, Lot 27, we have enclosed a draft "Easement Area for Building Encumbrance" related to the overhangs of decorative features planned for the above referenced Brick Market project. The legal description of the easement area will be provided after Planning Board review and approval.

Please note that this draft easement is identical in terms to a similar easement recently granted for the project located at 25 Maplewood Avenue. For your convenience, a copy of the previously granted easement is included for your quick reference.

Thank you for your kind attention to this matter.

Sincerely,



Francis X. Bruton, III, Esquire  
E-mail: [fx@brutonlaw.com](mailto:fx@brutonlaw.com)

Enclosures

cc: Dagny Taggart, LLC  
Robert P. Sullivan, Esquire, City Attorney



## **EASEMENT AREA FOR BUILDING ENCUMBRANCE**

**NOW COMES THE CITY OF PORTSMOUTH**, a municipality whose address in 1 Junkins Avenue, Portsmouth, New Hampshire, 03801, (hereinafter “Grantor”),

for consideration paid, grants to Dagny Taggart, LLC, a New Hampshire limited liability company, with a business address of 30 Penhallow Street, Suite 300 East, City of Portsmouth, County of Rockingham, and State of New Hampshire (hereinafter “Grantee”),

**AN EASEMENT FOR BUILDING ENCUMBRANCE OVER PUBLIC RIGHTS OF WAY** further bounded and described as follows:

A certain encumbrance over the southerly side of Daniel Street (a public way) and the westerly side of Penhallow Street (a public way) in the City of Portsmouth, County of Rockingham, State of New Hampshire, said building encumbrance being shown four (4) separate locations as “Proposed Easement Area” on a plan entitled “Easement Plan for Tax Map 107 - Lots 27, Over Rights-of Way of Daniel Street & Penhallow Street for Benefit of Dagny Taggart, LLC, property located at 60 Penhallow Street. City of Portsmouth, County of Rockingham, State of New Hampshire,” prepared by Ambit Engineering, Inc., dated December 23, 2019 and recorded herewith at the Rockingham County Registry of Deeds (the “Easement Plan”) bounded and described as follows:

### **Proposed Easement Area 1**

[LEGAL DESCRIPTION TO FOLLOW]

### **Proposed Easement Area 2**

[LEGAL DESCRIPTION TO FOLLOW]



**Proposed Easement Area 3**

[LEGAL DESCRIPTION TO FOLLOW]

**Proposed Easement Area 4**

[LEGAL DESCRIPTION TO FOLLOW]

Said building encumbrance contains 241 +/- S.F.

The purpose of the Easement is to permit the building over the property of the Grantee above the fourth floor to encroach upon the easement area as shown of the approved plan referenced above. Said Easement to expire when the Building shown on the Easement Plan no longer exists.

The granting of this Easement Area for Building Encumbrance was approved by a vote of the Portsmouth City Council on \_\_\_\_\_, 2020.

THIS IS NOT HOMESTEAD PROPERTY.

Signed the \_\_\_\_ day of \_\_\_\_\_, 2020.

**City of Portsmouth**

\_\_\_\_\_

Its: \_\_\_\_\_

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

Personally, appeared this \_\_\_\_ day of \_\_\_\_\_, 2020, \_\_\_\_\_, duly authorized on behalf of the City of Portsmouth, who acknowledged that she/he executed the foregoing instrument as its free act and deed for the purposes contained herein.

Before me,

\_\_\_\_\_  
Notary Public:  
My Commission Expires:



*Cathy Ann Tracy*

(M)  
City of Portsmouth  
Planning Dept

TRANSFER TAX R0077624 20.00  
RECORDING 14.00  
SURCHARGE 2.00



**EASEMENT AREA FOR BUILDING ENCUMBRANCE**

**NOW COMES THE CITY OF PORTSMOUTH**, a municipality whose address is 1 Junkins Avenue, Portsmouth, New Hampshire, 03801, (hereinafter "Grantor"),

for consideration paid, grants to The PROVIDENT BANK, a Massachusetts savings bank with a mailing address of 5 Market Street, PO Box, 37, Amesbury, MA 01915 (hereinafter "Grantee"),

**AN EASEMENT FOR BUILDING ENCUMBRANCE OVER PUBLIC RIGHT OF WAY** further bounded and described as follows:

A certain building encumbrance over the easterly side of Maplewood Avenue (a public way) and the southerly side of Hanover Street (a public way) in Portsmouth, County of Rockingham, State of New Hampshire, said building encumbrance being shown as 'Proposed 485 SF +/- Building Encumbrance Over Public ROW' on a plan prepared by James Verra and Associates, Inc. and Altus Engineering, Inc., entitled, "Proposed Easement and Licensing Plan, "owner:" The Provident Bank", dated November 7, 2017, said plan is recorded at the Rockingham County Registry of Deeds as Plan 40712, bounded and described as follows:

Beginning at the corner of said easement on the southerly side of Hanover Street at the northeast corner of land now or formerly of The Provident Bank said point bears South 53° 29' 09" West (NH State Plane Coordinate System) 31.28 feet from a found railroad spike at the northwest corner of land now or formerly of Bendetson Portsmouth Realty Trust and land of the City of Portsmouth on the southerly side of Hanover Street;

Thence by land of said Provident Bank on the following courses:

South 53° 48' 25" West 66.25 feet to a point of curvature; by the arc of a tangential curve concave to east having an arc length of 29.03 feet, a radius of 22.00 feet, the cord of said curve bears South 16° 00' 26" West 26.97 feet to a point on the easterly side of Maplewood Avenue; South 21° 47' 33" East 48.85 feet to a point; thence over said Maplewood Avenue and Hanover Street on the following courses:

North 30° 45' 02" West 24.11 feet to a point; North 21° 45' 02" West 29.98 feet to a point of curvature; by the arc of a tangential curve concave to the east having an arc length of 24.57 feet, a radius of 28.92 feet, the chord of said curve bears North 16° 19' 26" East 23.84 feet to a point; North 54° 14' 58" East 67.68 feet to a point, South 82° 45' 02" East 4.62 feet to the true point of beginning.




Said building encumbrance contains 485 S.F.

The purpose of this Easement is to permit the building over on the property of the Grantee above the first story to encroach upon the easement area as shown on the approved plan referenced above. Said Easement to expire when the Building shown on the Plan no longer exists.

The granting of this Easement Area for Building Encumbrance was approved by a vote of the Portsmouth City Council on December 18, 2017.

THIS IS NOT HOMESTEAD PROPERTY.


Signed this 14 day of February, 2018.


City of Portsmouth  
  
By: Deputy City Manager

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

Personally appeared this 14<sup>th</sup> day of February, 2018, Nanaj Colbert Ross, duly authorized on behalf of the City of Portsmouth, who acknowledged that he executed the foregoing instrument as its free act and deed for the purposes contained herein.

Before me,

  
\_\_\_\_\_  
Notary Public  
My commission expires:





After recording return to:  
City of Portsmouth  
Planning Department  
1 Junkins Avenue  
Portsmouth, NH 03801

[LOT 27]

**EASEMENT FOR PUBLIC ACCESS AND USE OF COMMUNITY SPACE**

**THIS EASEMENT HEREIN IS GRANTED** this \_\_\_\_ day of \_\_\_\_\_, 2020 by Dagny Taggart, LLC, a New Hampshire limited liability company having an address of 30 Penhallow Street, Suite 300 East, City of Portsmouth, County of Rockingham, State of New Hampshire 03801, (“Grantor”) and for consideration of One Dollar (\$1.00) paid by the City, and other good and valuable consideration, receipt of which is acknowledged by Grantor, grants unto the City of Portsmouth, a municipal corporation, 1 Junkins Avenue, Portsmouth, New Hampshire (“City”) with warranty covenants, and easement for public access to and use of certain community space as set forth herein as a plaza, pedestrian alley and wide pedestrian sidewalk easements.

**WITNESSETH**

**WHEREAS**, Grantor acquired a tract of land located at the corner of Daniel Street and Penhallow Street, City of Portsmouth, County of Rockingham, State of New Hampshire (the “Property”), by Warranty Deed of Jarbel Realty, LLC, dated April 5, 2019 and recorded at the Rockingham County Registry of Deeds at Book 5990, Page 1703; and

**WHEREAS**, reference is made to a plan entitled “Brick Market, Master Plan, Community Space, Tax Map 107, Lots 27, 31 & 42, Owners: Dagny Taggart, LLC & Coventry Assets, LTD., Property located at: 3 Pleasant Street, 30 Penhallow Street, 60 Penhallow Street, City of Portsmouth, County of Rockingham, State of New Hampshire,” prepared by Ambit Engineering, Inc., dated July 25, 2019, as revised, and recorded herewith at the Rockingham County Registry of Deeds (the “Easement Plan”); and

**NOW THEREFORE**, in consideration of the sum of One Dollar (\$1.00), to be paid by the City, and other good and valuable consideration, the receipt of which is hereby acknowledged by the Grantor, Grantor conveys the easements as follows, located in the City of Portsmouth,



County of Rockingham, State of New Hampshire (hereinafter collectively referred to as the “Easements”):

1. Wide Pedestrian Sidewalk Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy, as identified on the Easement Plan as a “Wide Pedestrian Sidewalk.”
2. Pedestrian Alley Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Pedestrian Alley as identified on the Easement Plan as “Pedestrian Alley.”
3. Plaza Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Plaza as identified on the Easement Plan as “Plaza.” Said area may be improved by the Grantor with permanent fixtures, such as public fountains, benches and other such landscaping features, at its sole expense, and as depicted in the Easement Plan. The construction of any permanent fixtures not depicted in the Site Plan shall be subject to a modified site plan approval by the Portsmouth Planning Board.

The Easement granted herein shall be subject to the following terms and conditions:

1. **Terms of Public Use:** The Public Use permitted by the Easements shall be governed and determined at the sole discretion of the City, as expressed by the City Manager or the highest-ranking administrative officer of the City, subject to the terms and conditions of these easement. The City shall provide reasonable notice to the Grantor of an extraordinary event to be scheduled for the easement areas but failure to do so shall not be a breach of these easements.
2. **Rights to Private Property:** This easement does not convey any right to the public to access or utilize the private property of the Grantor outside the easement areas. Grantor’s use of the Easements shall be subject to and regulated through the City of Portsmouth’s rules and ordinances governing public sidewalks.
3. **Maintenance:** Maintenance of the easement areas shall be the sole responsibility of the Grantor, its successors or assigns. The City shall have the right, but not the obligation, to access the easement areas for the purpose of maintenance, repair or replacement, after providing reasonable notice to the Grantor of the scope and cost of such work, all as reasonably determined by the City. Such maintenance costs incurred by the City shall be at the sole expense of the Grantor, its successors or assigns.
4. **Encroachments:** The Easements are subject to all existing encroachments of utilities and improvements on, over and under the Easements.
5. **Covenants Run with the Land:** The Easements granted herein shall be perpetual in nature, shall run with the land and shall benefit and be binding upon the Grantor, its successors and assigns. The Easements shall be recorded in the Rockingham County Registry of Deeds.



6. **City Ordinance Application:** Any use, public or private, of the Easements shall be subject to and comply with the City Ordinances of the City of Portsmouth.

7. **Notices:** Any notice, demand, request, or other communication that either party desires or is required to give to the other under this Easement shall be in writing and either served personally or sent by United States mail, postage prepaid, certified, return receipt requested, and shall be mailed to the parties at the following addresses:

To Grantor:

Dagny Taggart, LLC  
30 Penhallow Street, Suite 300 East  
Portsmouth, NH 03801

(or as listed and at the address shown on the City's current Tax Records)

To City:

City Manager (or the highest-ranking administrative officer)  
City of Portsmouth, New Hampshire  
1 Junkins Avenue  
Portsmouth, NH 03801

8. **Amendment:** Grantor, or its successors and/or assigns, and City may mutually agree to amend or modify this Community Space Easement, provided that any such amendment or modification is approved by the City Council at a noticed public hearing, in writing and signed by both parties, and is consistent with the purpose and intent of the Zoning Ordinance. No amendment or modification of this Community Space Easement shall take effect unless and until it is recorded in the Rockingham County Registry of Deeds.

9. **Costs and Liabilities:** Grantor agrees to bear all costs and liabilities of any kind related to the operation, upkeep, and maintenance of the Property, and to defend, indemnify, hold harmless, and release the City of Portsmouth, from and against any and all actions, claims, damages, liabilities, or expenses that may be asserted by any person or entity, including Grantor, relating thereto. Without limiting the foregoing, the City of Portsmouth shall not be liable to Grantor or any other person or entity in connection with any entry upon the Property pursuant to this Community Space Easement, or on account of any claim, liability, damage, or expense suffered or incurred by or threatened against Grantor or any other person or entity, except as such claim, liability, damage, or expense is the result of the City of Portsmouth's, its agents or employee's negligence or willful misconduct.

10. **Applicable Law:** This Community Space Easement shall be construed and interpreted according to the substantive law of the State of New Hampshire.



**11. Community Space Easement to Bind Successors:** The provisions of this Community Space Easement shall be binding upon and insure to the benefit of Grantor and its successors and assigns. The Community Space Easement shall be appurtenant to, and for the benefit of, Grantee and shall run with title to the Property and shall continue in perpetuity.

Meaning and intending to convey an easement over a portion of the Property conveyed to the Grantor by Warranty Deed of Jarbel Realty, LLC, dated April 5, 2019 and recorded at the Rockingham County Registry of Deeds at Book 5990, Page 1703.

This is an exempt transfer pursuant to RSA 78-B:2(I).

IN WITNESS WHEREOF, Grantor and City have executed this Community Space Easement as set forth, below.

Grantor:

Dagny Taggart, LLC

By: \_\_\_\_\_  
Mark A. McNabb, Manager

Grantee:

City of Portsmouth, New Hampshire

By: \_\_\_\_\_  
Karen S. Conard, City Manager



ACKNOWLEDGEMENTS

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before me, the undersigned notary public, personally appeared Mark A. McNabb, Manager of Dagny Taggart, a New Hampshire limited liability company, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it voluntarily for its stated purpose.

\_\_\_\_\_  
Notary Public:  
My Commission Expires:

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before: me, the undersigned notary public, personally appeared Karen S. Conard Manager of the City of Portsmouth New Hampshire, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it in his capacity as stated therein and voluntarily for its stated purpose.

\_\_\_\_\_  
Notary Public:  
My Commission Expires:



After recording return to:  
City of Portsmouth  
Planning Department  
1 Junkins Avenue  
Portsmouth, NH 03801

[LOT 31]

**EASEMENT FOR PUBLIC ACCESS AND USE OF COMMUNITY SPACE**

**THIS EASEMENT HEREIN IS GRANTED** this \_\_\_\_ day of \_\_\_\_\_, 2020 by Dagny Taggart, LLC, a New Hampshire limited liability company having an address of 30 Penhallow Street, Suite 300 East, City of Portsmouth, County of Rockingham, State of New Hampshire 03801, (“Grantor”) and for consideration of One Dollar (\$1.00) paid by the City, and other good and valuable consideration, receipt of which is acknowledged by Grantor, grants unto the City of Portsmouth, a municipal corporation, 1 Junkins Avenue, Portsmouth, New Hampshire (“City”) with warranty covenants, and easement for public access to and use of certain community space as set forth herein as a plaza, pedestrian alley and wide pedestrian sidewalk easements.

**WITNESSETH**

**WHEREAS**, Grantor acquired a tract of land located at 3 Pleasant Street, City of Portsmouth, County of Rockingham, State of New Hampshire (the “Property”), by Warranty Deed of Jarbel Realty, LLC, dated April 5, 2019 and recorded at the Rockingham County Registry of Deeds at Book 5990, Page 1701; and

**WHEREAS**, reference is made to a plan entitled “Brick Market, Master Plan, Community Space, Tax Map 107, Lots 27, 31 & 42, Owners: Dagny Taggart, LLC & Coventry Assets, LTD., Property located at: 3 Pleasant Street, 30 Penhallow Street, 60 Penhallow Street, City of Portsmouth, County of Rockingham, State of New Hampshire,” prepared by Ambit Engineering, Inc., dated July 25, 2019, as revised, and recorded herewith at the Rockingham County Registry of Deeds (the “Easement Plan”); and

**NOW THEREFORE**, in consideration of the sum of One Dollar (\$1.00), to be paid by the City, and other good and valuable consideration, the receipt of which is hereby acknowledged by the Grantor, Grantor conveys the easements as follows, located in the City of Portsmouth,



County of Rockingham, State of New Hampshire (hereinafter collectively referred to as the “Easements”):

1. Wide Pedestrian Sidewalk Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy, as identified on the Easement Plan as a “Wide Pedestrian Sidewalk.”
2. Pedestrian Alley Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Pedestrian Alley as identified on the Easement Plan as “Pedestrian Alley.”
3. Plaza Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Plaza as identified on the Easement Plan as “Plaza.” Said area may be improved by the Grantor with permanent fixtures, such as public fountains, benches and other such landscaping features, at its sole expense, and as depicted in the Easement Plan. The construction of any permanent fixtures not depicted in the Site Plan shall be subject to a modified site plan approval by the Portsmouth Planning Board.

The Easement granted herein shall be subject to the following terms and conditions:

1. **Terms of Public Use:** The Public Use permitted by the Easements shall be governed and determined at the sole discretion of the City, as expressed by the City Manager or the highest-ranking administrative officer of the City, subject to the terms and conditions of these easement. The City shall provide reasonable notice to the Grantor of an extraordinary event to be scheduled for the easement areas but failure to do so shall not be a breach of these easements.
2. **Rights to Private Property:** This easement does not convey any right to the public to access or utilize the private property of the Grantor outside the easement areas. Grantor’s use of the Easements shall be subject to and regulated through the City of Portsmouth’s rules and ordinances governing public sidewalks.
3. **Maintenance:** Maintenance of the easement areas shall be the sole responsibility of the Grantor, its successors or assigns. The City shall have the right, but not the obligation, to access the easement areas for the purpose of maintenance, repair or replacement, after providing reasonable notice to the Grantor of the scope and cost of such work, all as reasonably determined by the City. Such maintenance costs incurred by the City shall be at the sole expense of the Grantor, its successors or assigns.
4. **Encroachments:** The Easements are subject to all existing encroachments of utilities and improvements on, over and under the Easements.
5. **Covenants Run with the Land:** The Easements granted herein shall be perpetual in nature, shall run with the land and shall benefit and be binding upon the Grantor, its successors and assigns. The Easements shall be recorded in the Rockingham County Registry of Deeds.



6. **City Ordinance Application:** Any use, public or private, of the Easements shall be subject to and comply with the City Ordinances of the City of Portsmouth.

7. **Notices:** Any notice, demand, request, or other communication that either party desires or is required to give to the other under this Easement shall be in writing and either served personally or sent by United States mail, postage prepaid, certified, return receipt requested, and shall be mailed to the parties at the following addresses:

To Grantor:

Dagny Taggart, LLC  
30 Penhallow Street, Suite 300 East  
Portsmouth, NH 03801

(or as listed and at the address shown on the City's current Tax Records)

To City:

City Manager (or the highest-ranking administrative officer)  
City of Portsmouth, New Hampshire  
1 Junkins Avenue  
Portsmouth, NH 03801

8. **Amendment:** Grantor, or its successors and/or assigns, and City may mutually agree to amend or modify this Community Space Easement, provided that any such amendment or modification is approved by the City Council at a noticed public hearing, in writing and signed by both parties, and is consistent with the purpose and intent of the Zoning Ordinance. No amendment or modification of this Community Space Easement shall take effect unless and until it is recorded in the Rockingham County Registry of Deeds.

9. **Costs and Liabilities:** Grantor agrees to bear all costs and liabilities of any kind related to the operation, upkeep, and maintenance of the Property, and to defend, indemnify, hold harmless, and release the City of Portsmouth, from and against any and all actions, claims, damages, liabilities, or expenses that may be asserted by any person or entity, including Grantor, relating thereto. Without limiting the foregoing, the City of Portsmouth shall not be liable to Grantor or any other person or entity in connection with any entry upon the Property pursuant to this Community Space Easement, or on account of any claim, liability, damage, or expense suffered or incurred by or threatened against Grantor or any other person or entity, except as such claim, liability, damage, or expense is the result of the City of Portsmouth's, its agents or employee's negligence or willful misconduct.

10. **Applicable Law:** This Community Space Easement shall be construed and interpreted according to the substantive law of the State of New Hampshire.



**11. Community Space Easement to Bind Successors:** The provisions of this Community Space Easement shall be binding upon and insure to the benefit of Grantor and its successors and assigns. The Community Space Easement shall be appurtenant to, and for the benefit of, Grantee and shall run with title to the Property and shall continue in perpetuity.

Meaning and intending to convey an easement over a portion of the Property conveyed to the Grantor by Warranty Deed of Jarbel Realty, LLC, dated April 5, 2019 and recorded at the Rockingham County Registry of Deeds at Book 5990, Page 1701.

This is an exempt transfer pursuant to RSA 78-B:2(I).

IN WITNESS WHEREOF, Grantor and City have executed this Community Space Easement as set forth, below.

Grantor:

Dagny Taggart, LLC

By: \_\_\_\_\_  
Mark A. McNabb, Manager

Grantee:

City of Portsmouth, New Hampshire

By: \_\_\_\_\_  
Karen S. Conard, City Manager



ACKNOWLEDGEMENTS

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before me, the undersigned notary public, personally appeared Mark A. McNabb, Manager of Dagny Taggart, a New Hampshire limited liability company, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it voluntarily for its stated purpose.

---

Notary Public:  
My Commission Expires:

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before: me, the undersigned notary public, personally appeared Karen S. Conard Manager of the City of Portsmouth New Hampshire, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it in his capacity as stated therein and voluntarily for its stated purpose.

---

Notary Public:  
My Commission Expires:



After recording return to:  
City of Portsmouth  
Planning Department  
1 Junkins Avenue  
Portsmouth, NH 03801

[LOT 42]

**EASEMENT FOR PUBLIC ACCESS AND USE OF COMMUNITY SPACE**

**THIS EASEMENT HEREIN IS GRANTED** this \_\_\_\_ day of \_\_\_\_\_, 2020 by Coventry Assets, LLC, f/k/a Coventry Assets, Ltd., a New Hampshire limited liability company having an address of 30 Penhallow Street, Suite 300 East, City of Portsmouth, County of Rockingham, State of New Hampshire 03801, (“Grantor”) and for consideration of One Dollar (\$1.00) paid by the City, and other good and valuable consideration, receipt of which is acknowledged by Grantor, grants unto the City of Portsmouth, a municipal corporation, 1 Junkins Avenue, Portsmouth, New Hampshire (“City”) with warranty covenants, and easement for public access to and use of certain community space as set forth herein as a plaza, pedestrian alley and pocket park easements.

**WITNESSETH**

**WHEREAS**, Grantor acquired a tract of land located at 30 Penhallow Street, City of Portsmouth, County of Rockingham, State of New Hampshire (the “Property”), by Quitclaim Deed of City of Portsmouth, County of Rockingham, State of New Hampshire, dated June 16, 1994 and recorded at the Rockingham County Registry of Deeds at Book 3057, Page 2440; and

**WHEREAS**, reference is made to a plan entitled “Brick Market, Master Plan, Community Space, Tax Map 107, Lots 27, 31 & 42, Owners: Dagny Taggart, LLC & Coventry Assets, LTD., Property located at: 3 Pleasant Street, 30 Penhallow Street, 60 Penhallow Street, City of Portsmouth, County of Rockingham, State of New Hampshire,” prepared by Ambit Engineering, Inc., dated July 25, 2019, as revised, and recorded herewith at the Rockingham County Registry of Deeds (the “Easement Plan”); and

**NOW THEREFORE**, in consideration of the sum of One Dollar (\$1.00), to be paid by the City, and other good and valuable consideration, the receipt of which is hereby acknowledged by the Grantor, Grantor conveys the easements as follows, located in the City of Portsmouth,



County of Rockingham, State of New Hampshire (hereinafter collectively referred to as the “Easements”):

1. Pocket Park Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy, as identified on the Easement Plan as a “Pocket Park”
2. Pedestrian Alley Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Pedestrian Alley as identified on the Easement Plan as “Pedestrian Alley.”
3. Plaza Easement. The Grantor hereby grants to the City and declares for the benefit of the public a permanent right to use and enjoy the Plaza as identified on the Easement Plan as “Plaza.” Said area may be improved by the Grantor with permanent fixtures, such as public fountains, benches and other such landscaping features, at its sole expense, and as depicted in the Easement Plan. The construction of any permanent fixtures not depicted in the Site Plan shall be subject to a modified site plan approval by the Portsmouth Planning Board.

The Easement granted herein shall be subject to the following terms and conditions:

1. **Terms of Public Use:** The Public Use permitted by the Easements shall be governed and determined at the sole discretion of the City, as expressed by the City Manager or the highest-ranking administrative officer of the City, subject to the terms and conditions of these easement. The City shall provide reasonable notice to the Grantor of an extraordinary event to be scheduled for the easement areas but failure to do so shall not be a breach of these easements.
2. **Rights to Private Property:** This easement does not convey any right to the public to access or utilize the private property of the Grantor outside the easement areas. Grantor’s use of the Easements shall be subject to and regulated through the City of Portsmouth’s rules and ordinances governing public sidewalks.
3. **Maintenance:** Maintenance of the easement areas shall be the sole responsibility of the Grantor, its successors or assigns. The City shall have the right, but not the obligation, to access the easement areas for the purpose of maintenance, repair or replacement, after providing reasonable notice to the Grantor of the scope and cost of such work, all as reasonably determined by the City. Such maintenance costs incurred by the City shall be at the sole expense of the Grantor, its successors or assigns.
4. **Encroachments:** The Easements are subject to all existing encroachments of utilities and improvements on, over and under the Easements.
5. **Covenants Run with the Land:** The Easements granted herein shall be perpetual in nature, shall run with the land and shall benefit and be binding upon the Grantor, its successors and assigns. The Easements shall be recorded in the Rockingham County Registry of Deeds.



6. **City Ordinance Application:** Any use, public or private, of the Easements shall be subject to and comply with the City Ordinances of the City of Portsmouth.

7. **Notices:** Any notice, demand, request, or other communication that either party desires or is required to give to the other under this Easement shall be in writing and either served personally or sent by United States mail, postage prepaid, certified, return receipt requested, and shall be mailed to the parties at the following addresses:

To Grantor:

Coventry Assets, LLC  
30 Penhallow Street, Suite 300 East  
Portsmouth, NH 03801

(or as listed and at the address shown on the City's current Tax Records)

To City:

City Manager (or the highest-ranking administrative officer)  
City of Portsmouth, New Hampshire  
1 Junkins Avenue  
Portsmouth, NH 03801

8. **Amendment:** Grantor, or its successors and/or assigns, and City may mutually agree to amend or modify this Community Space Easement, provided that any such amendment or modification is approved by the City Council at a noticed public hearing, in writing and signed by both parties, and is consistent with the purpose and intent of the Zoning Ordinance. No amendment or modification of this Community Space Easement shall take effect unless and until it is recorded in the Rockingham County Registry of Deeds.

9. **Costs and Liabilities:** Grantor agrees to bear all costs and liabilities of any kind related to the operation, upkeep, and maintenance of the Property, and to defend, indemnify, hold harmless, and release the City of Portsmouth, from and against any and all actions, claims, damages, liabilities, or expenses that may be asserted by any person or entity, including Grantor, relating thereto. Without limiting the foregoing, the City of Portsmouth shall not be liable to Grantor or any other person or entity in connection with any entry upon the Property pursuant to this Community Space Easement, or on account of any claim, liability, damage, or expense suffered or incurred by or threatened against Grantor or any other person or entity, except as such claim, liability, damage, or expense is the result of the City of Portsmouth's, its agents or employee's negligence or willful misconduct.

10. **Applicable Law:** This Community Space Easement shall be construed and interpreted according to the substantive law of the State of New Hampshire.



**11. Community Space Easement to Bind Successors:** The provisions of this Community Space Easement shall be binding upon and insure to the benefit of Grantor and its successors and assigns. The Community Space Easement shall be appurtenant to, and for the benefit of, Grantee and shall run with title to the Property and shall continue in perpetuity.

Meaning and intending to convey an easement over a portion of the Property conveyed to the Grantor by Quitclaim Deed of City of Portsmouth, County of Rockingham, State of New Hampshire, dated June 16, 1994 and recorded at the Rockingham County Registry of Deeds at Book 3057, Page 2440.

This is an exempt transfer pursuant to RSA 78-B:2(I).

IN WITNESS WHEREOF, Grantor and City have executed this Community Space Easement as set forth, below.

Grantor:

Coventry Assets, LLC, f/k/a Coventry Assets, Ltd.

By: \_\_\_\_\_  
Mark A. McNabb, Manager

Grantee:

City of Portsmouth, New Hampshire

By: \_\_\_\_\_  
Karen S. Conard, City Manager



ACKNOWLEDGEMENTS

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before me, the undersigned notary public, personally appeared Mark A. McNabb, Manager of Coventry Assets, LLC, f/k/a Coventry Assets, Ltd., a New Hampshire limited liability company, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it voluntarily for its stated purpose.

\_\_\_\_\_  
Notary Public:  
My Commission Expires:

STATE OF NEW HAMPSHIRE  
COUNTY OF ROCKINGHAM

On this \_\_\_\_ day of \_\_\_\_\_, 2020, before: me, the undersigned notary public, personally appeared Karen S. Conard Manager of the City of Portsmouth New Hampshire, proved to me through satisfactory evidence of identification, which was a valid driver's license, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that he/she signed it in his capacity as stated therein and voluntarily for its stated purpose.

\_\_\_\_\_  
Notary Public:  
My Commission Expires:



[MENU](#)



[f \(https://www.facebook.com/VilligerEntsorgungssystemeAG/\)](https://www.facebook.com/VilligerEntsorgungssystemeAG/)



[DE](#)

[EN](#)



[/en](#)

**Swing o Mat**

**The underground system with a foldable walkway platform**

The walkway platform of our Swing o Mat underground container system is 90° foldable. Thus, no emptying hook is visible, and the waste can be collected with either a steel container or big bag.

**Product Specifications**

- Volume: 3.0 – 5.0 m<sup>3</sup>
- Modular System
- Steel Container or Big Bag
- Throw-in column: different models available
- Emptying Hooks : Mushroom, 1 Hook

**Suitable to collect**

- Mixed Waste
- Paper + Cardboard
- Plastic + Plastic Bottles
- Glass
- Aluminium
- Recycables

**Options**



[Fill Level Sensor](#)



[Electronic Access Control](#)

[/en/products/options/fuellstandsen](#) [/en/products/options/zutrittsystem](#)



[Weighing Systems](#)



[Service + Maintenance](#)

[/en/products/options/verwiegungssystem](#) [/en/services/service-maintenance](#)

**TRASH CHUTES**



[MENU](#)




[f \(https://www.facebook.com/VilligerEntsorgungssystemeAG/\)](https://www.facebook.com/VilligerEntsorgungssystemeAG/)



[DE](#)

[EN](#)

[/en/](#)



### Product Description

1. Throw-in Column
2. Tilttable Walkway Platform
3. Cylinder
4. Steel Container or Big Bag
5. Concrete Element

Get in touch with us



# BAMBOO

Design by Antoni Arola & Enric Rodríguez.

## Reference

**4812.**

## Application

Outdoor

## Installation type

Recessed

## Description

Bamboo is a recessed outdoor lamp with three arms. Available in two finishes – khaki, and oxide – that make it possible to camouflage and integrate it into the landscape, with the added surprise that it produces light. Designed by Antoni Arola & Enric Rodríguez.

## Diffuser

Acrylic diffuser

## Materials

Body: Resin + fiberglass

Diffuser: Acrylic

## Finishes




**4812-07** Khaki (RAL 7006)



**4812-54** Oxide (RAL 8017)

## Sketch



## Electrical characteristics

9 x LED 2.1W 700mA

Total 18.9 W



# VIBIA



**Light source:** 2700K CRI >80 1794 lm 95 lm/W

**Fixture:** 420 lm 22 lm/W

**Driver included:** CC - Constant Current 700 mA 120-277V 50/60Hz

**Electronic dimming:** NO DIMMING


## Installation and assembly

Please see the installation manual


## Light distribution

### Ground lighting

Outdoor lighting




## Photometric data



## Certificates







# TORQ EXTRUSIONS - ALUMINUM


Model: iQA



PRODUCT	FINISH	MOUNTING	LENS	TYPE	FINISHED FIXTURE LENGTH (IN)
TORQ	ST BK BZ	SST	CL/60 CL/70 FR PR DF ENC/CL ENC/TL	S1 S2 S3 S4  P1 P2 P3 P4  NI	1" increments from 1" - 98.43"  Tolerance +0.0"/-0.5"


- NOTES:**
- UL Listed when assembled with STRIP LEDs at Q-Tran
  - NRTL Listed for install in Storage Areas with Clothing, NEC Field 410.2 and 410.16 when assembled as a fixture, with 4.0 w/ft or less, at Q-Tran facility (Not applicable for encapsulation)
  - Field modifications must comply with Q-Tran's installation methods otherwise warranty is null and void

## FINISH




## MOUNTING


NOTE: 2 clips provided for 4' or less;  
4 clips provided for greater than 4'




## LENS with LED visibility



## DIMENSIONS




Profile




Profile with Stainless Steel Mounting Clip

## TYPE


SINGLE (Input only)




PASS THROUGH (Input/Output)




ORDER EXAMPLE



## END CAPS




QTY:




Endcap

## CUT OFF



LENGTH (IN) : Add to nominal LED length for fixture length



Endcap#1  
Endcap#2  
Space to solder wire

$$S1 \ .08" + .08" + .25" = .41"$$

$$P1 \ .08" + .08" + 2x(.25") = .66"$$

PROJECT NAME	DATE	COMPANY	TYPE	NOTE





# WURM-SW FIXTURES - FLEXIBLE (Q-CAP)



PRODUCT	MOUNTING	RATED	CCT	OUTPUT	LENS	TYPE	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS (NO FEED)	LENGTH (IN)
<b>WURM-SW</b> Voltage: 24 VDC Wattage: see table	<b>WSCS</b> <b>MCS</b>	<b>DRY</b> <b>WET</b>	<b>24</b> - 2400K <b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K	<b>SO</b> <b>HO</b> <b>VHO</b>	<b>ENC/CL</b> <b>ENC/TL</b>	<b>S1</b> <b>P1</b>	<b><sup>1</sup>BW</b> <b>BRL</b>	<b>N/A</b> <b><sup>1</sup>BW</b> <b>BRL</b>	<b>WH</b> <b>N/A</b>	1" increments from 1"-191"  Tolerance +0.0"/-outpoint for installed product*


ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
  - Data subject to change, all data has +/- 5% tolerance
  - <sup>1</sup>BW comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
  - Connector/Wire In or Out not needed to specify product. Standard configuration is Type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with White Endcap (WH)

## OUTPUT Tested for WURM-SW-WSCS-DRY (L70 = 40000 HRS)


CCT	SO Standard Output 1.5 W/ft				HO High Output 3.0 W/ft				VHO Very High Output 5.0 W/ft			
	ENC/CL		ENC/TL		ENC/CL		ENC/TL		ENC/CL		ENC/TL	
	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI
2400K	127	94	107	94	231	93	189	93	329	94	274	94
2700K	127	97	103	97	227	98	197	98	329	98	273	98
3000K	135	99	110	98	242	98	202	98	337	98	267	97
3500K	144	96	115	96	242	96	201	97	359	97	304	97
4000K	151	96	126	96	262	96	218	96	370	97	316	97

## MOUNTING NOTE: 2 clips provided per first 12", 1 clip provided per additional 12"



## FLEXIBILITY

Light Source



Up/Down & Helical\*


\*Max recommended rotation of 1 rotation per 16"

## DIMENSIONS




Profile (Standard)

## LENS with LED visibility




## TYPE


SINGLE (Input only)




PASS THROUGH (Input/Output)



ORDER EXAMPLE




## END CAPS (NO FEED)



WHITE ENDCAPS  
.11" added at end  
.24" dim spot

## END CAPS (WITH FEED)




WHITE ENDCAPS  
.0" added at end  
.38" dim spot

PROJECT NAME	DATE	COMPANY	TYPE	NOTE



# The Brightest Idea is Emergency Lighting with LEDs



## GENERAL DESCRIPTION

Operating in emergency mode or optional normal-on, this fixture is designed to mount directly on structural mullion beams used in typical glass-fronted entrances, with vertical surface as small as 2". This fixture has full 90° cut-off and will provide efficient emergency lighting in front of egress doorways, or along extended pathways.

## CONSTRUCTION

- Rugged extruded aluminum housing with stainless hardware is corrosion proof.
- Wet location listed UL 924. Certified IP66.
- Uniform, high brightness lighting over the path of egress.
- Full 90° cut-off.
- Three versions are available:

**RE**= Central Battery System Series CBS or other qualified source 12V- 24 VDC.

**BB**= Battery backup from Remote Battery Supply Series RPS.

**AC**= 120/ 277 VAC supply.

## ELECTRONICS

- Dual operation from either a battery or optional normally on power source.
- Lamps are connected in parallel-series strings, as required to meet requirements of NEC and Life Safety Codes. Lighting continues even after failure of One lamp or circuit.
- LED color temperature standard 5300K; available color temperatures from 2900K, 3200K, to 3800K.

## ENERGY EFFICIENT OPERATION

- Dual function operation for optional normally on night or security lighting as well as emergency lighting.
- Very low power consumption in optional night/ security mode. The security lighting circuit is independent of emergency lighting and may be switched manually, by an exterior photocell, or other automatic means.
- Over 50,000 hour lamp life in normal use.
- IES photometric data available for all models.

## CODES


- Manufactured and tested to UL Standard 924 and NFPA Life Safety Code 101.

## WARRANTY

- 5 year total customer satisfaction warranty. For Details see product catalog technical data section.

## FIXTURE SCHEDULE

<b>MODEL</b>	<b>CATALOG NO</b>
<b>APPROVAL</b>	<b>JOB INFORMATION</b>





# Moonlite LED®

## LED Outdoor Egress Emergency with Night Lighting Option


# Mullion Mount Emergency Light Series MUE

MUE.5.18.15


### SUGGESTED SPECIFICATIONS:

Supply and install the MOONLITE LED Series MUE Mullion Mount emergency lighting fixture manufactured by Sigtex Lighting Inc. The MUE assembly shall be listed for installation in wet locations in compliance with UL 924 and IP66 standards and shall be capable of operating from Sigtex remote power supply Series RPS, the Sigtex central battery system Series CBS, or from other remote power sources supplying 12-24 VDC or VAC. Upon loss of AC building power, emergency models shall operate for a minimum of 90 minutes in compliance with UL Standard 924 and NFPA LSC 101.

### MOUNTING DATA & DIMENSIONS:




### SPACING GUIDE




NOTE: FOR REFERENCE ONLY. STANDARD REFLECTANCES 80/50/20. SIGTEX IS NOT RESPONSIBLE FOR SPECIFIC CONDITIONS THAT MAY ALTER THE RESULTS.

CONTACT SIGTEX FOR LAYOUT ASSISTANCE  
Code Compliant Emergency lighting layouts provided free of charge!

### WALL MOUNT



### TOP MOUNT



**Typical Wiring Specification:**  
UL AWM Style: Control Cable  
#20 AWG 300V

BB and AC Models: 4 Conductors  
See Table 1

**TABLE 1**  
MAXIMUM WIRING LENGTH  
FROM RPS TO FIXTURE

WIRING SIZE AWG	LENGTH (FT)
	MUEBB
#18	25
#16	50
#14	75
#12	125

**LENGTH TABLE**

POWER	L
10 Watts	10"
20 Watts*	19"

\*RE & AC Models Only

### SECURITY LIGHTING CONTROL

**RE Models:** Requires SEC Option 'S' with CBL  
**BB Models:** Requires Option '-SB120' for connection to 120 VAC  
Requires Option '-SD277' for connection to 277 VAC  
**BB-DG Models:** Requires Option '-SD' for connection to 120/277 VAC

### RPS SELF-TEST DIAGNOSTIC FUNCTIONS BB MODELS WITH DG FUNCTION

STATUS	LED DISPLAY
NORMAL FULL CHARGE	GREEN ON
NORMAL FAST CHARGE	ORANGE ON
FAILED BATTERY	RED FLASH FAST
FAILED LAMP	GREEN FLASH
FAILED TRANSFER	ORANGE FLASH
FAILED CHARGER	RED FLASH SLOW

### FIXTURE ORDERING INFORMATION: EXAMPLE: MUEBB10AW-DG

MUE	BB	10	A	W	-DG
MODEL SERIES	OPERATION	POWER	HOUSING COLOR	MOUNT	OPTIONS
MUE	RE= Central Battery or other 12- 24 VDC Remote Source BB= Battery Backup (Includes RPS) AC= No Battery (Includes RPS)	10= 10 Watts Emergency & Normal On Power 20= 20 Watts Emergency & Normal On power (RE & AC Models Only)	W= Satin White A= Aluminum B= Dark Bronze X= Custom	T= Top W= Wall	DG= Self- Test Diagnostics (BB Models Only) SB120= Security Lighting with Control Switch for Standard BB Operation (120V) SD277= Security Lighting with Control Switch for Standard BB Operation (277V) SD= Security Lighting with Control Switch for BB Operation with DG option (120/ 277V) CW1= Custom Window Filter- 3800K CW2=Custom Window Filter- 3200K CW3=Custom Window Filter- 2900K DAC= Dual AC Input 2HT= 2" Canopy Height 5HT= 5" Canopy Height

### SUITABLE FOR WET LOCATIONS

AMBIENT TEMPERATURE LIMITS:  
-40° C to +50° C

### DISTRIBUTOR:

Specifications and Dimensions subject to change without notice.



**Sigtex Inc**  
LIGHTING

220 VFW Avenue, Grasonville, MD 21638

TEL: (410) 827-8300 Fax: (410) 827-8866

sales@sigtexinc.com www.sigtexinc.com



# Tumbler

## Specification Sheet

Project Name: \_\_\_\_\_ Job Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Fixture Quantity: \_\_\_\_\_

<b>Source</b>	LED
<b>Input Voltage</b>	120V-277V
<b>Frequency</b>	50/60 Hz
<b>EPA</b>	0.84 ft <sup>2</sup>
<b>Weight</b>	14.5 lbs (luminaire only)

The Tumbler luminaire is aluminum extrusion with a natural aluminum powdercoat finish offered by Santa & Cole Urbidermis with a clear or opal / diffused tempered glass.

Pole & Wall Mount Luminaire								
_____	<b>Product</b>	TML						
_____	<b>LED Configuration</b>	16	24	C ( CoB ) *				
_____	<b>Drive Current</b>	A ( 350 mA )	B ( 500 mA )					
_____	<b>Color Temperature</b>	1 ( 3000K )	2 ( 4000K )					
_____	<b>Distribution</b>	WF ( Wide Flood )	F ( Flood )	M ( Medium )	S ( Spot Flood )	TII ( Type II )	TIII ( Type III )	TIV ( Type IV )
_____	<b>Lens</b>	Null ( Clear )	O ( Opal / Diffused )					
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )					

\* CoB provides a Wide Flood distribution only.

EXAMPLE: TML - 16 - B - 1 - WF - O - AS

Catenary Luminaire				
_____	<b>Product</b>	TML		
_____	<b>LED Configuration</b>	16	24	C ( CoB ) *
_____	<b>Drive Current</b>	A ( 350 mA )	B ( 500 mA )	
_____	<b>Color Temperature</b>	1 ( 3000K )	2 ( 4000K )	
_____	<b>Distribution</b>	WF ( Wide Flood )	TII-II ( Quad Oval )	TV ( Type V )
_____	<b>Lens</b>	Null ( Clear )	O ( Opal / Diffused )	
_____	<b>Bracket</b>	C ( Catenary )		
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )	

\* CoB provides a Wide Flood distribution only.


EXAMPLE: TML - 16 - B - 1 - TV - O - C - BK




Catenary

Mounting Accessories				
_____	<b>Product</b>	TML		
_____	<b>Bracket</b>	01 ( Single Column )	02 ( Wall )	04 ( Double Column )
_____	<b>Color</b>	AS ( Aluminum Silver )	BK ( Black )	


EXAMPLE: TML – 01 – DK



Single Column



Wall



Double Column

Tumbler Aluminum Pole					
Height	Pole #	Mounting	Diameter	Wall	Weight
3.4m ( 11.2 ft )	TMF11P	( 1 ) Single Column Bracket	Straight 4.5"	0.13"	41 lbs
	TMF11P	( 1 ) Double Column Bracket	Straight 4.5"	0.13"	41 lbs
4.2m ( 13.8 ft )	TMF21P	( 1 ) Single Column Bracket	Straight 4.5"	0.13"	45 lbs
	TMF22P	( 2 ) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.13"	45 lbs
	TMF21P	( 1 ) Double Column Bracket	Straight 4.5"	0.13"	45 lbs
5.0m ( 16.4 ft )	TMF31P	( 1 ) Single Column Bracket	Straight 4.5"	0.13"	51 lbs
	TMF32P	( 2 ) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.13"	51 lbs
	TMF31P	( 1 ) Double Column Bracket	Straight 4.5"	0.13"	51 lbs
6.6m ( 21.7 ft )	TMF41P	( 3 ) Single Column Brackets, Spiral Configuration, 120° Orientation	Stepped 6"/4.5"	0.19"/0.13"	97 lbs

\* Landscape Forms can provide poles for your catenary project. Contact the factory for more information.

Pole Options								
_____	<b>Twist Lock</b>	Null ( None )	T ( Twist Lock Receptacle )					
_____	<b>Color</b>	BLK ( Black )	DSK ( Dusk )	MBK ( Matte Black )	MER ( Mercury ) *	SIL ( Silver )	SCL ( Storm Cloud )	TNM ( Titanium )

\* Mercury from Landscape Forms is our recommended color match for aluminum silver from Santa & Cole.

EXAMPLE: TMF41P – T – MER

**Modifications**

Don't see what you are looking for? Our goal is to partner with you as the designer to manufacture solutions needed for the space you are creating. We offer the option to modify our standard product to meet certain design specifications or needs. Common modifications can include GCFI outlets, custom RAL colors, banner arm(s) mounting, and custom pole heights. Contact your local Landscape Forms representative to learn more about these offerings.

**Notes**

---



---



---



---

Please send completed forms to your Landscape Forms representative or contact us at (800) 430-6209 with any questions.



December 23, 2019

Dagny Taggart, LLC  
McNabb Properties, LTD  
30 Penhallow Street, Suite 300 East  
Portsmouth, NH 03801

Dear Mark McNabb:

I am responding to your request to confirm the availability of electric service for the proposed 60 Penhallow Street project, known as Brick Market, being constructed by McNabb Construction for Dagny Taggart, LLC.

The proposed project consists of a 4-story building with approximately 41,600 s/f of general office space and 16,800 s/f of fast food and fast casual restaurant space at the ground level, as well as parking below grade. The proposed development will be constructed along Penhallow and Daniel Streets in Portsmouth, NH.

The developer will be responsible for the installation of all underground facilities and infrastructure required to service the new building. The proposed service and transformer locations to service your project will be as shown on attached plans (Daniel Street Offsite Improvements Plan P1, Penhallow Street Offsite Improvements Plan P2, and Utility Plan C4). The proposed building service will be fed from the circuits as depicted on the plans, with final layout to be determined by Eversource Engineering, as depicted on the final approved plans. The developer will work with Eversource and the City of Portsmouth to obtain all necessary approvals, easements, and licenses for the proposed overhead / underground facilities shown on attached plans.

This letter serves as confirmation that Eversource will need to extend its underground infrastructure to provide sufficient capacity for the proposed development. The cost of extending service to the aforementioned location and any associated infrastructure improvements necessary to provide service will be borne by the developer unless otherwise agreed upon.

Eversource tentatively approves the locations shown; assuming the final installed locations meet all clearances, physical protection, and access requirements as outlined in Eversource's "Information & Requirements For Electric Supply" (<https://www.eversource.com/content/docs/default-source/pdfs/requirements-for-electric-service-connections.pdf?sfvrsn=2>).

If you require additional information or I can be of further assistance please do not hesitate to contact me at our Portsmouth Office, 603-436-7708 Ext. 555-5678

Respectfully,



Michael J. Busby, PE

NH Eastern Regional Engineering and Design Manager, Eversource

cc: (via e-mail)

Michael Lee, Eastern Region Operations Manager, Eversource  
Mary Jo Hanson, Field Supervisor, Electric Design, Eversource



1/7/20

Ambit Engineering  
c/o John Chagnon  
200 Griffin Road; Unit 3  
Portsmouth, NH 03801

*RE: Natural gas service to the proposed Brick Market located at  
60 Penhallow Street, Portsmouth, NH*

Unitil's natural gas division has reviewed the requested site for natural gas service.

Unitil hereby confirms natural gas is available from Penhallow Street to supply the proposed Development.

Please contact me with any questions at 603-294-5144.

Sincerely,


A handwritten signature in black ink that reads "David Beaulieu". The signature is fluid and cursive, with a long horizontal stroke at the end.

David Beaulieu  
Business Development Executive  
Unitil  
325 West Road  
Portsmouth, NH 03801




DRAINAGE ANALYSIS  
SITE REDEVELOPMENT

60 PENHALLOW STREET  
PORTSMOUTH, NH



**October 8, 2019**

**Revised: November 18, 2019**



**Ambit Engineering, Inc.**



Civil Engineers and Land Surveyors  
200 Griffin Road, Unit 3  
Portsmouth, NH 03801  
Phone: 603.430.9282; Fax: 603.436.2315  
E-mail: [jlm@ambitengineering.com](mailto:jlm@ambitengineering.com)  
(Ambit Job Number 3039)

## TABLE OF CONTENTS

### REPORT

Executive Summary	1
Introduction / Project Description	2
Methodology	3
Site Specific Information	3
Pre-Development Drainage	4
Post-Development Drainage	4
Erosion and Sediment Control Practices	5
Conclusion	6
References	6

### APPENDIX

- A. Vicinity (Tax) Map
- B. Tables, Charts, Etc.
- C. HydroCAD Drainage Analysis Calculations
- D. Soil Survey Information
- E. Inspection & Maintenance Plan

### ATTACHMENTS

- Existing Drainage Plan - W1
- Proposed Drainage Plan - W2



## **EXECUTIVE SUMMARY**

This drainage analysis examines the pre-development (existing) and post-development (proposed) stormwater drainage patterns for the proposed development which includes a constructing a multi-story mixed use building at 60 Penhallow Street in Portsmouth, NH. The site is shown on the City of Portsmouth Assessor's Tax Map 107 as Lot 27. The lot size is 23,279 square-feet (0.53 acres).

The new building will be serviced by public water and public sewer. The development has the potential to increase stormwater runoff to adjacent properties, and therefore must be designed in a manner to prevent that occurrence. This will be done primarily by capturing stormwater runoff and routing it through appropriate stormwater facilities, designed to ensure that there will be no increase in peak runoff from the site as a result of this project.

The hydrologic modeling uses the "Extreme Precipitation" values from The Northeast Regional Climate Center (Cornell University) for modeling purposes. Because Portsmouth is in the Seacoast area, we have increased these values by 15% and incorporated these values in this report.

**SITE REDEVELOPMENT**

60 Penhallow Street

PORTSMOUTH, NH

**INTRODUCTION / PROJECT DESCRIPTION**

This drainage report is designed to assist the owner, planning board, contractor, regulatory reviewer, and others in understanding the impact of the proposed development project on local surface water runoff and quality. The project site is shown on the City of Portsmouth, NH Assessor's Tax Map 107 Lot 27.

Bounding the site to the north is Daniel Street. Bounding the site to the West are commercial buildings with frontage along Daniel Street and Market Square / Pleasant Street. Bounding the site to the south is a commercial building with frontage on Penhallow Street. Bounding the Site to the east is Penhallow Street. The subject property is situated in the Character District 4 (CD4), Downtown Overlay District (DOD) and the Historic District (HDC). A vicinity map is included in the Appendix to this report.

The proposed development plan is to construct a new commercial building with a below grade, two level garage and other associated improvements such as utilities and landscaping. The project is anticipated to begin construction in the spring of 2020 and be substantially completed by the summer of 2021.

This report includes information about the existing site and the proposed development necessary to analyze stormwater runoff and to design any required mitigation. The report includes maps of pre-development and post-development watersheds, sub-catchment areas and calculations of runoff. The report will provide a narrative of the stormwater runoff and describe numerically and graphically the surface water runoff patterns for this site. Proposed stormwater management and treatment structures and methods will also be described, as well as erosion and sediment control practices. To fully understand the proposed site development the reader should also review a complete site plan set in addition to this report.



## **METHODOLOGY**

This report uses the US Soil Conservation Service (SCS) Method for estimating stormwater runoff. The SCS method is published in The National Engineering Handbook (NEH), Section 4 "Hydrology" and includes the Technical Release No. 20, (TR-20) "Computer Program for Project Formulation Hydrology", and Technical Release No. 55 (TR-55) "Urban Hydrology for Small Watersheds" methods. This report uses the HydroCAD version 10.0 program, written by HydroCAD Software Solutions LLC, Chocorua, N.H., to apply these methods for the calculation of runoff and for pond modeling. Hydrologic modeling employs the "Extreme Precipitation" values from The Northeast Regional Climate Center (Cornell University) increased by 15%. These values have been used and are included in this report.

Time of Concentration (Tc) is calculated by entering measured flow path data such as flow path type, length, slope and surface characteristics into the HydroCAD program. For the purposes of this report, and as directed by TR55, a minimum time of concentration of 5 minutes is used.

The storm events used for the calculations in this report are the 2-year, 10-year and 50-year (24-hour) storms. Watershed basin boundaries have been delineated and subsequently revised using topographic maps prepared and updated by Ambit Engineering survey data, record plans and field observations to confirm.

## **SITE SPECIFIC INFORMATION**

Based on the United States Department of Agriculture (USDA) Natural Resources Conservation Service (NRCS), Soil Survey of Rockingham County, New Hampshire, the site is made up of one soil type:

699 – Urban land. This soil has been assigned a Hydrologic Soil Group (HSG) classification of B, with a Low runoff class.

The physical characteristics of the site consist of (3-15%) grades that generally slope downward into the center of the site. At least three catch basins located on site provide adequate drainage in the existing conditions. Elevations on the site range from 30 to 27 feet above sea level. Currently the site is a private commercial parking lot. The existing vegetation around the lot consists of established grasses, shrubs and trees.

According to the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map (FIRM) number 33015C0259E (effective date May 17, 2005), the project site is not located in a floodplain. A copy of the FIRM map is included in the Appendix.

## PRE-DEVELOPMENT DRAINAGE

The existing site drains via overland flow from the outer bounds of the property towards the center of the site to three catch basins located within the parking lot. These three catch basins combine and discharge to a 12" HDPE through CB 5966 located along the curb line in Penhallow Street. We have placed the design point at the end of the existing 12" HDPE, entering CB 5966 and then into an 18" HDPE main trunkline at DMH 5963. There is no existing stormwater detention or treatment on the site.

In the pre-development condition, the site has been analyzed as four watershed basins (ES1, ES2, ES3 and ES4) based on localized topography and discharge location. As described above, ES1 represents the majority of on site runoff while ES2, ES3 and ES4 are the offsite runoff from adjacent streets. The runoff curve number (CN) for Subcatchment ES1 is calculated to be 91 with impervious coverage of 76.9%. The runoff curve numbers for ES2, ES3 and ES4 is 98 since they are entirely impervious surface consisting of asphalt and brick sidewalk.

**Table 1: Pre-Development Watershed Basin Summary**

<b>Watershed Basin ID</b>	<b>Basin Area (SF)</b>	<b>Tc (MIN)</b>	<b>CN</b>	<b>2-Year Runoff (CFS)</b>	<b>10-Year Runoff (CFS)</b>	<b>50-Year Runoff (CFS)</b>	<b>Design Point</b>
ES1	30,432	5.0	91	2.25	3.67	5.80	DP1
ES2	4,330	5.0	98	0.37	0.56	0.86	DP1
ES3	1,701	5.0	98	0.14	0.22	0.34	DP1
ES4	803	5.0	98	0.07	0.10	0.16	DP1

## POST-DEVELOPMENT DRAINAGE

The proposed development has been designed to match the pre-development drainage patterns to the greatest extent feasible. In the post-development condition, the site has been analyzed as four (4) separate subcatchments (PS1, PS2, PS3 and PS4) based on localized topography and discharge locations. In general, the proposed subcatchments are similar area as the existing subcatchments. Basin PS1 is the rooftop runoff from the new building. PS2 is the runoff from Daniel Street. PS3 is the runoff from Penhallow Street. PS4 is runoff from the alley way that flows out to Penhallow Street.



The runoff curve number (CN), Time of Concentration (TC), % Impervious, and Peak Flow Rate (CFS) for the Post Development Watersheds are shown in Table 2: Post Development Water Shed Summary below.

**Table 2: Post-Development Watershed Basin Summary**

<b>Watershed Basin ID</b>	<b>Basin Area (SF)</b>	<b>Tc (MIN)</b>	<b>CN</b>	<b>2-Year Runoff (CFS)</b>	<b>10-Year Runoff (CFS)</b>	<b>50-Year Runoff (CFS)</b>	<b>Design Point</b>
PS1	17,104	5.0	98	1.46	2.23	3.39	DP1
PS2	5,601	5.0	98	0.48	0.73	1.11	DP1
PS3	1,995	5.0	98	0.17	0.26	0.40	DP1
PS4	12,558	5.0	94	1.00	1.58	2.45	DP1

The overall impervious coverage of the area analyzed in this report for all basins **increases** from 30,251 square feet (81.1%) in the pre-development condition to 35,773 square feet (95.9%) in the post-development condition. In the existing condition, parking is on the surface and surfaces treated with asphalt and used for vehicles are known to be high pollutant load areas. In the proposed condition this parking is located underground and since runoff from the site in the proposed condition is largely roof top and brick type paver walkways, there is no real need for treatment of stormwater runoff as the runoff will be relatively clean.

Table 3 shows a summary of the comparison between pre-developed flows and post-developed flows for the design point.

Table 3: Pre-Development to Post-Development Comparison

<b>Design Point</b>	<b>Q2 (CFS)</b>		<b>Q10 (CFS)</b>		<b>Q25 (CFS)</b>		<b>Q50 (CFS)</b>	
	<b>Pre</b>	<b>Post</b>	<b>Pre</b>	<b>Post</b>	<b>Pre</b>	<b>Post</b>	<b>Pre</b>	<b>Post</b>
DP1	2.83	3.11	4.56	4.80	5.90	6.11	7.16	7.34

## **EROSION AND SEDIMENT CONTROL PRACTICES**

The erosion potential for this site as it exists is low due to the existing pavement at the site. During construction, the major potential for erosion is wind and stormwater runoff. The

contractor will be required to inspect and maintain all necessary erosion control measures, as well as installing any additional measures as required. All erosion control practices shall conform to “The Stormwater Management and Erosion Control Handbook for Urban and Developing Areas in New Hampshire.” Some examples of erosion and sediment control measures to be utilized for this project during construction may include:

- Silt Soxx (or approved alternative) located at the toe of disturbed slopes
- Stabilized construction entrance at access point to the site
- Temporary mulching and seeding for disturbed areas
- Spraying water over disturbed areas to minimize wind erosion

After construction, permanent stabilization will be accomplished by permanent seeding, landscaping and surfacing the access drives and parking areas with asphalt paving

## CONCLUSION

The existing site is largely impervious surface. The proposed development will add a nominal amount of impervious surface to the overall area. This results in marginal increases between 0.28 cfs and 0.18 cfs in stormwater runoff for the range of storms analyzed. Considering that there is a closed drainage system located within Penhallow Street, in our opinion these increases can be absorbed with no concern for negative impacts.

## REFERENCES

1. City of Portsmouth, NH. Site Plan Review Regulations amended September 15, 2016.
2. Comprehensive Environmental Inc. and New Hampshire Department of Environmental Services. *New Hampshire Stormwater Manual (Volumes 1, 2 and 3)*, December 2008 (Revision 1.0).
3. Minnick, E.L. and H.T. Marshall. *Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire*, prepared by Rockingham County Conservation District, prepared for New Hampshire Department of Environmental Services, in cooperation with USDA Soil Conservation Service, August 1992.
4. HydroCAD Software Solution, LLC. *HydroCAD Stormwater Modeling System Version 10.0* copyright 2013. HydroCAD Software Solution, LLC. *HydroCAD Stormwater Modeling System Version 10.0* copyright 2013.
5. University of New Hampshire Stormwater Center 2009 Biannual Report, Pages 14-21 for references to Lag time (TC) for Porous Pavement and Filtration Basins.




APPENDIX A  
VICINITY (TAX) MAP





### 60 Penhallow Street



**Property Information**

**Property ID** 0107-0027-0000  
**Location** DANIEL ST  
**Owner** DAGNY TAGGART LLC



**MAP FOR REFERENCE ONLY  
NOT A LEGAL DOCUMENT**

City of Portsmouth, NH makes no claims and no warranties, expressed or implied, concerning the validity or accuracy of the GIS data presented on this map.

Geometry updated 4/1/2019  
Data updated 7/17/2019





**APPENDIX B**  
**TABLES, CHARTS, ETC.**





# Extreme Precipitation Tables

## Northeast Regional Climate Center

Data represents point estimates calculated from partial duration series. All precipitation amounts are displayed in inches.

Smoothing	Yes
State	New Hampshire
Location	
Longitude	70.756 degrees West
Latitude	43.077 degrees North
Elevation	0 feet
Date/Time	Mon, 30 Sep 2019 15:36:40 -0400

$Q2 = 3.20 \times 1.15 = 3.68$

$Q10 = 4.86 \times 1.15 = 5.59$

$Q25 = 6.16 \times 1.15 = 7.08$

$Q50 = 7.37 \times 1.15 = 8.48$

$Q100 = 8.83 \times 1.15 = 10.15$

### Extreme Precipitation Estimates

	5min	10min	15min	30min	60min	120min	1hr	2hr	3hr	6hr	12hr	24hr	48hr	1day	2day	4day	7day	10day	
1yr	0.26	0.40	0.50	0.65	0.81	1.04	0.70	0.98	1.21	1.56	2.03	2.65	2.92	2.35	2.81	3.22	3.94	4.54	1yr
2yr	0.32	0.50	0.62	0.81	1.02	1.30	0.88	1.18	1.52	1.94	2.48	3.20	3.57	2.84	3.43	3.93	4.67	5.32	2yr
5yr	0.37	0.58	0.73	0.97	1.25	1.61	1.08	1.47	1.89	2.43	3.14	4.06	4.57	3.59	4.40	5.03	5.93	6.69	5yr
10yr	0.41	0.65	0.82	1.11	1.45	1.89	1.25	1.73	2.23	2.89	3.74	4.86	5.52	4.30	5.31	6.07	7.09	7.96	10yr
25yr	0.48	0.76	0.97	1.34	1.77	2.34	1.53	2.14	2.78	3.63	4.73	6.16	7.09	5.45	6.81	7.79	9.00	10.03	25yr
50yr	0.54	0.86	1.10	1.54	2.07	2.76	1.79	2.53	3.29	4.32	5.65	7.37	8.57	6.52	8.24	9.40	10.79	11.95	50yr
100yr	0.60	0.97	1.25	1.77	2.42	3.26	2.09	2.98	3.90	5.15	6.76	8.83	10.36	7.81	9.96	11.35	12.93	14.24	100yr
200yr	0.67	1.10	1.43	2.05	2.82	3.83	2.44	3.51	4.61	6.12	8.07	10.58	12.52	9.36	12.04	13.72	15.50	16.97	200yr
500yr	0.80	1.31	1.71	2.48	3.48	4.76	3.00	4.38	5.76	7.70	10.20	13.44	16.10	11.90	15.48	17.62	19.72	21.43	500yr

### Lower Confidence Limits

	5min	10min	15min	30min	60min	120min	1hr	2hr	3hr	6hr	12hr	24hr	48hr	1day	2day	4day	7day	10day	
1yr	0.23	0.36	0.44	0.59	0.73	0.88	0.63	0.86	0.93	1.33	1.68	2.23	2.47	1.98	2.38	2.86	3.19	3.89	1yr
2yr	0.31	0.49	0.60	0.81	1.00	1.19	0.86	1.16	1.37	1.82	2.34	3.05	3.44	2.70	3.31	3.82	4.54	5.08	2yr
5yr	0.35	0.54	0.67	0.92	1.17	1.40	1.01	1.37	1.61	2.12	2.73	3.78	4.17	3.34	4.01	4.71	5.52	6.22	5yr
10yr	0.38	0.59	0.73	1.02	1.32	1.60	1.14	1.56	1.80	2.39	3.06	4.36	4.84	3.86	4.65	5.42	6.39	7.17	10yr

	5min	10min	15min	30min	60min	120min	1hr	2hr	3hr	6hr	12hr	24hr	48hr	1day	2day	4day	7day	10day	
<b>25yr</b>	0.44	0.67	0.83	1.18	1.56	1.90	1.35	1.86	2.10	2.75	3.53	4.71	5.86	4.17	5.63	6.61	7.75	8.64	<b>25yr</b>
<b>50yr</b>	0.48	0.73	0.91	1.31	1.76	2.16	1.52	2.12	2.34	3.07	3.92	5.32	6.75	4.71	6.50	7.67	8.99	9.97	<b>50yr</b>
<b>100yr</b>	0.53	0.81	1.01	1.46	2.00	2.47	1.73	2.41	2.62	3.41	4.34	5.98	7.79	5.30	7.49	8.89	10.43	11.50	<b>100yr</b>
<b>200yr</b>	0.59	0.89	1.12	1.63	2.27	2.81	1.96	2.75	2.93	3.78	4.78	6.71	8.97	5.93	8.63	10.30	12.13	13.29	<b>200yr</b>
<b>500yr</b>	0.68	1.01	1.31	1.90	2.70	3.36	2.33	3.28	3.41	4.31	5.43	7.80	10.82	6.90	10.41	12.52	14.82	16.09	<b>500yr</b>

## Upper Confidence Limits

	5min	10min	15min	30min	60min	120min	1hr	2hr	3hr	6hr	12hr	24hr	48hr	1day	2day	4day	7day	10day	
<b>1yr</b>	0.28	0.44	0.54	0.72	0.89	1.08	0.77	1.06	1.26	1.74	2.20	2.98	3.16	2.63	3.04	3.57	4.37	5.03	<b>1yr</b>
<b>2yr</b>	0.34	0.52	0.64	0.86	1.07	1.27	0.92	1.24	1.48	1.96	2.52	3.42	3.70	3.02	3.56	4.09	4.84	5.62	<b>2yr</b>
<b>5yr</b>	0.40	0.62	0.76	1.05	1.34	1.62	1.15	1.58	1.88	2.54	3.25	4.33	4.96	3.84	4.77	5.37	6.37	7.15	<b>5yr</b>
<b>10yr</b>	0.47	0.72	0.89	1.24	1.61	1.98	1.39	1.93	2.28	3.11	3.96	5.33	6.21	4.72	5.97	6.83	7.84	8.75	<b>10yr</b>
<b>25yr</b>	0.58	0.88	1.09	1.56	2.05	2.57	1.77	2.51	2.96	4.07	5.16	7.76	8.35	6.87	8.03	9.17	10.34	11.41	<b>25yr</b>
<b>50yr</b>	0.67	1.02	1.27	1.83	2.46	3.13	2.12	3.06	3.60	5.00	6.33	9.71	10.48	8.60	10.08	11.48	12.73	13.97	<b>50yr</b>
<b>100yr</b>	0.79	1.19	1.50	2.16	2.96	3.81	2.56	3.73	4.38	6.16	7.78	12.15	13.14	10.75	12.64	14.37	15.71	17.10	<b>100yr</b>
<b>200yr</b>	0.92	1.39	1.76	2.55	3.56	4.65	3.07	4.55	5.34	7.59	9.56	15.24	16.50	13.49	15.86	18.02	19.37	20.93	<b>200yr</b>
<b>500yr</b>	1.15	1.71	2.20	3.19	4.54	6.04	3.92	5.90	6.94	10.03	12.60	20.59	22.29	18.23	21.44	24.31	25.55	27.36	<b>500yr</b>







**APPENDIX C**  
**HYDROCAD DRAINAGE**  
**ANALYSIS CALCULATIONS**







**Routing Diagram for 3039-Pre**  
Prepared by Ambit Engineering, Inc., Printed 11/18/2019  
HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

**3039-Pre**

Prepared by Ambit Engineering, Inc.

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Printed 11/18/2019

Page 2

**Area Listing (selected nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.129	61	>75% Grass cover, Good, HSG B (E1)
0.032	85	Gravel roads, HSG B (E1)
0.459	98	Paved parking, HSG B (E1)
0.157	98	Paved roads w/curbs & sewers, HSG B (E2, E3, E4)
0.078	98	Unconnected roofs, HSG B (E1)
<b>0.856</b>	<b>92</b>	<b>TOTAL AREA</b>



**Soil Listing (selected nodes)**

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.856	HSG B	E1, E2, E3, E4
0.000	HSG C	
0.000	HSG D	
0.000	Other	
<b>0.856</b>		<b>TOTAL AREA</b>

**3039-Pre**

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 4

**Ground Covers (selected nodes)**

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.129	0.000	0.000	0.000	0.129	>75% Grass cover, Good	E1
0.000	0.032	0.000	0.000	0.000	0.032	Gravel roads	E1
0.000	0.459	0.000	0.000	0.000	0.459	Paved parking	E1
0.000	0.157	0.000	0.000	0.000	0.157	Paved roads w/curbs & sewers	E2, E3, E4
0.000	0.078	0.000	0.000	0.000	0.078	Unconnected roofs	E1
<b>0.000</b>	<b>0.856</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.856</b>	<b>TOTAL AREA</b>	



**Pipe Listing (selected nodes)**

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	E1	0.00	0.00	62.0	0.0050	0.013	12.0	0.0	0.0
2	E1	0.00	0.00	42.0	0.0031	0.013	12.0	0.0	0.0

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment E1: On Site**

Runoff Area=30,432 sf 76.89% Impervious Runoff Depth=2.71"  
Flow Length=227' Tc=5.0 min CN=91 Runoff=2.25 cfs 0.158 af

**Subcatchment E2: Daniel Street**

Runoff Area=4,330 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=0.37 cfs 0.029 af

**Subcatchment E3: Penhallow Street**

Runoff Area=1,701 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=0.14 cfs 0.011 af

**Subcatchment E4: Penhallow Street**

Runoff Area=803 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=0.07 cfs 0.005 af

**Link DP1: Penhallow Closed Drainage System**

Inflow=2.83 cfs 0.203 af  
Primary=2.83 cfs 0.203 af

**Total Runoff Area = 0.856 ac Runoff Volume = 0.203 af Average Runoff Depth = 2.85"**  
**18.87% Pervious = 0.161 ac 81.13% Impervious = 0.694 ac**



### Summary for Subcatchment E1: On Site

Runoff = 2.25 cfs @ 12.07 hrs, Volume= 0.158 af, Depth= 2.71"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
3,398	98	Unconnected roofs, HSG B
20,002	98	Paved parking, HSG B
5,633	61	>75% Grass cover, Good, HSG B
1,399	85	Gravel roads, HSG B
30,432	91	Weighted Average
7,032		23.11% Pervious Area
23,400		76.89% Impervious Area
3,398		14.52% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.0	80	0.0179	1.27		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.26"
0.2	43	0.0306	3.55		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
0.3	62	0.0050	3.21	2.52	<b>Pipe Channel, RCP_Round 12"</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
0.3	42	0.0031	2.53	1.98	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
1.8	227	Total, Increased to minimum Tc = 5.0 min			

### Subcatchment E1: On Site

Hydrograph





**Summary for Subcatchment E2: Daniel Street**

Runoff = 0.37 cfs @ 12.07 hrs, Volume= 0.029 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
4,330	98	Paved roads w/curbs & sewers, HSG B
4,330		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: Daniel Street**

Hydrograph



**Summary for Subcatchment E3: Penhallow Street**

Runoff = 0.14 cfs @ 12.07 hrs, Volume= 0.011 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
1,701	98	Paved roads w/curbs & sewers, HSG B
1,701		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E3: Penhallow Street**

Hydrograph





**Summary for Subcatchment E4: Penhallow Street**

Runoff = 0.07 cfs @ 12.07 hrs, Volume= 0.005 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
803	98	Paved roads w/curbs & sewers, HSG B
803		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E4: Penhallow Street**

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.856 ac, 81.13% Impervious, Inflow Depth = 2.85" for 2YR-Extreme event  
Inflow = 2.83 cfs @ 12.07 hrs, Volume= 0.203 af  
Primary = 2.83 cfs @ 12.07 hrs, Volume= 0.203 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System

Hydrograph





Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**SubcatchmentE1: On Site** Runoff Area=30,432 sf 76.89% Impervious Runoff Depth=4.56"  
Flow Length=227' Tc=5.0 min CN=91 Runoff=3.67 cfs 0.265 af

**SubcatchmentE2: Daniel Street** Runoff Area=4,330 sf 100.00% Impervious Runoff Depth=5.35"  
Tc=5.0 min CN=98 Runoff=0.56 cfs 0.044 af

**SubcatchmentE3: Penhallow Street** Runoff Area=1,701 sf 100.00% Impervious Runoff Depth=5.35"  
Tc=5.0 min CN=98 Runoff=0.22 cfs 0.017 af

**SubcatchmentE4: Penhallow Street** Runoff Area=803 sf 100.00% Impervious Runoff Depth=5.35"  
Tc=5.0 min CN=98 Runoff=0.10 cfs 0.008 af

**Link DP1: Penhallow Closed Drainage System** Inflow=4.56 cfs 0.335 af  
Primary=4.56 cfs 0.335 af

**Total Runoff Area = 0.856 ac Runoff Volume = 0.335 af Average Runoff Depth = 4.70"**  
**18.87% Pervious = 0.161 ac 81.13% Impervious = 0.694 ac**

**Summary for Subcatchment E1: On Site**

Runoff = 3.67 cfs @ 12.07 hrs, Volume= 0.265 af, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"


Area (sf)	CN	Description
3,398	98	Unconnected roofs, HSG B
20,002	98	Paved parking, HSG B
5,633	61	>75% Grass cover, Good, HSG B
1,399	85	Gravel roads, HSG B
30,432	91	Weighted Average
7,032		23.11% Pervious Area
23,400		76.89% Impervious Area
3,398		14.52% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.0	80	0.0179	1.27		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.26"
0.2	43	0.0306	3.55		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
0.3	62	0.0050	3.21	2.52	<b>Pipe Channel, RCP_Round 12"</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
0.3	42	0.0031	2.53	1.98	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
1.8	227	Total, Increased to minimum Tc = 5.0 min			



### Subcatchment E1: On Site

Hydrograph



**Summary for Subcatchment E2: Daniel Street**

Runoff = 0.56 cfs @ 12.07 hrs, Volume= 0.044 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
4,330	98	Paved roads w/curbs & sewers, HSG B
4,330		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: Daniel Street**

Hydrograph





**Summary for Subcatchment E3: Penhallow Street**

Runoff = 0.22 cfs @ 12.07 hrs, Volume= 0.017 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
1,701	98	Paved roads w/curbs & sewers, HSG B
1,701		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E3: Penhallow Street**

Hydrograph



**Summary for Subcatchment E4: Penhallow Street**

Runoff = 0.10 cfs @ 12.07 hrs, Volume= 0.008 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
803	98	Paved roads w/curbs & sewers, HSG B
803		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E4: Penhallow Street**

Hydrograph






### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.856 ac, 81.13% Impervious, Inflow Depth = 4.70" for 10YR-Extreme event  
Inflow = 4.56 cfs @ 12.07 hrs, Volume= 0.335 af  
Primary = 4.56 cfs @ 12.07 hrs, Volume= 0.335 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System

Hydrograph



Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment E1: On Site**

Runoff Area=30,432 sf 76.89% Impervious Runoff Depth=6.02"  
Flow Length=227' Tc=5.0 min CN=91 Runoff=4.78 cfs 0.350 af

**Subcatchment E2: Daniel Street**

Runoff Area=4,330 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=0.72 cfs 0.057 af

**Subcatchment E3: Penhallow Street**

Runoff Area=1,701 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=0.28 cfs 0.022 af

**Subcatchment E4: Penhallow Street**

Runoff Area=803 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=0.13 cfs 0.011 af

**Link DP1: Penhallow Closed Drainage System**

Inflow=5.90 cfs 0.440 af  
Primary=5.90 cfs 0.440 af

**Total Runoff Area = 0.856 ac Runoff Volume = 0.440 af Average Runoff Depth = 6.17"**  
**18.87% Pervious = 0.161 ac 81.13% Impervious = 0.694 ac**



**Summary for Subcatchment E1: On Site**

Runoff = 4.78 cfs @ 12.07 hrs, Volume= 0.350 af, Depth= 6.02"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
3,398	98	Unconnected roofs, HSG B
20,002	98	Paved parking, HSG B
5,633	61	>75% Grass cover, Good, HSG B
1,399	85	Gravel roads, HSG B
30,432	91	Weighted Average
7,032		23.11% Pervious Area
23,400		76.89% Impervious Area
3,398		14.52% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.0	80	0.0179	1.27		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.26"
0.2	43	0.0306	3.55		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
0.3	62	0.0050	3.21	2.52	<b>Pipe Channel, RCP_Round 12"</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
0.3	42	0.0031	2.53	1.98	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
1.8	227	Total, Increased to minimum Tc = 5.0 min			

### Subcatchment E1: On Site

Hydrograph





**Summary for Subcatchment E2: Daniel Street**

Runoff = 0.72 cfs @ 12.07 hrs, Volume= 0.057 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
4,330	98	Paved roads w/curbs & sewers, HSG B
4,330		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: Daniel Street**

Hydrograph



**Summary for Subcatchment E3: Penhallow Street**

Runoff = 0.28 cfs @ 12.07 hrs, Volume= 0.022 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
1,701	98	Paved roads w/curbs & sewers, HSG B
1,701		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E3: Penhallow Street**

Hydrograph





**Summary for Subcatchment E4: Penhallow Street**

Runoff = 0.13 cfs @ 12.07 hrs, Volume= 0.011 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
803	98	Paved roads w/curbs & sewers, HSG B
803		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E4: Penhallow Street**

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.856 ac, 81.13% Impervious, Inflow Depth = 6.17" for 25YR-Extreme event  
Inflow = 5.90 cfs @ 12.07 hrs, Volume= 0.440 af  
Primary = 5.90 cfs @ 12.07 hrs, Volume= 0.440 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System

Hydrograph





Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment E1: On Site**

Runoff Area=30,432 sf 76.89% Impervious Runoff Depth=7.40"  
Flow Length=227' Tc=5.0 min CN=91 Runoff=5.80 cfs 0.431 af

**Subcatchment E2: Daniel Street**

Runoff Area=4,330 sf 100.00% Impervious Runoff Depth=8.24"  
Tc=5.0 min CN=98 Runoff=0.86 cfs 0.068 af

**Subcatchment E3: Penhallow Street**

Runoff Area=1,701 sf 100.00% Impervious Runoff Depth=8.24"  
Tc=5.0 min CN=98 Runoff=0.34 cfs 0.027 af

**Subcatchment E4: Penhallow Street**

Runoff Area=803 sf 100.00% Impervious Runoff Depth=8.24"  
Tc=5.0 min CN=98 Runoff=0.16 cfs 0.013 af

**Link DP1: Penhallow Closed Drainage System**

Inflow=7.16 cfs 0.538 af  
Primary=7.16 cfs 0.538 af

**Total Runoff Area = 0.856 ac Runoff Volume = 0.538 af Average Runoff Depth = 7.55"**  
**18.87% Pervious = 0.161 ac 81.13% Impervious = 0.694 ac**

**Summary for Subcatchment E1: On Site**

Runoff = 5.80 cfs @ 12.07 hrs, Volume= 0.431 af, Depth= 7.40"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"


Area (sf)	CN	Description
3,398	98	Unconnected roofs, HSG B
20,002	98	Paved parking, HSG B
5,633	61	>75% Grass cover, Good, HSG B
1,399	85	Gravel roads, HSG B
30,432	91	Weighted Average
7,032		23.11% Pervious Area
23,400		76.89% Impervious Area
3,398		14.52% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
1.0	80	0.0179	1.27		<b>Sheet Flow,</b> Smooth surfaces n= 0.011 P2= 3.26"
0.2	43	0.0306	3.55		<b>Shallow Concentrated Flow,</b> Paved Kv= 20.3 fps
0.3	62	0.0050	3.21	2.52	<b>Pipe Channel, RCP_Round 12"</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
0.3	42	0.0031	2.53	1.98	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
1.8	227	Total, Increased to minimum Tc = 5.0 min			



### Subcatchment E1: On Site

Hydrograph



**Summary for Subcatchment E2: Daniel Street**

Runoff = 0.86 cfs @ 12.07 hrs, Volume= 0.068 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
4,330	98	Paved roads w/curbs & sewers, HSG B
4,330		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E2: Daniel Street**

Hydrograph



**Summary for Subcatchment E3: Penhallow Street**

Runoff = 0.34 cfs @ 12.07 hrs, Volume= 0.027 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
1,701	98	Paved roads w/curbs & sewers, HSG B
1,701		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment E3: Penhallow Street**

Hydrograph





Summary for Subcatchment E4: Penhallow Street

Runoff = 0.16 cfs @ 12.07 hrs, Volume= 0.013 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
803	98	Paved roads w/curbs & sewers, HSG B
803		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Subcatchment E4: Penhallow Street

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.856 ac, 81.13% Impervious, Inflow Depth = 7.55" for 50YR-Extreme event  
Inflow = 7.16 cfs @ 12.07 hrs, Volume= 0.538 af  
Primary = 7.16 cfs @ 12.07 hrs, Volume= 0.538 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs


### Link DP1: Penhallow Closed Drainage System

Hydrograph









**Routing Diagram for 3039-Post**  
 Prepared by Ambit Engineering, Inc., Printed 11/18/2019  
 HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

**Area Listing (selected nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.035	61	>75% Grass cover, Good, HSG B (P4)
0.350	98	Paved roads w/curbs & sewers, HSG B (P2, P3, P4)
0.471	98	Roofs, HSG B (P1, P4)
<b>0.855</b>	<b>96</b>	<b>TOTAL AREA</b>

**3039-Post**

Prepared by Ambit Engineering, Inc.

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Printed 11/18/2019

Page 3

**Soil Listing (selected nodes)**

Area (acres)	Soil Group	Subcatchment Numbers
0.000	HSG A	
0.855	HSG B	P1, P2, P3, P4
0.000	HSG C	
0.000	HSG D	
0.000	Other	
<b>0.855</b>		<b>TOTAL AREA</b>



**3039-Post**

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 4

**Ground Covers (selected nodes)**

HSG-A (acres)	HSG-B (acres)	HSG-C (acres)	HSG-D (acres)	Other (acres)	Total (acres)	Ground Cover	Subcatchment Numbers
0.000	0.035	0.000	0.000	0.000	0.035	>75% Grass cover, Good	P4
0.000	0.350	0.000	0.000	0.000	0.350	Paved roads w/curbs & sewers	P2, P3, P4
0.000	0.471	0.000	0.000	0.000	0.471	Roofs	P1, P4
<b>0.000</b>	<b>0.855</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.855</b>	<b>TOTAL AREA</b>	

**3039-Post**

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 5

**Pipe Listing (selected nodes)**

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	1P	23.80	21.75	150.0	0.0137	0.013	24.0	0.0	0.0

**3039-Post**

Type III 24-hr 2YR-Extreme Rainfall=3.68"

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 6

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**SubcatchmentP1: 60 Penhallow Roof** Runoff Area=17,104 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=1.46 cfs 0.113 af

**SubcatchmentP2: Daniel Street** Runoff Area=5,601 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=0.48 cfs 0.037 af

**SubcatchmentP3: Penhallow Street** Runoff Area=1,995 sf 100.00% Impervious Runoff Depth=3.45"  
Tc=5.0 min CN=98 Runoff=0.17 cfs 0.013 af

**SubcatchmentP4: Alley & Penhallow Street** Runoff Area=12,558 sf 87.97% Impervious Runoff Depth=3.01"  
Tc=5.0 min CN=94 Runoff=1.00 cfs 0.072 af

**Pond 1P:** Peak Elev=24.54' Inflow=2.46 cfs 0.185 af  
24.0" Round Culvert n=0.013 L=150.0' S=0.0137 '/' Outflow=2.46 cfs 0.185 af

**Link DP1: Penhallow Closed Drainage System** Inflow=3.11 cfs 0.235 af  
Primary=3.11 cfs 0.235 af

**Total Runoff Area = 0.855 ac Runoff Volume = 0.235 af Average Runoff Depth = 3.30"**  
**4.06% Pervious = 0.035 ac 95.94% Impervious = 0.821 ac**



**3039-Post**

Prepared by Ambit Engineering, Inc.  
HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Type III 24-hr 2YR-Extreme Rainfall=3.68"

Printed 11/18/2019

Page 7

**Summary for Subcatchment P1: 60 Penhallow Roof Drain**

Runoff = 1.46 cfs @ 12.07 hrs, Volume= 0.113 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
17,104	98	Roofs, HSG B
17,104		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1: 60 Penhallow Roof Drain**

Hydrograph



**Summary for Subcatchment P2: Daniel Street**

Runoff = 0.48 cfs @ 12.07 hrs, Volume= 0.037 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
5,601	98	Paved roads w/curbs & sewers, HSG B
5,601		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: Daniel Street**

Hydrograph



**Summary for Subcatchment P3: Penhallow Street**

Runoff = 0.17 cfs @ 12.07 hrs, Volume= 0.013 af, Depth= 3.45"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
1,995	98	Paved roads w/curbs & sewers, HSG B
1,995		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P3: Penhallow Street**

Hydrograph





**Summary for Subcatchment P4: Alley & Penhallow Street**


Runoff = 1.00 cfs @ 12.07 hrs, Volume= 0.072 af, Depth= 3.01"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 2YR-Extreme Rainfall=3.68"

Area (sf)	CN	Description
7,649	98	Paved roads w/curbs & sewers, HSG B
1,511	61	>75% Grass cover, Good, HSG B
3,398	98	Roofs, HSG B
12,558	94	Weighted Average
1,511		12.03% Pervious Area
11,047		87.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P4: Alley & Penhallow Street**



**Summary for Pond 1P:**

Inflow Area = 0.681 ac, 94.91% Impervious, Inflow Depth = 3.26" for 2YR-Extreme event  
 Inflow = 2.46 cfs @ 12.07 hrs, Volume= 0.185 af  
 Outflow = 2.46 cfs @ 12.07 hrs, Volume= 0.185 af, Atten= 0%, Lag= 0.0 min  
 Primary = 2.46 cfs @ 12.07 hrs, Volume= 0.185 af


Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs / 2  
 Peak Elev= 24.54' @ 12.07 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	23.80'	<b>24.0" Round Culvert</b> L= 150.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 23.80' / 21.75' S= 0.0137 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

Primary OutFlow Max=2.46 cfs @ 12.07 hrs HW=24.54' TW=0.00' (Dynamic Tailwater)  
 1=Culvert (Inlet Controls 2.46 cfs @ 2.32 fps)

**Pond 1P:**

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.855 ac, 95.94% Impervious, Inflow Depth = 3.30" for 2YR-Extreme event  
Inflow = 3.11 cfs @ 12.07 hrs, Volume= 0.235 af  
Primary = 3.11 cfs @ 12.07 hrs, Volume= 0.235 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System





**3039-Post**

Type III 24-hr 10YR-Extreme Rainfall=5.59"

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 13

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**SubcatchmentP1: 60 Penhallow Roof** Runoff Area=17,104 sf 100.00% Impervious Runoff Depth=5.35"  
 Tc=5.0 min CN=98 Runoff=2.23 cfs 0.175 af

**SubcatchmentP2: Daniel Street** Runoff Area=5,601 sf 100.00% Impervious Runoff Depth=5.35"  
 Tc=5.0 min CN=98 Runoff=0.73 cfs 0.057 af

**SubcatchmentP3: Penhallow Street** Runoff Area=1,995 sf 100.00% Impervious Runoff Depth=5.35"  
 Tc=5.0 min CN=98 Runoff=0.26 cfs 0.020 af

**SubcatchmentP4: Alley & Penhallow Street** Runoff Area=12,558 sf 87.97% Impervious Runoff Depth=4.89"  
 Tc=5.0 min CN=94 Runoff=1.58 cfs 0.117 af

**Pond 1P:** Peak Elev=24.74' Inflow=3.81 cfs 0.293 af  
 24.0" Round Culvert n=0.013 L=150.0' S=0.0137 '/' Outflow=3.81 cfs 0.293 af

**Link DP1: Penhallow Closed Drainage System** Inflow=4.80 cfs 0.370 af  
 Primary=4.80 cfs 0.370 af

**Total Runoff Area = 0.855 ac Runoff Volume = 0.370 af Average Runoff Depth = 5.20"**  
**4.06% Pervious = 0.035 ac 95.94% Impervious = 0.821 ac**

**Summary for Subcatchment P1: 60 Penhallow Roof Drain**

Runoff = 2.23 cfs @ 12.07 hrs, Volume= 0.175 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
17,104	98	Roofs, HSG B
17,104		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1: 60 Penhallow Roof Drain**

Hydrograph



**Summary for Subcatchment P2: Daniel Street**

Runoff = 0.73 cfs @ 12.07 hrs, Volume= 0.057 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
5,601	98	Paved roads w/curbs & sewers, HSG B
5,601		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: Daniel Street**

Hydrograph





### Summary for Subcatchment P3: Penhallow Street

Runoff = 0.26 cfs @ 12.07 hrs, Volume= 0.020 af, Depth= 5.35"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
1,995	98	Paved roads w/curbs & sewers, HSG B
1,995		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

### Subcatchment P3: Penhallow Street

Hydrograph



**Summary for Subcatchment P4: Alley & Penhallow Street**

Runoff = 1.58 cfs @ 12.07 hrs, Volume= 0.117 af, Depth= 4.89"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 10YR-Extreme Rainfall=5.59"

Area (sf)	CN	Description
7,649	98	Paved roads w/curbs & sewers, HSG B
1,511	61	>75% Grass cover, Good, HSG B
3,398	98	Roofs, HSG B
12,558	94	Weighted Average
1,511		12.03% Pervious Area
11,047		87.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P4: Alley & Penhallow Street**

Hydrograph



**Summary for Pond 1P:**

Inflow Area = 0.681 ac, 94.91% Impervious, Inflow Depth = 5.16" for 10YR-Extreme event  
 Inflow = 3.81 cfs @ 12.07 hrs, Volume= 0.293 af  
 Outflow = 3.81 cfs @ 12.07 hrs, Volume= 0.293 af, Atten= 0%, Lag= 0.0 min  
 Primary = 3.81 cfs @ 12.07 hrs, Volume= 0.293 af


Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs / 2  
 Peak Elev= 24.74' @ 12.07 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	23.80'	<b>24.0" Round Culvert</b> L= 150.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 23.80' / 21.75' S= 0.0137 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

Primary OutFlow Max=3.81 cfs @ 12.07 hrs HW=24.74' TW=0.00' (Dynamic Tailwater)  
 1=Culvert (Inlet Controls 3.81 cfs @ 2.61 fps)

**Pond 1P:**

Hydrograph






### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.855 ac, 95.94% Impervious, Inflow Depth = 5.20" for 10YR-Extreme event  
Inflow = 4.80 cfs @ 12.07 hrs, Volume= 0.370 af  
Primary = 4.80 cfs @ 12.07 hrs, Volume= 0.370 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System

Hydrograph



**3039-Post**

Type III 24-hr 25YR-Extreme Rainfall=7.08"

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 20

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Subcatchment P1: 60 Penhallow Roof** Runoff Area=17,104 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=2.83 cfs 0.224 af

**Subcatchment P2: Daniel Street** Runoff Area=5,601 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=0.93 cfs 0.073 af

**Subcatchment P3: Penhallow Street** Runoff Area=1,995 sf 100.00% Impervious Runoff Depth=6.84"  
Tc=5.0 min CN=98 Runoff=0.33 cfs 0.026 af

**Subcatchment P4: Alley & Penhallow Street** Runoff Area=12,558 sf 87.97% Impervious Runoff Depth=6.37"  
Tc=5.0 min CN=94 Runoff=2.03 cfs 0.153 af

**Pond 1P:** Peak Elev=24.88' Inflow=4.85 cfs 0.377 af  
24.0" Round Culvert n=0.013 L=150.0' S=0.0137 ' /' Outflow=4.85 cfs 0.377 af

**Link DP1: Penhallow Closed Drainage System** Inflow=6.11 cfs 0.476 af  
Primary=6.11 cfs 0.476 af

**Total Runoff Area = 0.855 ac Runoff Volume = 0.476 af Average Runoff Depth = 6.68"**  
**4.06% Pervious = 0.035 ac 95.94% Impervious = 0.821 ac**

**Summary for Subcatchment P1: 60 Penhallow Roof Drain**

Runoff = 2.83 cfs @ 12.07 hrs, Volume= 0.224 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
17,104	98	Roofs, HSG B
17,104		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1: 60 Penhallow Roof Drain**

Hydrograph





**Summary for Subcatchment P2: Daniel Street**

Runoff = 0.93 cfs @ 12.07 hrs, Volume= 0.073 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
5,601	98	Paved roads w/curbs & sewers, HSG B
5,601		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: Daniel Street**

Hydrograph



**Summary for Subcatchment P3: Penhallow Street**

Runoff = 0.33 cfs @ 12.07 hrs, Volume= 0.026 af, Depth= 6.84"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
1,995	98	Paved roads w/curbs & sewers, HSG B
1,995		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P3: Penhallow Street**

Hydrograph



**Summary for Subcatchment P4: Alley & Penhallow Street**


Runoff = 2.03 cfs @ 12.07 hrs, Volume= 0.153 af, Depth= 6.37"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 25YR-Extreme Rainfall=7.08"

Area (sf)	CN	Description
7,649	98	Paved roads w/curbs & sewers, HSG B
1,511	61	>75% Grass cover, Good, HSG B
3,398	98	Roofs, HSG B
12,558	94	Weighted Average
1,511		12.03% Pervious Area
11,047		87.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P4: Alley & Penhallow Street**





**Summary for Pond 1P:**

Inflow Area = 0.681 ac, 94.91% Impervious, Inflow Depth = 6.64" for 25YR-Extreme event  
 Inflow = 4.85 cfs @ 12.07 hrs, Volume= 0.377 af  
 Outflow = 4.85 cfs @ 12.07 hrs, Volume= 0.377 af, Atten= 0%, Lag= 0.0 min  
 Primary = 4.85 cfs @ 12.07 hrs, Volume= 0.377 af


Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs / 2  
 Peak Elev= 24.88' @ 12.07 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	23.80'	<b>24.0" Round Culvert</b> L= 150.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 23.80' / 21.75' S= 0.0137 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

**Primary OutFlow** Max=4.85 cfs @ 12.07 hrs HW=24.88' TW=0.00' (Dynamic Tailwater)  
 1=Culvert (Inlet Controls 4.85 cfs @ 2.80 fps)

**Pond 1P:**

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.855 ac, 95.94% Impervious, Inflow Depth = 6.68" for 25YR-Extreme event  
Inflow = 6.11 cfs @ 12.07 hrs, Volume= 0.476 af  
Primary = 6.11 cfs @ 12.07 hrs, Volume= 0.476 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System



**3039-Post**

Type III 24-hr 50YR-Extreme Rainfall=8.48"

Prepared by Ambit Engineering, Inc.

Printed 11/18/2019

HydroCAD® 10.00 s/n 00801 © 2013 HydroCAD Software Solutions LLC

Page 27

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points x 2  
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**SubcatchmentP1: 60 Penhallow Roof** Runoff Area=17,104 sf 100.00% Impervious Runoff Depth=8.24"  
 Tc=5.0 min CN=98 Runoff=3.39 cfs 0.270 af

**SubcatchmentP2: Daniel Street** Runoff Area=5,601 sf 100.00% Impervious Runoff Depth=8.24"  
 Tc=5.0 min CN=98 Runoff=1.11 cfs 0.088 af

**SubcatchmentP3: Penhallow Street** Runoff Area=1,995 sf 100.00% Impervious Runoff Depth=8.24"  
 Tc=5.0 min CN=98 Runoff=0.40 cfs 0.031 af

**SubcatchmentP4: Alley & Penhallow Street** Runoff Area=12,558 sf 87.97% Impervious Runoff Depth=7.76"  
 Tc=5.0 min CN=94 Runoff=2.45 cfs 0.186 af

**Pond 1P:** Peak Elev=25.00' Inflow=5.83 cfs 0.456 af  
 24.0" Round Culvert n=0.013 L=150.0' S=0.0137 '/' Outflow=5.83 cfs 0.456 af

**Link DP1: Penhallow Closed Drainage System** Inflow=7.34 cfs 0.576 af  
 Primary=7.34 cfs 0.576 af

**Total Runoff Area = 0.855 ac Runoff Volume = 0.576 af Average Runoff Depth = 8.08"**  
**4.06% Pervious = 0.035 ac 95.94% Impervious = 0.821 ac**



**Summary for Subcatchment P1: 60 Penhallow Roof Drain**

Runoff = 3.39 cfs @ 12.07 hrs, Volume= 0.270 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
17,104	98	Roofs, HSG B
17,104		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P1: 60 Penhallow Roof Drain**

Hydrograph



**Summary for Subcatchment P2: Daniel Street**

Runoff = 1.11 cfs @ 12.07 hrs, Volume= 0.088 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
5,601	98	Paved roads w/curbs & sewers, HSG B
5,601		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P2: Daniel Street**

Hydrograph



**Summary for Subcatchment P3: Penhallow Street**

Runoff = 0.40 cfs @ 12.07 hrs, Volume= 0.031 af, Depth= 8.24"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
1,995	98	Paved roads w/curbs & sewers, HSG B
1,995		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P3: Penhallow Street**

Hydrograph





**Summary for Subcatchment P4: Alley & Penhallow Street**

Runoff = 2.45 cfs @ 12.07 hrs, Volume= 0.186 af, Depth= 7.76"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Type III 24-hr 50YR-Extreme Rainfall=8.48"

Area (sf)	CN	Description
7,649	98	Paved roads w/curbs & sewers, HSG B
1,511	61	>75% Grass cover, Good, HSG B
3,398	98	Roofs, HSG B
12,558	94	Weighted Average
1,511		12.03% Pervious Area
11,047		87.97% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment P4: Alley & Penhallow Street**

Hydrograph



**Summary for Pond 1P:**

Inflow Area = 0.681 ac, 94.91% Impervious, Inflow Depth = 8.04" for 50YR-Extreme event  
 Inflow = 5.83 cfs @ 12.07 hrs, Volume= 0.456 af  
 Outflow = 5.83 cfs @ 12.07 hrs, Volume= 0.456 af, Atten= 0%, Lag= 0.0 min  
 Primary = 5.83 cfs @ 12.07 hrs, Volume= 0.456 af


Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs / 2  
 Peak Elev= 25.00' @ 12.07 hrs

Device	Routing	Invert	Outlet Devices
#1	Primary	23.80'	<b>24.0" Round Culvert</b> L= 150.0' CPP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 23.80' / 21.75' S= 0.0137 '/ Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 3.14 sf

**Primary OutFlow** Max=5.83 cfs @ 12.07 hrs HW=25.00' TW=0.00' (Dynamic Tailwater)  
 ↳1=Culvert (Inlet Controls 5.83 cfs @ 2.95 fps)

**Pond 1P:**

Hydrograph




### Summary for Link DP1: Penhallow Closed Drainage System

Inflow Area = 0.855 ac, 95.94% Impervious, Inflow Depth = 8.08" for 50YR-Extreme event  
Inflow = 7.34 cfs @ 12.07 hrs, Volume= 0.576 af  
Primary = 7.34 cfs @ 12.07 hrs, Volume= 0.576 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Link DP1: Penhallow Closed Drainage System

Hydrograph








**APPENDIX D**  
**SOIL SURVEY INFORMATION**





Soil Map—Rockingham County, New Hampshire















Soil Map may not be valid at this scale.

Map Scale: 1:699 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 19N WGS84

## MAP LEGEND

-  Area of Interest (AOI)
-  Area of Interest (AOI)
- Soils**
-  Soil Map Unit Polygons
-  Soil Map Unit Lines
-  Soil Map Unit Points
- Special Point Features**
-  Blowout
-  Borrow Pit
-  Clay Spot
-  Closed Depression
-  Gravel Pit
-  Gravelly Spot
-  Landfill
-  Lava Flow
-  Marsh or swamp
-  Mine or Quarry
-  Miscellaneous Water
-  Perennial Water
-  Rock Outcrop
-  Saline Spot
-  Sandy Spot
-  Severely Eroded Spot
-  Sinkhole
-  Slide or Slip
-  Sodic Spot
-  **Water Features**
-  Streams and Canals
- Transportation**
-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads
- Background**
-  Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

**Warning:** Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
 Web Soil Survey URL:  
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Rockingham County, New Hampshire  
 Survey Area Data: Version 21, Sep 16, 2019

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Dec 31, 2009—Sep 9, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
699	Urban land	1.3	100.0%
<b>Totals for Area of Interest</b>		<b>1.3</b>	<b>100.0%</b>





APPENDIX E  
INSPECTION & MAINTENANCE PLAN

## ***INSPECTION & MAINTENANCE PLAN***

*FOR*

**60 Penhallow Street**

**Portsmouth, NH**

### **Introduction**

The intent of this plan is to provide 60 Penhallow Street (herein referred to as “owner”) with a list of procedures that document the inspection and maintenance requirements of the stormwater management system for this development. Specifically, the filtration system and associated structures on the project site (collectively referred to as the “Stormwater Management System”).

The following inspection and maintenance program is necessary to keep the stormwater management system functioning properly. These measures will also help minimize potential environmental impacts. By following the enclosed procedures, the owner will be able to maintain the functional design of the stormwater management system and maximize its ability to remove sediment and other contaminants from site generated stormwater runoff.

### **Annual Report**

The owner shall prepare an annual Inspection & Maintenance Report. The report shall include a summary of the system’s maintenance and repair by transmission of the Inspection & Maintenance Log and other information as required. A copy of the report shall be delivered annually to the City of Portsmouth Code Enforcement Officer.

### ***Inspection & Maintenance Checklist/Log***

The following pages contain a Stormwater Management System Inspection & Maintenance Checklist and a blank copy of the Stormwater Management System Inspection & Maintenance Log. These forms are provided to the owner as a guideline for performing the inspection and maintenance of the Stormwater Management System. This is a guideline and should be periodically reviewed for conformance with current practice and standards.



## *STORMWATER MANAGEMENT SYSTEM COMPONENTS*

The Stormwater Management System is designed to mitigate both the quantity and quality of site-generated stormwater runoff. As a result, the design includes the following elements:

### **Non-Structural BMP's**

Non-Structural best management practices (BMP's) include temporary and permanent measures that typically require less labor and capital inputs and are intended to provide protection against erosion of soils. Examples of non-structural BMP's on this project include but are not limited to: temporary and permanent mulching, temporary and permanent grass cover, trees, shrubs and ground covers, miscellaneous landscape plantings, dust control, tree protection, topsoiling, sediment barriers, and a stabilized construction entrance.

### **Structural BMP's**

Structural BMP's are more labor and capital-intensive structures or installations that require more specialized personnel to install. Examples on this project include but are not limited to: storm drain catch basins, slot drains and pipes.

### **Inspection and Maintenance Requirements**

The following summarizes the inspection and maintenance requirements for the various BMP's that may be found on this project.

1. **Grassed areas:** After each rain event of 0.5" or more during a 24-hour period, inspect grassed areas for signs of disturbance, such as erosion. If damaged areas are discovered, immediately repair the damage. Repairs may include adding new topsoil, lime, seed, fertilizer and mulch.
2. **Plantings:** Planting and landscaping (trees, shrubs) shall be monitored bi-monthly during the first year to insure viability and vigorous growth. Replace dead or dying vegetation with new stock and adjust the conditions that caused the dead or dying vegetation. During dryer times of the year, provide weekly watering or irrigation during the establishment period of the first year. Make the necessary adjustments to ensure long-term health of the vegetated covers, i.e. provide more permanent mulch or compost or other means of protection.
3. **Storm Drain Catch Basins, Slot Drains and Pipes:** Monitor drain inlets and outlets where visible. Monitor slot drains for clogging and follow manufacturers recommendations for maintenance. Monitor sediment levels in catch basin sumps and remove as necessary.

### **Invasive Species**

Monitor Stormwater Management System for signs of invasive species growth. If caught earlier enough, their eradication is much easier. The most likely places where invasions start is in wetter, disturbed soils or detention ponds. Species such as phragmites and purple loose-strife are common invaders in these wetter areas. If they are found, then the owner shall contact a wetlands scientist with

experience in invasive species control to implement a plan of action to eradicate the invaders. Measures that do not require the application of chemical herbicides should be the first line of defense.

**Stormwater Management System**

***Inspection & Maintenance Checklist for Post Construction Condition—for 60 Penhallow Street, Portsmouth, NH***

<b>BMP/System Component</b>	<b>Minimum Inspection Frequency</b>	<b>Minimum Inspection Requirements</b>	<b>Maintenance/Cleanout Threshold</b>
<b>Closed Drainage System</b>			
Drainage Pipes	Yearly	<i>Check for sediment clogging, or soiled runoff.</i>	Clean entire drainage system and remove all sediments if discovered in piping.
Slot Drains	Bi-Annually	<i>Check for sediment clogging, or soiled runoff.</i>	Clean per manufacturers recommendations
Catch Basins	Bi-Annually	<i>Check for excessive accumulation of sediment in sump</i>	Remove sediment as necessary
<b>Annual Report</b>	Yearly	<i>Prepare Annual Report, including all Inspection &amp; Maintenance Logs. Provide to City (if required).</i>	N/A






**NOTES:**  
 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 107 AS LOT 27.  
 2) OWNER OF RECORD:  
 DAGNY TAGGART, LLC  
 30 PENHALLOW STREET, SUITE 300 EAST  
 PORTSMOUTH, NH 03801

**NOTES:**  
 1) THIS PLAN IS INTENDED FOR RUNOFF ANALYSIS ONLY AND SHALL NOT BE USED FOR CONSTRUCTION.  
 2) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.  
 3) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.  
 4) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION, (NHDES DECEMBER 2008).



**BRICK MARKET  
 60 PENHALLOW STREET  
 PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
0	ISSUED FOR APPROVAL	11/18/19



SCALE: 1" = 10'  
**PLAN OF EXISTING  
 SUBCATCHMENTS** **W1**


EXISTING	PROPOSED	DESCRIPTION
D	D	STORM DRAIN
X-X	X-X	SILT FENCE
100	100	CONTOUR
97x3	98x0	SPOT ELEVATION
---	---	EDGE OF PAVEMENT (EP)
---	---	SUBCATCHMENT LINE
6	600	SUBCATCHMENT NUMBER
1234	1234	AREA IN SQUARE FEET
WOODS	WOODS	DESCRIPTION OF COVER
6	600	POND (DESIGN MODEL)
6	600	REACH (DESIGN MODEL)
→	→	DRAINAGE VECTOR
---	---	EDGE OF WOODS / TREES
CB	CB	CATCH BASIN
DMH	DMH	DRAIN MANHOLE
W	W	WELL
EL	EL	ELEVATION
EP	EP	EDGE OF PAVEMENT
FF	FF	FINISHED FLOOR
INV	INV	INVERT
TBM	TBM	TEMPORARY BENCH MARK
TYP	TYP	TYPICAL
Tc	Tc	Tc PATH
HSC	HSC	HYDROLOGIC SOIL GROUP
SF	SF	SHEET FLOW
SCF	SCF	SHALLOW CONCENTRATED FLOW
CHANNEL	CHANNEL	CHANNEL FLOW






LEGEND

EXISTING	PROPOSED	DESCRIPTION
D	D	STORM DRAIN
X-X	X-X	SILT FENCE
100	100	CONTOUR
97x3	98x0	SPOT ELEVATION
		EDGE OF PAVEMENT (EP)
		SUBCATCHMENT LINE
6	600	SUBCATCHMENT NUMBER
1234	1234	AREA IN SQUARE FEET
WOODS	WOODS	DESCRIPTION OF COVER
6	600	POND (DESIGN MODEL)
6	600	REACH (DESIGN MODEL)
		DRAINAGE VECTOR
		EDGE OF WOODS / TREES
CB	CB	CATCH BASIN
DMH	DMH	DRAIN MANHOLE
W	W	WELL
EL	EL	ELEVATION
EP	EP	EDGE OF PAVEMENT
FF	FF	FINISHED FLOOR
INV	INV	INVERT
TBM	TBM	TEMPORARY BENCH MARK
TYP	TYP	TYPICAL
		Tc PATH
HSG	HSG	HYDROLOGIC SOIL GROUP
SF	SF	SHEET FLOW
SCF	SCF	SHALLOW CONCENTRATED FLOW
CHANNEL	CHANNEL	CHANNEL FLOW



2000  
MAGNETIC  
R.C.R.D. PLAN  
C-28714



**AMBIT ENGINEERING, INC.**  
Civil Engineers & Land Surveyors  
200 Griffin Road - Unit 3  
Portsmouth, N.H. 03801-7114  
Tel (603) 436-8282  
Fax (603) 436-2915

- NOTES:**
- 1) THIS PLAN IS INTENDED FOR RUNOFF ANALYSIS ONLY AND SHALL NOT BE USED FOR CONSTRUCTION.
  - 2) THE CONTRACTOR SHALL NOTIFY DIG SAFE AT 1-888-DIG-SAFE (1-888-344-7233) AT LEAST 72 HOURS PRIOR TO COMMENCING ANY EXCAVATION ON PUBLIC OR PRIVATE PROPERTY.
  - 3) UNDERGROUND UTILITY LOCATIONS ARE BASED UPON BEST AVAILABLE EVIDENCE AND ARE NOT FIELD VERIFIED. LOCATING AND PROTECTING ANY ABOVEGROUND OR UNDERGROUND UTILITIES IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND/OR THE OWNER. UTILITY CONFLICTS SHOULD BE REPORTED AT ONCE TO THE DESIGN ENGINEER.
  - 4) CONTRACTOR SHALL INSTALL AND MAINTAIN EROSION CONTROL MEASURES IN ACCORDANCE WITH THE "NEW HAMPSHIRE STORMWATER MANUAL, VOLUME 3, EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION. (NHDES DECEMBER 2008).

**BRICK MARKET  
60 PENHALLOW STREET  
PORTSMOUTH, N.H.**

NO.	DESCRIPTION	DATE
0	ISSUED FOR APPROVAL	11/18/19



SCALE: 1" = 10'  
**PLAN OF PROPOSED  
SUBCATCHMENTS**  
**W2**



January 3, 2020

MAX-2019184.00

Mr. Eric B. Eby, P.E.  
Department of Public Works  
City of Portsmouth  
680 Peverly Hill Road  
Portsmouth, New Hampshire 03801

SUBJECT: Updated Trip Generation Summary  
#60 Penhallow Street – Portsmouth, NH

Dear Mr. Eby:

**Greenman-Pedersen, Inc.** (GPI) is in the process of preparing a *Traffic Impact and Access Study (TIAS)* for a proposed mixed-use development, referred to as Brick Market, to located at #60 Penhallow Street in Portsmouth, New Hampshire. The existing site is currently a public 50-space parking lot with a single full-access / egress curb cut on Penhallow Street. The project consists of constructing a mixed-use development with a ±16,800 square foot (SF) of fast-food and fast-casual restaurant space on the first floor and ±41,600 SF of general office space on the second through fourth floors. The existing driveway will remain at Penhallow Street but be modified to provide garage access below street level. The site location in relation to the surrounding roadways is shown on the Project Location Map in Figure 1.

GPI and the Applicant met with representatives of the City of Portsmouth Planning Department on October 28, 2019 to review the scope of the TIAS. During this meeting, the Planning Department requested that the trip generation and distribution assumptions of the Project be provided to the City's Parking and Transportation Engineer for review prior to finalizing the TIAS. This information was provided to the City in a letter titled *Trip Generation Summary Letter*<sup>1</sup> on November 18, 2019. On December 3, 2019, GPI received comments from the City's Technical Advisory Committee (TAC) related to the *Trip Generation Summary Letter* regarding the distribution of office trips, missing numbers from some figures, and the critical time period for analysis. This letter is intended to provide an update to the previous trip generation and distribution assumptions to address the comments from TAC, as well as identify the scope of the full *Traffic Impact and Access Study (TIAS)*.

---

<sup>1</sup> *Trip Generation Summary Letter; #60 Penhallow Street – Portsmouth, NH; Greenman-Pedersen, Inc.; November 18, 2019.*






Figure 1  
Site Location Map



## **TRIP GENERATION**

The Project is proposed to consist of the construction of approximately 41,600 SF of office space and 16,800 SF of restaurant space. The restaurant space will be a food-court style restaurant, similar to Faneuil Hall in Boston, with a mix of fast-food and fast-casual dining options with shared seating. To estimate the volume of traffic to be generated by the proposed redevelopment, trip-generation rates published by the Institute of Transportation Engineers (ITE) *Trip Generation Manual*<sup>2</sup> were utilized for Land Use Code (LUC) 710 (General Office), LUC 930 (Fast Casual Restaurant), and LUC 933 (Fast-Food Restaurant without Drive-Through Window). Approximately half of the restaurant space was assumed to be fast-food style and half was assumed to be fast-casual style. The detailed trip generation calculations are provided as an Attachment and are summarized in Table 1.

### **Multi-Use Trips**

#### **Internal Capture**

Studies have shown that for developments of mixed-use or multi-use sites, it is realistic to assume that there will be some multi-use trips within the site itself. For example, someone working in the office spaces may dine at one of the restaurants on-site. Therefore, a reduction in the overall trips experienced at the site driveway can be anticipated as a result of multi-use trips that include stops at more than one use on the site. Based on information published in ITE's *Trip Generation Handbook*<sup>3</sup>, it is estimated that multi-use trips account for 2 to 10 percent of the trips generated by the site. The Multi-Use Development Trip Generation and Internal Capture Worksheets are provided in the Attachments.

#### **External Capture**

The proposed development is located within the downtown central business district of Portsmouth, in close proximity to numerous other retail, restaurant, office, residential, entertainment, hotel, and commercial uses. While many of the office trips generated by the project will be new to the area, a large portion of the restaurant trips will be shared with other retail, office, residential, and other uses within the downtown area. It is anticipated that patrons will park at a single location either within one of the public parking garages or within on-street parking spaces and visit multiple uses within the downtown, stopping at one of the restaurants as part of their trip. In addition, employees of surrounding area businesses, residents of downtown, or patrons of area hotels may choose to dine at one of the on-site restaurants. These patrons would likely walk to the site from other locations and would not be new to the area. GPI utilized the Multi-Use Development Trip Generation and Internal Capture worksheets contained within ITE's *Trip Generation Handbook* to estimate the potential number of trips that could be shared between the proposed restaurants and the surround area businesses, hotels, and residences. Based on this information, 45 to 75 percent of restaurant trips are anticipated to be shared with other downtown uses.

### **Pass-by Trips**

Studies have shown that for restaurant developments, a substantial portion of the site-generated vehicle trips are already present in the adjacent passing stream of traffic or are diverted from another route to the proposed site. For example, some vehicles which are already on the roadways may decide to visit the site on their way to another destination. Based on information published in the ITE *Trip Generation Handbook*, the average *pass-by* trip percentage is 43 to 50 percent for fast-food and high-turnover sit-down restaurants. Due to the location of the proposed restaurants in the downtown business district, it is likely that pass-by trips will arrive to the site

---

<sup>2</sup> *Trip Generation, 10<sup>th</sup> Edition*. Institute of Transportation Engineers; Washington, DC; 2017.

<sup>3</sup> *Trip Generation Handbook, 3<sup>rd</sup> Edition*. Institute of Transportation Engineers; Washington, DC; September 2017.



in the form of walking trips from patrons parking at another location downtown and visiting multiple stops before returning to their vehicle. For example, an area employee may stop at the restaurants to purchase dinner before leaving the downtown in their vehicle, or a person shopping in the downtown area may stop at the restaurant to grab lunch while shopping. Therefore, any pass-by trips generated by the proposed restaurant have been accounted for within the *external capture multi-use trips* described above.

### **Walking and Bicycling Trips**

As previously noted, the proposed development is located within downtown Portsmouth in close proximity to multiple retail, restaurant, office, and commercial developments. In addition, a strong sidewalk network on the surrounding area roadways provides pedestrian connections between the site and these establishments. The City of Portsmouth has also made concerted efforts to provide bicycle accommodations throughout the downtown including dedicated bicycle lanes, shared lanes, and bicycle parking. As described in the *Multi-Use Trips – External Capture* section of this letter, approximately 45 to 75 percent of the restaurant trips are anticipated to be shared with surrounding area businesses and residences, and will travel to the site via walking or bicycling. In addition, based on U.S. Census Bureau information on means of travel for residence of Portsmouth, approximately 7.7 percent of Portsmouth residents travel to work via walking or biking. To provide a conservative (worse case) analysis scenario, 5 percent of the office trips were assumed to travel to/from the site via walking or bicycle.

### **Transit Trips**

The Cooperative Alliance for Seacoast Transportation (COAST) and the University of New Hampshire (UNH) Wildcat Transit provide bus service along Congress Street / Daniel Street, Hanover Street, and Maplewood Avenue in the vicinity of the site. Based on U.S. Census Bureau data for residence of Portsmouth, approximately 1.4 percent of Portsmouth residents utilize public transit services to travel to/from work. It should be noted that this percentage includes also Portsmouth residents traveling to all places of employment, most of which may be located outside of the City. The percentage of residents using public transit to travel to places of employment within the City is likely to be much higher. To provide a conservative (worse case) analysis condition, no credit was applied for trips traveling to the site via public transportation.

The detailed trip generation and mode split calculations are provided in the Attachments. Table 1 provides a summary of the resulting site-generated trips.

**Table 1**  
**TRIP-GENERATION SUMMARY**

Time Period / Direction	External Trips		Walking / Biking Trips		New Primary Trips		
	Office Trips <sup>a</sup>	Restaurant Trips <sup>b</sup>	Office Trips <sup>c</sup>	Restaurant Trips <sup>d</sup>	Office Trips <sup>e</sup>	Restaurant Trips <sup>f</sup>	Total Trips <sup>g</sup>
<b>Weekday Daily</b>	377	5,479	19	3,534	358	1,945	2,303
<b>Weekday AM Peak Hour</b>							
<i>In</i>	49	132	2	131	47	1	48
<i>Out</i>	<u>3</u>	<u>82</u>	<u>0</u>	<u>40</u>	<u>3</u>	<u>42</u>	<u>45</u>
<i>Total</i>	52	214	2	171	50	43	93
<b>Weekday PM Peak Hour</b>							
<i>In</i>	6	182	0	96	6	86	92
<i>Out</i>	<u>39</u>	<u>171</u>	<u>2</u>	<u>131</u>	<u>37</u>	<u>40</u>	<u>77</u>
<i>Total</i>	45	353	2	227	43	126	169
<b>Saturday Daily</b>	80	8,510	4	4,846	76	3,664	3,740
<b>Saturday Midday Peak Hour</b>							
<i>In</i>	7	380	0	204	7	176	183
<i>Out</i>	<u>8</u>	<u>358</u>	<u>0</u>	<u>130</u>	<u>8</u>	<u>228</u>	<u>236</u>
<i>Total</i>	15	738	0	334	15	404	419

<sup>a</sup> Based on ITE LUC 710 (General Office) for ±41,600 SF.

<sup>b</sup> Based on sum of ITE LUC 930 (Fast Casual Restaurant) for ±8,400 SF and ITE LUC 933 (Fast-Food Restaurant without Drive-Through) for ±8,400 SF.

<sup>c</sup> Five percent of office trips based on U.S. Census data.

<sup>d</sup> Trips based on mixed-use percentages to retail, residential, hotel, and entertainment uses.

<sup>e</sup> General office external trips minus walking / biking trips.

<sup>f</sup> Restaurant external trips minus walking / biking trips.

<sup>g</sup> New Primary Office Trips plus New Primary Restaurant Trips.

## TRIP DISTRIBUTION

Having estimated project-generated vehicle trips, the next step is to determine the distribution of project traffic and assign these trips to the local roadway network. The *Trip Generation Summary Letter* assumed that a portion of the office trips coming from the Memorial Bridge would utilize Sheafe Street to access the on-site parking garage. The TAC noted that Sheafe Street is a narrow, residential street, and that use of Sheafe Street was not desirable. The Applicant agreed to place a condition in the office lease(s) that employees must be directed not to utilize Sheafe Street to access the parking garage. As a result, these site-generated trips were reassigned to utilize Church Street to State Street to access Penhallow Street. The updated trip distribution and site-generated trip networks are provided as an Attachment to this letter.

### Office Trips

The distribution of site-generated office trips was based on a Journey-to-Work model using U.S. Census Data for the place of residency of employees of Portsmouth, which was prepared as part of the Traffic Impact Study for the proposed McIntyre Building Federal property redevelopment project by Tighe & Bond. As part of the #60 Penhallow Street project, 77 parking spaces will be provided on-site within an underground garage to accommodate the proposed office use. Therefore, the trip distribution prepared as part of the McIntyre Building study was slightly modified to account for vehicles traveling directly to/from the on-site parking garage. The resulting trip distribution is graphically depicted in Figure 2 and summarized in Table 2 below.

### Restaurant Trips

Similarly, the McIntyre Building redevelopment includes a retail / restaurant component and is located in close proximity to the #60 Penhallow Street site. Therefore, the trip distribution assumptions used for the McIntyre project were utilized to distribute restaurant trips for the #60 Penhallow Street project. As previously noted in the *Trip Generation* section of this letter, the majority of restaurant trips are likely to be shared with other uses in the downtown area and will travel to/from the site via walking. However, the portion of *new primary* trips traveling to the proposed restaurants will likely park in nearby parking garages and walk to the site. The Hanover Garage and Portwalk Garage provide a large amount of parking at relatively low costs and are in close proximity to the site. Therefore, all of the *new primary* restaurant trips were assumed to travel to one of these two garages on Hanover Street. The resulting trip distribution is graphically depicted in Figure 3 and summarized in Table 2 below.

**Table 2**  
**TRIP DISTRIBUTION SUMMARY**

Direction	Office Distribution (%)	Restaurant Distribution (%)
Middle Street to/from South	5	25
Market Street to/from North	20	15
Maplewood Avenue to/from North	60	30
Memorial Bridge to/from East	10	20
<u>Islington Street to/from West</u>	<u>5</u>	<u>10</u>
Total	100	100



The site-generated trips were distributed to the study area intersections based on the percentages in Table 2 above. The resulting site-generated trips are illustrated in Figures 4A, 4B, and 4C for the weekday AM, weekday PM, and Saturday midday peak hours, respectfully.

### DETERMINATION OF CRITICAL PEAK HOUR

During the October 28, 2019 scoping meeting, the City’s Planning Department requested that the TIAS include an analysis of the Project-related traffic impacts during the weekday PM peak period, as this time period had previously been determined to be the critical time period for traffic volumes within the downtown area. On December 3, 2019, the TAC noted that based on the findings of the *Trip Generation Summary Letter*, the Project is anticipated to generate the highest volume of traffic during the Saturday midday peak period. The TAC requested that GPI provide a traffic volume comparison to assess whether the weekday PM or Saturday midday peak period would be the critical period for analysis based on Build traffic volumes with the proposed development in place.

GPI obtained existing traffic volumes from two sources, New Hampshire Department of Transportation (NHDOT) count station data provided on the Transportation Data Management System, and manual turning movement counts collected at several downtown intersections provided by the City’s Department of Public Works (DPW). GPI then added the projected site-generated trips through each of these count locations during the weekday PM and Saturday midday peak hours to estimate the Build traffic volumes. The Build volumes for the weekday PM and Saturday midday peak hours were compared to assess which was higher and establish an overall critical time period for analysis. The detailed calculations are provided as an Attachment to this letter and the results are summarized in Tables 3 and 4 below.

**Table 3**  
**TRAFFIC VOLUME COMPARISON – NHDOT COUNT STATION DATA**

Location	Existing Volume		Site-Generated Trips		Build Volume	
	Weekday PM	Saturday Midday	Weekday PM	Saturday Midday	Weekday PM	Saturday Midday
Maplewood Avenue	987	865	60	127	<b>1,047</b>	992
Market Street	1,036	875	32	64	<b>1,068</b>	939
Memorial Bridge	1,232	1,202	26	69	1,258	<b>1,271</b>
Islington Street	841	753	15	39	<b>856</b>	792
Middle Road	957	992	32	100	989	<b>1,092</b>
Congress Street	548	506	27	21	<b>575</b>	527
<b>Total Network</b>	<b>5,601</b>	<b>5,193</b>	<b>192</b>	<b>420</b>	<b>5,793</b>	<b>5,613</b>

Four out of six of the NHDOT count stations indicate that the weekday PM peak hour will be the critical time period for analysis under Build conditions. The Existing weekday PM peak hour volumes are higher than Saturday volumes at five of the six locations. For the two locations where the Saturday volumes are higher (both on Route 1), the weekday PM peak hour volumes are within one (1) to nine (9) percent of the Saturday midday volumes. When considering the overall network (sum of all count station data), the weekday PM peak hour volumes are approximately three (3) percent higher than the Saturday midday volumes.

**Table 4**  
**TRAFFIC VOLUME COMPARISON – CITY’S TMC DATA**

Location	Existing Volume		Site-Generated Trips		Build Volume	
	Weekday PM	Saturday Midday	Weekday PM	Saturday Midday	Weekday PM	Saturday Midday
Maplewood Ave / Congress St / Islington St / Middle St	1,442	1,387	66	146	1,508	<b>1,533</b>
Maplewood Ave / Deer St	1,611	1,165	60	127	<b>1,671</b>	1,292
Maplewood Ave / Hanover St	1,371	1,255	99	243	1,470	<b>1,498</b>
State St / Middle St	1,158	1,077	36	104	<b>1,194</b>	1,181
<b>Total Network</b>	<b>5,582</b>	<b>4,884</b>	<b>261</b>	<b>620</b>	<b>5,843</b>	<b>5,504</b>

Based on the TMC data that the City collected in Fall 2019, the existing volumes are higher during the weekday PM peak hour for all four study area intersections. However, based on the total (Build) trips, two of the intersections indicate the weekday PM peak hour is the critical time period and two indicate that the Saturday midday is the critical time period. For those where the Saturday volumes are higher, the weekday PM volumes are within two (2) percent of the Saturday midday volumes. For the Maplewood Avenue / Deer Street intersection, the weekday PM volumes are 23 percent higher than the Saturday volumes. When considering the overall network (sum of all intersection data), the weekday PM peak hour volumes are approximately six (6) percent higher than the Saturday midday volumes.

It should be noted that the Saturday midday peak hour results in the critical time period at the Maplewood / Congress / Islington / Middle and the Maplewood / Hanover intersections mainly due to the assumption that all restaurant trips will park in the Hanover Street garage. In reality, some of these trips will park in on-street parking spaces along the surrounding roadways or in other parking areas. In addition, only a 45 percent walking/biking credit was applied to restaurant trips during the Saturday midday peak hour based on ITE data, while a 64 percent walking/biking credit was applied in the weekday PM condition. GPI anticipates that a significantly higher portion of restaurant trips will be walking/biking trips that are shared with other uses in the downtown during the Saturday midday time period, particularly during the warmer-weather months. Therefore, the Project’s impact on these intersections during the Saturday midday peak hour may be heavily over-stated in Table 4.

GPI submitted the data above to the City’s Parking and Transportation Engineer, Eric Eby, P.E., via email on December 9, 2019 and received confirmation on the same date that the weekday PM peak hour continues to be the critical peak period for analysis based on Build conditions traffic volumes. Therefore, the full TIAS will be prepared based on the weekday PM peak hour only for analysis purposes.

## STUDY AREA INTERSECTIONS

The City's Department of Public Works (DPW) has requested that the full TIAS evaluate the Project's impacts on any intersection that will experience an increase of 50 trips or more during the peak hour as a result of the Project. Based on this threshold, detailed capacity and queue analyses will be performed for the following intersections as part of the TIAS:

- Maplewood Avenue / Hanover Street
- Maplewood Avenue / Islington Street / Congress Street / Middle Street
- Middle Street / State Street
- Daniel Street / Chapel Street
- Daniel Street / Penhallow Street
- Market Street / Hanover Street

## SUMMARY

GPI has estimated the site-generated vehicle trips associated with the proposed redevelopment of #60 Penhallow Street as described in this letter. The site-generated trips were added to the existing traffic volumes at multiple locations within the downtown area to assess the critical time period for analysis, which was confirmed with the City's Parking and Traffic Engineer to be the weekday PM peak hour. This information was utilized to define the study area for detailed capacity and queue analyses to be included within a comprehensive Traffic Impact and Access Study (TIAS). The detailed site-generated traffic-volume networks have been submitted to the City's Consultant, Resource Systems Group, Inc. (RSG) to conduct the capacity and queue analysis. Once this information is received, the full TIAS will be prepared and submitted to the City for review.

Should you have any questions, or require additional information, please contact me at (978) 570-2946.

Sincerely,

**GREENMAN-PEDERSEN, INC.**




Rebecca L. Brown, P.E., PTOE  
Senior Project Manager

Enclosures:

Site-Generated Vehicle Trip Traffic-Volume Networks  
Trip Generation Calculations  
Mode Split Calculations  
Trip Distribution Calculations  
Critical Peak Hour Volume Comparison

cc: Mark McNabb – Dagny Taggart, LLC (via email)  
John Chagnon, P.E., LLS – Ambit Engineering (via email)






NOT TO SCALE

\*ASSUMED 10% TO UTILIZE DEER STREET

XX(X) = ENTERING(EXITING)


**Figure 2**  
**Office Vehicle Trip**  
**Distribution**



XX(XX) = ENTERING(EXITING)

NOT TO SCALE


**Figure 3**  
**Restaurant Vehicle Trip**  
**Distribution**



NOT TO SCALE


**Figure 4A**  
**Site-Generated Trips**  
**Weekday AM**





NOT TO SCALE

**Figure 4B**  
**Site-Generated Trips**  
**Weekday PM**



NOT TO SCALE

**Figure 4C**  
**Site-Generated Trips**  
**Saturday MIDDAY**

Size	Units	Land Use
41,600 SF		LUC 710
8,400 SF		LUC 933
8,400 SF		LUC 930

Walk/Bike Credit: 5%

		Total Trips				External Trips				Walking / Biking Trips				New Primary Trips			
		LUC 710	LUC 933	LUC 930	TOTAL	LUC 710	LUC 933	LUC 930	TOTAL	LUC 710	LUC 933	LUC 930	TOTAL	LUC 710	LUC 933	LUC 930	TOTAL
Weekday Daily	Entering	227	1,454	1,324	3,005	159	2,769	2,928	8	1,464	1,472	151	1,305	1,456			
	Exiting	227	1,454	1,324	3,005	218	2,710	2,928	11	2,070	2,081	207	640	847			
	Total	454	2,908	2,648	6,010	377	5,479	5,856	19	3,534	3,553	358	1,945	2,303			
Weekday AM Peak Hour	Entering	57	127	11	195	49	132	181	2	131	133	47	1	48			
	Exiting	9	84	6	99	3	82	85	0	40	40	3	42	45			
	Total	66	211	17	294	52	214	266	2	171	173	50	43	93			
Weekday PM Peak Hour	Entering	8	119	65	192	6	182	188	0	96	96	6	86	92			
	Exiting	41	119	54	214	39	171	210	2	131	133	37	40	77			
	Total	49	238	119	406	45	353	398	2	227	229	43	126	169			
Saturday Daily	Entering	46	2,923	1,338	4,307	36	4,259	4,295	2	2,683	2,685	34	1,576	1,610			
	Exiting	46	2,923	1,338	4,307	44	4,251	4,295	2	2,163	2,165	42	2,088	2,130			
	Total	92	5,846	2,676	8,614	80	8,510	8,590	4	4,846	4,850	76	3,664	3,740			
Saturday Midday Peak Hour	Entering	12	225	157	394	7	380	387	0	204	204	7	176	183			
	Exiting	10	234	129	373	8	358	366	0	130	130	8	228	236			
	Total	22	459	286	767	15	738	753	0	334	334	15	404	419			



***Institute of Transportation Engineers (ITE)***

**Land Use Code (LUC) 710 - General Office Building**

**General Urban/Suburban**

Average Vehicle Trips Ends vs: 1000 Sq. Feet Gross Floor Area  
Independent Variable (X): 41.600

**AVERAGE WEEKDAY DAILY**

$$\ln(T) = 0.97 \ln(X) + 2.50$$

$$\ln(T) = 0.97 \ln(41.600) + 2.50$$

$$\ln(T) = 6.12$$

$$T = 453.17$$

$$T = 454 \text{ vehicle trips}$$

with 50% ( 227 vpd) entering and 50% ( 227 vpd) exiting.

**WEEKDAY MORNING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$T = 0.94 * (X) + 26.49$$

$$T = 0.94 * 41.600 + 26.49$$

$$T = 65.59$$

$$T = 66 \text{ vehicle trips}$$

with 86% ( 57 vph) entering and 14% ( 9 vph) exiting.

**WEEKDAY EVENING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$\ln(T) = 0.95 \ln(X) + 0.36$$

$$\ln(T) = 0.95 \ln(41.600) + 0.36$$

$$\ln(T) = 3.90$$

$$T = 49.49$$

$$T = 49 \text{ vehicle trips}$$

with 16% ( 8 vph) entering and 84% ( 41 vph) exiting.

**SATURDAY DAILY**

$$T = 2.21 * (X)$$

$$T = 2.21 * 41.600$$

$$T = 91.94$$

$$T = 92 \text{ vehicle trips}$$

with 50% ( 46 vph) entering and 50% ( 46 vph) exiting.

**SATURDAY PEAK HOUR OF GENERATOR**

$$T = 0.53 * (X)$$

$$T = 0.53 * 41.600$$

$$T = 22.05$$

$$T = 22 \text{ vehicle trips}$$

with 54% ( 12 vph) entering and 46% ( 10 vph) exiting.

***Institute of Transportation Engineers (ITE)***

**Land Use Code (LUC) 933 - Fast-Food Restaurant without Drive-Through Window**

**General Urban/Suburban**

Average Vehicle Trips Ends vs: 1,000 Sq. Ft. Gross Floor Area

Independent Variable (X): 8.400

**AVERAGE WEEKDAY DAILY**

$$T = 346.23 * (X)$$

$$T = 346.23 * 8.400$$

$$T = 2908.33$$

T = 2,908 vehicle trips

with 50% ( 1,454 vpd) entering and 50% ( 1,454 vpd) exiting.

**WEEKDAY MORNING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$T = 25.10 * (X)$$

$$T = 25.1 * 8.400$$

$$T = 210.84$$

T = 211 vehicle trips

with 60% ( 127 vph) entering and 40% ( 84 vph) exiting.

**WEEKDAY EVENING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$T = 28.34 * (X)$$

$$T = 28.34 * 8.400$$

$$T = 238.06$$

T = 238 vehicle trips

with 50% ( 119 vph) entering and 50% ( 119 vph) exiting.

**SATURDAY DAILY**

$$T = 696.00 * (X)$$

$$T = 696.00 * 8.400$$

$$T = 5846.40$$

T = 5,846 vehicle trips

with 50% ( 2,923 vpd) entering and 50% ( 2,923 vpd) exiting.

**SATURDAY PEAK HOUR OF GENERATOR**

$$T = 54.60 * (X)$$

$$T = 54.60 * 8.400$$

$$T = 458.64$$

T = 459 vehicle trips

with 49% ( 225 vph) entering and 51% ( 234 vph) exiting.

***Institute of Transportation Engineers (ITE)***

**Land Use Code (LUC) 930 - Fast Casual Restaurant**

**General Urban/Suburban**

Average Vehicle Trips Ends vs: 1,000 Sq. Ft. Gross Floor Area

Independent Variable (X): 8.400

**AVERAGE WEEKDAY DAILY**

$$T = 315.17 * (X)$$

$$T = 315.17 * 8.400$$

$$T = 2647.43$$

T = 2,648 vehicle trips

with 50% ( 1,324 vpd) entering and 50% ( 1,324 vpd) exiting.

**WEEKDAY MORNING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$T = 2.07 * (X)$$

$$T = 2.07 * 8.400$$

$$T = 17.39$$

T = 17 vehicle trips

with 67% ( 11 vph) entering and 33% ( 6 vph) exiting.

**WEEKDAY EVENING PEAK HOUR OF ADJACENT STREET TRAFFIC**

$$T = 14.13 * (X)$$

$$T = 14.13 * 8.400$$

$$T = 118.69$$

T = 119 vehicle trips

with 55% ( 65 vph) entering and 45% ( 54 vph) exiting.

**SATURDAY DAILY**

$$T = 318.62 * (X)$$

$$T = 318.62 * 8.400$$

$$T = 2676.41$$

T = 2,676 vehicle trips

with 50% ( 1,338 vpd) entering and 50% ( 1,338 vpd) exiting.

**SATURDAY PEAK HOUR OF GENERATOR**

$$T = 34.02 * (X)$$

$$T = 34.02 * 8.400$$


$$T = 285.77$$

T = 286 vehicle trips

with 55% ( 157 vph) entering and 45% ( 129 vph) exiting.




**MULTI-USE DEVELOPMENT  
 TRIP GENERATION  
 AND INTERNAL CAPTURE SUMMARY**



	Enter	Exit	Total	Single-Use Trip Gen Est.
Section 1	0	0	0	0
Section 2	0	0	0	0
Section 3	2,769	2,710	5,479	5,556
Section 4	0	0	0	0
Section 5	0	0	0	0
Section 6	159	218	377	454
<b>TOTAL</b>	<b>2,928</b>	<b>2,928</b>	<b>5,856</b>	<b>6,010</b>
				<b>3%</b>

Based on Weekday PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.  
 Based on an average of Weekday AM or PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.


**MULTI-USE DEVELOPMENT  
TRIP GENERATION  
AND INTERNAL CAPTURE SUMMARY**



	Enter	Exit	Total	Single-Use Trip Gen Est.	Internal Capture
Section 1	0	0	0	0	
Section 2	0	0	0	0	
Section 3	132	82	214	228	
Section 4	0	0	0	0	
Section 5	0	0	0	0	
Section 6	49	3	52	66	
<b>TOTAL</b>	<b>181</b>	<b>85</b>	<b>266</b>	<b>294</b>	<b>10%</b>

Based on ITE Trip Generation Handbook, 3rd Edition, August 2014.

**MULTI-USE DEVELOPMENT  
 TRIP GENERATION  
 AND INTERNAL CAPTURE SUMMARY**




	Enter	Exit	Total	Single-Use Trip Gen Est.	Internal Capture
Section 1	0	0	0	0	
Section 2	0	0	0	0	
Section 3	182	171	353	357	
Section 4	0	0	0	0	
Section 5	0	0	0	0	
Section 6	6	39	45	49	
<b>TOTAL</b>	<b>188</b>	<b>210</b>	<b>398</b>	<b>406</b>	<b>2%</b>

Based on ITE Trip Generation Handbook, 3rd Edition, August 2014.




**MULTI-USE DEVELOPMENT  
TRIP GENERATION  
AND INTERNAL CAPTURE SUMMARY**



	Enter	Exit	Total	Single-Use Trip Gen Est.
Section 1	0	0	0	0
Section 2	0	0	0	0
Section 3	4259	4251	8510	8522
Section 4	0	0	0	0
Section 5	0	0	0	0
Section 6	36	44	80	92
<b>TOTAL</b>	<b>4295</b>	<b>4295</b>	<b>8590</b>	<b>8614</b>
				<b>0%</b> Internal Capture

Based on most conservative of Weekday AM or PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.  
Based on an average of Weekday AM or PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.  
Based on ITE Trip Generation Handbook, 2nd Edition, June 2004.

**MULTI-USE DEVELOPMENT  
 TRIP GENERATION  
 AND INTERNAL CAPTURE SUMMARY**



	Enter	Exit	Total	Single-Use Trip Gen Est.
Section 1	0	0	0	0
Section 2	0	0	0	0
Section 3	380	358	738	745
Section 4	0	0	0	0
Section 5	0	0	0	0
Section 6	7	8	15	22
<b>TOTAL</b>	<b>387</b>	<b>366</b>	<b>753</b>	<b>767</b>

Internal Capture: 2%

Based on most conservative of Weekday AM or PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.  
 Based on an average of Weekday AM or PM from ITE Trip Generation Handbook, 3rd Edition, August 2014.  
 Based on ITE Trip Generation Handbook, 2nd Edition, June 2004.

ARIZON  
NEW MEXICO

OKLAHOMA

ARKANSAS

TENNESSEE

NORTH CAROLINA

SOUTH CAROLINA

B08101

## MEANS OF TRANSPORTATION TO WORK BY AGE

Universe: Workers 16 years and over

2013-2017 American Community Survey 5-Year Estimates

Supporting documentation on code lists, subject definitions, data accuracy, and statistical testing can be found on the American Community Survey website in the Technical Documentation section.

Sample size and data quality measures (including coverage rates, allocation rates, and response rates) can be found on the American Community Survey website in the Methodology section.

Although the American Community Survey (ACS) produces population, demographic and housing unit estimates, it is the Census Bureau's Population Estimates Program that produces and disseminates the official estimates of the population for the nation, states, counties, cities, and towns and estimates of housing units for states and counties.

	Portsmouth city, New Hampshire	
	Estimate	Margin of Error
Total:	12,584	+/-398
16 to 19 years	381	+/-161
20 to 24 years	1,265	+/-251
25 to 44 years	6,084	+/-431
45 to 54 years	2,327	+/-249
55 to 59 years	1,096	+/-198
60 to 64 years	714	+/-168
65 years and over	717	+/-141
Car, truck, or van - drove alone:	9,564	+/-465
16 to 19 years	145	+/-68
20 to 24 years	981	+/-267
25 to 44 years	4,631	+/-414
45 to 54 years	1,859	+/-245
55 to 59 years	838	+/-187
60 to 64 years	512	+/-120
65 years and over	598	+/-131
Car, truck, or van - carpooled:	896	+/-235
16 to 19 years	132	+/-106
20 to 24 years	54	+/-37
25 to 44 years	475	+/-173
45 to 54 years	97	+/-63
55 to 59 years	84	+/-58
60 to 64 years	54	+/-44
65 years and over	0	+/-21
Public transportation (excluding taxicab):	180	+/-79
16 to 19 years	0	+/-21
20 to 24 years	57	+/-47
25 to 44 years	71	+/-58
45 to 54 years	21	+/-24
55 to 59 years	15	+/-15
60 to 64 years	16	+/-17
65 years and over	0	+/-21
Walked:	761	+/-240
16 to 19 years	79	+/-86



	Portsmouth city, New Hampshire	
	Estimate	Margin of Error
20 to 24 years	131	+/-88
25 to 44 years	376	+/-154
45 to 54 years	70	+/-60
55 to 59 years	27	+/-22
60 to 64 years	57	+/-58
65 years and over	21	+/-24
Taxicab, motorcycle, bicycle, or other means:	210	+/-90
16 to 19 years	6	+/-11
20 to 24 years	0	+/-21
25 to 44 years	134	+/-74
45 to 54 years	55	+/-39
55 to 59 years	0	+/-21
60 to 64 years	15	+/-16
65 years and over	0	+/-21
Worked at home:	973	+/-225
16 to 19 years	19	+/-45
20 to 24 years	42	+/-58
25 to 44 years	397	+/-115
45 to 54 years	225	+/-70
55 to 59 years	132	+/-63
60 to 64 years	60	+/-46
65 years and over	98	+/-64

Data are based on a sample and are subject to sampling variability. The degree of uncertainty for an estimate arising from sampling variability is represented through the use of a margin of error. The value shown here is the 90 percent margin of error. The margin of error can be interpreted roughly as providing a 90 percent probability that the interval defined by the estimate minus the margin of error and the estimate plus the margin of error (the lower and upper confidence bounds) contains the true value. In addition to sampling variability, the ACS estimates are subject to nonsampling error (for a discussion of nonsampling variability, see Accuracy of the Data). The effect of nonsampling error is not represented in these tables.

Workers include members of the Armed Forces and civilians who were at work last week.


While the 2013-2017 American Community Survey (ACS) data generally reflect the February 2013 Office of Management and Budget (OMB) definitions of metropolitan and micropolitan statistical areas; in certain instances the names, codes, and boundaries of the principal cities shown in ACS tables may differ from the OMB definitions due to differences in the effective dates of the geographic entities.

Estimates of urban and rural populations, housing units, and characteristics reflect boundaries of urban areas defined based on Census 2010 data. As a result, data for urban and rural areas from the ACS do not necessarily reflect the results of ongoing urbanization.

Source: U.S. Census Bureau, 2013-2017 American Community Survey 5-Year Estimates


#### Explanation of Symbols:


1. An '\*\*\*' entry in the margin of error column indicates that either no sample observations or too few sample observations were available to compute a standard error and thus the margin of error. A statistical test is not appropriate.
2. An '-' entry in the estimate column indicates that either no sample observations or too few sample observations were available to compute an estimate, or a ratio of medians cannot be calculated because one or both of the median estimates falls in the lowest interval or upper interval of an open-ended distribution.
3. An '-' following a median estimate means the median falls in the lowest interval of an open-ended distribution.
4. An '+' following a median estimate means the median falls in the upper interval of an open-ended distribution.
5. An '\*\*\*\*' entry in the margin of error column indicates that the median falls in the lowest interval or upper interval of an open-ended distribution. A statistical test is not appropriate.
6. An '\*\*\*\*\*' entry in the margin of error column indicates that the estimate is controlled. A statistical test for sampling variability is not appropriate.
7. An 'N' entry in the estimate and margin of error columns indicates that data for this geographic area cannot be displayed because the number of sample cases is too small.
8. An '(X)' means that the estimate is not applicable or not available.



**Legend**


- (S) Traffic Signal
- XX Entering Traffic
- (XX) Exiting Traffic

Portsmouth, NH	
McIntyre Building Federal Property Redevelopment	
Retail Trip Distribution	
DATE 10/17/2019	 <a href="http://www.tighebond.com">www.tighebond.com</a>
FIGURE 3	



**Legend**

- (S) Traffic Signal
- XX Entering Traffic
- (XX) Exiting Traffic

Portsmouth, NH	
McIntyre Building Federal Property Redevelopment	
Office Trip Distribution	
DATE 10/17/2019	 <a href="http://www.tighebond.com">www.tighebond.com</a>
FIGURE 5	



## Critical Peak Hour Traffic Volume Comparison - Weekday PM versus Saturday Midday

Based on NHDOT Count Station Data

Location ID	Location	Date	Volume		Site Gen Trips		Sum		% Difference	
			PM	SAT	PM	SAT	PM	SAT	PM	SAT
82379035	Maplewood Avenue east of Raynes Avenue	11/3/2011	987		60		1047		5%	
		11/5/2011		865		127		992		-6%
82379081	Market Street west of Hanover Street	7/14/2011	1036		32		1068		12%	
		7/16/2011		875		64		939		-14%
82379079	US 1 (Memorial Bridge) at Maine State Line	4/27/2017	1232		26		1258		-1%	
		4/29/2017		1202		69		1271		1%
82379044	Islington Street east of Summer Street	8/30/2012	841		15		856		7%	
		8/25/2012		753		39		792		-8%
82379076	US 1 (Middle Road) north of Richards Avenue)	7/28/2011	957		32		989		-10%	
		7/30/2011		992		100		1092		9%
82379084	Congress Street east of Mapplewood Avenue	7/21/2011	548		27		575		8%	
		7/23/2011		506		21		527		-9%
<b>TOTAL NETWORK VOLUME</b>			<b>5601</b>		<b>192</b>		<b>5793</b>		<b>3%</b>	
				<b>5193</b>		<b>420</b>		<b>5613</b>		<b>-3%</b>

**Critical Peak Hour Volume Comparison - Weekday PM versus Saturday Midday**  
**Based on City of Portsmouth TMC Data**

Location ID	Location	Date	Existing Volume		Site Gen Trips		Build Trips		Difference		% Difference	
			PM	SAT	PM	SAT	PM	SAT	PM	SAT	PM	SAT
695168	Maplewood Avenue / Congress Street / Islington Street / Middle Street	9/13/2019	1442		66		1508		-25		-2%	
		9/14/2019		1387		146		1533		25		2%
693453	Maplewood Avenue / Deer Street	9/10/2019	1611		60		1671		379		23%	
		9/7/2019		1165		127		1292		-379		-29%
698419	Maplewood Avenue / Hanover Street	9/10/2019	1371		99		1470		-28		-2%	
		9/21/2019		1255		243		1498		28		2%
82379044	State Street / Middle Street	9/12/2019	1158		36		1194		13		1%	
		9/14/2019		1077		104		1181		-13		-1%
<b>TOTAL NETWORK VOLUME</b>			<b>5582</b>		<b>261</b>		<b>5843</b>		<b>339</b>		<b>6%</b>	
				<b>4884</b>		<b>620</b>		<b>5504</b>		<b>-339</b>		<b>-6%</b>