

C0960-011
March 22, 2021

Ms. Barbara McMillan, Chair
City of Portsmouth Conservation Commission
1 Junkins Avenue
Portsmouth, New Hampshire 03801

**Re: Wetland Conditional Use Permit Application
Proposed Mixed Use Development, 53 Green Street, Portsmouth, NH**

Dear Barbara:

On behalf of Stone Creek Realty, LLC (owner), and CPI Management, LLC (applicant), we are pleased to submit ten (10) sets of hard copies and one (1) set of digital copies (.pdf) of the following information to support a request for a Wetland Conditional Use Permit for the above referenced project:

- One (1) full size and nine (9) half size copies of the Site Plan Set, dated March 22, 2021;
- Drainage Analysis, dated March 22, 2021;
- Wetland and Buffer Report, dated January 6, 2020;
- Wetland Buffer Impervious Surface Exhibit, dated March 22, 2021;
- Aerial Site Plan, dated March 22, 2021;
- Community Space Exhibit, dated March 22, 2021;
- Truck Turning Exhibit, dated March 22, 2021;
- Existing Buffer Photograph Log, dated January 27, 2021;
- Wetland CUP Application fee check in the amount of \$1,000.00

The applicant is pleased to provide the enclosed information which has been prepared in response to comments and feedback received from the Planning Board, Technical Advisory Committee (TAC), Conservation Commission during the work session and conceptual consultation process.

PROJECT SUMMARY

Existing Conditions

The proposed project is located at 53 Green Street on property identified as Map 119 Lot 2 on the City of Portsmouth Tax Maps. The existing 1.66-acre parcel is bound by Green Street to south, the AC Hotel to the west, North Mill Pond to the north and the railroad to the east. The property includes 315+/- linear feet of tidal wetlands and buffers along the North Mill Pond. The limited functions and values of these areas are described in the enclosed Wetland and Buffer Report and shown on the Existing Buffer Photograph Log.

The existing lot contains a L-shaped commercial building that is located within the southwestern portion of the project area and extends towards the center of the property. This building houses several businesses. Several small and discontinuous disturbed forested areas lie to the west of this existing building and along the railroad track to the east, and a small discontinuous disturbed shrub thicket exists within the northernmost portion of the property, near the on-site utility tower. The majority of the eastern portion of the property is paved parking.



The property in question includes a portion of the City of Portsmouth's long planned improvements to the shoreline of the North Mill Pond, the concept of which has been a focus of the City's planning for years. It was included in the Portsmouth Bicycle and Pedestrian Plan in 2014 and the North End Vision Plan in 2015. Many of the stated goals set forth in the City's Master Plan in 2016 called for its creation. The Final Report on the North Mill Pond Greenway and Community Park was issued in 2019.

The Final Plan calls for *"a linear greenway and community park along the North Mill Pond which will create a new north-south pedestrian and bicycle connection from Bartlett Street to Market Street. This multi-use public path with civic amenities is envisioned to be constructed along the southeast shoreline of the pond, will include wetland restoration and pond edge stabilization and is anticipated and constructed through a series of public-private partnerships with private landowners."*

The City's Zoning Ordinance was amended in 2016 to create an overlay district specifically allowing the construction of taller buildings in the area as incentive for real estate developers to join in these important public private partnerships.

Proposed Redevelopment

The proposed project will include the construction of a 5-story mixed-use residential building that includes basement level parking, first floor residential lobby, commercial space and parking, and 48 upper floor residential units. The project includes associated site improvements that consist of a paved access driveway, pedestrian access, utilities, lighting, landscaping and stormwater management systems that provide treatment for runoff.

The existing condition of the development property does not provide any stormwater treatment. The proposed development will provide stormwater management improvements which are described in further detail in the enclosed Drainage Analysis. The following is a summary:

- Proposed treatment to runoff from the new buildings and paved access driveway will be provided via a stormwater treatment unit. In addition, a lined and under drained underground chamber system with an isolator row has been incorporated into the design to mitigate temperature of the runoff from the paved access driveway area. An additional benefit of the underground chamber system is that it will also reduce peak rates of runoff to the North Mill Pond even though peak rate reduction is not required for direct discharges to tidal waters.
- Stormwater treatment measures have been implemented where the greenway connection area connects to the North Mill Pond greenway trail. Yard drains will capture runoff and put them route through the treatment unit.
- A porous asphalt design has been incorporated into the stormwater design for North Mill Pond greenway trail at the direction of City staff.

Open Space & Buffer Enhancement

The project is located in the North End incentive overlay district. The applicant will be providing 15,494 SF community spaces, which will include 10,532 SF of Greenway Community Space located between the North Mill Pond mean high water line and the 50-foot wetland buffer setback. Providing this community space will contribute towards the City realizing a goal of the Master Plan to create public access along the North Mill Pond with a multi-use trail. This Community Space is 20% of the development parcel meeting the requirement of the Zoning Ordinance to receive the incentive bonus for one additional story (10 ft) above the maximum height requirement. The community space calculation is depicted in the enclosed Community Space Exhibit. Overall, the project will be providing 35% open space on the development lot where only 5% is required by zoning.



Proposed work within the 100-foot Tidal Buffer and subject to conditional use approval includes demolition and construction activities. The 100-foot tidal buffer within the development area includes impervious parking surface, walkways and building and a large maintained lawn area.

The project will provide an overall improvement by reducing the impervious cover within the 100-foot tidal buffer. The impervious surface impacts from the design are shown in Table 1. In addition to the summary in Table 1 below, detailed calculations of the impervious surfaces within the buffer for the existing and proposed condition are depicted in the enclosed Wetland Buffer Impervious Surface Exhibit.

The projects landscape plan proposes to replace existing maintained lawn with low mow grass mix and plant native trees in an effort to enhance the previously disturbed wetlands buffer. The work done by the proposed project within the 25-foot buffer to North Mill Pond is limited to the construction of stormwater outlets.

Table 1. 53 Green Street, Wetland Buffer Impervious Surfaces

Buffer Segment	Existing Impervious (SF)	Final Impervious(SF)
0-25 feet	0	0
25-50 feet	745	98
50-100 feet	10,836	8,425
Total	11,581	8,523
Net Impervious Surface	-3,058	

Section 10.1017.24 of the Zoning Ordinance which indicates “Where feasible, the application shall include removal of impervious surfaces at least equal in area to the area of impervious surface impact. The intent of this provision is that the project will not result in a net loss of pervious surface within a jurisdictional wetland buffer.” As shown in Table 1, the proposed project exceeds this requirement by providing a 3,058 SF reduction in impervious surface.

Conditional Use Permit

Jurisdictional wetland areas, including 315+/- linear feet of tidal wetlands and buffers along the North Mill Pond, were identified by Leonard A. Lord, PhD, CSS, CWS, Senior Environmental Scientist at Tighe & Bond, Inc. on October 29 and December 2, 2019. The results of the tidal wetland and buffer review and the assessment of the wetlands functions and values on the proposed project site in the enclosed “Wetland and Buffer” Report dated January 6, 2020.

Conditional Use Permit Criteria

Based on the above described and enclosed materials, the following addresses how the proposed project warrants the granting of a Wetland Conditional Use Permit by satisfying the following six (6) criteria for approval in Section 10.1017.50 of the Zoning Ordinance:

(1) The land is reasonably suited to the use, activity or alteration.

The land is currently a previously disturbed site which consists of an office building and parking lot and is suited for enhancement. Section 10.5A41.10D of the Zoning Ordinance defines the CD5 district as consisting “of high density center with a mix



of building types and residential, retail and other commercial uses". The proposed project design is consistent with the descriptions of uses in these zoning districts. Additionally, the proposed project site consists of previously disturbed tidal buffer area which has historically been used as a commercial area. The proposed project will result in impervious surface reduction in the buffer, buffer enhancement, and will provide public access along North Mill Pond which is a goal of the City's Master Plan.

(2) There is no alternative location outside the wetland buffer that is feasible and reasonable for the proposed use, activity or alteration.

The placement of the proposed buildings and access driveway areas was done in a way to reduce the areas of impervious surface within the 100-foot tidal buffer, as well as to adhere to the required setbacks to the abutting railroad. The proposed project design reduces the impervious surface within the 100' buffer and proposes to replace existing maintained lawn with low mow grass mix and plant native trees.

(3) There will be no adverse impact on the wetland functional values of the site or surrounding properties;

There will be no adverse impact on the wetland functional values of the site as the existing condition is previously disturbed and consists of building, lawn, parking area and minor scrub at the water's edge. There is no real functional wetland buffer area on the project site. The proposed project designs site and landscape plans enhance the previously disturbed tidal buffer area given the existing condition and provide added value by creating public open space for recreation along the North Mill Pond..

(4) Alteration of the natural vegetative state or managed woodland will occur only to the extent necessary to achieve construction goals; and

The proposed project design proposes no alteration to any natural woodland or wetlands area. The area impacted consists of impervious surfaces and maintained lawn. Any temporary disturbances of the wetland buffer for construction of the stormwater outlet will be restored following construction.

(5) The proposal is the alternative with the least adverse impact to areas and environments under the jurisdiction of this Section.

The proposed project design would enhance the buffer, reduce overall impervious surface on the site and provide public access to the North Mill Pond which is a goal of the City's master plan. Impervious surfaces have been reduced with the use of underground parking. The proposed project will reduce the impervious area within the 100-foot tidal buffer.

(6) Any area within the vegetated buffer strip will be returned to a natural state to the extent feasible.

The proposed project design within the vegetated buffer strip is limited to construction of the stormwater outlet from the stormwater collection and treatment system. The existing property has no stormwater treatment measures. The proposed project will collect and treat the onsite impervious surfaces prior to discharging to North Mill Pond. Implementing these treatment measures will help improve the water quality in North Mill Pond. In order for this system to work, disturbances with the buffer strip are necessary. Areas temporarily disturbed for the construction of the outlet will be restored following construction. The landscape plan proposes replacing the existing lawn within the 25' foot wetland

buffer with a low mow grass mix, mown as required to keep the space open and avoid incursions of invasive species, and the addition of several native trees on the water side of the path.

Conclusion

We trust the above described and enclosed materials address the criteria to grant a Wetland Conditional Use Permit for the proposed project. The proposed project meets requirements of the Zoning Ordinance. The proposed project achieves the goals of City’s Master Plan to provide public access along the North Mill Pond with a Greenway Community Space and to provide buffer enhancement.

As shown in the enclosed information, the latest proposed plan will reduce impervious surface within the buffer area, improve stormwater management, enhance the North Mill Pond tidal wetland buffer and provide public benefit in the form of open space along the North Mill Pond.

We respectfully request to be placed on the Conservation Committee meeting agenda as a for April 14, 2021. If you have any questions or need any additional information, please contact Patrick Crimmins by phone at (603) 433-8818 or by email at pmcrimmins@tighebond.com.

Sincerely,
TIGHE & BOND, INC.



Patrick M. Crimmins, PE
Senior Project Manager





Neil A. Hansen, PE
Project Engineer

Copy: Stone Creek Realty, LLC (via E-mail)
CPI Management, LLC (via E-mail)




PROPOSED MIXED USE DEVELOPMENT

53 GREEN STREET
 PORTSMOUTH, NEW HAMPSHIRE
 JANUARY 27, 2021
 LAST REVISED: MARCH 22, 2021



LIST OF DRAWINGS		
SHEET NO.	SHEET TITLE	LAST REVISED
	COVER SHEET	3/22/2021
1 OF 2	EXISTING CONDITIONS PLAN	11/1/2019
2 OF 2	EXISTING CONDITIONS PLAN	11/1/2019
C-101	DEMOLITION PLAN	3/22/2021
C-102.1	SITE PLAN	3/22/2021
C-102.2	BASEMENT & UPPER FLOOR PLAN	3/22/2021
C-103	GRADING, DRAINAGE AND EROSION CONTROL PLAN	3/22/2021
C-104	UTILITIES PLAN	3/22/2021
C-201	WATER MAIN REPLACEMENT PLAN	3/22/2021
C-301	EASEMENT PLAN	3/22/2021
C-501	EROSION CONTROL NOTES AND DETAILS SHEET	3/22/2021
C-502	DETAILS SHEET	3/22/2021
C-503	DETAILS SHEET	3/22/2021
C-504	DETAILS SHEET	3/22/2021
C-505	DETAILS SHEET	3/22/2021
C-506	DETAILS SHEET	3/22/2021
C-507	DETAILS SHEET	3/22/2021
C-508	DETAILS SHEET	3/22/2021
L-1	LANDSCAPE PLAN	3/22/2021
L-2	LANDSCAPE RENDERING	3/22/2021
1 OF 1	PHOTOMETRIC PLAN	3/22/2021
1	BUILDING ELEVATION	3/22/2021



LOCATION MAP
 SCALE: 1" = 2,000'

PREPARED BY:
Tighe & Bond
 177 CORPORATE DRIVE
 PORTSMOUTH, NEW HAMPSHIRE 03801
 603-433-8818



APPLICANT:
 CPI MANAGEMENT, LLC
 100 SUMMER STREET, SUITE 1600
 BOSTON, MASSACHUSETTS 02110

OWNER:
 TAX MAP 119, LOT 12
 STONE CREEK REALTY, LLC
 C/O DOUGLAS PINCIARO
 PO BOX 121
 NEW CASTLE, NEW HAMPSHIRE 03854

SURVEYOR:
 DOUCET SURVEY, LLC
 192 KENT PLACE
 NEWMARKET, NEW HAMPSHIRE 30857

LIST OF PERMITS		
LOCAL	STATUS	DATE
SITE PLAN REVIEW PERMIT	PENDING	
LOT LINE REVISION PERMIT	PENDING	
CONDITIONAL USE PERMIT - WETLAND BUFFER	PENDING	
STATE		
NHDES - SHORELAND PERMIT	PENDING	
NHDES - SEWER CONNECTION PERMIT	PENDING	
NHDES - ALTERATION OF TERRAIN PERMIT	PENDING	
NHDES - WETLAND PERMIT	PENDING	

**TAC & CC SUBMISSION SET
 COMPLETE SET 22 SHEETS**



I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE (N.H.R.S.A. TITLE LXIV) AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN. I CERTIFY THAT THIS SURVEY AND PLAN WERE PREPARED BY ME OR BY THOSE UNDER MY DIRECT SUPERVISION AND FALLS UNDER THE URBAN SURVEY CLASSIFICATION OF THE NH CODE OF ADMINISTRATIVE RULES OF THE BOARD OF LICENSURE FOR LAND SURVEYORS. I CERTIFY THAT THIS SURVEY WAS MADE ON THE GROUND AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. RANDOM TRAVERSE SURVEY BY TOTAL STATION, WITH A PRECISION GREATER THAN 1:15,000.



LLS. #989
DATE

THE CERTIFICATIONS SHOWN HEREON ARE INTENDED TO MEET REGISTRY OF DEED REQUIREMENTS AND ARE NOT A CERTIFICATION TO TITLE OR OWNERSHIP OF PROPERTY SHOWN. OWNERS OF ADJOINING PROPERTIES ARE ACCORDING TO CURRENT TOWN ASSESSORS RECORDS.

SEE SHEET 2 FOR NOTES, REFERENCE PLANS & LOCUS

LINE	BEARING	DISTANCE
L1	S14°35'01"E	83.72'
L2	S12°28'29"W	29.13'
L3	S37°36'49"W	30.50'
L4	S52°42'58"E	18.50'
L5	S36°00'42"W	86.88'
L6	N36°56'03"E	6.50'
L7	N52°57'56"W	19.04'
L8	N51°03'57"W	34.83'
L9	N38°56'03"E	6.26'

- LEGEND**
- LOT LINE
 - - - APPROXIMATE ABUTTERS LOT LINE
 - STOCKADE FENCE
 - CHAIN LINK FENCE
 - OVERHEAD WIRE
 - SS SEWER LINE
 - SD DRAIN LINE
 - G GAS LINE
 - 100 MAJOR CONTOUR LINE
 - 98 MINOR CONTOUR LINE
 - MEAN HIGH WATER LINE
 - HIGH TIDE LINE
 - TREE LINE
 - SHRUB LINE
 - EDGE OF WETLAND
 - WETLAND AREA
 - CONCRETE
 - CRUSHED STONE
 - BRICK
 - UTILITY POLE
 - LIGHT POLE
 - LIGHT POLE W/ARM
 - SIGN
 - BOUND FOUND
 - IRON PIPE/ROD FOUND
 - FIRE HYDRANT
 - WATER GATE VALVE
 - WATER SHUTOFF VALVE
 - GAS GATE VALVE
 - PAD MOUNTED TRANSFORMER
 - ELECTRIC MANHOLE
 - SEWER MANHOLE
 - HAND HOLE
 - DECIDUOUS TREE
 - CONIFEROUS SHRUB
 - TYP. TYPICAL
 - BND. FND. BOUND FOUND
 - CONC. CONCRETE
 - FF FINISHED FLOOR ELEVATION
 - EP EDGE OF PAVEMENT
 - VGC VERTICAL GRANITE CURB
 - SWL SINGLE WHITE LINE
 - 5/8" REBAR W/D CAP TO BE SET



EXISTING CONDITIONS PLAN FOR TIGHE & BOND OF STONE CREEK REALTY LLC (TAX MAP 119, LOT 2) 53 GREEN STREET PORTSMOUTH, NEW HAMPSHIRE

NO.	DATE	DESCRIPTION	BY

DRAWN BY:	E.D.P.	DATE:	NOVEMBER 2019
CHECKED BY:	M.W.F.	DRAWING NO.:	4383F
JOB NO.:	4383	SHEET	1 OF 2

DOUCET SURVEY
 Serving Your Professional Surveying & Mapping Needs
 102 Kent Place, Newmarket, NH 03857 (603) 659-6560
 2 Commerce Drive (Suite 202) Bedford, NH 03110 (603) 614-4060
 10 Storer Street (Riverview Suite) Kennebunk, ME (207) 502-7005
<http://www.doucetsurvey.com>


FILE NAME: Y:\PROJECTS\MAINE\CONV\MAINE\119-10-16 (T) 119-10-16.dwg (119-10-16) LAYOUT NAME: 11901 PLAN (1) PLOTTED: Monday, December 16, 2018 10:31:11 PM

NOTES:

1. REFERENCE: TAX MAP 119, LOT 2
53 GREEN STREET
D.S.I. PROJECT NO. 4383
 2. TOTAL PARCEL AREA: 72,420 SQ. FT.± OR 1.66 AC.±
(AREA CALCULATED TO MEAN HIGH WATER)
(SEE NOTE #12)
 3. OWNER OF RECORD: STONE CREEK REALTY LLC
C/O DOUGLAS PINCIARO
PO BOX 121
NEW CASTLE, NH 03854
R.C.R.D. BOOK 3300, PAGE 329
 4. ZONE: CDS OVERLAY DISTRICTS
-DOWNTOWN OVERLAY DISTRICT
-HISTORIC DISTRICT
- ZONING DISTRICTS BASED ON THE CITY OF PORTSMOUTH ZONING MAP DATED 11/12/15 AS AVAILABLE ON THE CITY WEBSITE ON 11/18/19. SEE CITY OF PORTSMOUTH ZONING ORDINANCE ARTICLE 5A, SECTION 10.5440 FOR DIMENSIONAL REGULATIONS. THE LAND OWNER IS RESPONSIBLE FOR COMPLYING WITH ALL APPLICABLE MUNICIPAL, STATE AND FEDERAL REGULATIONS.
- THE SITE IS SUBJECT TO THE STATE OF NH SHORELAND WATER QUALITY PROTECTION ACT. SEE NHDES WEBSITE FOR SPECIFIC DIMENSIONAL REQUIREMENT.
5. FIELD SURVEY PERFORMED BY D.C.B. & K.J.L. DURING NOVEMBER 2019 USING A TRIMBLE S7 TOTAL STATION AND A TRIMBLE R8 SURVEY GRADE GPS WITH A TRIMBLE TSC3 DATA COLLECTOR AND A TRIMBLE DINI DIGITAL LEVEL. TRAVERSE ADJUSTMENT BASED ON LEAST SQUARE ANALYSIS.
 6. JURISDICTIONAL WETLANDS DELINEATED BY TIGHE & BOND, DURING OCTOBER 2019 IN ACCORDANCE WITH 1987 CORPS OF ENGINEERS WETLANDS DELINEATION MANUAL, TECHNICAL REPORT Y-87-1 AND THE INTERIM REGIONAL SUPPLEMENT TO THE CORPS OF ENGINEERS WETLAND DELINEATION MANUAL: NORTH CENTRAL AND NORTHEAST REGION (OCTOBER, 2009).
 7. VERTICAL DATUM IS BASED ON NGVD29 PER DISK B2 1923.
 8. HORIZONTAL DATUM BASED ON NEW HAMPSHIRE STATE PLANE(2800) NAD83(2011) DERIVED FROM REDUNDANT GPS OBSERVATIONS UTILIZING THE KEYNET GPS VRS NETWORK.
 9. PROPER FIELD PROCEDURES WERE FOLLOWED IN ORDER TO GENERATE CONTOURS AT 2' INTERVALS. ANY MODIFICATION OF THIS INTERVAL WILL DIMINISH THE INTEGRITY OF THE DATA AND DOUCET SURVEY, INC. WILL NOT BE RESPONSIBLE FOR ANY SUCH ALTERATION PERFORMED BY THE USER.
 10. UNDERGROUND UTILITIES SHOWN HEREON ARE BASED ON OBSERVABLE PHYSICAL EVIDENCE AND PAINT MARKS FOUND ON-SITE.
 11. THE ACCURACY OF MEASURED UTILITY INVERTS AND PIPE SIZES/TYPES IS SUBJECT TO NUMEROUS FIELD CONDITIONS, INCLUDING; THE ABILITY TO MAKE VISUAL OBSERVATIONS, DIRECT ACCESS TO THE VARIOUS ELEMENTS, MANHOLE CONFIGURATION, ETC.
 12. WATER BOUNDARIES ARE DYNAMIC IN NATURE AND ARE SUBJECT TO CHANGE DUE TO NATURAL CAUSES SUCH AS EROSION OR ACCRETION.
 13. MEAN HIGH WATER (EL. 3.0' NGVD1929) AND HIGHEST OBSERVABLE TIDE (EL. 4.3' NGVD1929) ELEVATIONS PER "MAPLEWOOD AVENUE CULVERT REPLACEMENT AND NORTH MILL POND RESTORATION, WATERFRONT/STRUCTURAL BASIS OF DESIGN, BY WATERFRONT ENGINEERS, LLC, DATED DECEMBER 30, 2009", PROVIDED BY TIGHE & BOND ON 11-30-15.
 14. THE INTENT OF THIS PLAN IS TO SHOW THE LOCATION OF BOUNDARIES IN ACCORDANCE WITH AND IN RELATION TO THE CURRENT LEGAL DESCRIPTION, AND IS NOT AN ATTEMPT TO DEFINE UNWRITTEN RIGHTS, DETERMINE THE EXTENT OF OWNERSHIP, OR DEFINE THE LIMITS OF TITLE.
 15. DUE TO THE COMPLEXITY OF RESEARCHING ROAD RECORDS AS A RESULT OF INCOMPLETE, UNORGANIZED, INCONCLUSIVE, OBLITERATED, OR LOST DOCUMENTS, THERE IS AN INHERENT UNCERTAINTY INVOLVED WHEN ATTEMPTING TO DETERMINE THE LOCATION AND WIDTH OF A ROADWAY RIGHT OF WAY. THE EXTENT OF GREEN STREET AS DEPICTED HEREON IS/ARE BASED ON RESEARCH CONDUCTED AT THE CITY OF PORTSMOUTH CITY HALL, THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS & THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.
 16. THE GEOMETRY SHOWN ON REFERENCE PLANS 1, 12 & 13 INDICATE A POSSIBLE DISCREPANCY IN TITLE TO THE HATCHED AREA SHOWN. A TITLE EXAMINATION IS REQUIRED TO CLEAR UP ANY ISSUES IN THIS AREA.
 17. TAX MAP 119 LOT 2 SHOWN HEREON IS SUBJECT TO AND/OR IN BENEFIT OF THE FOLLOWING EASEMENTS & COVENANTS.
 - A) SIGNAL FACILITIES EXCEPTIONS AND RESERVATIONS, SEE R.C.R.D. BOOK 1339, PAGE 298, (LOCATION UNKNOWN).
 - B) EASEMENT IN FAVOR OF WESTERN UNION TELEGRAPH COMPANY, SEE R.C.R.D. BOOK 1339, PAGE 298 (NO DIMENSIONS GIVEN).
 - C) ELECTRIC EASEMENT IN FAVOR OF NEW HAMPSHIRE ELECTRIC COMPANY, SEE R.C.R.D. BOOK 1339, PAGE 298 (NO DIMENSIONS GIVEN).
 - D) SEWER LINE EASEMENT IN FAVOR OF THE CITY OF PORTSMOUTH, SEE R.C.R.D. BOOK 1339, PAGE 298 (LOCATION UNKNOWN).
 - E) ADDITIONAL FIRE RESTRICTION, SEE R.C.R.D. BOOK 1339, PAGE 298.
 - F) POLE AND WIRE AGREEMENT, PER NOTE #9 ON REFERENCE PLAN #1. (RECORDED AGREEMENT NOT FOUND).
 - G) ACCESS RIGHTS, SEE R.C.R.D. BOOK 589, PAGE 206 (LOCATION UNKNOWN).
 - H) COMMON PASSAGEWAY, SEE R.C.R.D. PLAN 266 (PUBLIC RIGHTS UNKNOWN).
 18. ALL UNDERGROUND UTILITIES (ELECTRIC, GAS, TEL. WATER, SEWER DRAIN SERVICES) ARE SHOWN IN SCHEMATIC FASHION. THEIR LOCATIONS ARE NOT PRECISE OR NECESSARILY ACCURATE. NO WORK WHATSOEVER SHALL BE UNDERTAKEN USING THIS PLAN TO LOCATE THE ABOVE SERVICES. CONSULT WITH THE PROPER AUTHORITIES CONCERNED WITH THE SUBJECT SERVICE LOCATIONS FOR INFORMATION REGARDING SUCH. CALL DIG-SAFE AT 1-888-DIG-SAFE.

REFERENCE PLANS:

1. "STANDARD BOUNDARY SURVEY, TAX MAP 119 - LOT 2, LAND OF STONE CREEK REALTY", DATED MARCH 2016, BY AMBIT ENGINEERING, INC., NOT RECORDED.
2. "PLAN OF LAND, VAUGHAN AND GREEN STREETS, PORTSMOUTH, NH" DATED JULY 1955 BY JOHN W. DURGIN R.C.R.D. PLAN #02541.
3. "STANDARD BOUNDARY SURVEY, TAX MAP 123 - LOT 15 & TAX MAP 124 LOT 10" DATED JULY 2008, REVISED 4/25/13 BY AMBIT ENGINEERING, INC. R.C.R.D. PLAN #D-37722.
4. "EASEMENT PLAN, EGRESS EASEMENT TO 319 VAUGHAN STREET CENTER, LLC, TAX MAP 124, LOT 9 & TAX MAP 123, LOT 15, PROPERTY OF 299 VAUGHAN STREET, LLC C/O CATHARTES PRIVATE INVESTMENTS", BY AMBIT ENGINEERING, INC., DATED MARCH 2014, R.C.R.D. PLAN #D-38358.
5. "CONDOMINIUM SITE PLAN TAX MAP 124 LOT 14, 233 VAUGHAN STREET, A CONDOMINIUM FOR 233 VAUGHAN STREET, LLC", BY AMBIT ENGINEERING, INC., DATED NOVEMBER 2013, R.C.R.D. PLAN #D-39078.
6. "LOT LINE RELOCATION PLAN PROPERTY OF HARBORCORP. LLC & BOSTON & MAINE CORPORATION", BY AMES MSC, DATED MARCH 15, 2005, R.C.R.D. PLAN #D-32675.
7. "LAND AT 233 VAUGHAN STREET PORTSMOUTH, NH BOSTON & MAINE CORPORATION TO BLUE STAR PROPERTIES, LLC", BY JAMES VERRA & ASSOCIATES, INC., DATED 6/3/01, R.C.R.D. PLAN #D-29702.
8. "VAUGHAN STREET URBAN RENEWAL PROJECT N.H. R-10 PORTSMOUTH, NH, DISPOSITION MAP", BY ANDERSON-NICHOLS & CO., INC., DATED NOVEMBER 1969, R.C.R.D. PLAN D-2408
9. "PLAN OF LAND FOR SOLIMON NEGM", BY TOWN PLANNING & ENGINEERING ASSOCIATES, INC., DATED 3/28/79, R.C.R.D. PLAN #C-8575.
10. "VAUGHAN STREET URBAN RENEWAL PROJECT N.H. R-10 PORTSMOUTH, NH, DISPOSITION PLAN PARCEL 2", BY ANDERSON-NICHOLS & CO., INC., DATED OCTOBER 1973, R.C.R.D. PLAN D-4115.
11. "PLAN OF PROPERTY CORNER VAUGHAN AND GREEN STREETS", DATED FEBRUARY 1907, R.C.R.D. PLAN #306.
12. "LAND SHOWING LAND AND WHARFAGE OWNED BY SILAS PEIRCE AND CO. LTD.", BY A.C. HOYT SURVEYOR, DATED AUGUST 8, 1902, R.C.R.D. PLAN #266.
13. "PLAN OF LAND PORTSMOUTH, NH FOR GEORGE D. EMERSON CO., BY JOHN W. DURGIN, DATED APRIL 1952, ON FILE AT JAMES VERRA AND ASSOCIATES.
14. "PLAN OF LAND VAUGHAN AND GREEN STREETS PORTSMOUTH, NH FOR SAMUEL W. & SUMNER L. POORVU", BY JOHN W. DURGIN, DATED JANUARY 1956, ON FILE AT JAMES VERRA AND ASSOCIATES.
15. "PLAN OF PROPERTY IN PORTSMOUTH, NH OWNED BY R.I. SUGDEN", BY WM A. GROVER, DATED APRIL 15, 1919, ON FILE AT JAMES VERRA AND ASSOCIATES.
16. "LAND ON VAUGHAN STREET PORTSMOUTH, NH, ESTATE OF CARRIE HAM TO LAWRENCE V. REGAN" BY JOHN W. DURGIN, DATED AUGUST 6, 1937, ON FILE AT JAMES VERRA AND ASSOCIATES.
17. "LAND IN PORTSMOUTH, NH, BOSTON & MAINE RAILROAD TO GEORGE D. EMERSON COMPANY", DATED JUNE 1954, R.C.R.D. BOOK 1339, PAGE 305.
18. TRACK PLAN, R.C.R.D. BOOK 1345, PAGE 51.
19. "VAUGHAN STREET URBAN RENEWAL PROJECT N.H. R-10 PORTSMOUTH, NH, APPROVED AS SHOWING VAUGHAN STREET URBAN RENEWAL PROJECT BOUNDARIES AND AREA ONLY, CONDEMNATION MAP", BY ANDERSON-NICHOLS & CO., INC., DATED FEBRUARY 1971, R.C.R.D. PLAN 2425.
20. "SURVEY OF HARBORSIDE & HARBORPARK LAND IN PORTSMOUTH, NH", BY BRIGGS ASSOCIATES, INC., DATED AUGUST 13, 1985, REV. AUGUST 27, 1985, R.C.R.D. PLAN 14043.
21. "SUBDIVISION PLAN OF TAX MAP 123, LOT 15 FOR 299 VAUGHAN STREET, LLC", BY DOUCET SURVEY, INC., DATED MAY 19, 2017, R.C.R.D. PLAN D-40759.
22. "LICENSE, EASEMENT & LAND TRANSFER PLAN FOR VAUGHAN STREET, LLC AND VAUGHAN STREET HOTEL, LLC", BY DOUCET SURVEY, INC., DATED AUGUST 2017, R.C.R.D. PLAN D-40760.
23. "LOT MERGER PLAN FOR VAUGHAN STREET HOTEL, LLC", BY DOUCET SURVEY, INC., DATED SEPTEMBER 2017.
24. "STATION MAP - LANDS, BOSTON AND MAINE RAILROAD OPERATED BY THE BOSTON AND MAINE RAILROAD, STATION 2966+20 TO STATION 3019+0", DATED JUNE 30, 1914, ON FILE AT THE BOSTON AND MAINE CORPORATION.
25. "VAUGHAN STREET PROJECT, PROJECT NO. N.H. R-10, RIGHT OF WAY ADJUSTMENT", BY METCALF & EDDY, DATED MAY 5, 1966, R.C.R.D. PLAN D-2413.
26. "SKETCH OF RAILROAD CONVEYANCE, SEE R.C.R.D. BOOK 446, PAGE 164A.



Location Map (n.t.s.)

EXISTING CONDITIONS PLAN
FOR
TIGHE & BOND
OF
STONE CREEK REALTY LLC
(TAX MAP 119, LOT 2)
53 GREEN STREET
PORTSMOUTH, NEW HAMPSHIRE


NO.	DATE	DESCRIPTION	BY

DRAWN BY:	E.D.P.	DATE:	NOVEMBER 2019
CHECKED BY:	M.W.F.	DRAWING NO.	4383F
JOB NO.	4383	SHEET	2 OF 2



I CERTIFY THAT THIS SURVEY PLAT IS NOT A SUBDIVISION PURSUANT TO THIS TITLE (NHRSA TITLE LXIV) AND THAT THE LINES OF STREETS AND WAYS SHOWN ARE THOSE OF PUBLIC OR PRIVATE STREETS OR WAYS ALREADY ESTABLISHED AND THAT NO NEW WAYS ARE SHOWN. I CERTIFY THAT THIS SURVEY AND PLAN WERE PREPARED BY ME OR BY THOSE UNDER MY DIRECT SUPERVISION AND FALLS UNDER THE URBAN SURVEY CLASSIFICATION OF THE NH CODE OF ADMINISTRATIVE RULES OF THE BOARD OF LICENSURE FOR LAND SURVEYORS. I CERTIFY THAT THIS SURVEY WAS MADE ON THE GROUND AND IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. RANDOM TRAVERSE SURVEY BY TOTAL STATION, WITH A PRECISION GREATER THAN 1:15,000.

_____, L.L.S. #989
_____, DATE

THE CERTIFICATIONS SHOWN HEREON ARE INTENDED TO MEET REGISTRY OF DEED REQUIREMENTS AND ARE NOT A CERTIFICATION TO TITLE OR OWNERSHIP OF PROPERTY SHOWN. OWNERS OF ADJOINING PROPERTIES ARE ACCORDING TO CURRENT TOWN ASSESSORS RECORDS.



Serving Your Professional Surveying & Mapping Needs
102 Kent Place, Newmarket, NH 03857 (603) 659-6560
2 Commerce Drive (Suite 202) Bedford, NH 03110 (603) 614-4060
10 Storer Street (Riverview Suite) Kennebunk, ME (207) 502-7005
http://www.doucetsurvey.com



- DEMOLITION NOTES:**
1. THE LOCATIONS OF UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR THE ENGINEER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK.
 2. THE CONTRACTOR SHALL VERIFY LOCATION OF ALL EXISTING UTILITIES. CALL DIG SAFE AT LEAST 72 HOURS PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
 3. ALL MATERIALS SCHEDULED TO BE REMOVED SHALL BECOME THE PROPERTY OF THE CONTRACTOR UNLESS OTHERWISE SPECIFIED. THE CONTRACTOR SHALL DISPOSE OF ALL MATERIALS OFF-SITE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCES AND CODES.
 4. COORDINATE REMOVAL, RELOCATION, DISPOSAL OR SALVAGE OF UTILITIES WITH THE OWNER AND APPROPRIATE UTILITY COMPANY.
 5. ANY EXISTING WORK OR PROPERTY DAMAGED OR DISRUPTED BY CONSTRUCTION/DEMOLITION ACTIVITIES SHALL BE REPLACED OR REPAIRED TO MATCH ORIGINAL EXISTING CONDITIONS BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
 6. SAW CUT AND REMOVE PAVEMENT ONE (1) FOOT OFF PROPOSED EDGE OF PAVEMENT OR EXISTING CURB LINE IN ALL AREAS WHERE PAVEMENT TO BE REMOVED ABUTS EXISTING PAVEMENT OR CONCRETE TO REMAIN.
 7. IT IS THE CONTRACTOR'S RESPONSIBILITY TO FAMILIARIZE THEMSELVES WITH THE CONDITIONS OF ALL OF THE PERMIT APPROVALS.
 8. THE CONTRACTOR SHALL OBTAIN AND PAY FOR ADDITIONAL PERMITS, NOTICES AND FEES NECESSARY TO COMPLETE THE WORK AND ARRANGE FOR AND PAY FOR NECESSARY INSPECTIONS AND APPROVALS FROM THE AUTHORITIES HAVING JURISDICTION.
 9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEMOLITION AND OFF-SITE DISPOSAL OF MATERIALS REQUIRED TO COMPLETE THE WORK, EXCEPT FOR WORK NOTED TO BE COMPLETED BY OTHERS.
 10. UTILITIES SHALL BE TERMINATED AT THE MAIN LINE PER UTILITY COMPANY STANDARDS. THE CONTRACTOR SHALL REMOVE ALL ABANDONED UTILITIES LOCATED WITHIN THE LIMITS OF WORK. CONTRACTOR SHALL VERIFY ORIGIN OF ALL DRAINS AND UTILITIES PRIOR TO REMOVAL/TERMINATION TO DETERMINE IF DRAINS OR UTILITY IS ACTIVE, AND SERVICES ANY ON OR OFF-SITE STRUCTURE TO REMAIN. CONTRACTOR SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY SUCH UTILITY FOUND AND SHALL MAINTAIN THESE UTILITIES UNTIL PERMANENT SOLUTION IS IN PLACE.
 11. PAVEMENT REMOVAL LIMITS ARE SHOWN FOR CONTRACTOR'S CONVENIENCE. ADDITIONAL PAVEMENT REMOVAL MAY BE REQUIRED DEPENDING ON THE CONTRACTOR'S OPERATION. CONTRACTOR TO VERIFY FULL LIMITS OF PAVEMENT REMOVAL PRIOR TO BID.
 12. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL EXISTING STRUCTURES, CONCRETE PADS, UTILITIES AND PAVEMENT WITHIN THE WORK LIMITS SHOWN UNLESS SPECIFICALLY IDENTIFIED TO REMAIN. ITEMS TO BE REMOVED INCLUDE BUT ARE NOT LIMITED TO: CONCRETE, PAVEMENT, CURBS, LIGHTING, MANHOLES, CATCH BASINS, UNDER GROUND PIPING, POLES, STAIRS, SIGNS, FENCES, RAMPS, WALLS, BOLLARDS, BUILDING SLABS, FOUNDATION, TREES AND LANDSCAPING.
 13. COORDINATE ALL WORK WITHIN THE PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH.
 14. REMOVE TREES AND BRUSH AS REQUIRED FOR COMPLETION OF WORK. CONTRACTOR SHALL GRUB AND REMOVE ALL STUMPS WITHIN LIMITS OF WORK AND DISPOSE OF OFF SITE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.
 15. CONTRACTOR SHALL PROTECT ALL PROPERTY MONUMENTATION THROUGHOUT DEMOLITION AND CONSTRUCTION OPERATIONS. SHOULD ANY MONUMENTATION BE DISTURBED BY THE CONTRACTOR, THE CONTRACTOR SHALL EMPLOY A NEW HAMPSHIRE LICENSED SURVEYOR TO REPLACE DISTURBED MONUMENTS.
 16. PROVIDE INLET PROTECTION BARRIERS AT ALL CATCH BASINS/CURB INLETS WITHIN CONSTRUCTION LIMITS AS WELL AS CATCH BASINS/CURB INLETS THAT MAY RECEIVE RUNOFF FROM CONSTRUCTION ACTIVITIES. INLET PROTECTION BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT. INLET PROTECTION BARRIERS SHALL BE "HIGH FLOW SILT SACK" BY ACF ENVIRONMENTAL OR EQUAL. INSPECT BARRIERS WEEKLY AND AFTER EACH RAIN EVENT OF 0.25 INCHES OR GREATER. CONTRACTOR SHALL COMPLETE A MAINTENANCE INSPECTION REPORT AFTER EACH INSPECTION. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED OR SEDIMENT HAS ACCUMULATED TO 1/3 THE DESIGN DEPTH OF THE BARRIER.
 17. THE CONTRACTOR SHALL PHASE DEMOLITION AND CONSTRUCTION AS REQUIRED TO PROVIDE CONTINUOUS SERVICE TO EXISTING BUSINESSES AND HOMES THROUGHOUT THE CONSTRUCTION PERIOD. EXISTING BUSINESS AND HOME SERVICES INCLUDE, BUT ARE NOT LIMITED TO ELECTRICAL, COMMUNICATION, FIRE PROTECTION, DOMESTIC WATER AND SEWER SERVICES. TEMPORARY SERVICES, IF REQUIRED, SHALL COMPLY WITH ALL FEDERAL, STATE, LOCAL AND UTILITY COMPANY STANDARDS. CONTRACTOR SHALL PROVIDE DETAILED CONSTRUCTION SCHEDULE TO OWNER PRIOR TO ANY DEMOLITION/CONSTRUCTION ACTIVITIES.
 18. EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO THE START OF ANY CLEARING OR DEMOLITION ACTIVITIES.
 19. THE CONTRACTOR SHALL PAY ALL COSTS NECESSARY FOR TEMPORARY PARTITIONING, BARRICADING, FENCING, SECURITY AND SAFETY DEVICES REQUIRED FOR THE MAINTENANCE OF A CLEAN AND SAFE CONSTRUCTION SITE.
 20. SAW CUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL UTILITIES TO BE REMOVED AND PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN.

LEGEND

	APPROXIMATE LIMIT OF PROPOSED SAW CUT
	PROPERTY LINE
	PROPERTY LINE TO BE REMOVED
	LIMIT OF WORK
	PROPOSED SILT SOCK
	APPROXIMATE LIMIT OF PAVEMENT TO BE REMOVED
	LOCATION OF PROPOSED BUILDING
	BUILDING TO BE REMOVED
TBR	TO BE REMOVED
TYP	TYPICAL

Proposed Mixed Use Development

CPI Management, LLC


53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session


PROJECT NO: C0960-011
DATE: January 27, 2021
FILE: C0960-011_C-DSGN.DWG
DRAWN BY: AFS
CHECKED: NAH/PMC
APPROVED: BLM

DEMOLITION PLAN


SCALE: AS SHOWN



Last Saved: 3/19/2021
 Plotted On: Mar 22, 2021 10:18am By: ASelvar
 Tighe & Bond File: C:\Projects\C0960-011_53 Green St., Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-DSGN.dwg



- SITE NOTES:**
1. STRIPE PARKING AREAS AS SHOWN, INCLUDING PARKING SPACES, STOP BARS, ADA SYMBOLS, PAINTED ISLANDS, CROSS WALKS, ARROWS, LEGENDS AND CENTERLINES SHALL BE THERMOPLASTIC MATERIAL. THERMOPLASTIC MATERIAL SHALL MEET THE REQUIREMENTS OF AASHTO M249. (ALL MARKINGS EXCEPT CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING WHITE TRAFFIC PAINT. CENTERLINE AND MEDIAN ISLANDS TO BE CONSTRUCTED USING YELLOW TRAFFIC PAINT. ALL TRAFFIC PAINT SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F").
 2. ALL PAVEMENT MARKINGS AND SIGNS TO CONFORM TO "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", "STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS", AND THE AMERICANS WITH DISABILITIES ACT REQUIREMENTS, LATEST EDITIONS.
 3. SEE DETAILS FOR PARKING STALL MARKINGS, ADA SYMBOLS, SIGNS AND SIGN POSTS.
 4. CENTERLINES SHALL BE FOUR (4) INCH WIDE YELLOW LINES. STOP BARS SHALL BE EIGHTEEN (18) INCHES WIDE.
 5. PAINTED ISLANDS SHALL BE FOUR (4) INCH WIDE DIAGONAL LINES AT 3'-0" O.C. BORDERED BY FOUR (4) INCH WIDE LINES.
 6. THE CONTRACTOR SHALL EMPLOY A NEW HAMPSHIRE LICENSED LAND SURVEYOR TO DETERMINE ALL LINES AND GRADES.
 7. CLEAN AND COAT VERTICAL FACE OF EXISTING PAVEMENT AT SAW CUT LINE WITH RS-1 EMULSION IMMEDIATELY PRIOR TO PLACING NEW BITUMINOUS CONCRETE.
 8. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND CITY CODES & SPECIFICATIONS.
 9. COORDINATE ALL WORK WITHIN PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH.
 10. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILE) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR.
 11. SEE BUILDING DRAWINGS FOR ALL CONCRETE PADS & SIDEWALKS ADJACENT TO BUILDING.
 12. ALL WORK SHALL CONFORM TO THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS, STANDARD SPECIFICATIONS.
 13. CONTRACTOR TO PROVIDE BACKFILL AND COMPACTION AT CURB LINE AFTER CONCRETE FORMS FOR SIDEWALKS AND PADS HAVE BEEN STRIPPED. COORDINATE WITH BUILDING CONTRACTOR.
 14. COORDINATE ALL WORK ADJACENT TO BUILDING WITH BUILDING CONTRACTOR.
 15. ALL DIMENSIONS ARE TO THE FACE OF CURB UNLESS OTHERWISE NOTED.
 16. THE STREET LIGHTING TYPE TO BE DISTRICT STYLE FIXTURE AND POLE TO MATCH EXISTING LIGHTING ON GREEN STREET.
 17. ALL CONDITIONS ON THIS PLAN SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO THE REQUIREMENTS OF THE SITE PLAN REVIEW REGULATIONS.
 18. THE APPLICANT SHALL HAVE A SITE SURVEY CONDUCTED BY A RADIO COMMUNICATIONS CARRIER APPROVED BY THE CITY'S COMMUNICATIONS DIVISION. THE RADIO COMMUNICATIONS CARRIER MUST BE FAMILIAR AND CONVERSANT WITH THE POLICE AND RADIO CONFIGURATION. IF THE SITE SURVEY INDICATES IT IS NECESSARY TO INSTALL A SIGNAL REPEATER EITHER ON OR NEAR THE PROPOSED PROJECT, THOSE COSTS SHALL BE THE RESPONSIBILITY OF THE PROPERTY OWNER. THE OWNER SHALL COORDINATE WITH THE SUPERVISOR OF RADIO COMMUNICATIONS FOR THE CITY.
 19. ALL TREES PLANTED ARE TO BE INSTALLED UNDER THE SUPERVISION OF THE CITY OF PORTSMOUTH DPW USING STANDARD INSTALLATION METHODS.
 20. THE APPLICANT SHALL PREPARE A CONSTRUCTION MITIGATION AND MANAGEMENT PLAN (CMMP) FOR REVIEW AND APPROVAL BY THE CITY'S LEGAL AND PLANNING DEPARTMENTS.
 21. A TEMPORARY SUPPORT OF EXCAVATION (SOE) PLAN SHALL BE PREPARED BY THE APPLICANT'S CONTRACTOR TO CONFIRM ANY TEMPORARY ENCUMBRANCES OF THE CITY'S RIGHT-OF-WAY. IF LICENSES ARE REQUIRED FOR THE SOE, THE APPLICANT WILL BE REQUIRED TO OBTAIN THESE FROM THE CITY PRIOR TO CONSTRUCTION.
 22. ALL EXCESS SNOW SHALL BE HAULED OFF-SITE IN ACCORDANCE TO ALL LOCAL AND STATE LAWS. PROPOSED SNOW STAGING AREAS HAVE BEEN PROVIDED TO SHOW TEMPORARY SNOW STORAGE AREAS.



LEGEND

--- (dashed line)	PROPERTY LINE	[Pattern]	PROPOSED POROUS PAVEMENT
- - - (long dashed line)	PROPOSED PROPERTY LINE	[Pattern]	PROPOSED PAVEMENT
- · - · - (dash-dot line)	ABUTTER PROPERTY LINE	[Pattern]	PROPOSED GRASS PAVER FIRE LANE TYPICAL
- · - · - (dash-dot line)	PROPOSED EASEMENT	[Pattern]	PROPOSED CURB RADIUS
- · - · - (dash-dot line)	PROPOSED EDGE OF PAVEMENT	[Pattern]	PROPOSED VERTICAL GRANITE CURB
- · - · - (dash-dot line)	PROPOSED CURB	[Pattern]	PROPOSED SLOPED GRANITE CURB
[Pattern]	PROPOSED BUILDING	[Pattern]	TYP
[Pattern]	PROPOSED BRICK SIDEWALK	[Pattern]	VGC
[Pattern]	PROPOSED CONCRETE SIDEWALK	[Pattern]	SGC

SITE DATA:

LOCATION: TAX MAP 119, LOT 2
 OWNER: STONE CREEK REALTY LLC
 C/O DOUGLAS PINCIARO MGR
 PO BOX 121
 NEW CASTLE, NH 03854

ZONING DISTRICT: CHARACTER DISTRICT 5 (CD5)
 DOWNTOWN OVERLAY DISTRICT
 NORTH END INCENTIVE OVERLAY DISTRICT
 HISTORIC DISTRICT
 FLOOD PLAIN DISTRICT

PROPOSED USE: MULTI-FAMILY RESIDENTIAL/COMMERCIAL
 PROPOSED LOT SIZE: ±1.77 ACRES (±77,311 SF)

BUILDING FORM (PRINCIPAL BUILDING):

	REQUIRED	PROPOSED
BUILDING HEIGHT:	5 STORIES ⁽³⁾ 60 FT	5 STORIES <60 FT
MAXIMUM FINISHED FLOOR SURFACE OF GROUND FLOOR ABOVE SIDEWALK GRADE:	36 IN	0 IN
MINIMUM GROUND STORY HEIGHT:	12 FT	>12 FT
MINIMUM SECOND STORY HEIGHT:	10 FT	>10 FT
FAÇADE GLAZING:		
SHOP FRONT	20% - 50%	20% - 50%
ALLOWED ROOF TYPES		
FLAT, GABLE, HIP, GAMBREL, MANSARD		FLAT

(3) - ADDITIONAL 1 STORY UP TO 10FT ALLOWED FOR PROVIDING AT LEAST 20% OF THE SITE TO BE ASSIGNED AS COMMUNITY SPACE.

DEVELOPMENT STANDARDS

BUILDING PLACEMENT (PRINCIPAL BUILDING):	REQUIRED	PROPOSED
MAXIMUM PRINCIPAL FRONT YARD:	5 FT	16 FT ⁽¹⁾
SIDE YARD:	NR	
MINIMUM REAR YARD:	5 FT	>5 FT
MINIMUM FRONT LOT LINE BUILDOUT:	80%	80%

BUILDING AND LOT OCCUPATION:	REQUIRED	PROPOSED
MAXIMUM BUILDING BLOCK LENGTH:	225 FT	205 FT
MAXIMUM FAÇADE MODULATION LENGTH:	100 FT	<100 FT
MAXIMUM ENTRANCE SPACING:	50 FT	<50 FT
MAXIMUM BUILDING COVERAGE:	95%	36%
MAXIMUM BUILDING FOOTPRINT:	30,000 SF ⁽²⁾	29,374 SF
MINIMUM LOT AREA:	NR	
MINIMUM OPEN SPACE:	5%	
MAXIMUM GROUND FLOOR GFA PER USE:	15,000 SF	5,500 SF

COMMUNITY SPACE:

	REQUIRED	PROPOSED
	20%	20%
	15,462 SF	15,494 SF

PARKING REQUIREMENTS

RESIDENTIAL UNITS (>750 SF)	48 UNITS x 1.3 SPACES	63 SPACES
VISITOR SPACES	1 SPACE / 5 UNITS	10 SPACES
DOWNTOWN OVERLAY DISTRICT		4 SPACES
TOTAL MINIMUM PARKING SPACES REQUIRED =		73 SPACES

PARKING SPACES

	REQUIRED	PROPOSED
	73 SPACES	96 SPACES

*15 PROPOSED SPACES ARE TANDEM SPACES

ADA PARKING SPACES

	REQUIRED	PROPOSED
	4 SPACES	6 SPACES

BICYCLE SPACES

	REQUIRED	PROPOSED
1 BICYCLE SPACE / 10 PARKING SPACES:	10 SPACES	10 SPACES

*INDOOR BIKE STORAGE WILL BE PROVIDED THAT MEETS OR EXCEEDS REQUIRED.

PROPOSED MIXED USE GROSS FLOOR AREA

FLOOR	COMMERCIAL (SF)	LOBBY (SF)	UNITS	TOTAL FLOOR AREA (SF)
FIRST	1,898	3,526	0	29,374
SECOND	0	0	15	26,692
THIRD	0	0	15	26,692
FOURTH	0	0	9	19,393
FIFTH	0	0	9	19,393
TOTAL	1,898	3,526	48	121,544

Last Saved: 3/22/2021
 Plotted On: Mar 22, 2021 11:12:04am By: Asellier
 Tighe & Bond 221 Commercial Center, Portsmouth, NH 03801
 Figures: AutoCAD (C:\960-011_C-DSGN.dwg)

Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
 Portsmouth, NH







MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session

PROJECT NO:	C0960-011
DATE:	January 27, 2021
FILE:	C0960-011_C-DSGN.DWG
DRAWN BY:	AFS
CHECKED:	NAH/PMC
APPROVED:	BLM

SITE PLAN

SCALE: AS SHOWN

C-102.1



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session



PROJECT NO:	C0960-011
DATE:	January 27, 2021
FILE:	C0960-011_C-DSGN.DWG
DRAWN BY:	AFS
CHECKED BY:	NAH/PMC
APPROVED BY:	BLM

BASEMENT & UPPER FLOOR PLAN

SCALE: AS SHOWN

C-102.2


Last Saved: 3/19/2021
 Plotted On: Mar 22, 2021 10:23am By: ASellar
 Tighe & Bond 212 Concord Camarillo C:\0960-011_53 Green St., Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-DSGN.dwg



- GRADING AND DRAINAGE NOTES:**
1. COMPACTION REQUIREMENTS:
BELOW PAVED OR CONCRETE AREAS 95%
TRENCH BEDDING MATERIAL AND SAND BLANKET BACKFILL 95%
BELOW LOAM AND SEED AREAS 90%
* ALL PERCENTAGES OF COMPACTION SHALL BE OF THE MAXIMUM DRY DENSITY AT THE OPTIMUM MOISTURE CONTENT AS DETERMINED AND CONTROLLED IN ACCORDANCE WITH ASTM D-1557, METHOD C FIELD DENSITY TESTS SHALL BE MADE IN ACCORDANCE WITH ASTM D-1556 OR ASTM-2922.
 2. ALL STORM DRAINAGE PIPES SHALL BE HIGH DENSITY POLYETHYLENE (HANCOR HI-Q, ADS N-12 OR EQUAL), UNLESS OTHERWISE SPECIFIED.
 3. SEE UTILITY PLAN FOR ALL SITE UTILITY INFORMATION.
 4. ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
 5. CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE AND LAWN AREAS FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE BUILDING ENTRANCES, EXITS, RAMPS AND LOADING DOCK AREAS ADJACENT TO THE BUILDING.
 6. CONTRACTOR SHALL THOROUGHLY CLEAN ALL CATCH BASINS AND DRAIN LINES, WITHIN THE LIMIT OF WORK, OF SEDIMENT IMMEDIATELY UPON COMPLETION OF CONSTRUCTION.
 7. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND LOCAL CODES.
 8. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED FERTILIZER AND MULCH.
 9. ALL STORM DRAIN CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE NHDOT STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES, LATEST EDITION.
 10. ALL PROPOSED CATCH BASINS SHALL BE EQUIPPED WITH OIL/GAS SEPARATOR HOODS AND 4' SUMPS.
 11. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM WITH APPLICABLE FEDERAL, STATE AND CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS AND CONSTRUCTION SPECIFICATIONS, LATEST REVISIONS.
 12. CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILE) ON DISK TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
 13. SEE EXISTING CONDITIONS PLAN FOR BENCH MARK INFORMATION.
 14. ALL DRAIN LINES WITH LESS THAN FOUR (4) FEET OF COVER SHALL BE INSULATED.

- EROSION CONTROL NOTES:**
1. INSTALL EROSION CONTROL BARRIERS AS SHOWN AS FIRST ORDER OF WORK.
 2. SEE GENERAL EROSION CONTROL NOTES ON "EROSION CONTROL NOTES & DETAILS SHEET".
 3. PROVIDE INLET PROTECTION AROUND ALL EXISTING AND PROPOSED CATCH BASIN INLETS WITHIN THE WORK LIMITS. MAINTAIN FOR THE DURATION OF THE PROJECT UNTIL PAVEMENT HAS BEEN INSTALLED.
 4. INSTALL STABILIZED CONSTRUCTION ENTRANCES.
 5. INSPECT INLET PROTECTION AND PERIMETER EROSION CONTROL MEASURES DAILY AND AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS 1/3 THE FILTER HEIGHT.
 6. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED SHALL RECEIVE 6" LOAM, SEED, FERTILIZER AND MULCH.
 7. CONSTRUCT EROSION CONTROL BLANKET ON ALL SLOPES STEEPER THAN 3:1.
 8. PRIOR TO ANY WORK OR SOIL DISTURBANCE COMMENCING ON THE SUBJECT PROPERTY, INCLUDING MOVING OF EARTH, THE APPLICANT SHALL INSTALL ALL EROSION AND SILTATION MITIGATION AND CONTROL MEASURES AS REQUIRED BY STATE AND LOCAL PERMITS AND APPROVALS.
 9. CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST AND WIND EROSION THROUGHOUT THE CONSTRUCTION PERIOD. DUST CONTROL MEASURES SHALL INCLUDE, BUT ARE NOT LIMITED TO, SPRINKLING WATER ON UNSTABLE SOILS SUBJECT TO ARID CONDITIONS.
 10. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION.
 11. ALL CATCH BASIN SUMPS AND PIPING SHALL BE THOROUGHLY CLEANED TO REMOVE ALL SEDIMENT AND DEBRIS AFTER THE PROJECT HAS BEEN FULLY PAVED.
 12. TEMPORARY SOIL STOCKPILE SHALL BE SURROUNDED BY SILT FENCE AND SHALL BE STABILIZED BY TEMPORARY EROSION CONTROL SEEDING. STOCKPILE AREAS TO BE LOCATED AS FAR AS POSSIBLE FROM THE DELINEATED EDGE OF WETLANDS.
 13. SAFETY FENCING SHALL BE PROVIDED AROUND STOCKPILES OVER 10 FT.
 14. CONCRETE TRUCKS WILL BE REQUIRED TO WASH OUT (IF NECESSARY) SHOOTS ONLY WITHIN AREAS WHERE CONCRETE HAS BEEN PLACED. NO OTHER WASH OUT WILL BE ALLOWED.

- LEGEND**
- 5 — PROPOSED MAJOR CONTOUR LINE
 - 6 — PROPOSED MINOR CONTOUR LINE
 - PUD — PROPOSED DRAIN LINE
 - ○ — PROPOSED UNDERDRAIN
 - ○ — PROPOSED SILT SOCK
 - [] — PROPOSED RIP RAP
 - [] — INLET PROTECTION SILT SACK
 - [] — PROPOSED CATCHBASIN
 - [] — PROPOSED DRAIN MANHOLE
 - [] — PROPOSED YARD DRAIN
 - [] — PROPOSED JELLYFISH FILTER
 - [] — JELLYFISH FILTER
 - [] — PROPOSED CATCH BASIN
 - [] — PROPOSED DRAIN MANHOLE
 - [] — PROPOSED YARD DRAIN
 - [] — TYPICAL



Last Saved: 3/19/2021
 Plotted On: Mar 22, 2021 10:06am By: Aseller
 Tighe & Bond 212 Concord Cabot Rd Portsmouth, NH Drawings Figures AutoCAD (C:\960-011_C-DSGN.dwg)

Proposed Mixed Use Development

CPI Management, LLC


53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session



PROJECT NO:	C0960-011
DATE:	January 27, 2021
FILE:	C0960-011_C-DSGN.DWG
DRAWN BY:	AFS
CHECKED:	NAH/PMC
APPROVED:	BLM

GRADING, DRAINAGE, AND EROSION CONTROL PLAN

SCALE: AS SHOWN



- UTILITY NOTES:**
- THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES ARE APPROXIMATE AND THE LOCATIONS ARE NOT GUARANTEED BY THE OWNER OR ENGINEER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES, ANTICIPATE CONFLICTS, REPAIR EXISTING UTILITIES, AND RELOCATE EXISTING UTILITIES REQUIRED TO COMPLETE THE WORK AT NO ADDITIONAL COST TO THE OWNER.
 - COORDINATE ALL UTILITY WORK WITH APPROPRIATE UTILITY COMPANY.
 - NATURAL GAS - UNITIL
 - WATER/SEWER - CITY OF PORTSMOUTH
 - ELECTRIC - EVERSOURCE
 - COMMUNICATIONS - FAIRPOINT AND COMCAST
 - SEE EXISTING CONDITIONS PLAN FOR BENCHMARK INFORMATION.
 - SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR PROPOSED GRADING AND EROSION CONTROL MEASURES.
 - ALL WATER MAIN INSTALLATIONS SHALL BE CLASS 52, CEMENT LINED DUCTILE IRON PIPE.
 - ALL WATER MAIN INSTALLATIONS SHALL BE PRESSURE TESTED AND CHLORINATED AFTER CONSTRUCTION PRIOR TO ACTIVATING THE SYSTEM. CONTRACTOR SHALL COORDINATE CHLORINATION AND TESTING WITH THE PORTSMOUTH WATER DEPARTMENT.
 - ALL SEWER PIPE SHALL BE PVC SDR 35 UNLESS OTHERWISE STATED.
 - COORDINATE ALL WORK WITHIN PUBLIC RIGHT OF WAYS WITH THE CITY OF PORTSMOUTH.
 - CONTRACTOR SHALL MAINTAIN UTILITY SERVICES TO ADJUTING PROPERTIES THROUGHOUT CONSTRUCTION.
 - CONNECTION TO EXISTING WATER MAIN SHALL BE CONSTRUCTED TO CITY OF PORTSMOUTH STANDARDS.
 - EXISTING UTILITIES TO BE REMOVED SHALL BE CAPPED AT THE MAIN AND MEET THE DEPARTMENT OF PUBLIC WORKS STANDARDS FOR CAPPING OF WATER AND SEWER SERVICES.
 - ALL ELECTRICAL MATERIAL WORKMANSHIP SHALL CONFORM TO THE NATIONAL ELECTRIC CODE, LATEST EDITION, AND ALL APPLICABLE STATE AND LOCAL CODES.
 - THE EXACT LOCATION OF NEW UTILITY SERVICES AND CONNECTIONS SHALL BE COORDINATED WITH THE BUILDING DRAWINGS AND THE APPLICABLE UTILITY COMPANIES.
 - ADJUST ALL MANHOLES, CATCH BASINS, CURB BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE.
 - ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES TO FACILITATE PULLING CABLES.
 - THE CONTRACTOR SHALL OBTAIN, PAY FOR, AND COMPLY WITH ALL REQUIRED PERMITS, ARRANGE FOR ALL INSPECTIONS, AND SUBMIT COPIES OF ACCEPTANCE CERTIFICATES TO THE OWNER PRIOR TO THE COMPLETION OF THIS PROJECT.
 - THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES, AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER INSTALLATION OF UTILITIES COMPLETE AND OPERATIONAL.
 - CONTRACTOR SHALL PROVIDE EXCAVATION, BEDDING, BACKFILL AND COMPACTION FOR NATURAL GAS SERVICES.
 - A 10-FOOT MINIMUM EDGE TO EDGE HORIZONTAL SEPARATION SHALL BE PROVIDED BETWEEN ALL WATER AND SANITARY SEWER LINES. AN 18-INCH MINIMUM OUTSIDE TO OUTSIDE VERTICAL SEPARATION SHALL BE PROVIDED AT ALL WATER/SANITARY SEWER CROSSINGS.
 - THE CONTRACTOR SHALL CONTACT "DIG-SAFE" 72 HOURS PRIOR TO COMMENCING CONSTRUCTION. THE CONTRACTOR SHALL HAVE THE "DIG-SAFE" NUMBER ON SITE AT ALL TIMES.
 - CONTRACTOR TO SUBMIT AS-BUILT PLANS ON REPRODUCIBLE MYLARS AND IN DIGITAL FORMAT (.DWG FILES) TO THE OWNER AND ENGINEER UPON COMPLETION OF THE PROJECT. AS-BUILTS SHALL BE PREPARED AND CERTIFIED BY A NEW HAMPSHIRE LICENSED LAND SURVEYOR OR PROFESSIONAL ENGINEER.
 - SAW CUT AND REMOVE PAVEMENT AND CONSTRUCT PAVEMENT TRENCH PATCH FOR ALL PROPOSED UTILITIES LOCATED IN EXISTING PAVEMENT AREAS TO REMAIN
 - HYDRANTS, GATE VALVES, FITTINGS, ETC. SHALL MEET THE REQUIREMENTS OF THE CITY OF PORTSMOUTH.
 - COORDINATE TESTING OF SEWER CONSTRUCTION WITH THE CITY OF PORTSMOUTH.
 - ALL SEWER PIPE WITH LESS THAN 5' OF COVER SHALL BE INSULATED.
 - CONTRACTOR SHALL COORDINATE ALL ELECTRIC WORK INCLUDING BUT NOT LIMITED TO: CONDUIT CONSTRUCTION, MANHOLE CONSTRUCTION, UTILITY POLE CONSTRUCTION, OVERHEAD WIRE RELOCATION, AND TRANSFORMER CONSTRUCTION WITH POWER COMPANY.
 - CONTRACTOR SHALL PHASE UTILITY CONSTRUCTION, PARTICULARLY WATER MAIN AND GAS MAIN CONSTRUCTION AS TO MAINTAIN CONTINUOUS SERVICE TO ADJUTING PROPERTIES. CONTRACTOR SHALL COORDINATE TEMPORARY SERVICES TO ADJUTING PROPERTIES WITH THE UTILITY COMPANY AND AFFECTED ADJUTING.
 - SITE LIGHTING SPECIFICATIONS, CONDUIT LAYOUT AND CIRCUITRY FOR PROPOSED SITE LIGHTING AND SIGN ILLUMINATION SHALL BE PROVIDED BY THE PROJECT ELECTRICAL ENGINEER.
 - CONTRACTOR SHALL PERFORM TEST PITS TO VERIFY THE LOCATION OF EXISTING UTILITIES PRIOR TO CONSTRUCTION AND SHALL NOTIFY ENGINEER IF LOCATIONS DIFFER FROM PLAN.
 - PROPOSED GREASE TRAP AND GREASE WATER SERVICE CONNECTION TO BE CONSTRUCTED IF PROPOSED COMMERCIAL SPACE BECOMES RESTAURANT USE.



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

LEGEND

SD	EXISTING STORM DRAIN	SS	EXISTING SANITARY SEWER
SS	EXISTING SANITARY SEWER TO BE ABANDONED	W	EXISTING WATER SERVICE
G	EXISTING GAS SERVICE	E	EXISTING UNDERGROUND ELECTRIC SERVICE
OHW	EXISTING OVERHEAD UTILITY SERVICE	SS	PREVIOUSLY APPROVED SEWER
SS	PROPOSED STORM DRAIN	SS	PROPOSED SANITARY SEWER
PW	PROPOSED WATER SERVICE	G	PROPOSED GAS SERVICE
E	PROPOSED STREET LIGHTING CONDUIT	PE&C	PROPOSED UNDERGROUND ELECTRIC AND COMMUNICATION SERVICE

⊙	EXISTING DRAIN MANHOLE	⊙	PROPOSED CATCHBASIN
⊙	EXISTING SEWER MANHOLE	⊙	PROPOSED DRAIN MANHOLE
⊙	PREVIOUSLY APPROVED SEWER MANHOLE	⊙	PROPOSED SEWER MANHOLE
⊙	EXISTING HYDRANT	⊙	PROPOSED WATER VALVE
⊙	EXISTING WATER VALVE	⊙	PROPOSED FIRE DEPARTMENT BUILDING CONNECTION
⊙	EXISTING WATER SHUTOFF	⊙	PROPOSED GAS VALVE
⊙	EXISTING ELECTRIC MANHOLE	⊙	PROPOSED LIGHT POLE BASE
⊙	EXISTING PAD MOUNTED TRANSFORMER	BLDG	BUILDING
⊙	EXISTING GAS VALVE	TYP	TYPICAL
⊙	EXISTING HANDHOLE	COORD	COORDINATE
⊙	EXISTING COMMUNICATION MANHOLE	VIF	VERIFY IN FIELD

B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
MARK	DATE	DESCRIPTION
PROJECT NO:	C0960-011	
DATE:	January 27, 2021	
FILE:	C0960-011_C-DSGN.DWG	
DRAWN BY:	AFS	
CHECKED BY:	NAH/PMC	
APPROVED:	BLM	

UTILITIES PLAN

SCALE: AS SHOWN

Last Saved: 3/22/2021 1:40pm By: ASelbir
 Plotted On: Mar 22, 2021 1:40pm
 Tighe & Bond P:\C0960-011_53 Green St., Portsmouth, NH\Drawings - Figures\AutoCAD\C0960-011_C-DSGN.dwg

PROJECT NAME AND LOCATION

PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET
PORTSMOUTH, NH 03801
43°-04'-48"N
70°-45'-43"W

PROJECT DESCRIPTION

THE PROJECT CONSISTS OF THE CONSTRUCTION OF A FIVE-STORY MIXED USE RESIDENTIAL BUILDING WITH ASSOCIATED SITE IMPROVEMENTS.

DISTURBED AREA

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 1.75 ACRES.

SOIL CHARACTERISTICS

BASED ON THE NRCS WEB SOIL SURVEY FOR ROCKINGHAM COUNTY - NEW HAMPSHIRE, THE SOILS ON SITE CONSIST OF URBAN LAND.

NAME OF RECEIVING WATERS

THE STORMWATER RUNOFF FROM THE SITE WILL BE DISCHARGED VIA A PROPOSED OUTLET PIPE TO NORTH MILL POND AND WILL ULTIMATELY FLOW TO THE PISCATAQUA RIVER.

CONSTRUCTION SEQUENCE OF MAJOR ACTIVITIES:

- 1. CUT AND CLEAR TREES.
2. CONSTRUCT TEMPORARY AND PERMANENT SEDIMENT, EROSION AND DETENTION CONTROL FACILITIES. EROSION, SEDIMENT AND DETENTION MEASURES SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OPERATIONS THAT WILL INFLUENCE STORMWATER RUNOFF SUCH AS:
- NEW CONSTRUCTION
- NEARNESS OF CONSTRUCTION SITE TO RECEIVING WATERS
- CONSTRUCTION DURING LATE WINTER AND EARLY SPRING
3. ALL PERMANENT DITCHES, SWALES, DETENTION, RETENTION AND SEDIMENTATION BASINS TO BE STABILIZED USING THE VEGETATIVE AND NON-STRUCTURAL BMPs PRIOR TO DIRECTING RUNOFF TO THEM.
4. CLEAR AND DISPOSE OF DEBRIS.
5. CONSTRUCT TEMPORARY CULVERTS AND DIVERSION CHANNELS AS REQUIRED.
6. GRADE AND GRAVEL ROADWAYS AND PARKING AREAS - ALL ROADS AND PARKING AREA SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
7. BEGIN PERMANENT AND TEMPORARY SEEDING AND MULCHING. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. DAILY, OR AS REQUIRED, CONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, PERIMETER EROSION CONTROL MEASURES, SEDIMENT TRAPS, ETC., MULCH AND SEED AS REQUIRED.
8. FINISH PAVING ALL ROADWAYS AND PARKING LOTS.
9. INSPECT AND MAINTAIN ALL EROSION AND SEDIMENT CONTROL MEASURES.
10. COMPLETE PERMANENT SEEDING AND LANDSCAPING.
11. REMOVE TRAPPED SEDIMENTS FROM COLLECTOR DEVICES AS APPROPRIATE AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES.

EROSION CONTROL NOTES:

- 1. ALL EROSION CONTROL MEASURES AND PRACTICES SHALL CONFORM TO THE "NEW HAMPSHIRE STORMWATER MANUAL VOLUME 3: EROSION AND SEDIMENT CONTROLS DURING CONSTRUCTION" PREPARED BY THE NHDES.
2. PRIOR TO ANY WORK OR SOIL DISTURBANCE, CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR EROSION CONTROL MEASURES AS REQUIRED IN THE PROJECT MANUAL. CONTRACTOR SHALL INSTALL TEMPORARY EROSION CONTROL BARRIERS, INCLUDING HAY BALE, SILT FENCES, MULCH BERMS, SILT SACKS AND SILT SOCKS AS SHOWN IN THESE DRAWINGS AS THE FIRST ORDER OF WORK.
3. SILT SACK INLET PROTECTION SHALL BE INSTALLED IN ALL EXISTING AND PROPOSED CATCH BASIN INLETS WITHIN THE WORK LIMITS AND BE MAINTAINED FOR THE DURATION OF THE PROJECT.
4. PERIMETER CONTROLS INCLUDING SILT FENCES, MULCH BERM, SILT SOCK, AND/OR HAY BALE BARRIERS SHALL BE MAINTAINED FOR THE DURATION OF THE PROJECT UNTIL NON-PAVED AREAS HAVE BEEN STABILIZED.
5. THE CONTRACTOR SHALL REMOVE AND PROPERLY DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES UPON COMPLETION OF CONSTRUCTION.
6. ALL DISTURBED AREAS NOT OTHERWISE BEING TREATED SHALL RECEIVE 6" LOAM, SEED AND FERTILIZER.
7. INSPECT ALL INLET PROTECTION AND PERIMETER CONTROLS WEEKLY AND AFTER EACH RAIN STORM OF 0.25 INCH OR GREATER. REPAIR/MODIFY PROTECTION AS NECESSARY TO MAXIMIZE EFFICIENCY OF FILTER. REPLACE ALL FILTERS WHEN SEDIMENT IS 1/3 THE FILTER HEIGHT.
8. CONSTRUCT EROSION CONTROL BLANKETS ON ALL SLOPES STEEPER THAN 3:1.

STABILIZATION:

- 1. AN AREA SHALL BE CONSIDERED STABLE WHEN ONE OF THE FOLLOWING HAS OCCURRED:
A. BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED;
B. A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED;
C. A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED;
D. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
2. WINTER STABILIZATION PRACTICES:
A. ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS;
B. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85 PERCENT VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS;
C. AFTER NOVEMBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOW AFTER EACH STORM EVENT;
3. STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES, AND DISTURBED AREAS, WHERE CONSTRUCTION ACTIVITY SHALL NOT OCCUR FOR MORE THAN TWENTY-ONE (21) CALENDAR DAYS BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR TEMPORARILY CEASED IN THAT AREA. STABILIZATION MEASURES TO BE USED INCLUDE:
A. TEMPORARY SEEDING;
B. MULCHING.
4. WHEN CONSTRUCTION ACTIVITY PERMANENTLY OR TEMPORARILY CEASES WITHIN 100 FEET OF NEARBY SURFACE WATERS OR DELINEATED WETLANDS, THE AREA SHALL BE STABILIZED WITHIN SEVEN (7) DAYS OR PRIOR TO A RAIN EVENT. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN AN THESE AREAS, SILT FENCES, MULCH BERMS, HAY BALE BARRIERS AND ANY EARTH/DIKES SHALL BE REMOVED ONCE PERMANENT MEASURES ARE ESTABLISHED.
5. DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STABILIZED CHANNELS WHERE POSSIBLE. SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILT FENCES, MULCH BERMS, HAY BALE BARRIERS, OR SILT SOCKS. ALL STORM DRAIN BASIN INLETS SHALL BE PROVIDED WITH FLARED END SECTIONS AND TRASH RACKS. THE SITE SHALL BE STABILIZED FOR THE WINTER BY NOVEMBER 15.

DUST CONTROL:

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST THROUGHOUT THE CONSTRUCTION PERIOD.
2. DUST CONTROL METHODS SHALL INCLUDE, BUT BE NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY MULCHING.
3. DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ADJUTING AREAS.

STOCKPILES:

- 1. LOCATE STOCKPILES A MINIMUM OF 50 FEET AWAY FROM CATCH BASINS, SWALES, AND

CULVERTS.

- 2. ALL STOCKPILES SHOULD BE SURROUNDED WITH TEMPORARY EROSION CONTROL MEASURES PRIOR TO THE ONSET OF PRECIPITATION.
3. PERIMETER BARRIERS SHOULD BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE INTEGRITY OF THE BARRIER SHOULD BE INSPECTED AT THE END OF EACH WORKING DAY.
4. PROTECT ALL STOCKPILES FROM STORMWATER RUN-OFF USING TEMPORARY EROSION CONTROL MEASURES SUCH AS BERMS, SILT SOCK, OR OTHER APPROVED PRACTICE TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.

OFF SITE VEHICLE TRACKING:

- 1. THE CONTRACTOR SHALL CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE(S) PRIOR TO ANY EXCAVATION ACTIVITIES.

VEGETATION:

- 1. TEMPORARY GRASS COVER:
A. SEEDED PREPARATION:
a. APPLY FERTILIZER AT THE RATE OF 600 POUNDS PER ACRE OF 10-10-10. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF THREE (3) TONS PER ACRE;
b. SEEDING:
a. UTILIZE ANNUAL RYE GRASS AT A RATE OF 40 LBS/ACRE;
b. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF TWO (2) INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED;
c. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). HYDROSEEDINGS, WHICH INCLUDE MULCH, MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10% WHEN HYDROSEEDING;
C. MAINTENANCE:
a. TEMPORARY SEEDING SHALL BE PERIODICALLY INSPECTED. AT A MINIMUM, 95% OF THE SOIL SURFACE SHOULD BE COVERED BY VEGETATION. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND OTHER TEMPORARY MEASURES USED IN THE INTERIM (MULCH, FILTER BARRIERS, CHECK DAMS, ETC.).
2. VEGETATIVE PRACTICE:
A. FOR PERMANENT MEASURES AND PLANTINGS:
a. LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF THREE (3) TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5;
b. FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 800 POUNDS PER ACRE OF 10-20-20 FERTILIZER;
c. SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN, AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE REQUIRED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4-1/2 POUNDS AND 5-1/2 POUNDS PER INCH OF WIDTH;
d. SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR FOOT OF WIDTH;
e. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AS INDICATED ABOVE;
f. THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED, AND ALL NOXIOUS WEEDS REMOVED;
g. THE CONTRACTOR SHALL PROTECT AND MAINTAIN THE SEEDED AREAS UNTIL ACCEPTED;
h. A GRASS SEED MIXTURE CONTAINING THE FOLLOWING SEED REQUIREMENTS SHALL BE APPLIED AT THE INDICATED RATE:
SEED MIX APPLICATION RATE
CREEPING RED FESCUE 20 LBS/ACRE
TALL FESCUE 20 LBS/ACRE
REDTOP 2 LBS/ACRE
IN NO CASE SHALL THE WEED CONTENT EXCEED ONE (1) PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH STATE AND FEDERAL SEED LAWS. SEEDING SHALL BE DONE NO LATER THAN SEPTEMBER 15. IN NO CASE SHALL SEEDING TAKE PLACE OVER SNOW.
3. DORMANT SEEDING (SEPTEMBER 15 TO FIRST SNOWFALL):
A. FOLLOW PERMANENT MEASURES SLOPE, LIME, FERTILIZER AND GRADING REQUIREMENTS. APPLY SEED MIXTURE AT TWICE THE INDICATED RATE. APPLY MULCH AS INDICATED FOR PERMANENT MEASURES.

CONCRETE WASHOUT AREA:

- 1. THE FOLLOWING ARE THE ONLY NON-STORMWATER DISCHARGES ALLOWED. ALL OTHER NON-STORMWATER DISCHARGES ARE PROHIBITED ON SITE:
A. THE CONCRETE DELIVERY TRUCKS SHALL, WHENEVER POSSIBLE, USE WASHOUT FACILITIES AT THEIR OWN PLANT OR DISPATCH FACILITY;
B. IF IT IS NECESSARY, SITE CONTRACTOR SHALL DESIGNATE SPECIFIC WASHOUT AREAS AND DESIGN FACILITIES TO HANDLE ANTICIPATED WASHOUT WATER;
C. CONTRACTOR SHALL LOCATE WASHOUT AREAS AT LEAST 150 FEET AWAY FROM STORM DRAINS, SWALES AND SURFACE WATERS OR DELINEATED WETLANDS;
D. INSPECT WASHOUT FACILITIES DAILY TO DETECT LEAKS OR TEARS AND TO IDENTIFY WHEN MATERIALS NEED TO BE REMOVED.

ALLOWABLE NON-STORMWATER DISCHARGES:

- 1. FIRE-FIGHTING ACTIVITIES;
2. FIRE HYDRANT FLUSHING;
3. WATERS USED TO WASH VEHICLES WHERE DETERGENTS ARE NOT USED;
4. WATER USED TO CONTROL DUST;
5. POTABLE WATER INCLUDING UNCONTAMINATED WATER LINE FLUSHING;
6. ROUTINE EXTERNAL BUILDING WASH DOWN WHERE DETERGENTS ARE NOT USED;
7. PAVEMENT WASH WATERS WHERE DETERGENTS ARE NOT USED;
8. UNCONTAMINATED AIR CONDITIONING/COMPRESSOR CONDENSATION;
9. UNCONTAMINATED GROUND WATER OR SPRING WATER;
10. FOUNDATION OR FOOTING DRAINS WHICH ARE UNCONTAMINATED;
11. UNCONTAMINATED EXCAVATION DEWATERING;
12. LANDSCAPE IRRIGATION.

WASTE DISPOSAL:

- 1. WASTE MATERIAL:
A. ALL WASTE MATERIALS SHALL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE SHALL BE DEPOSITED IN A DUMPSTER;
B. NO CONSTRUCTION WASTE MATERIALS SHALL BE BURIED ON SITE;
C. ALL PERSONNEL SHALL BE INSTRUCTED REGARDING THE CORRECT PROCEDURE FOR WASTE DISPOSAL BY THE SUPERINTENDENT.
2. HAZARDOUS WASTE:
A. ALL HAZARDOUS WASTE MATERIALS SHALL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER;
B. SITE PERSONNEL SHALL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTENDENT.
3. SANITARY WASTE:
A. ALL SANITARY WASTE SHALL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.


SPILL PREVENTION:

- 1. CONTRACTOR SHALL BE FAMILIAR WITH SPILL PREVENTION MEASURES REQUIRED BY LOCAL, STATE AND FEDERAL AGENCIES. AT A MINIMUM, CONTRACTOR SHALL FOLLOW THE BEST MANAGEMENT SPILL PREVENTION PRACTICES OUTLINED BELOW.
2. THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT SHALL BE USED TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING CONSTRUCTION TO STORMWATER RUNOFF:

- A. GOOD HOUSEKEEPING - THE FOLLOWING GOOD HOUSEKEEPING PRACTICE SHALL BE FOLLOWED ON SITE DURING CONSTRUCTION:
a. ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB SHALL BE STORED ON SITE;
b. ALL MATERIALS STORED ON SITE SHALL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR PROPER (ORIGINAL IF POSSIBLE) CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE;
c. MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL SHALL BE FOLLOWED;
d. THE SITE SUPERINTENDENT SHALL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS;
e. SUBSTANCES SHALL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER;
f. WHENEVER POSSIBLE ALL OF A PRODUCT SHALL BE USED UP BEFORE DISPOSING OF THE CONTAINER.
B. HAZARDOUS PRODUCTS - THE FOLLOWING PRACTICES SHALL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
g. PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT RESEALABLE;
h. ORIGINAL LABELS AND MATERIAL SAFETY DATA SHALL BE RETAINED FOR IMPORTANT PRODUCT INFORMATION;
i. SURPLUS PRODUCT THAT MUST BE DISPOSED OF SHALL BE DISCARDED ACCORDING TO THE MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL.
C. PRODUCT SPECIFIC PRACTICES - THE FOLLOWING PRODUCT SPECIFIC PRACTICES SHALL BE FOLLOWED ON SITE:
a. PETROLEUM PRODUCTS:
a.1. ALL ON SITE VEHICLES SHALL BE MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO REDUCE LEAKAGE;
a.2. PETROLEUM PRODUCTS SHALL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE SHALL BE APPLIED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.
b. FERTILIZERS:
b.1. FERTILIZERS USED SHALL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS;
b.2. ONCE APPLIED FERTILIZER SHALL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO STORMWATER;
b.3. STORAGE SHALL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER SHALL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.
c. PAINTS:
c.1. ALL CONTAINERS SHALL BE TIGHTLY SEALED AND STORED WHEN NOT REQUIRED FOR USE;
c.2. EXCESS PAINT SHALL NOT BE DISCHARGED TO THE STORM SEWER SYSTEM;
c.3. EXCESS PAINT SHALL BE DISPOSED OF PROPERLY ACCORDING TO MANUFACTURER'S INSTRUCTIONS OR STATE AND LOCAL REGULATIONS.
D. SPILL CONTROL PRACTICES - IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION, THE FOLLOWING PRACTICES SHALL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP:
a. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP SHALL BE CLEARLY POSTED AND SITE PERSONNEL SHALL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES;
b. MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP SHALL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS SHALL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS, RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS SPECIFICALLY FOR THIS PURPOSE;
c. ALL SPILLS SHALL BE CLEANED UP IMMEDIATELY AFTER DISCOVERY;
d. THE SPILL AREA SHALL BE KEPT WELL VENTILATED AND PERSONNEL SHALL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A HAZARDOUS SUBSTANCE;
e. SPILLS OF TOXIC OR HAZARDOUS MATERIAL SHALL BE REPORTED TO THE APPROPRIATE LOCAL, STATE OR FEDERAL AGENCIES AS REQUIRED;
f. THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS SHALL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.
E. VEHICLE FUELING AND MAINTENANCE PRACTICE:
a. CONTRACTOR SHALL MAKE AN EFFORT TO PERFORM EQUIPMENT/VEHICAL FUELING AND MAINTENANCE AT AN OFF-SITE FACILITY;
b. CONTRACTOR SHALL PROVIDE AN ON-SITE FUELING AND MAINTENANCE AREA THAT IS CLEAN AND DRY;
c. IF POSSIBLE THE CONTRACTOR SHALL KEEP AREA COVERED;
d. CONTRACTOR SHALL KEEP A SPILL KIT AT THE FUELING AND MAINTENANCE AREA;
e. CONTRACTOR SHALL REGULARLY INSPECT VEHICLES FOR LEAKS AND DAMAGE;
f. CONTRACTOR SHALL USE DRIP PANS, DRIP CLOTHS, OR ABSORBENT PADS WHEN REPLACING SPENT FLUID.

EROSION CONTROL OBSERVATIONS AND MAINTENANCE PRACTICES

- 1. THIS PROJECT EXCEEDS ONE (1) ACRE OF DISTURBANCE AND THUS REQUIRES A SWPPP. THE SWPPP SHALL BE PREPARED BY THE CONTRACTOR. THE CONTRACTOR SHALL BE FAMILIAR WITH THE SWPPP AND KEEP AN UPDATED COPY OF THE SWPPP ONSITE AT ALL TIMES.
2. THE FOLLOWING REPRESENTS THE GENERAL OBSERVATION AND REPORTING PRACTICES THAT SHALL BE FOLLOWED AS PART OF THIS PROJECT:
A. OBSERVATIONS OF THE PROJECT FOR COMPLIANCE WITH THE SWPPP SHALL BE MADE BY THE CONTRACTOR AT LEAST ONCE A WEEK OR WITHIN 24 HOURS OF A STORM 0.25 INCHES OR GREATER;
B. AN OBSERVATION REPORT SHALL BE MADE AFTER EACH OBSERVATION AND DISTRIBUTED TO THE ENGINEER, THE OWNER, AND THE CONTRACTOR;
C. A REPRESENTATIVE OF THE SITE CONTRACTOR, SHALL BE RESPONSIBLE FOR MAINTENANCE AND REPAIR ACTIVITIES;
D. IF A REPAIR IS NECESSARY, IT SHALL BE INITIATED WITHIN 24 HOURS OF REPORT.




NOTES:

- 1. THE TRAP SHALL BE INSTALLED AS CLOSE TO THE DISTURBED AREA AS POSSIBLE.
2. THE MAXIMUM CONTRIBUTING AREA TO A SINGLE TRAP SHALL BE LESS THAN 5 ACRES.
3. THE MINIMUM VOLUME OF THE TRAP SHALL BE 3,600 CUBIC FEET OF STORAGE FOR EACH ACRE OF DRAINAGE AREA.
4. TRAP OUTLET SHALL BE MINIMUM OF ONE FOOT BELOW THE CREST OF THE TRAP.
5. TRAP SHALL DISCHARGE TO A STABILIZED AREA.
6. TRAP SHALL BE CLEANED WHEN 50 PERCENT OF THE ORIGINAL VOLUME IS FILLED.
7. MATERIALS REMOVED FROM THE TRAP SHALL BE PROPERLY DISPOSED OF AND STABILIZED.
8. SEDIMENT TRAPS MUST BE USED AS NEEDED TO CONTAIN RUNOFF UNTIL SOILS ARE STABILIZED.

SEDIMENT TRAP

NO SCALE




NOTES:

- 1. SILT SOCK SHALL BE SILT SOCK BY FILTREXX OR APPROVED EQUAL
2. INSTALL SILT SOCK IN ACCORDANCE WITH...

SILT SOCK

NO SCALE




NOTES:

- 1. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OF SEDIMENT FROM THE SITE. WHEN WASHING IS REQUIRED, IT SHALL BE DONE SO RUNOFF DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING STORM DRAINS, DITCHES, OR WATERWAYS


STABILIZED CONSTRUCTION EXIT

NO SCALE



SILT SACK

NO SCALE



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street Portsmouth, NH



Table with 3 columns: MARK, DATE, DESCRIPTION. Row B: 3/22/2021, TAC & CC Submission. Row A: 1/27/2021, CC Work Session.

Table with 2 columns: PROJECT NO., DATE. Row 1: C0960-011, January 27, 2021. Row 2: FILE: C0960-011_C-DTLS.DWG. Row 3: DRAWN BY: AFS. Row 4: CHECKED: NAH/PMC. Row 5: APPROVED: BLM.

EROSION CONTROL NOTES AND DETAILS SHEET

SCALE: AS SHOWN


Vertical text on the left margin: Last Saved: 3/22/2021 11:11:17 AM By: ASellier, Plotted On: Mar 22, 2021 11:11:17 AM By: ASellier, Tighe & Bond Engineering, Inc., Portsmouth, NH Drawings: Figures\AutoCAD\C0960-011_C-DTLS.dwg



NOTES:
 1. SYMBOL SHALL BE CONSTRUCTED IN ALL ACCESSIBLE SPACES USING FAST DRYING TRAFFIC PAINT, MEETING THE REQUIREMENTS OF AASHTO M248-TYPE F. PAINT SHALL BE APPLIED AS SPECIFIED BY MANUFACTURER.
 2. SYMBOL SHALL BE CONSTRUCTED TO THE LATEST ADA, STATE AND LOCAL REQUIREMENTS.


ACCESSIBLE SYMBOL
NO SCALE

NHDOT ITEM No. 304.2 (GRAVEL)		NHDOT ITEM No. 304.3 (CRUSHED GRAVEL)	
SIEVE SIZE	% PASSING	SIEVE SIZE	% PASSING
6"	100	3"	100
#4	25-70	2"	95-100
#200	0-12	1"	55-85
		#4	27-52
		#200	0-12



NOTES:
 1. SEE SITE PLAN FOR PAVEMENT WIDTH AND LOCATION.
 2. SEE GRADING, DRAINAGE AND EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.
 3. A TACK COAT SHALL BE PLACED ON TOP OF BINDER COURSE PAVEMENT PRIOR TO PLACING WEARING COURSE.
 4. REFER TO CITY SPECIFICATIONS FOR ASPHALT MIX DESIGN.


ON-SITE PAVEMENT SECTION
NO SCALE



CURB RADIUS TABLE	
RADIUS	MAX. LENGTH
<20'	USE CURVED CURB
21'	3'
22'-28'	4'
29'-35'	5'
36'-42'	6'
43'-49'	7'
50'-56'	8'
57'-60'	9'
>60'	10'

NOTES:
 1. SEE SITE PLAN(S) FOR LIMITS OF VERTICAL GRANITE CURB (VGC).
 2. ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.
 3. MINIMUM LENGTH OF STRAIGHT CURB STONES = 3'
 4. MAXIMUM LENGTH OF STRAIGHT CURB STONES = 10'
 5. MAXIMUM LENGTH OF STRAIGHT CURB STONES LAID ON CURVES (SEE TABLE).
 6. ALL RADII 20 FEET AND SMALLER SHALL BE CONSTRUCTED USING CURVED SECTIONS.
 7. JOINTS BETWEEN STONES SHALL HAVE A MAXIMUM SPACING OF 1/2" AND SHALL BE MORTARED.


VERTICAL GRANITE CURB
NO SCALE



R1-1
30" X 30"
WHITE ON RED




R7-8
12" X 18"
BLUE AND GREEN ON WHITE




R7-8P
18" X 9"
GREEN ON WHITE

NOTES:
 ALL SIGNS TO BE INSTALLED AS INDICATED IN THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
POST: SCHEDULE 40 GALVANIZED STEEL PIPE (OUTSIDE DIA. = 2.375").
FINISH: POST TO BE POWDER COATED GLOSS BLACK
LENGTH: AS REQUIRED
WEIGHT PER LINEAR FOOT: 2.50 LBS (MIN.)
HOLES: 3/8" DIAMETER (AS REQUIRED)
STEEL: SHALL CONFORM TO ASTM A-499 (GRADE 60) OR ASTM A-576 (GRADE 1070-1080)




SIGN LEGEND & SIGN POST
NO SCALE




NOTES:
 1. CONTAINMENT MUST BE STRUCTURALLY SOUND AND LEAK FREE AND CONTAIN ALL LIQUID WASTES.
 2. CONTAINMENT DEVICES MUST BE OF SUFFICIENT QUANTITY OR VOLUME TO COMPLETELY CONTAIN THE LIQUID WASTES GENERATED.
 3. WASHOUT MUST BE CLEANED OR NEW FACILITIES CONSTRUCTED AND READY TO USE ONCE WASHOUT IS 75% FULL.
 4. WASHOUT AREA(S) SHALL BE INSTALLED IN A LOCATION EASILY ACCESSIBLE BY CONCRETE TRUCKS. ONE OR MORE AREAS MAY BE INSTALLED ON THE CONSTRUCTION SITE AND MAY BE RELOCATED AS CONSTRUCTION PROGRESSES. AT LEAST WEEKLY REMOVE ACCUMULATION OF SAND AND AGGREGATE AND DISPOSE OF PROPERLY.

CONCRETE WASHOUT AREA
NO SCALE




NOTE:
 1. PAVEMENT MARKINGS TO BE INSTALLED IN LOCATIONS AS SHOWN ON SITE PLAN.
 2. ALL STOP BARS, WORDS, SYMBOLS AND ARROWS SHALL BE CONSTRUCTED USING WHITE THERMO PLASTIC, REFLECTORIZED PAVEMENT MARKING MATERIAL MEETING THE REQUIREMENTS OF ASTM D 4505

PAVEMENT MARKINGS
NO SCALE




NOTES:
 1. DETECTABLE WARNING SURFACE SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.

DETECTABLE WARNING SURFACE




CONCRETE WASHOUT AREA
NO SCALE




NOTES:
 1. ALL PAINT SHALL BE FAST DRYING TRAFFIC PAINT, MEETING THE REQUIREMENTS OF AASHTO M248-TYPE F. PAINT SHALL BE APPLIED AS SPECIFIED BY MANUFACTURER.
 2. SYMBOLS & PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICAN W/ DISABILITIES ACT.

ACCESSIBLE PARKING STALL
NO SCALE




SIDEWALK PLAN VIEW



SIDEWALK SECTION

NOTES:
 1. BRICK SIDEWALK SHALL BE INSTALLED AS DETAILED AND PER CITY OF PORTSMOUTH REQUIREMENTS/SPECIFICATIONS AND SHALL INCLUDE A CONTINUOUS APPROVED PAVER EDGE RESTRAINT SYSTEM AT ALL LOCATIONS NOT ADJACENT TO CURB OR BUILDINGS.
 2. CITY STANDARD BRICK SHALL BE TRADITIONAL EDGE, PATHWAY, FULL RANGE 2.25" X 4" X 8" PAVER, BY PINE HALL BRICK, INC. BRICK MATERIAL SAMPLES SHALL BE PROVIDED TO DPW PRIOR TO INSTALLATION FOR REVIEW AND APPROVAL.
 3. BEDDING MATERIAL SHALL BE A PORTLAND CEMENT / COURSE SAND MIX THAT IS 1 PART PORTLAND CEMENT AND 3 PARTS COURSE SAND. SAND SHALL CONFORM WITH ASTM C-33 AND CEMENT SHALL BE PORTLAND CEMENT TYPE I/TYPE II.

BRICK SIDEWALK
NO SCALE



SECTION A-A

NHDOT ITEM No. 304.3 (CRUSHED GRAVEL)	
SIEVE SIZE	% PASSING
3"	100
2"	95-100
1"	55-85
#4	27-52
#200	0-12

NOTES:
 1. RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICANS WITH DISABILITIES ACT AND LOCAL AND STATE REQUIREMENTS.
 2. A 6" COMPACTED CRUSHED GRAVEL BASE (NHDOT ITEM No. 304.3) SHALL BE PROVIDED BENEATH RAMPS.
 3. DETECTABLE WARNING PANEL SHALL BE CAST IRON SET IN CONCRETE (SEE DETAIL).
 4. PROVIDE DETECTABLE WARNING SURFACES ANYTIME THAT A CURB RAMP, BLENDED TRANSITION, OR LANDING CONNECTS TO A STREET.
 5. LOCATE THE DETECTABLE WARNING SURFACES AT THE BACK OF THE CURB ALONG THE EDGE OF THE LANDING.
 6. THE MAXIMUM RUNNING SLOPE OF ANY SIDEWALK CURB RAMP IS 12:1, THE MAXIMUM CROSS SLOPE IS 2%. THE SLOPE OF THE LANDING SHALL NOT EXCEED 2% IN ANY DIRECTION.
 7. TRANSITIONS SHALL BE FLUSH AND FREE OF ABRUPT CHANGES. ROADWAY SHOULDER SLOPES ADJOINING SIDEWALK CURB RAMPS SHALL BE A MAXIMUM OF 5% (FULL WIDTH) FOR A DISTANCE OF 2 FT. FROM THE ROADWAY CURBLINE.
 8. THE BOTTOM OF THE SIDEWALK CURB RAMP OR LANDING, EXCLUSIVE OF THE FLARED SIDES, SHALL BE WHOLLY CONTAINED WITHIN THE CROSSWALK MARKINGS.
 9. DETECTABLE WARNING PANELS SHALL BE A MINIMUM OF 2 FEET IN DEPTH. THE ROWS OF TRUNCATED DOMES SHALL BE ALIGNED PERPENDICULAR TO THE GRADE BREAK BETWEEN THE RAMP, BLENDED TRANSITION, OR LANDING AND THE STREET.
 10. THE TEXTURE OF THE DETECTABLE WARNING FEATURE MUST CONTRAST VISUALLY WITH THE SURROUNDING SURFACES (EITHER LIGHT-ON-DARK OR DARK-ON-LIGHT).

CONCRETE WHEELCHAIR ACCESSIBLE RAMP
NO SCALE

Proposed Mixed Use Development

CPI Management, LLC

53 Green Street Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session

PROJECT NO: C0960-011
 DATE: January 27, 2021
 FILE: C0960-011_C-DTLS.DWG
 DRAWN BY: AFS
 CHECKED BY: NAH/PMC
 APPROVED BY: BLM

DETAILS SHEET


SCALE: AS SHOWN

C-502


Last Saved: 3/22/2021 11:11:11 AM By: ASeller Plotted On: Mar 22, 2021 11:11:11 AM File: C:\Users\ASeller\Documents\C0960-011_53 Green St - Portsmouth, NH Drawings - Figures\AutoCAD\C0960-011_C-DTLS.dwg Tighe & Bond

STATE OF NEW HAMPSHIRE
 BRADLEE MEZQUITA
 No. 09830
 LICENSED PROFESSIONAL ENGINEER
 10/23/2018

STATE OF NEW HAMPSHIRE
 PATRICK CRIMMINS
 No. 12378
 LICENSED PROFESSIONAL ENGINEER
 03/22/2021




POROUS PAVEMENT SECTION
NO SCALE




ROADWAY TRENCH PATCH
NO SCALE

NOTE:
 COORDINATE AND OBTAIN APPROVAL FOR ALL TRENCHING AND PATCHING WITHIN CITY RIGHT OF WAY WITH CITY OF PORTSMOUTH DPW PRIOR TO COMMENCING WORK.



MOUNTABLE VERTICAL GRANITE CURB
NO SCALE


NOTES:
 1. SEE SITE PLAN(S) FOR LIMITS OF MOUNTABLE VERTICAL GRANITE CURB (MVG).
 2. ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.
 3. MINIMUM LENGTH OF STRAIGHT CURB STONES = 3'
 4. MAXIMUM LENGTH OF STRAIGHT CURB STONES = 10'
 5. MAXIMUM LENGTH OF STRAIGHT CURB STONES LAID ON CURVES (SEE TABLE).
 6. ALL RADII 20 FEET AND SMALLER SHALL BE CONSTRUCTED USING CURVED SECTIONS.
 7. JOINTS BETWEEN STONES SHALL HAVE A MAXIMUM SPACING OF 1/2\"/>



SLOPED GRANITE CURB
NO SCALE

NOTES:
 1. SEE SITE PLAN(S) FOR LIMITS OF SLOPED GRANITE CURB (SGC).
 2. ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE SAME LENGTH.
 3. MINIMUM LENGTH OF STRAIGHT CURB STONES = 18\"/>

RADIUS	MAX LENGTH
<2'	USE CURVED CURB
2'-15'	USE RADIAL JOINTS
16'-28'	1'-6"
29'-41'	2'
42'-55'	3'
56'-68'	4'
69'-82'	5'
83'-96'	6'
97'-110'	7'
>110'	8'




CONCRETE SIDEWALK
NO SCALE

NOTES:
 1. SEE SITE PLAN FOR SIDEWALK WIDTH AND LOCATIONS.
 2. SEE GRADING, DRAINAGE & EROSION CONTROL PLAN FOR WALK AND SIDE SLOPE GRADES.


NHDOT ITEM No. 304.3 (CRUSHED GRAVEL)	
SIEVE SIZE	% PASSING
3"	100
2"	95-100
1"	55-85
#4	27-52
#200	0-12

NHDOT ITEM No. 304.2 (GRAVEL)	
SIEVE SIZE	% PASSING
6"	100
#4	25-70
#200	0-12




GRASS PAVER FIRE LANE SECTION
NO SCALE

NOTES:
 1. SEE GRADING, DRAINAGE, UTILITIES AND EROSION CONTROL PLAN FOR SLOPE AND CROSS-SLOPE.
 2. POROUS GRASS PAVER SHALL BE GRASSPAVE², BY INVISIBLE STRUCTURESTM OR APPROVED EQUAL.
 3. INSTALL BASE COURSE AGGREGATE TO A MAXIMUM OF 95% COMPACTION STANDARD PROCTOR (ASTM D698 / AASHTO T99).
 4. THE DENSITY OF SUBBASE COURSES SHALL BE DETERMINED BY AASHTO T 191 (SAND-CONE METHOD), AASHTO T 204 (DRIVE CYLINDER METHOD), OR AASHTO T 238 (NUCLEAR METHODS), OR OTHER APPROVED METHODS AT THE DISCRETION OF THE SUPERVISING ENGINEER.



CURB TRANSITION
NO SCALE

NOTES:
 1. THE INTENT OF THIS ITEM IS TO PROVIDE A SMOOTH TRANSITION BETWEEN VERTICAL GRANITE CURB AND MOUNTABLE VERTICAL GRANITE CURB WITHOUT REQUIRING FIELD CHIPPING DURING INSTALLATION. THE MOUNTABLE VERTICAL GRANITE CURB MAY REQUIRE ADJUSTMENTS TO MEET THE TRANSITION PIECE HEIGHT. TRANSITION SLOPE CURB TO STANDARD REVEAL AS QUICKLY AS POSSIBLE TO PROVIDE FOR THIS SMOOTH TRANSITION.



CONCRETE STAMPED COBBLE STONE ISLAND
NO SCALE

NOTES:
 1. CONCRETE TO BE 4500 PSI, 7% AIR ENTRAINMENT

Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
 Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session


PROJECT NO: C0960-011
 DATE: January 27, 2021
 FILE: C0960-011_C-DTLS.DWG
 DRAWN BY: AFS
 CHECKED: NAH/PMC
 APPROVED: BLM

DETAILS SHEET



SCALE: AS SHOWN

C-503



Last Saved: 3/22/2021 11:17:11 AM By: ASeller
 Plotted On: Mar 22, 2021 11:17:11 AM
 Tighe & Bond File: C:\Users\ASeller\OneDrive\Documents\C0960-011_53 Green St. Portsmouth, NH Drawings_Figures\AutoCAD\C0960-011_C-DTLS.dwg



- NOTE:
1. GRATE TO BE CAST IRON (NHDOT TYPE B)
 2. FRAME AND GRATE TO BE MANUFACTURED IN THE USA




CATCH BASIN FRAME & GRATE
NO SCALE




- NOTES:
1. MANHOLE FRAME AND COVER SHALL BE 32" HINGED ERGO XL BY EJ CO.
 2. ALL DIMENSIONS ARE NOMINAL.
 3. FRAMES USING NARROWER DIMENSIONS FOR THICKNESS ARE ALLOWED PROVIDED:
 - A. THE FRAMES MEET OR EXCEED THE SPECIFIED LOAD RATING.
 - B. THE INTERIOR PERIMETER (SEAT AREA) DIMENSIONS OF THE FRAMES REMAIN THE SAME TO ALLOW CONTINUED USE OF EXISTING GRATES/COVERS AS THE EXISTING FRAMES ALLOW, WITHOUT SHIMS OR OTHER MODIFICATIONS OR ACCOMMODATIONS.
 - C. ALL OTHER PERTINENT REQUIREMENTS OF THE SPECIFICATIONS ARE MET.
 4. LABEL TYPE OF MANHOLE WITH 3" HIGH LETTERS IN THE CENTER OF THE COVER.


DRAIN MANHOLE FRAME & COVER
NO SCALE



DRAIN CLEAN-OUT
NO SCALE



STORM DRAIN TRENCH
NO SCALE




- NOTES:
1. ALL CATCH BASIN OUTLETS TO HAVE "ELIMINATOR" OIL AND FLOATING DEBRIS TRAP MANUFACTURED BY KLEANSTREAM (NO EQUAL)
 2. INSTALL DEBRIS TRAP TIGHT TO INSIDE OF STRUCTURE.
 3. 1/4" HOLE SHALL BE DRILLED IN TOP OF DEBRIS TRAP

"ELIMINATOR" OIL FLOATING DEBRIS TRAP
NO SCALE


NOMINAL PIPE SIZE I.D.*		OVERALL LENGTH**		NUMBER OF CLAMPS	CUFF DEPTH		BACK PRESSURE RATING	
Inches	Millimeters	Inches	Millimeters		Inches	Millimeters	Feet	Meters
18	450	31	787	1	4	102	20	6

Mounting Styles and Configurations




Flange shape and bolt pattern can be customized. Flangeless thimble inserts are available.

TYPICAL BACK FLOW PREVENTER
NO SCALE



- NOTES:
1. GRATES/SOLID COVER SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05.
 2. FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
 3. SEE GRADING, DRAINAGE, AND EROSION CONTROL PLAN FOR LOCATIONS.


YARD DRAIN
NO SCALE



- NOTES:
1. ALL SECTIONS SHALL BE CONCRETE CLASS AA(4000 PSI).
 2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQ. IN. PER LINEAR FT. IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
 3. THE TONGUE AND GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQ. IN. PER LINEAR FT.
 4. RISERS OF 1', 2', 3' & 4' CAN BE USED TO REACH DESIRED DEPTH.
 5. THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.
 6. FITTING FRAME TO GRADE MAY BE DONE WITH PREFABRICATED ADJUSTMENT RINGS OR CLAY BRICKS (2 COURSES MAX.).
 7. CONE SECTIONS MAY BE EITHER CONCENTRIC OR ECCENTRIC, OR FLAT SLAB TOPS MAY BE USED WHERE PIPE WOULD OTHERWISE ENTER INTO THE CONE SECTION OF THE STRUCTURE AND WHERE PERMITTED.
 8. PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING.
 9. OUTSIDE EDGES OF PIPES SHALL PROJECT NO MORE THAN 3" BEYOND INSIDE WALL OF STRUCTURE.
 10. PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS.
 11. THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.
 12. "ELIMINATOR" OIL/WATER SEPARATOR SHALL BE INSTALLED TIGHT TO INSIDE OF CATCHBASIN.


4\"/>

NHDOT ITEM No. 304.4 (CRUSHED STONE - FINE)	
SIEVE SIZE	% PASSING
2"	100
1-1/2"	85-100
3/4"	45-75
#4	10-45
#200	0-5



- NOTES:
1. ALL SECTIONS SHALL BE 4,000 PSI CONCRETE.
 2. CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
 3. THE TONGUE AND THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.
 4. THE STRUCTURES SHALL BE DESIGNED FOR H2O LOADING.
 5. CONSTRUCT CRUSHED STONE BEDDING AND BACKFILL UNDER (6" MINIMUM THICKNESS)
 6. THE TONGUE AND GROOVE JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.
 7. PIPE ELEVATIONS SHOWN ON PLANS SHALL BE FIELD VERIFIED PRIOR TO PRECASTING.
 8. OUTSIDE EDGES OF PIPES SHALL PROJECT NO MORE THAN 3" BEYOND INSIDE WALL OF STRUCTURE.
 9. PRECAST SECTIONS SHALL HAVE A TONGUE AND GROOVE JOINT 4" HIGH AT AN 11° ANGLE CENTERED IN THE WIDTH OF THE WALL AND SHALL BE ASSEMBLED USING AN APPROVED FLEXIBLE SEALANT IN JOINTS.
 10. ALL STRUCTURES WITH MULTIPLE PIPES SHALL HAVE A MINIMUM OF 12" OF INSIDE SURFACE BETWEEN HOLES, NO MORE THAN 75% OF A HORIZONTAL CROSS SECTION SHALL BE HOLES, AND THERE SHALL BE NO HOLES CLOSER THAN 3" TO JOINTS.

4\"/>



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
PROJECT NO:	C0960-011	
DATE:	January 27, 2021	
FILE:	C0960-011_C-DTLS.DWG	
DRAWN BY:	AFS	
CHECKED:	NAH/PMC	
APPROVED:	BLM	


DETAILS SHEET

SCALE: AS SHOWN


C-504

STATE OF NEW HAMPSHIRE
 BRADLEE MEZQUITA
 No. 0983-D
 LICENSED PROFESSIONAL ENGINEER

STATE OF NEW HAMPSHIRE
 PATRICK CRIMMINS
 No. 12378
 LICENSED PROFESSIONAL ENGINEER
 03/22/2021




PLAN VIEW



SECTION VIEW


1,000 GALLON GREASE TRAP
NO SCALE

- NOTES:**
1. STEEL REINFORCEMENT SHALL CONFORM TO LATEST ASTM SPECIFICATIONS: ASTM-A615 GRADE 60 REBAR.
 2. CONCRETE SHALL BE $F_c=5,000$ PSI @ 28 DAYS MINIMUM.
 3. FLEXIBLE SLEEVES SHALL BE PROVIDED ON ALL PIPE CONNECTIONS.
 4. JOINT SHALL BE SEALED WITH ONE STRIP OF BUTYL RUBBER SEALANT.
 5. INLET SHALL PENETRATE AT LEAST 9" BELOW THE LIQUID LEVEL, BUT NOT DEEPER THAN THE OUTLET BAFFLE.
 6. OUTLET SHALL EXTEND BELOW THE SURFACE OF THE LIQUID EQUAL TO 40% OF THE LIQUID DEPTH (19").
 7. DESIGN LOADING SHALL BE: AASHTO-HS20-44, ASTM C-890-06.
 8. DESIGN SPECIFIED AS: ASTM C-1227-08, ASTM C-913-08.
 9. FRAMES AND COVERS: MANHOLE FRAMES AND COVERS WITHIN CITY RIGHT OF WAY SHALL BE CITY STANDARD HINGE COVERS MANUFACTURED BY EJ. FRAMES AND COVERS WILL BE PURCHASED FROM THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS. ALL OTHER MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A 30-INCH CLEAR OPENING. A 3-INCH (MINIMUM HEIGHT) WORD "SEWER" SHALL BE PLAINLY CAST INTO THE CENTER OF EACH COVER.
 10. GREASE TRAP SHALL BE PHOENIX PRECAST CONCRETE P/N: C-6420 OR EQUAL.
 11. TANK SHALL BE PUMPED AS NEEDED.




MANHOLE JOINTS
NO SCALE

- NOTES:**
1. HORIZONTAL JOINTS BETWEEN THE SECTIONS OF PRECAST CONCRETE BARRELS SHALL BE PER CITY OF PORTSMOUTH DPW STANDARD AND SHALL BE SEALED FOR WATERTIGHTNESS USING A DOUBLE ROW ELASTOMERIC OR MASTIC-LIKE GASKET.
 2. PIPE TO MANHOLE JOINTS SHALL BE PER CITY OF PORTSMOUTH STANDARD.
 3. FOR BITUMASTIC TYPE JOINTS THE AMOUNT OF SEALANT SHALL BE SUFFICIENT TO FILL AT LEAST 75% OF THE JOINT CAVITY.
 4. ALL GASKETS, SEALANTS, MORTAR, ETC. SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS' WRITTEN INSTRUCTIONS.




SEWER SERVICE TRENCH
NO SCALE

- NOTE:**
1. CRUSHED STONE BEDDING FOR FULL WIDTH OF THE TRENCH FROM 6" BELOW PIPE IN EARTH AND 12" BELOW PIPE IN ROCK. CRUSHED STONE SHALL ALSO COMPLETELY ENCASE THE PIPE AND COVER THE PIPE TO A GRADE 6" OVER THE TOP OF THE PIPE FOR THE ENTIRE WIDTH OF THE TRENCH.
 2. COORDINATE ALL INSTALLATIONS WITH THE CITY OF PORTSMOUTH.




SECTION A-A




PLAN

INSIDE DROP MANHOLE
NO SCALE


- NOTES:**
1. RISER PIPE AND FITTINGS SHALL BE THE SAME DIAMETER AS THE INLET PIPE AND SHALL BE CONSTRUCTED OF SDR35 PVC PIPE.
 2. SANITARY SEWER SHALL BE INSTALLED PER THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS STANDARDS.
 3. COORDINATE ALL INSTALLATIONS WITH THE CITY OF PORTSMOUTH.



PIPE STRAP DETAIL




SECTION B-B



SECTION A-A

SEWER MANHOLE
NO SCALE

- NOTES:**
1. INVERT AND SHELF TO BE PLACED AFTER EACH LEAKAGE TEST.
 2. CARE SHALL BE TAKEN TO INSURE THAT THE BRICK INVERT IS A SMOOTH CONTINUATION OF THE SEWER INVERT.
 3. INVERT BRICKS SHALL BE LAID ON EDGE.
 4. TWO (2) COATS OF BITUMINOUS WATERPROOF COATING SHALL BE APPLIED TO ENTIRE EXTERIOR OF MANHOLE.
 5. FRAMES AND COVERS: MANHOLE FRAMES AND COVERS WITHIN CITY RIGHT OF WAY SHALL BE CITY STANDARD HINGE COVERS MANUFACTURED BY EJ. FRAMES AND COVERS WILL BE PURCHASED FROM THE CITY OF PORTSMOUTH DEPARTMENT OF PUBLIC WORKS. ALL OTHER MANHOLE FRAMES AND COVERS SHALL BE OF HEAVY DUTY DESIGN AND PROVIDE A 30-INCH CLEAR OPENING. A 3-INCH (MINIMUM HEIGHT) WORD "SEWER" SHALL BE PLAINLY CAST INTO THE CENTER OF EACH COVER.
 6. HORIZONTAL JOINTS SHALL BE SEALED FOR WATER TIGHTNESS USING A DOUBLE ROW OF ELASTOMERIC OR MASTIC-LIKE SEALANT.
 7. BARREL AND CONE SECTIONS SHALL BE PRECAST REINFORCED CONCRETE DESIGNED FOR H20 LOADING, AND CONFORMING TO ASTM C478-06.



TYPICAL SECTION

Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
MARK	DATE	DESCRIPTION


PROJECT NO: C0960-011
 DATE: January 27, 2021
 FILE: C0960-011_C-DTLS.DWG
 DRAWN BY: AFS
 CHECKED: NAH/PMC
 APPROVED: BLM

DETAILS SHEET

SCALE: AS SHOWN

C-505


Last Saved: 3/22/2021 11:11:18am By: ASeller
 Plotted On: Mar 22, 2021 11:11:18am By: ASeller
 Tighe & Bond File: C:\Users\ASeller\OneDrive\Documents\C0960-011_53 Green St., Portsmouth, NH Drawings - Figures\AutoCAD\C0960-011_C-DTLS.dwg




THRUST BLOCKING DETAIL
NO SCALE

REACTION TYPE	PIPE SIZE				
	4"	6"	8"	10"	12"
A 90°	0.89	2.19	3.82	11.14	17.24
B 180°	0.65	1.55	2.78	8.38	12.00
C 45°	0.48	1.19	2.12	6.02	9.32
D 22-1/2°	0.25	0.60	1.06	3.08	4.74
E 11-1/4°	0.13	0.30	0.54	1.54	2.38


- TEST PRESSURE = 200PSI
- NOTES:
- POUR THRUST BLOCKS AGAINST UNDISTURBED MATERIAL, WHERE TRENCH WALL HAS BEEN DISTURBED, EXCAVATE LOOSE MATERIAL AND EXTEND THRUST BLOCK TO UNDISTURBED MATERIAL. NO JOINTS SHALL BE COVERED WITH CONCRETE.
 - ON BENDS AND TEES, EXTEND THRUST BLOCKS FULL LENGTH OF FITTING.
 - PLACE BOARD IN FRONT OF ALL PLUGS BEFORE POURING THRUST BLOCKS.
 - WHERE M.J. PIPE IS USED, M.J. PLUG WITH RETAINER GLAND MAY BE SUBSTITUTED FOR END BLOCKINGS.
 - INSTALLATION AND STANDARD DIMENSIONAL REQUIREMENTS SHALL BE WITH CITY OF PORTSMOUTH WATER DEPARTMENT STANDARDS.




GAS TRENCH
NO SCALE



WATER TRENCH
NO SCALE




PLAN



SECTION A-A


- NOTES:
- DIMENSIONS SHOWN REPRESENT TYPICAL REQUIREMENTS. MANHOLE LOCATIONS AND REQUIREMENTS SHALL BE COORDINATED WITH EVERSOURCE PRIOR TO CONSTRUCTION
 - CONCRETE MINIMUM STRENGTH - 4,000 PSI @ 28 DAYS
 - STEEL REINFORCEMENT - ASTM A615, GRADE 60
 - PAD MEETS OR EXCEEDS EVERSOURCE SPECIFICATIONS

3-PHASE TRANSFORMER PAD
NO SCALE




PAD-MOUNTED EQUIPMENT GROUNDING GRID DETAIL
NO SCALE

- NOTES:
- THE GROUND GRID SHALL BE SUPPLIED AND INSTALLED BY THE CONTRACTOR AND IS TO BE BURIED AT LEAST 12 INCHES BELOW GRADE. EIGHT FEET OF EXTRA WIRE FOR EACH GROUND GRID LEG SHALL BE LEFT EXPOSED IN THE CABLE COMPARTMENT TO ALLOW FOR THE CONNECTION TO THE TRANSFORMER. THE TWO 8-FOOT GROUND RODS MAY BE EITHER GALVANIZED STEEL OR COPPERWELD AND THEY SHALL BE CONNECTED TO THE GRID WITH NEC APPROVED CONNECTORS.




ELECTRICAL AND COMMUNICATION CONDUIT
NO SCALE

- NOTES:
- NUMBER, MATERIAL, AND SIZE OF UTILITY CONDUITS TO BE DETERMINED BY LOCAL UTILITY OR AS SHOWN ON ELECTRICAL DRAWINGS. CONTRACTOR TO PROVIDE ONE SPARE CONDUIT FOR EACH UTILITY TO BUILDING.
 - DIMENSIONS SHOWN REPRESENT OWNERS MINIMUM REQUIREMENTS. ACTUAL DIMENSIONS MAY BE GREATER BASED ON UTILITY COMPANY STANDARDS, BUT SHALL NOT BE LESS THAN THOSE SHOWN. NO CONDUIT RUN SHALL EXCEED 360 DEGREES IN TOTAL BENDS.
 - A SUITABLE PULLING STRING, CAPABLE OF 200 POUNDS OF PULL, MUST BE INSTALLED IN THE CONDUIT BEFORE UTILITY COMPANY IS NOTIFIED TO INSTALL CABLE. THE STRING SHOULD BE BLOWN INTO THE CONDUIT AFTER THE RUN IS ASSEMBLED TO AVOID BONDING THE STRING TO THE CONDUIT.
 - UTILITY COMPANY MUST BE GIVEN THE OPPORTUNITY TO INSPECT THE CONDUIT PRIOR TO BACKFILL. THE CONTRACTOR IS RESPONSIBLE FOR ALL REPAIRS SHOULD THE UTILITY COMPANY BE UNABLE TO INSTALL ITS CABLE IN A SUITABLE MANNER.
 - ALL CONDUIT INSTALLATIONS MUST CONFORM TO THE CURRENT EDITION OF THE NATIONAL ELECTRIC SAFETY CODE, STATE AND LOCAL CODES AND ORDINANCES, AND, WHERE APPLICABLE, THE NATIONAL ELECTRIC CODE.
 - ALL 90° SWEEPS WILL BE MADE USING RIGID GALVANIZED STEEL. SWEEPS WITH A 36 TO 48 INCH RADIUS.
 - SAND BEDDING TO BE REPLACED WITH CONCRETE ENCASEMENT WHERE COVER IS LESS THAN 3 FEET, WHEN LOCATED BELOW PAVEMENT, OR WHERE SHOWN ON THE UTILITIES PLAN.





DISTRICT STANDARD LIGHT FIXTURE BASE
NO SCALE

- NOTES:
- REFER TO ELECTRICAL PLANS FOR WIRING DETAILS.
 - CONCRETE: 4000 PSI, AIR ENTRAINED STEEL: 60 KSI
 - LIGHT POLE FOUNDATIONS SHALL BE PLACED PRIOR TO INSTALLATION OF BRICK PAVERS.
 - CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL, TO INCLUDE PERFORMANCE SPECIFICATIONS, CALCULATIONS AND NH LICENSED STRUCTURAL ENGINEER'S STAMP FOR LIGHT POLE FOUNDATION.
 - STANDARD BASE SHALL BE CONSTRUCTED UNLESS THERE IS CONFLICT WITH THE EXISTING DUCT BANK. SPREAD FOOTING BASE SHALL BE USED IN LIEU OF STANDARD BASE IN LOCATIONS WHERE TOP OF DUCT BANK ELEVATION WILL CONFLICT WITH STANDARD POLE BASE DEPTH. CONTRACTOR SHALL VERIFY LOCATIONS WHERE SPREAD FOOTINGS ARE REQUIRED PRIOR TO CONSTRUCTION. SEE NOTE#4 FOR SUBMITTAL REQUIREMENTS.



DISTRICT STANDARD LIGHT POLE & FIXTURE
NO SCALE

- LUMINAIRE SPECIFICATIONS:
- CATALOGUE NO.: K729-P4FL-II-60(SSL)
-7030-120-277-3K S/F KPL20
- GLOBE MAT'L: FLAT ARRAY, CLEAR FLAT LENS
TYPE II
- WATTAGE: 60W (7030 SERIES)
- LIGHT SOURCE: SOLID STATE LIGHTING
- LINE VOLTAGE: 120-277V
- CCT: 3000K
- PAINT: TEXTURED BLACK
- OPTIONS: S/F KPL-20 LEVELING DEVICE
- ARM SPECIFICATIONS:
- CATALOGUE NO.: (MOD.) KA72-T-1-3
- MATERIAL: ALUMINUM
- PAINT: TEXTURED BLACK
- OPTIONS: KPL20 LEVELING DEVICE
- POLE SPECIFICATIONS:
- CATALOGUE NO.: KBH16-G-S11-SBP
- C/W 140-30/100 & DR
- SECTION: OCTAGONAL
- COLOUR: POLISHED
- FINISH: POLISHED
- POLE TOP: 6 3/8" FL/FL
- POLE BUTT: 9 1/2" Ø
- POLE LENGTH: 16' 6"
- APPROX. WEIGHT: 1,190 LBS.
- MIN. RACEWAY: 1 1/8" Ø



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session

PROJECT NO: C0960-011
DATE: January 27, 2021
FILE: C0960-011_C-DTLS.DWG
DRAWN BY: AFS
CHECKED BY: NAH/PMC
APPROVED BY: BLM

DETAILS SHEET



SCALE: AS SHOWN

Last Saved: 3/22/2021 11:11:11 AM By: ASeller
Plotted On: Mar 22, 2021 11:11:11 AM
Tighe & Bond 221 Commercial Center Portsmouth, NH 03801
Figures: AutoCAD (C0960-011_C-DTLS.dwg)


STATE OF NEW HAMPSHIRE
 BRADLEE MEZQUITA
 No. 09830
 LICENSED PROFESSIONAL ENGINEER

STATE OF NEW HAMPSHIRE
 PATRICK CRIMMINS
 No. 12378
 LICENSED PROFESSIONAL ENGINEER
 03/22/2021


OUTLET PLUNGE POOL SIZING						
HW1	Do	S	W	L	D ₅₀	D
18'	18'	9'	3.0'	5.0'	6'	15'



- NOTES:**
- ALL SECTIONS SHALL BE 4,000 PSI CONCRETE.
 - CIRCUMFERENTIAL REINFORCEMENT SHALL BE 0.12 SQUARE INCHES PER LINEAR FOOT IN ALL SECTIONS AND SHALL BE PLACED IN THE CENTER THIRD OF THE WALL.
 - THE TONGUE AND THE GROOVE OF THE JOINT SHALL CONTAIN ONE LINE OF CIRCUMFERENTIAL REINFORCEMENT EQUAL TO 0.12 SQUARE INCHES PER LINEAR FOOT.
 - THE STRUCTURES SHALL BE DESIGNED FOR H20 LOADING.
 - CONSTRUCT CRUSHED STONE BEDDING AND BACKFILL UNDER (6\"/>



OUTLET STRUCTURE DETAIL (PDMH4)
NO SCALE



**ELEVATION VIEW
JELLYFISH JFPD0806**
NO SCALE

JELLYFISH JFPD0806 - DESIGN NOTES

JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE CARTRIDGE LENGTH AND THE NUMBER OF CARTRIDGES. THE STANDARD PEAK DIVERSION STYLE WITH PRECAST TOP SLAB IS SHOWN. ALTERNATE OFFLINE VAULT AND/OR SHALLOW ORIENTATIONS ARE AVAILABLE. PEAK CONVEYANCE CAPACITY TO BE DETERMINED BY ENGINEER OF RECORD.

CARTRIDGE SELECTION	54"	40"	27"	15"
CARTRIDGE LENGTH	54"	40"	27"	15"
OUTLET INVERT TO STRUCTURE INVERT (A)	6'-6"	5'-4"	4'-3"	3'-3"
FLOW RATE HF-FLO / DRAINDOWN (CFS) (PER CART)	0.178 / 0.089	0.133 / 0.067	0.089 / 0.045	0.049 / 0.025
MAX. TREATMENT (CFS)	1.96	1.47	0.98	0.54
DECK TO INSIDE TOP (MIN) (B)	5.00	4.00	4.00	4.00

SITE SPECIFIC DATA REQUIREMENTS


STRUCTURE ID	JF-1
MODEL SIZE	JFPD0806
WATER QUALITY FLOW RATE (cfs)	0.95
PEAK FLOW RATE (cfs)	5.30
RETURN PERIOD OF PEAK FLOW (yrs)	25
# OF CARTRIDGES REQUIRED (HF / DD)	5/1
CARTRIDGE SIZE	54"

JELLYFISH FILTER DETAIL (JF-1)
NO SCALE


- GENERAL NOTES:**
- CONTECH TO PROVIDE ALL MATERIALS UNLESS NOTED OTHERWISE.
 - FOR SITE SPECIFIC DRAWINGS WITH DETAILED STRUCTURE DIMENSIONS AND WEIGHT, PLEASE CONTACT YOUR CONTECH ENGINEERED SOLUTIONS REPRESENTATIVE. www.contechES.com
 - JELLYFISH WATER QUALITY STRUCTURE SHALL BE IN ACCORDANCE WITH ALL DESIGN DATA AND INFORMATION CONTAINED IN THIS DRAWING. CONTRACTOR TO CONFIRM STRUCTURE MEETS REQUIREMENTS OF PROJECT.
 - STRUCTURE SHALL MEET AASHTO HS-20 OR PER APPROVING JURISDICTION REQUIREMENTS, WHICHEVER IS MORE STRINGENT, ASSUMING EARTH COVER OF 7'-3" AND GROUNDWATER ELEVATION AT OR BELOW THE OUTLET PIPE INVERT ELEVATION. ENGINEER OF RECORD TO CONFIRM ACTUAL GROUNDWATER ELEVATION. CASTINGS SHALL MEET AASHTO M306 LOAD RATING AND BE CAST WITH THE CONTECH LOGO.
 - STRUCTURE SHALL BE PRECAST CONCRETE CONFORMING TO ASTM C-478 AND AASHTO LOAD FACTOR DESIGN METHOD.
 - OUTLET PIPE INVERT IS EQUAL TO THE CARTRIDGE DECK ELEVATION.
 - THE OUTLET PIPE DIAMETER FOR NEW INSTALLATIONS IS TO BE ONE PIPE SIZE LARGER THAN THE INLET PIPE AT EQUAL OR GREATER SLOPE.
 - NO PRODUCT SUBSTITUTIONS SHALL BE ACCEPTED UNLESS SUBMITTED 10 DAYS PRIOR TO PROJECT BID DATE, OR AS DIRECTED BY THE ENGINEER OF RECORD.

- INSTALLATION NOTES:**
- ANY SUB-BASE, BACKFILL DEPTH, AND/OR ANTI-FLOTATION PROVISIONS ARE SITE-SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SPECIFIED BY ENGINEER OF RECORD.
 - CONTRACTOR TO PROVIDE EQUIPMENT WITH SUFFICIENT LIFTING AND REACH CAPACITY TO LIFT AND SET THE STRUCTURE (LIFTING CLUTCHES PROVIDED).
 - CONTRACTOR WILL INSTALL AND LEVEL THE STRUCTURE, SEALING THE JOINTS, LINE ENTRY AND EXIT POINTS (NON-SHRINK GROUT WITH APPROVED WATERSTOP OR FLEXIBLE BOOT).
 - CONTRACTOR TO TAKE APPROPRIATE MEASURES TO PROTECT CARTRIDGES FROM CONSTRUCTION-RELATED EROSION RUNOFF.
 - CARTRIDGE INSTALLATION, BY CONTECH, SHALL OCCUR ONLY AFTER SITE HAS BEEN STABILIZED AND THE JELLYFISH UNIT IS CLEAN AND FREE OF DEBRIS. CONTACT CONTECH TO COORDINATE CARTRIDGE INSTALLATION WITH SITE STABILIZATION AT (866) 749-5318.

Jellyfish Filter
 CONTECH ENGINEERED SOLUTIONS LLC
 www.contechES.com
 8025 Centre Pointe Dr., Suite 400, West Chester, OH 45399
 800-338-1122 513-645-7000 513-645-7993 FAX



HEADWALL WITH WINGWALLS
NO SCALE



DIMENSIONS AND QUANTITIES FOR ONE WING TYPE ENDWALL

D	B	C	G	H	K	L	P	Q	R	W	VOL.
IN. * FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	FT-IN	CY
18 1'-6"	2'-0"	3'-3"	6'-9"	9'-1 1/2"	7'-3 3/4"	1'-4 1/2"	0'-9 3/4"	3'-4 1/2"	5'-5 1/2"	5.87	
36 1'-6"	2'-0"	3'-3"	6'-8"	9'-1 1/2"	7'-3 3/4"	1'-4 1/2"	0'-9 3/4"	3'-4 1/2"	5'-5 1/2"	5.87	
42 1'-6"	2'-0"	3'-3"	7'-2"	9'-10 1/2"	7'-9 3/4"	1'-6 1/2"	0'-9 3/4"	3'-10 1/2"	6'-7 3/4"	6.67	

* FOR D < 36" USE DIMENSIONS LISTED FOR D = 36"

Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
MARK	DATE	DESCRIPTION
PROJECT NO:	C0960-011	
DATE:	January 27, 2021	
FILE:	C0960-011_C-DTLS.DWG	
DRAWN BY:	AFS	
CHECKED:	NAH/PMC	
APPROVED:	BLM	

DETAILS SHEET


SCALE: AS SHOWN

C-507

ACCEPTABLE FILL MATERIALS: STORMTECH SC-310 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBERS. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	AASHTO M145 ¹ A-1, A-2.4, A-3 OR AASHTO M43 ² 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN), DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN).
B	EMBEDMENT STONE: FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	AASHTO M43 ³ 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED.
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	AASHTO M43 ³ 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. ²

- PLEASE NOTE:
- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR, FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
 - STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
 - WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN AND CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.



NOTES:

- SC-310 CHAMBERS SHALL CONFORM TO THE REQUIREMENTS OF ASTM F2418 "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS", OR ASTM F2922 "STANDARD SPECIFICATION FOR POLYETHYLENE (PE) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-310 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- "ACCEPTABLE FILL MATERIALS" TABLE ABOVE PROVIDES MATERIAL LOCATIONS, DESCRIPTIONS, GRADATIONS, AND COMPACTION REQUIREMENTS FOR FOUNDATION, EMBEDMENT, AND FILL MATERIALS.
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- ONCE LAYER 'C' IS PLACED, ANY SOIL MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.

STORMTECH CHAMBER SPECIFICATIONS

- CHAMBERS SHALL BE STORMTECH SC-740, SC-310, OR APPROVED EQUAL.
- CHAMBERS SHALL BE MANUFACTURED FROM VIRGIN POLYPROPYLENE OR POLYETHYLENE RESINS.¹
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORT PANELS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL MEET ASTM F2922 (POLYETHYLENE) OR ASTM F2418 (POLYPROPYLENE), "STANDARD SPECIFICATION FOR THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".¹
- CHAMBERS SHALL BE DESIGNED AND ALLOWABLE LOADS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. THE CHAMBER MANUFACTURER SHALL SUBMIT THE FOLLOWING UPON REQUEST TO THE SITE DESIGN ENGINEER FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE:
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY AASHTO FOR THERMOPLASTIC PIPE.
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET. THE 50 YEAR CREEP MODULUS DATA SPECIFIED IN ASTM F2418 OR ASTM F2922 MUST BE USED AS PART OF THE AASHTO STRUCTURAL EVALUATION TO VERIFY LONG-TERM PERFORMANCE.
 - STRUCTURAL CROSS SECTION DETAIL ON WHICH THE STRUCTURAL EVALUATION IS BASED.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

NOTES FOR CONSTRUCTION EQUIPMENT¹


- STORMTECH SC-310 & SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".¹
- THE USE OF CONSTRUCTION EQUIPMENT OVER SC-310 & SC-740 CHAMBERS IS LIMITED:
 - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
 - NO RUBBER TIRE LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
 - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".¹
- FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.


CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-310/SC-740 SYSTEM

- STORMTECH SC-310 & SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.¹
- STORMTECH SC-310 & SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".¹
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS.¹ STORMTECH RECOMMENDS 3 BACKFILL METHODS:
 - STONESHOOTER LOCATED OFF THE CHAMBER BED.
 - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
 - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.¹
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.¹
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.¹
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.¹
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4"-2" (20-50 mm).¹
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.¹
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.



UNDERDRAIN DETAIL
NTS




SC-310 ISOLATOR ROW DETAIL
NTS

INSPECTION & MAINTENANCE

- STEP 1) INSPECT ISOLATOR ROW FOR SEDIMENT
- INSPECTION PORTS (IF PRESENT)
 - REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
 - REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
 - USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
 - LOWER A CAMERA INTO ISOLATOR ROW FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
 - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
 - ALL ISOLATOR ROWS
 - REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW
 - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW THROUGH OUTLET PIPE
 - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
 - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
 - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW USING THE JETVAC PROCESS
- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
 - APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
 - VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.


NOTES

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



SC-310 6\"/>

SC-310 TECHNICAL SPECIFICATION
NTS



NOMINAL CHAMBER SPECIFICATIONS

SIZE (W X H X INSTALLED LENGTH)	34.0\"/>	
CHAMBER STORAGE	14.7 CUBIC FEET (0.42 m ³)	(864 mm X 406 mm X 2169 mm)
MINIMUM INSTALLED STORAGE*	31.0 CUBIC FEET (0.88 m ³)	
WEIGHT	35.0 lbs. (16.8 kg)	

*ASSUMES 6" (152 mm) ABOVE, BELOW, AND BETWEEN CHAMBERS


PRE-FAB STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"
PRE-FAB STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"
PRE-GORED END CAPS END WITH "PC"

PART #	STUB	A	B	C
SC310EPE06T / SC310EPE06TPC	6" (150 mm)	9.6" (244 mm)	5.8" (147 mm)	—
SC310EPE08B / SC310EPE08BPC	8" (200 mm)	11.9" (302 mm)	—	0.5" (13 mm)
SC310EPE08T / SC310EPE08TPC	8" (200 mm)	11.9" (302 mm)	3.5" (89 mm)	—
SC310EPE08B / SC310EPE08BPC	10" (250 mm)	12.7" (323 mm)	—	0.6" (15 mm)
SC310EPE10T / SC310EPE10TPC	10" (250 mm)	12.7" (323 mm)	1.4" (36 mm)	—
SC310EPE10B / SC310EPE10BPC	12" (300 mm)	13.5" (343 mm)	—	0.7" (18 mm)
SC310EPE12B	12" (300 mm)	13.5" (343 mm)	—	0.9" (23 mm)

ALL STUBS, EXCEPT FOR THE SC310EPE12B ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

* FOR THE SC310EPE12B THE STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 0.25" (6 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session

PROJECT NO:	C0960-011
DATE:	January 27, 2021
FILE:	C0960-011_C-DTLS.DWG
DRAWN BY:	AFS
CHECKED:	NAH/PMC
APPROVED:	BLM

DETAILS SHEET

SCALE: AS SHOWN


C-508




Sculptures - Images



Wayfinding Signage



Pavers



Murals



Plant List

TREES

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Ap	<i>Acer palmatum</i>	Japanese Maple	1	4-5' Ht	B&B, specimen, dwarf
Ar	<i>Acer rubrum</i> 'Bowhall'	Bowhall Red Maple	3	2.5-3' Cal	B&B
Cc	<i>Crataegus crus-galli</i> 'Inermis'	Thornless Cockspur Hawthorn	5	2.5-3' Cal	B&B
Ns	<i>Nyssa Sylvatica</i> 'Red Rage'	Black Tupelo	3	4' Cal	B&B
Qr	<i>Quercus rubra</i>	Red Oak	6	2.5-3' Cal	B&B
Z	<i>Zelkova serrata</i> 'Green Vase'	Green Vase Zelkova	4	2.5-3' Cal	B&B


SHRUBS

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Rh	<i>Rhododendron maximum</i>	Rosebay Rhododendron	32	3-4' Ht	
Mic	<i>Microbiota decussata</i>	Russian Cypress	25	3 gal	B&B
Tax2	<i>Taxus media</i> 'Greenwave'	Greenwave Yew	14	5 gal	
Ig1	<i>Ilex glabra</i> 'Compacta'	Dwarf Inkberry	64	5 gal	
Ig2	<i>Ilex glabra</i> 'Shamrock'	Shamrock Inkberry	44	5 gal	full to ground
Jv	<i>Juniperus virginiana</i> 'Emerald Sentinel'	Emerald Sentinel Red Cedar	16	7-8' Ht	B&B
Rh	<i>Rhus aromatica</i> 'Grow-Low'	Grow Low Sumac	70	3 gal	
Tax1	<i>Taxus media</i> 'Ever-Low'	Ever-Low Yew	22	3 gal	
Arb	<i>Thuja occidentalis</i> 'Smaragd'	Emerald Green Arborvitae	29	7-8' Ht	B&B

PERENNIALS, GROUNDCOVERS, VINES and ANNUALS

Symbol	Botanical Name	Common Name	Quantity	Size	Comments
Am	<i>Amsonia hubrichtii</i>	Blue Star Flower	74	1 gal	
Ca	<i>Carex appalachica</i>	Appalachian Sedge	196	1 gal	
Cal	<i>Calamagrostis acutifolia</i> 'Karl Foerster'	Feather Reed Grass	62	1 gal	
Hak	<i>Hakonechloa macra</i>	Japanese Frost Grass	65	1 gal	
Lir	<i>Liriope spicata</i>	Lily Turf	20	1 gal	
Lawn	Penninton Smartseed Tall Fescue Blend				

Drawn By: VM
Checked By: RW
Scale: 1" = 20' - 0"
Date: March 22, 2021
Revisions:



Luminaire Schedule				
Symbol	Qty	Label	Arrangement	Description
☐	11	XW1	SINGLE	WS-W54614-XX
☐	13	XW2	SINGLE	WP-LED119-30

Calculation Summary						
Label	Units	Avg	Max	Min	Avg/Min	Max/Min
CalcPts_1	Fc	0.07	10.2	0.0	N.A.	N.A.

Date	Comments
* **/**/**	*****

Drawn By:	Checked By:
Date:	Specifier:
Scale:	N.T.S.

53 Green Street
Portsmouth, NH





Tighe & Bond

Proposed Mixed-Use Development
53 Green Street
Portsmouth, NH

Drainage Analysis

Prepared For:
CPI Management, LLC
100 Summer Street
Boston, Massachusetts 02110

March 22, 2021

Section 1 Project Description

1.1 On-Site Soil Description1-1
1.2 Pre- and Post-Development Comparison1-1
1.3 Calculation Methods.....1-2

Section 2 Pre-Development Conditions

2.1 Pre-Development Calculations.....2-1
2.2 Pre-Development Watershed Plans2-1

Section 3 Post-Development Conditions

3.1 Peak Rate Comparison3-2
3.2 Post-Development Calculations3-2
3.3 Post-Development Watershed Plans.....3-2

Section 4 Stormwater Treatment

4.1 Pre-Treatment Methods for Protecting Water Quality4-1
4.2 Treatment Methods for Protecting Water Quality4-1

Section 5 BMP Worksheet and Sizing Memos

Section 6 Long-Term Operation & Maintenance Plan

6.1 Contact/Responsible Party5-1
6.2 Maintenance Items5-1
6.3 Overall Site Operation & Maintenance Schedule5-2
6.3.1 Disposal Requirements.....5-5
6.3.2 Snow & Ice Management for Standard Asphalt and Walkways....5-5
6.4 Chloride Management Plan5-5
6.4.1 Background Information.....5-5
6.4.2 Operational Guidelines – Chloride Management.....5-5
6.4.3 Salt Usage Evaluation and Monitoring5-7
6.4.4 Summary5-7
6.5 Invasive Species5-10
6.6 Annual Updates and Log Requirements5-10

Appendices

A Site Specific Soils Report
B Extreme Precipitation Tables
C “Examination of Thermal Impacts from Stormwater BMPs”, By The University of
New Hampshire Stormwater Center

Section 1

Project Description

The proposed project is located at 53 Green Street in Portsmouth and is identified as Map 119, Lot 2 on the City of Portsmouth's Tax Maps. This parcel is approximately 1.65 acres. As part of this project, this parcel will acquire a portion of the adjacent lot that contains the rail line, identified as Tax Map 119 Lot 3. This will result in a total acreage of approximately 1.77 acres for the proposed parcel. The parcel is bounded to the north and west by North Mill Pond, to the south by an adjacent parcel, and to the east by Green Street and the Boston and Maine (B&M) railroad.

The lot is currently occupied by two (2) single-story commercial tenant buildings, which total approximately 21,000 square feet, and associated parking. The lot is predominantly impervious and has a maintained lawn area along the North Mill Pond shoreline. There is an existing utility easement on the north corner of the parcel which contains a utility tower with overhead wire connections, not directly associated with the site.

The proposed project includes the demolition of the two existing single-story structures and construction of a single five story mixed-use building. The project will include associated site improvements that consist of below grade parking, utilities, stormwater management and treatment, landscaping, lighting, and a public recreation trail in coordination with the City. Additionally, the land associated with the public recreation trail will be deeded to the City of Portsmouth and designated as community space for the City's North Mill Pond Trail project.

1.1 On-Site Soil Description

The site is a highly disturbed site along the North Mill Pond. The property shows evidence of what appears to be very old filling and grading associated with the existing development. The site consists of terrain that is generally flat and slopes from the south to the north to North Mill Pond. The existing property has an approximate high point of elevation of 14 near Green Street

A site specific soils survey was conducted by Leonard Lord, PhD, CSS, CWS of Tighe & Bond, Inc and can be found in Appendix A of this Report. Based on the soil survey, the runoff analyzed within these studies has been modeled using mostly Hydrologic Soil Group B soils and some portions of Hydrologic Soil Group C soils, as much of the site is comprised of Udorthents with two drainage classifications, moderately poorly drained soils and portions of well drained soils.

1.2 Pre- and Post-Development Comparison

The pre-development and post-development watershed areas have been analyzed at a single point of analysis. While the point of analysis remained unchanged, its contributing sub-catchment areas varied between pre-development and post-development conditions. These adjustments were made to reflect the differences in drainage patterns between the existing and proposed conditions. The overall area analyzed as part of this drainage analysis was held constant. For reference, PA-1 assesses flows that discharge directly to North Mill Pond via overland flow or various outlets.

Since North Mill Pond is a tidal water, NHDES does not require peak runoff control requirements to be met (Env-Wq 1507.06(d)). However, a Stormtech Isolator Row and detention system is proposed on the development site for the purpose of mitigating temperature differences between the stormwater runoff and the North Mill Pond.

1.3 Calculation Methods

The design storms analyzed in this study are the 2-year, 10-year, 25-year and 50-year 24-hour duration storm events. The stormwater modeling system, HydroCAD 10.0 was utilized to predict the peak runoff rates from these storm events. The peak discharge rates were determined by analyzing Type III 24-hour storm events. The rainfall data for these storm events was obtained from the data published by the Northeast Regional Climate Center at Cornell University, with an additional 15% added factor of safety as required by Env-Wq 1503.08(l).

Table 1.2: Extreme Precipitation Estimates (NRCC)

YEAR	24-hr Estimate (inches)	+ 15% (inches)
2	3.20	3.68
10	4.86	5.59
25	6.16	7.08
50	7.37	8.48

The time of concentration was computed using the TR-55 Method, which provides a means of determining the time for an entire watershed to contribute runoff to a specific location via sheet flows, shallow concentrated flow and channel flow. Runoff curve numbers were calculated by estimating the coverage areas and then summing the curve number for the coverage area as a percent of the entire watershed.

References:

1. HydroCAD Stormwater Modeling System, by HydroCAD Software Solutions LLC, Chocorua, New Hampshire.
2. New Hampshire Stormwater Management Manual, Volume 2, Post-Construction Best Management Practices Selection and Design, December 2008.
3. "Extreme Precipitation in New York & New England." Extreme Precipitation in New York & New England by Northeast Regional Climate Center (NRCC), 26 June 2012.

Section 2

Pre-Development Conditions

In order to analyze the pre-development condition, the site has been divided into one (1) watershed area modeled at one (1) point of analysis. This point of analysis and watershed are depicted on the plan entitled "Pre-Development Watershed Plan", Sheets C-801.

The point of analysis and its contributing watershed area is described below:


Point of Analysis (PA-1)

Point of Analysis 1 (PA-1) is the North Mill Pond which borders the northwest boundary of the site. The North Mill Pond is a tidal wetland which directly feeds into the Piscataqua River.



Pre-development Watershed 1.0 (PRE 1.0) is the single watershed analyzed in the pre-development condition. It is comprised of mostly impervious surfaces including paved parking and structures, disturbed forested areas to the north and west adjacent to the North Mill Pond shoreline and a maintained lawn between the building and shoreline. Runoff from this watershed area travels via overland flow to discharge into North Mill Pond. The runoff is currently untreated before discharge.

2.1 Pre-Development Calculations

2.2 Pre-Development Watershed Plans



POINT OF ANALYSIS 1



C0960-011 PRE

Prepared by Tighe & Bond

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Printed 3/22/2021

Page 2

Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
26,605	61	>75% Grass cover, Good, HSG B (PRE 1.0)
2,659	74	>75% Grass cover, Good, HSG C (PRE 1.0)
23,291	98	Paved parking, HSG B (PRE 1.0)
21,715	98	Roofs, HSG B (PRE 1.0)
4,041	55	Woods, Good, HSG B (PRE 1.0)
78,311	82	TOTAL AREA

C0960-011 PRE

Prepared by Tighe & Bond

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Printed 3/22/2021

Page 3

Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
0	HSG A	
75,652	HSG B	PRE 1.0
2,659	HSG C	PRE 1.0
0	HSG D	
0	Other	
78,311		TOTAL AREA

C0960-011 PRE

Type III 24-hr 2 Year Storm Rainfall=3.68"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 4

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentPRE 1.0:

Runoff Area=78,311 sf 57.47% Impervious Runoff Depth=1.93"
Flow Length=380' Tc=5.0 min CN=82 Runoff=4.17 cfs 12,610 cf

Link PA-1: POINT OF ANALYSIS1

Inflow=4.17 cfs 12,610 cf
Primary=4.17 cfs 12,610 cf

Total Runoff Area = 78,311 sf Runoff Volume = 12,610 cf Average Runoff Depth = 1.93"
42.53% Pervious = 33,305 sf 57.47% Impervious = 45,006 sf

C0960-011 PRE

Type III 24-hr 10 Year Storm Rainfall=5.59"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 5

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentPRE 1.0:

Runoff Area=78,311 sf 57.47% Impervious Runoff Depth=3.61"
Flow Length=380' Tc=5.0 min CN=82 Runoff=7.74 cfs 23,570 cf

Link PA-1: POINT OF ANALYSIS1

Inflow=7.74 cfs 23,570 cf
Primary=7.74 cfs 23,570 cf

Total Runoff Area = 78,311 sf Runoff Volume = 23,570 cf Average Runoff Depth = 3.61"
42.53% Pervious = 33,305 sf 57.47% Impervious = 45,006 sf

Summary for Subcatchment PRE 1.0:

Runoff = 7.74 cfs @ 12.08 hrs, Volume= 23,570 cf, Depth= 3.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
 Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
21,715	98	Roofs, HSG B
23,291	98	Paved parking, HSG B
26,605	61	>75% Grass cover, Good, HSG B
4,041	55	Woods, Good, HSG B
2,659	74	>75% Grass cover, Good, HSG C
78,311	82	Weighted Average
33,305		42.53% Pervious Area
45,006		57.47% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
0.9	100	0.0330	1.80		Sheet Flow, Smooth surfaces n= 0.011 P2= 3.68"
1.9	223	0.0090	1.93		Shallow Concentrated Flow, Paved Kv= 20.3 fps
0.7	57	0.0400	1.40		Shallow Concentrated Flow, Short Grass Pasture Kv= 7.0 fps
3.5	380	Total, Increased to minimum Tc = 5.0 min			

Summary for Link PA-1: POINT OF ANALYSIS 1

Inflow Area = 78,311 sf, 57.47% Impervious, Inflow Depth = 3.61" for 10 Year Storm event
 Inflow = 7.74 cfs @ 12.08 hrs, Volume= 23,570 cf
 Primary = 7.74 cfs @ 12.08 hrs, Volume= 23,570 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs

C0960-011 PRE

Type III 24-hr 25 Year Storm Rainfall=7.08"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 1

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

SubcatchmentPRE 1.0:

Runoff Area=78,311 sf 57.47% Impervious Runoff Depth=4.99"
Flow Length=380' Tc=5.0 min CN=82 Runoff=10.58 cfs 32,572 cf

Link PA-1: POINT OF ANALYSIS1

Inflow=10.58 cfs 32,572 cf
Primary=10.58 cfs 32,572 cf

Total Runoff Area = 78,311 sf Runoff Volume = 32,572 cf Average Runoff Depth = 4.99"
42.53% Pervious = 33,305 sf 57.47% Impervious = 45,006 sf

C0960-011 PRE

Type III 24-hr 50 Year Storm Rainfall=8.48"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 2

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method




SubcatchmentPRE 1.0:

Runoff Area=78,311 sf 57.47% Impervious Runoff Depth=6.32"
Flow Length=380' Tc=5.0 min CN=82 Runoff=13.25 cfs 41,222 cf

Link PA-1: POINT OF ANALYSIS1

Inflow=13.25 cfs 41,222 cf
Primary=13.25 cfs 41,222 cf

Total Runoff Area = 78,311 sf Runoff Volume = 41,222 cf Average Runoff Depth = 6.32"
42.53% Pervious = 33,305 sf 57.47% Impervious = 45,006 sf









Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

LEGEND

-  PRE-DEVELOPMENT WATERSHED BOUNDARY
-  LONGEST FLOW PATH
-  SOIL TYPE BOUNDARY
-  SOIL TYPE (SEE SITE SPECIFIC SOIL MAP)
-  PRE DEVELOPMENT WATERSHED AREA DESIGNATION
-  POINT OF ANALYSIS

Last Saved: 3/19/2021
 Plotted On: Mar 22, 2021 10:16am By: ASellar
 Tighe & Bond 2310 Copied Calendars\C0960-011_53 Green St. Portsmouth, NH Drawings_Figures\AutoCAD\C0960-011_C-DSGN.dwg

B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
MARK	DATE	DESCRIPTION
PROJECT NO:	C0960-011	
DATE:	January 27, 2021	
FILE:	C0960-011_C-DSGN.DWG	
DRAWN BY:	AFS	
CHECKED:	NAH/PMC	
APPROVED:	BLM	

PRE-DEVELOPMENT WATERSHED PLAN

SCALE: AS SHOWN

Section 3

Post-Development Conditions

The post-development condition was analyzed by dividing the watersheds into five (5) watershed areas. Stormwater runoff from these sub-catchments predominantly flows via subsurface drainage systems prior to discharging into North Mill Pond (PA-1). A negligible amount of runoff from the sidewalk along Green Street will sheet flow into the City's closed drainage system due to the existing grades of the street sloping away from the site. The City's drainage system eventually discharges into North Mill Pond (PA-1), and, therefore, has been included in the single point of analysis.

A Stormtech Isolator Row and detention system is included on the development site for the purpose of mitigating temperature differences between the stormwater runoff and the North Mill Pond. This system and outlet structure have been designed to mitigate temperature of the water quality volume (WQV). Runoff that exceeds this volume will utilize an overflow and discharge into North Mill Pond (PA-1). This detention basin is used to mitigate increased temperature of the initial surface runoff, based on data provided in a publication by the University of New Hampshire Stormwater Center (UNHSC), titled "Examination of Thermal Impacts from Stormwater BMPs" and can be found in Appendix C. Due to this system being included in the design, post-development flows from the site have been reduced from the pre-development condition. As previously described, North Mill Pond is a tidal water, therefore, NHDES does not require peak runoff control requirements to be met (per Env-Wq 1507.06(d)).

The point of analysis and sub-catchment areas are depicted on the plan entitled "Post-Development Watershed Plan," Sheet C-802. The points of analysis and its contributing watershed areas are described below:

Point of Analysis (PA-1)

Point of Analysis 1 (PA-1), North Mill Pond, has the same overall contributing area as in the pre-development condition. PA-1 includes an underground detention basin, which is designed to detain the water quality volume of the paved surface runoff. Additional impervious surface runoff will be collected and filtered prior to discharging into the North Mill Pond.

Post-development Watershed 1.1 (POST-1.1) is approximately 74% impervious surface of either pavement or concrete surface. The area includes in the site access driveway and entrance turnaround. The pervious portion of this watershed includes a porous grass paver section intended for emergency use for fire truck access. Additional pervious areas that contribute to this watershed include a small amount of landscaped areas along the building façade. The stormwater runoff created from this area is collected via offline deep-sump and hooded catch basins and conveyed via a closed drainage system to the underground stormtech chamber system (POND-1). The detention basin is equipped with an isolator row as recommended by the UNHSC publication and is lined due to high seasonal high water table in the area. The system is underdrained and treatment is attained post detention by use of a proprietary membrane filtration treatment device identified as Jellyfish Filter 1 (JF-1). All collected runoff from this catchment is discharged into the North Mill Pond (PA-1).

Post-development Watershed 1.2 (POST-1.2) is 100% impervious roof surface that is collected via internal building plumbing system and conveyed via piping to a proprietary membrane filtration treatment device identified as Jellyfish Filter 1 (JF-1). The treated runoff eventually discharges into North Mill Pond (PA-1).

Post-development Watershed 1.3 (POST-1.3) is the connection path for public access to the public recreation trail along the shoreline. The area is approximately 45% impervious surface and consists of landscaping and grassed lawn areas in the post-development condition. The runoff associated with this area is captured via yard drains and is conveyed via piping to a proprietary membrane filtration treatment device identified as Jellyfish Filter 1 (JF-1). The treated runoff eventually discharges into North Mill Pond (PA-1).

Post-development Watershed 1.4 (POST-1.4) is 100% pervious surface. The area consists mostly of lawn, wooded, and landscaped areas. Runoff from this area remains similar to existing conditions and flows overland and discharges into the North Mill Pond.

Post-development Watershed 1.5 (POST-1.5) is 100% impervious sidewalk surface and flows overland onto Green Street. This subcatchment represents a proposed city sidewalk which flows onto the city street for collection. The closed drainage system associated with Green Street eventually discharges into North Mill Pond (PA-1).

Post-development Watershed 1.6 (POST-1.6) includes a city recreation trail which the city requested that be porous pavement, as not to increase impervious area so close to the waterfront. The runoff associated with this area flows overland and is captured and treated by the porous pavement section and is conveyed via piping to discharge into North Mill Pond.




3.1 Peak Rate Comparison

The following table summarizes and compares the pre- and post-development peak runoff rates for the 2-year, 10-year, 25-year and 50-year storm events at each point of analysis. Though peak flow mitigation is not required, the following table is provided for reference.

Point of Analysis	Pre/ Post 2-Year Storm (cfs)	Pre/ Post 10-Year Storm (cfs)	Pre/ Post 25-Year Storm (cfs)	Pre/ Post 50-Year Storm (cfs)
PA1	4.17/ 3.29	7.74/ 5.52	10.58/ 7.73	13.25/ 10.39

3.2 Post-Development Calculations

3.3 Post-Development Watershed Plans



C0960-011 POST

Prepared by Tighe & Bond

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Printed 3/22/2021

Page 2

Area Listing (all nodes)

Area (sq-ft)	CN	Description (subcatchment-numbers)
26,191	61	>75% Grass cover, Good, HSG B (1.1, 1.3, 1.4, 1.6)
2,659	74	>75% Grass cover, Good, HSG C (1.4)
14,240	98	Paved parking, HSG B (1.1, 1.3, 1.5, 1.6)
3,421	98	Porous Paved Path, HSG B (1.6)
29,373	98	Roofs, HSG B (1.2)
1,427	55	Woods, Good, HSG B (1.4)
77,311	84	TOTAL AREA

C0960-011 POST

Prepared by Tighe & Bond

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Printed 3/22/2021

Page 3

Soil Listing (all nodes)

Area (sq-ft)	Soil Group	Subcatchment Numbers
0	HSG A	
74,652	HSG B	1.1, 1.2, 1.3, 1.4, 1.5, 1.6
2,659	HSG C	1.4
0	HSG D	
0	Other	
77,311		TOTAL AREA

C0960-011 POST

Type III 24-hr 2 Year Storm Rainfall=3.68"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 4

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment 1.1: Runoff Area=13,620 sf 74.19% Impervious Runoff Depth=2.43"
 Tc=5.0 min CN=88 Runoff=0.91 cfs 2,762 cf

Subcatchment 1.2: Building Runoff Area=29,373 sf 100.00% Impervious Runoff Depth=3.45"
 Tc=5.0 min CN=98 Runoff=2.47 cfs 8,435 cf

Subcatchment 1.3: Runoff Area=5,929 sf 44.53% Impervious Runoff Depth=1.57"
 Tc=5.0 min CN=77 Runoff=0.25 cfs 774 cf

Subcatchment 1.4: Runoff Area=12,355 sf 0.00% Impervious Runoff Depth=0.75"
 Tc=5.0 min CN=63 Runoff=0.21 cfs 771 cf

Subcatchment 1.5: Runoff Area=1,145 sf 100.00% Impervious Runoff Depth=3.45"
 Tc=5.0 min CN=98 Runoff=0.10 cfs 329 cf

Subcatchment 1.6: Runoff Area=14,889 sf 25.33% Impervious Runoff Depth=1.12"
 Tc=5.0 min CN=70 Runoff=0.43 cfs 1,391 cf

Pond JF-1: JELLYFISH FILTER Peak Elev=7.39' Inflow=2.99 cfs 11,970 cf
 24.0" Round Culvert n=0.013 L=70.0' S=0.0043 '/' Outflow=2.99 cfs 11,970 cf

Pond PDMH1: Peak Elev=7.04' Inflow=2.99 cfs 12,670 cf
 24.0" Round Culvert n=0.013 L=7.0' S=0.0071 '/' Outflow=2.99 cfs 12,670 cf

Pond POND 1: 310 STORMTECH CHAMBERS Peak Elev=7.59' Storage=474 cf Inflow=0.91 cfs 2,762 cf
 Outflow=0.57 cfs 2,761 cf

Pond POND 2: POROUS PAVEMENT Peak Elev=6.54' Storage=821 cf Inflow=0.43 cfs 1,391 cf
 Outflow=0.03 cfs 700 cf

Link PA-1: POINT OF ANALYSIS 1 Inflow=3.29 cfs 13,770 cf
 Primary=3.29 cfs 13,770 cf

Total Runoff Area = 77,311 sf Runoff Volume = 14,461 cf Average Runoff Depth = 2.24"
39.16% Pervious = 30,277 sf 60.84% Impervious = 47,034 sf

C0960-011 POST

Type III 24-hr 10 Year Storm Rainfall=5.59"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 5

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment 1.1: Runoff Area=13,620 sf 74.19% Impervious Runoff Depth=4.23"
 Tc=5.0 min CN=88 Runoff=1.54 cfs 4,803 cf

Subcatchment 1.2: Building Runoff Area=29,373 sf 100.00% Impervious Runoff Depth=5.35"
 Tc=5.0 min CN=98 Runoff=3.77 cfs 13,101 cf

Subcatchment 1.3: Runoff Area=5,929 sf 44.53% Impervious Runoff Depth=3.12"
 Tc=5.0 min CN=77 Runoff=0.51 cfs 1,543 cf

Subcatchment 1.4: Runoff Area=12,355 sf 0.00% Impervious Runoff Depth=1.89"
 Tc=5.0 min CN=63 Runoff=0.62 cfs 1,951 cf

Subcatchment 1.5: Runoff Area=1,145 sf 100.00% Impervious Runoff Depth=5.35"
 Tc=5.0 min CN=98 Runoff=0.15 cfs 511 cf

Subcatchment 1.6: Runoff Area=14,889 sf 25.33% Impervious Runoff Depth=2.48"
 Tc=5.0 min CN=70 Runoff=1.01 cfs 3,082 cf

Pond JF-1: JELLYFISH FILTER Peak Elev=7.68' Inflow=4.76 cfs 19,447 cf
 24.0" Round Culvert n=0.013 L=70.0' S=0.0043 '/' Outflow=4.76 cfs 19,447 cf

Pond PDMH1: Peak Elev=7.30' Inflow=4.76 cfs 21,839 cf
 24.0" Round Culvert n=0.013 L=7.0' S=0.0071 '/' Outflow=4.76 cfs 21,839 cf

Pond POND 1: 310 STORMTECH CHAMBERS Peak Elev=8.21' Storage=874 cf Inflow=1.54 cfs 4,803 cf
 Outflow=0.84 cfs 4,803 cf

Pond POND 2: POROUS PAVEMENT Peak Elev=6.97' Storage=1,410 cf Inflow=1.01 cfs 3,082 cf
 Outflow=0.36 cfs 2,391 cf

Link PA-1: POINT OF ANALYSIS 1 Inflow=5.52 cfs 24,300 cf
 Primary=5.52 cfs 24,300 cf

Total Runoff Area = 77,311 sf Runoff Volume = 24,991 cf Average Runoff Depth = 3.88"
39.16% Pervious = 30,277 sf 60.84% Impervious = 47,034 sf

Summary for Subcatchment 1.1:

Runoff = 1.54 cfs @ 12.07 hrs, Volume= 4,803 cf, Depth= 4.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
10,105	98	Paved parking, HSG B
3,515	61	>75% Grass cover, Good, HSG B
13,620	88	Weighted Average
3,515		25.81% Pervious Area
10,105		74.19% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 1.2: Building

Runoff = 3.77 cfs @ 12.07 hrs, Volume= 13,101 cf, Depth= 5.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
29,373	98	Roofs, HSG B
29,373		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 1.3:

Runoff = 0.51 cfs @ 12.08 hrs, Volume= 1,543 cf, Depth= 3.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
2,640	98	Paved parking, HSG B
3,289	61	>75% Grass cover, Good, HSG B
5,929	77	Weighted Average
3,289		55.47% Pervious Area
2,640		44.53% Impervious Area

C0960-011 POST

Type III 24-hr 10 Year Storm Rainfall=5.59"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 2

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 1.4:

Runoff = 0.62 cfs @ 12.08 hrs, Volume= 1,951 cf, Depth= 1.89"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
8,269	61	>75% Grass cover, Good, HSG B
1,427	55	Woods, Good, HSG B
2,659	74	>75% Grass cover, Good, HSG C
12,355	63	Weighted Average
12,355		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 1.5:

Runoff = 0.15 cfs @ 12.07 hrs, Volume= 511 cf, Depth= 5.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

Area (sf)	CN	Description
1,145	98	Paved parking, HSG B
1,145		100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Subcatchment 1.6:

Runoff = 1.01 cfs @ 12.08 hrs, Volume= 3,082 cf, Depth= 2.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
Type III 24-hr 10 Year Storm Rainfall=5.59"

C0960-011 POST

Type III 24-hr 10 Year Storm Rainfall=5.59"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 3

Area (sf)	CN	Description
350	98	Paved parking, HSG B
11,118	61	>75% Grass cover, Good, HSG B
* 3,421	98	Porous Paved Path, HSG B
14,889	70	Weighted Average
11,118		74.67% Pervious Area
3,771		25.33% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

Summary for Pond JF-1: JELLYFISH FILTER

Inflow Area = 48,922 sf, 86.09% Impervious, Inflow Depth = 4.77" for 10 Year Storm event
 Inflow = 4.76 cfs @ 12.08 hrs, Volume= 19,447 cf
 Outflow = 4.76 cfs @ 12.08 hrs, Volume= 19,447 cf, Atten= 0%, Lag= 0.0 min
 Primary = 4.76 cfs @ 12.08 hrs, Volume= 19,447 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
 Peak Elev= 7.68' @ 12.09 hrs
 Flood Elev= 12.00'

Device	Routing	Invert	Outlet Devices
#1	Primary	6.45'	24.0" Round Culvert L= 70.0' CMP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 6.45' / 6.15' S= 0.0043 ' / ' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf

Primary OutFlow Max=4.37 cfs @ 12.08 hrs HW=7.66' TW=7.29' (Dynamic Tailwater)
 ↑**1=Culvert** (Outlet Controls 4.37 cfs @ 3.14 fps)

Summary for Pond PDMH1:

[80] Warning: Exceeded Pond POND 2 by 0.85' @ 12.04 hrs (0.71 cfs 1,056 cf)

Inflow Area = 63,811 sf, 71.91% Impervious, Inflow Depth = 4.11" for 10 Year Storm event
 Inflow = 4.76 cfs @ 12.08 hrs, Volume= 21,839 cf
 Outflow = 4.76 cfs @ 12.08 hrs, Volume= 21,839 cf, Atten= 0%, Lag= 0.0 min
 Primary = 4.76 cfs @ 12.08 hrs, Volume= 21,839 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
 Peak Elev= 7.30' @ 12.08 hrs
 Flood Elev= 10.10'

Device	Routing	Invert	Outlet Devices
#1	Primary	6.15'	24.0" Round Culvert L= 7.0' CMP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 6.15' / 6.10' S= 0.0071 ' / ' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf

Primary OutFlow Max=4.71 cfs @ 12.08 hrs HW=7.29' TW=0.00' (Dynamic Tailwater)

↑1=Culvert (Barrel Controls 4.71 cfs @ 3.67 fps)

Summary for Pond POND 1: 310 STORMTECH CHAMBERS

Exfiltration Rate derived from Site Specific Soil Survey report which compares existing soil classification to Sutton Soil HSG-B, which has a low Hydraulic conductivity rate of 0.6 in/hr, per NHDES regulations shall be modeling as 0.3 in/hr.

Inflow Area = 13,620 sf, 74.19% Impervious, Inflow Depth = 4.23" for 10 Year Storm event
 Inflow = 1.54 cfs @ 12.07 hrs, Volume= 4,803 cf
 Outflow = 0.84 cfs @ 12.28 hrs, Volume= 4,803 cf, Atten= 46%, Lag= 12.1 min
 Primary = 0.84 cfs @ 12.28 hrs, Volume= 4,803 cf

Routing by Dyn-Store-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
 Peak Elev= 8.21' @ 12.21 hrs Surf.Area= 964 sf Storage= 874 cf
 Flood Elev= 9.36' Surf.Area= 964 sf Storage= 1,209 cf

Plug-Flow detention time= 16.0 min calculated for 4,799 cf (100% of inflow)
 Center-of-Mass det. time= 16.3 min (809.3 - 793.0)

Volume	Invert	Avail.Storage	Storage Description
#1A	6.70'	693 cf	18.17"W x 53.04"L x 2.33"H Field A 2,248 cf Overall - 516 cf Embedded = 1,732 cf x 40.0% Voids
#2A	7.20'	516 cf	ADS_StormTech SC-310 +Cap x 35 Inside #1 Effective Size= 28.9"W x 16.0"H => 2.07 sf x 7.12'L = 14.7 cf Overall Size= 34.0"W x 16.0"H x 7.56'L with 0.44' Overlap 5 Rows of 7 Chambers
		1,209 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices
#1	Primary	6.40'	15.0" Round Culvert L= 12.0' CMP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 6.40' / 6.30' S= 0.0083 '/ Cc= 0.900 n= 0.013, Flow Area= 1.23 sf
#2	Device 1	6.70'	6.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	8.40'	4.0' long Sharp-Crested Rectangular Weir 2 End Contraction(s)
#4	Device 3	7.20'	12.0" Vert. Orifice/Grate C= 0.600

Primary OutFlow Max=0.86 cfs @ 12.28 hrs HW=8.15' TW=7.33' (Dynamic Tailwater)

↑1=Culvert (Passes 0.86 cfs of 5.36 cfs potential flow)
 ↑2=Orifice/Grate (Orifice Controls 0.86 cfs @ 4.37 fps)
 ↑3=Sharp-Crested Rectangular Weir (Controls 0.00 cfs)
 ↑4=Orifice/Grate (Controls 0.00 cfs)

Summary for Pond POND 2: POROUS PAVEMENT

Inflow Area = 14,889 sf, 25.33% Impervious, Inflow Depth = 2.48" for 10 Year Storm event
 Inflow = 1.01 cfs @ 12.08 hrs, Volume= 3,082 cf
 Outflow = 0.36 cfs @ 12.60 hrs, Volume= 2,391 cf, Atten= 65%, Lag= 31.3 min
 Primary = 0.36 cfs @ 12.60 hrs, Volume= 2,391 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs
 Peak Elev= 6.97' @ 12.46 hrs Surf.Area= 3,421 sf Storage= 1,410 cf
 Flood Elev= 9.35' Surf.Area= 3,421 sf Storage= 3,017 cf

Plug-Flow detention time= 185.2 min calculated for 2,391 cf (78% of inflow)
 Center-of-Mass det. time= 100.1 min (941.0 - 840.9)

Volume	Invert	Avail.Storage	Storage Description	
#1	5.94'	3,017 cf	Custom Stage Data (Prismatic) Listed below (Recalc)	
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
5.94	3,421	0.0	0	0
7.52	3,421	40.0	2,162	2,162
8.52	3,421	10.0	342	2,504
9.02	3,421	30.0	513	3,017
9.35	3,421	0.0	0	3,017

Device	Routing	Invert	Outlet Devices
#1	Primary	6.44'	6.0" Vert. Underdrain C= 0.600
#2	Device 1	5.94'	10.000 in/hr Filter Media Infiltration over Surface area

Primary OutFlow Max=0.38 cfs @ 12.60 hrs HW=6.93' TW=6.76' (Dynamic Tailwater)
 ↑1=Underdrain (Orifice Controls 0.38 cfs @ 1.95 fps)
 ↑2=Filter Media Infiltration (Passes 0.38 cfs of 0.79 cfs potential flow)

Summary for Link PA-1: POINT OF ANALYSIS 1

Inflow Area = 77,311 sf, 60.84% Impervious, Inflow Depth = 3.77" for 10 Year Storm event
 Inflow = 5.52 cfs @ 12.08 hrs, Volume= 24,300 cf
 Primary = 5.52 cfs @ 12.08 hrs, Volume= 24,300 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-48.00 hrs, dt= 0.04 hrs

C0960-011 POST

Type III 24-hr 25 Year Storm Rainfall=7.08"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 1

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment 1.1: Runoff Area=13,620 sf 74.19% Impervious Runoff Depth=5.67"
 Tc=5.0 min CN=88 Runoff=2.03 cfs 6,437 cf

Subcatchment 1.2: Building Runoff Area=29,373 sf 100.00% Impervious Runoff Depth=6.84"
 Tc=5.0 min CN=98 Runoff=4.78 cfs 16,745 cf

Subcatchment 1.3: Runoff Area=5,929 sf 44.53% Impervious Runoff Depth=4.44"
 Tc=5.0 min CN=77 Runoff=0.72 cfs 2,193 cf

Subcatchment 1.4: Runoff Area=12,355 sf 0.00% Impervious Runoff Depth=2.96"
 Tc=5.0 min CN=63 Runoff=1.00 cfs 3,048 cf

Subcatchment 1.5: Runoff Area=1,145 sf 100.00% Impervious Runoff Depth=6.84"
 Tc=5.0 min CN=98 Runoff=0.19 cfs 653 cf

Subcatchment 1.6: Runoff Area=14,889 sf 25.33% Impervious Runoff Depth=3.68"
 Tc=5.0 min CN=70 Runoff=1.51 cfs 4,572 cf

Pond JF-1: JELLYFISH FILTER Peak Elev=7.91' Inflow=6.20 cfs 25,374 cf
 24.0" Round Culvert n=0.013 L=70.0' S=0.0043 '/' Outflow=6.20 cfs 25,374 cf

Pond PDMH1: Peak Elev=7.48' Inflow=6.20 cfs 29,255 cf
 24.0" Round Culvert n=0.013 L=7.0' S=0.0071 '/' Outflow=6.20 cfs 29,255 cf

Pond POND 1: 310 STORMTECH CHAMBERS Peak Elev=8.55' Storage=1,024 cf Inflow=2.03 cfs 6,437 cf
 Outflow=1.54 cfs 6,436 cf

Pond POND 2: POROUS PAVEMENT Peak Elev=7.38' Storage=1,976 cf Inflow=1.51 cfs 4,572 cf
 Outflow=0.58 cfs 3,882 cf

Link PA-1: POINT OF ANALYSIS 1 Inflow=7.37 cfs 32,956 cf
 Primary=7.37 cfs 32,956 cf

Total Runoff Area = 77,311 sf Runoff Volume = 33,647 cf Average Runoff Depth = 5.22"
39.16% Pervious = 30,277 sf 60.84% Impervious = 47,034 sf

C0960-011 POST

Type III 24-hr 50 Year Storm Rainfall=8.48"

Prepared by Tighe & Bond

Printed 3/22/2021

HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Page 2

Time span=0.00-48.00 hrs, dt=0.04 hrs, 1201 points
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
 Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

Subcatchment 1.1: Runoff Area=13,620 sf 74.19% Impervious Runoff Depth=7.04"
 Tc=5.0 min CN=88 Runoff=2.49 cfs 7,988 cf

Subcatchment 1.2: Building Runoff Area=29,373 sf 100.00% Impervious Runoff Depth=8.24"
 Tc=5.0 min CN=98 Runoff=5.73 cfs 20,169 cf

Subcatchment 1.3: Runoff Area=5,929 sf 44.53% Impervious Runoff Depth=5.72"
 Tc=5.0 min CN=77 Runoff=0.92 cfs 2,824 cf

Subcatchment 1.4: Runoff Area=12,355 sf 0.00% Impervious Runoff Depth=4.05"
 Tc=5.0 min CN=63 Runoff=1.37 cfs 4,170 cf

Subcatchment 1.5: Runoff Area=1,145 sf 100.00% Impervious Runoff Depth=8.24"
 Tc=5.0 min CN=98 Runoff=0.22 cfs 786 cf

Subcatchment 1.6: Runoff Area=14,889 sf 25.33% Impervious Runoff Depth=4.88"
 Tc=5.0 min CN=70 Runoff=2.00 cfs 6,054 cf

Pond JF-1: JELLYFISH FILTER Peak Elev=8.23' Inflow=8.80 cfs 30,981 cf
 24.0" Round Culvert n=0.013 L=70.0' S=0.0043 '/' Outflow=8.80 cfs 30,981 cf

Pond PDMH1: Peak Elev=7.79' Inflow=8.80 cfs 36,345 cf
 24.0" Round Culvert n=0.013 L=7.0' S=0.0071 '/' Outflow=8.80 cfs 36,345 cf

Pond POND 1: 310 STORMTECH CHAMBERS Peak Elev=8.65' Storage=1,062 cf Inflow=2.49 cfs 7,988 cf
 Outflow=2.32 cfs 7,988 cf

Pond POND 2: POROUS PAVEMENT Peak Elev=8.39' Storage=2,460 cf Inflow=2.00 cfs 6,054 cf
 Outflow=0.79 cfs 5,364 cf

Link PA-1: POINT OF ANALYSIS 1 Inflow=10.39 cfs 41,301 cf
 Primary=10.39 cfs 41,301 cf

Total Runoff Area = 77,311 sf Runoff Volume = 41,992 cf Average Runoff Depth = 6.52"
39.16% Pervious = 30,277 sf 60.84% Impervious = 47,034 sf

C0960-011 POST

Prepared by Tighe & Bond



HydroCAD® 10.00-20 s/n 03436 © 2017 HydroCAD Software Solutions LLC

Type III 24-hr 50 Year Storm Rainfall=8.48"

Printed 3/22/2021

Stage-Area-Storage for Pond POND 1: 310 STORMTECH CHAMBERS

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
6.70	0	7.74	581	8.78	1,111
6.72	8	7.76	594	8.80	1,119
6.74	15	7.78	608	8.82	1,127
6.76	23	7.80	621	8.84	1,134
6.78	31	7.82	634	8.86	1,142
6.80	39	7.84	647	8.88	1,150
6.82	46	7.86	661	8.90	1,158
6.84	54	7.88	674	8.92	1,165
6.86	62	7.90	686	8.94	1,173
6.88	69	7.92	699	8.96	1,181
6.90	77	7.94	712	8.98	1,188
6.92	85	7.96	725	9.00	1,196
6.94	93	7.98	737	9.02	1,204
6.96	100	8.00	749	9.04	1,209
6.98	108	8.02	762	9.06	1,209
7.00	116	8.04	774	9.08	1,209
7.02	123	8.06	786	9.10	1,209
7.04	131	8.08	798	9.12	1,209
7.06	139	8.10	809	9.14	1,209
7.08	146	8.12	821	9.16	1,209
7.10	154	8.14	833	9.18	1,209
7.12	162	8.16	844	9.20	1,209
7.14	170	8.18	855	9.22	1,209
7.16	177	8.20	866	9.24	1,209
7.18	185	8.22	877	9.26	1,209
7.20	193	8.24	887	9.28	1,209
7.22	208	8.26	897	9.30	1,209
7.24	223	8.28	907	9.32	1,209
7.26	237	8.30	917	9.34	1,209
7.28	252	8.32	926	9.36	1,209
7.30	267	8.34	936		
7.32	282	8.36	944		
7.34	297	8.38	953		
7.36	311	8.40	962		
7.38	326	8.42	970		
7.40	341	8.44	979		
7.42	355	8.46	987		
7.44	370	8.48	995		
7.46	384	8.50	1,003		
7.48	399	8.52	1,011		
7.50	413	8.54	1,019		
7.52	427	8.56	1,026		
7.54	442	8.58	1,034		
7.56	456	8.60	1,042		
7.58	470	8.62	1,050		
7.60	484	8.64	1,057		
7.62	498	8.66	1,065		
7.64	512	8.68	1,073		
7.66	526	8.70	1,080		
7.68	540	8.72	1,088		
7.70	553	8.74	1,096		
7.72	567	8.76	1,104		



Proposed Mixed Use Development

CPI Management, LLC

53 Green Street
Portsmouth, NH

B	3/22/2021	TAC & CC Submission
A	1/27/2021	CC Work Session
MARK	DATE	DESCRIPTION
PROJECT NO: C0960-011		
DATE: January 27, 2021		
FILE: C0960-011_C-DSGN.DWG		
DRAWN BY: AFS		
CHECKED: NAH/PMC		
APPROVED: BLM		

POST-DEVELOPMENT WATERSHED PLAN

SCALE: AS SHOWN

C-802



LEGEND

- POST-DEVELOPMENT WATERSHED BOUNDARY
- LONGEST FLOW PATH
- SOIL TYPE BOUNDARY
- SOIL TYPE (SEE SITE SPECIFIC SOIL MAP)
- PRE DEVELOPMENT WATERSHED AREA DESIGNATION
- POST-DEVELOPMENT POND DESIGNATION
- POINT OF ANALYSIS

Last Saved: 3/19/2021
 Plotted On: Mar 22, 2021 9:15am By: ASellar
 Tighe & Bond 230 Corporate Center Portsmouth, NH Drawings Figures AutoCAD C0960-011_C-DSGN.dwg

Section 4

Stormwater Treatment

The stormwater management system has been designed to provide stormwater treatment as required by the City of Portsmouth Site Review Regulations and NHDES AoT Regulations (Env-Wq 1500).

4.1 Pre-Treatment Methods for Protecting Water Quality

Pre-treatment for the stormwater that is collected on-site is pretreated through use of offline deep-sump and hooded catch basins .

4.2 Treatment Methods for Protecting Water Quality

The runoff from proposed impervious areas will be treated by a Contech Jellyfish stormwater filtration system. The Jellyfish system is sized to treat the Water Quality Flow from the contributing subcatchment areas. The system is outfitted with an internal bypass that diverts peak flows away from treatment. The BMP worksheet for this practice has been included in Section 5 of this report.

The multiuse path along the North Mill Pond will be constructed as porous pavement with and underdrain. The underdrain will discharge to the onsite closed drainage system prior to discharging to the Pond.

BMP	Total Suspended Solids	Total Nitrogen	Total Phosphorus
Jellyfish Filter w/Pretreatment ¹	91%	53%	61%
Porous Pavement w/Underdrain ²	90%	10%	45%

1. Pollutant removal calculations for Jellyfish Filter with deep sump catch basin pretreatment shown in Table 4.2.
2. Pollutant removal efficiencies from NH Stormwater Manual Volume 2, Appendix B.

Table 4.2 – Pollutant Removal Calculations				
Contech Jellyfish Filter				
BMP	TSS Removal Rate	Starting TSS Load	TSS Removed	Remaining TSS Load
Deep Sump Catchbasin w/Hood ¹	0.15	1.00	0.15	0.85
Jellyfish Filter ²	0.89	0.85	0.76	0.09
Total Suspended Solids Removed:				91%
	TN Removal Rate	Starting TN Load	TN Removed	Remaining TN Load
Deep Sump Catchbasin w/Hood ¹	0.05	1.00	0.05	0.95
Jellyfish Filter ²	0.51	0.95	0.48	0.47
Total Nitrogen Removed:				53%
	TP Removal Rate	Starting TP Load	TP Removed	Remaining TP Load
Deep Sump Catchbasin w/Hood ¹	0.05	1.00	0.05	0.95
Jellyfish Filter ²	0.59	0.95	0.56	0.39
Total Phosphorus Removed:				61%

1. Pollutant removal efficiencies from NH Stormwater Manual Volume 2, Appendix E.
2. Pollutant removal efficiencies from Contech Engineered Solutions, Jellyfish Filter Stormwater Treatment performance testing results.

Section 5

BMP Worksheet and Sizing Memos



GENERAL CALCULATIONS - WQV and WQF (optional worksheet)

This worksheet may be useful when designing a BMP **that does not fit into one of the specific worksheets already provided** (i.e. for a technology which is not a stormwater wetland, infiltration practice, etc.)

Water Quality Volume (WQV)

1.12 ac	A = Area draining to the practice
0.97 ac	A _i = Impervious area draining to the practice
0.87 decimal	I = Percent impervious area draining to the practice, in decimal form
0.83 unitless	R _v = Runoff coefficient = 0.05 + (0.9 x I)
0.93 ac-in	WQV = 1" x R _v x A
3,372 cf	WQV conversion (ac-in x 43,560 sf/ac x 1ft/12")

Water Quality Flow (WQF)

1 inches	P = Amount of rainfall. For WQF in NH, P = 1".
0.83 inches	Q = Water quality depth. Q = WQV/A
98 unitless	CN = Unit peak discharge curve number. CN = 1000 / (10 + 5P + 10Q - 10 * [Q ² + 1.25 * Q * P] ^{0.5})
0.2 inches	S = Potential maximum retention. S = (1000/CN) - 10
0.032 inches	I _a = Initial abstraction. I _a = 0.2S
5.0 minutes	T _c = Time of Concentration
655.0 cfs/mi ² /in	q _u is the unit peak discharge. Obtain this value from TR-55 exhibits 4-II and 4-III.
0.951 cfs	WQF = q _u x WQV. Conversion: to convert "cfs/mi ² /in * ac-in" to "cfs" multiply by 1mi ² /640ac.

Designer's Notes:

This calculation represents the treatment train directed to the Contech Jellyfish Filter (JF-1).

Full Treatment in compliance with Env-Wq 1508.10 shall be achieved by use of a proprietary flow-through device. A Contech Jellyfish Filter model JFPD0806-5-1 will be used to treat the WQF as calculated in the above spreadsheet. The specified device is designed to treat up to 0.80 cfs of flow.

See attached sizing calculation sheet from manufacturer.



CONTECH Stormwater Solutions Inc. Engineer:
Date Prepared:

DRA
3/17/2021

Site Information

Project Name **53 Green Street**
Project State **NH**
Project City **Portsmouth**

Total Drainage Area, Ad **1.12** ac
Post Development Impervious Area, Ai **0.97** ac
Pervious Area, Ap **0.15** ac
% Impervious **87%**
Runoff Coefficient, Rc **0.83**

Mass Loading Calculations

Mean Annual Rainfall, P **50** in
Agency Required % Removal **80%**
Percent Runoff Capture **90%**
Mean Annual Runoff, Vt **151752** ft³
Event Mean Concentration of Pollutant, EMC **75** mg/l
Annual Mass Load, M total **710.10** lbs

Filter System

Filtration Brand **Jelly Fish**
Cartridge Length **54** in

Jelly Fish Sizing

Mass to be Captured by System **568.08** lbs
Water Quality Flow **0.95** cfs

Method to Use

FLOW BASED

Summary

Flow	Treatment Flow Rate	0.98 cfs
	Required Size	JFPD0806-5-1



GENERAL CALCULATIONS - WQV and WQF (optional worksheet)

This worksheet may be useful when designing a BMP **that does not fit into one of the specific worksheets already provided** (i.e. for a technology which is not a stormwater wetland, infiltration practice, etc.)

Water Quality Volume (WQV)

0.31	ac	A = Area draining to the practice
0.23	ac	A _i = Impervious area draining to the practice
0.74	decimal	I = Percent impervious area draining to the practice, in decimal form
0.72	unitless	R _v = Runoff coefficient = 0.05 + (0.9 x I)
0.22	ac-in	WQV = 1" x R _v x A
815	cf	WQV conversion (ac-in x 43,560 sf/ac x 1ft/12")

Water Quality Flow (WQF)

1	inches	P = Amount of rainfall. For WQF in NH, P = 1".
0.72	inches	Q = Water quality depth. Q = WQV/A
97	unitless	CN = Unit peak discharge curve number. CN = 1000 / (10 + 5P + 10Q - 10 * [Q ² + 1.25 * Q * P] ^{0.5})
0.3	inches	S = Potential maximum retention. S = (1000/CN) - 10
0.059	inches	I _a = Initial abstraction. I _a = 0.2S
5.0	minutes	T _c = Time of Concentration
655.0	cfs/mi ² /in	q _u is the unit peak discharge. Obtain this value from TR-55 exhibits 4-II and 4-III.
0.230	cfs	WQF = q _u x WQV. Conversion: to convert "cfs/mi ² /in * ac-in" to "cfs" multiply by 1mi ² /640ac.

Designer's Notes: _____

This calculation represents the treatment train directed to the underground detention pond.

Pretreatment is accomplished by use a offline deep sump/hooded catch basins prior to entering the underground detention structure.

Treatment is achieved by use of the Jellyfish filter structure (JF-1). This treatment is represented

Temperature mitigation is achieved by detaining WQV and dispersing through stone and underdrain.

Section 6 Long-Term Operation & Maintenance Plan

It is the intent of this Operation and Maintenance Plan to identify the areas of this site that need special attention and consideration, as well as implementing a plan to assure routine maintenance. By identifying the areas of concern as well as implementing a frequent and routine maintenance schedule the site will maintain a high-quality stormwater runoff.

6.1 Contact/Responsible Party

Maintenance Area	Contact/Responsible Party
Map 119 Lot 2	CPI Management, LLC 100 Summer Street, Suite 1600 Boston, MA 02110
North Mill Pond Trail (City Easement)	City of Portsmouth DPW 680 Peverly Hill Road Portsmouth, NH 03801

(Note: The contact information for the Contact/Responsible Party shall be kept current. If ownership changes, the Operation and Maintenance Plan must be transferred to the new party.)

6.2 Maintenance Items

Maintenance of the following items shall be recorded:

- Litter/Debris Removal
- Landscaping
- Catchbasin Cleaning
- Pavement Sweeping
- Contech Jellyfish Filtration System
- ADS Stormtech Isolator Row
- Porous Pavement

The following maintenance items and schedule represent the minimum action required. Periodic site inspections shall be conducted, and all measures must be maintained in effective operating condition. The following items shall be observed during site inspection and maintenance:

- Inspect vegetated areas, particularly slopes and embankments for areas of erosion. Replant and restore as necessary
- Inspect catch basins for sediment buildup
- Inspect site for trash and debris

6.3 Overall Site Operation & Maintenance Schedule

Maintenance Item	Frequency of Maintenance	Responsible Party
Litter/Debris Removal	Weekly	CPI Management, LLC
Pavement Sweeping - Sweep impervious areas to remove sand and litter.	Annually	CPI Management, LLC
Landscaping - Landscaped islands to be maintained and mulched.	Maintained as required and mulched each Spring	CPI Management, LLC
Catch Basin (CB) Cleaning - CB to be cleaned of solids and oils.	Annually	CPI Management, LLC
Jelly Fish Units	In accordance with Manufacturer's Recommendations	CPI Management, LLC
Underground Detention Basin & Isolator Row - Visual observation of sediment levels within system	In accordance with Manufacturer's Recommendations	CPI Management, LLC
Porous Pavement - Clean using a vacuum sweeper	Bi-Annually	City of Portsmouth DPW

Contech Jellyfish Filter System Inspection/Maintenance Requirements		
Inspection/ Maintenance	Frequency	Action
Inspect vault for sediment build up, static water, plugged media and bypass condition	One (1) time annually and after any rainfall event exceeding 2.5" in a 24-hr period	Maintenance required for any of the following: <ul style="list-style-type: none"> - >4" of sediment on the vault floor - >1/4" of sediment on top of the cartridge - .4" of static water above the cartridge bottom more than 24 hours after a rain event - If pore space between media is absent. - If vault is in bypass condition during an average rainfall event.
Replace Cartridges	As required by inspection, 1-5 years.	<ul style="list-style-type: none"> - Remove filter cartridges per manufacturer methods. - Vacuum sediment from vault. - Install new cartridges per manufacturer methods

Stormtech Isolator Row Inspection/Maintenance Requirements		
Inspection/ Maintenance	Frequency	Action
Inspect Isolator Row for sediment	6 months for the first year, then adjust based on previous observations of sediment accumulation and high water elevations.	<ul style="list-style-type: none"> - Inspect inside the isolator row through inspection ports (if provided) or through the upstream structure.
Jetting and Vactoring	Annually or as required by inspection.	<ul style="list-style-type: none"> - If sediment is 3" or above, then clean out isolator row using the jetvac process. - Vacuum structure sump as required.

Porous Asphalt Inspection/Maintenance Requirements		
Inspection/ Maintenance	Frequency	Action
Monitor for sediment build up, particularly in the winter.	Two (2) – Four (4) Times Annually.	- Clean with vacuum sweeper, bi-annually - Loose debris such as leaves or can be removed using a power/leaf blower or gutter broom. Fall and spring cleanup should be accompanied by pavement vacuuming.
Inspect Adjacent Vegetation	Two (2) – Four (4) Times Annually.	- Repair or replace any eroded areas.
Inspect for standing water -Within 30 minutes following a rain event.	One (1) – Two (2) Times Annually	- Use of a power washer or compressed air blower at an angle of 30 degrees or less can be effective, vacuum or vacuum sweeper if necessary.
Damage to pavement	As needed	- Repairs should be made as identified.

Additional Porous Asphalt Operation and Maintenance Requirements:

- ***No winter sanding or salting of porous pavements is permitted***
- Watering plants as necessary during the first growing season.
- Never reseal or repave with impermeable materials.
- Inspect annually for pavement deterioration or spalling.
- Monitor periodically to ensure the pavement surface drains effectively after storms.

6.3.1 Disposal Requirements

Disposal of debris, trash, sediment and other waste material should be done at suitable disposal/recycling sites and in compliance with all applicable local, state and federal waste regulations.

6.3.2 Snow & Ice Management for Standard Asphalt and Walkways

Snow storage areas shall be located such that no direct untreated discharges are possible to receiving waters from the storage site (snow storage areas have been shown on the Site Plan). The property manager will be responsible for timely snow removal from all private sidewalks, driveways, and parking areas. Snow removal will be hauled off-site and legally disposed of when snowbanks exceed 6 feet in height. Salt storage areas shall be covered or located such that no direct untreated discharges are possible to receiving waters from the storage site. Salt and sand shall be used to the minimum extent practical (refer to the attached for de-icing application rate guideline from the New Hampshire Stormwater Management Manual, Volume 2,).

6.4 Chloride Management Plan

Winter Operational Guidelines

The following Chloride Management Plan is for the Raynes Avenue, Mixed Use Development in Portsmouth, New Hampshire. The Plan includes operational guidelines including winter operator certification requirements, weather monitoring, equipment calibration requirements, mechanical removal, and salt usage evaluation and monitoring. Due to the evolving nature of chloride management efforts, the Chlorides Management Plan will be reviewed annually, in advance of the winter season, to reflect the current management standards.

6.4.1 Background Information

The Green Street, Mixed Use Development is located along the North Mill Pond in Portsmouth, New Hampshire.

6.4.2 Operational Guidelines – Chloride Management

All private contractors engaged at the development site for the purposes of winter operational snow removal and surface maintenance, are responsible for assisting in meeting compliance for the following protocols. Private contractors are expected to minimize the effects of the use of de-icing, anti-icing and pretreatment materials by adhering to the strict guidelines outlined below.

The winter operational de-icing, anti-icing and pretreatment materials will adhere to the following protocols

6.4.2.1 Winter Operator Certification Requirements

All private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance must be current UNHT2 Green SnowPro Certified operators or equivalent and will use only pre-approved methods for spreading abrasives on private roadways and parking lots. All private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance shall provide to the property management two copies of the annual UNHT2 Green SnowPro certificate or equivalent for each operator utilized on the premises. The annual UNHT2 Green SnowPro certificate or equivalent for each operator will be available on file in the Facilities Management office and be present in the vehicle/carrier at all times.

6.4.2.2 Improved Weather Monitoring

The property manager will coordinate weather information for use by winter maintenance contractors. This information in conjunction with site specific air/ground surface temperature monitoring will ensure that private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance will make more informed decisions as to when and to what extent de-icing, anti-icing and pretreatment materials are applied to private roadways, sidewalks, and parking lots.

6.4.2.3 Equipment Calibration Requirements

All equipment utilized on the premises for the purpose of winter operational snow removal and surface maintenance will conform to the following calibration requirements.

6.4.2.3.1 Annual Calibration Requirements

All private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance shall provide two copies of the annual calibration report for each piece of equipment utilized on the premises. Each calibration report shall include the vehicle/carrier VIN number and the serial numbers for each component including, but not limited to, spreader control units, salt aggregate spreader equipment, brining/pre-wetting equipment, ground speed orientation unit, and air/ground surface temperature monitor. Annual calibration reports will be available on file in the Facilities Management office and be present in the vehicle/carrier at all times.

Prior to each use, each vehicle/carrier operator will perform a systems check to verify that unit settings remain within the guidelines established by the Management Team in order to accurately dispense material. All private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance will be subject to spot inspections by members of the Property Management Team to ensure that each vehicle/carrier is operating in a manner consistent with the guidelines set herein or State and Municipal regulations. All units will be recalibrated, and the updated calibration

reports will be provided each time repairs or maintenance procedures affect the hydraulic system of the vehicle/carrier.

6.4.2.4 Increased Mechanical Removal Capabilities

All private contractors engaged at the premises will endeavor to use mechanical removal means on a more frequent basis for roadways, parking lots and sidewalks. Dedicating more manpower and equipment to increase snow removal frequencies prevents the buildup of snow and the corresponding need for de-icing, anti-icing and pretreatment materials. Shortened maintenance routes, with shorter service intervals, will be used to stay ahead of snowfall. Minimized snow and ice packing will reduce the need for abrasives, salt aggregates, and/or brining solution to restore surfaces back to bare surface states after winter precipitation events.

After storm events the management team will be responsible for having the streets swept to recapture un-melted de-icing materials, when practical.

6.4.3 Salt Usage Evaluation and Monitoring

All private contractors engaged at the premises for the purpose of winter operational snow removal and surface maintenance shall provide two copies of a storm report, which includes detailed information regarding treatment areas and the use of de-icing, anti-icing and pretreatment materials applied for the removal of snow and surface maintenance on the premises. The property manager will maintain copies of Summary Documents, including copies of the Storm Reports, operator certifications, equipment used for roadway and sidewalk winter maintenance, calibration reports and amount of de-icing materials used.

6.4.4 Summary

The above-described methodologies are incorporated into the Operational Manual and are to be used to qualify and retain all private contractors engaged at the 105 Bartlett Street premises for the purpose of winter operational snow removal and surface maintenance. This section of the Manual is intended to be an adaptive management document that is modified as required based on experience gained from past practices and technological advancements that reflect chloride BMP standards. All employees directly involved with winter operational activities are required to review this document and the current standard Best Management Practices published by the UNH Technology Transfer (T2) program annually. All employees directly involved with winter operational activities, and all private contractors engaged at the premises for the purposes of winter operational snow removal and surface maintenance, must be current UNHT2 Green SnowPro Certified operators or equivalent and undergo the necessary requirements to maintain this certification annually.

Deicing Application Rate Guidelines

24' of pavement (typical two-lane road)

These rates are not fixed values, but rather the middle of a range to be selected and adjusted by an agency according to its local conditions and experience.

Pavement Temp. (°F) and Trend (↑↓)	Weather Condition	Maintenance Actions	Pounds per two-lane mile			
			Salt Prewetted / Pretreated with Salt Brine	Salt Prewetted / Pretreated with Other Blends	Dry Salt*	Winter Sand (abrasives)
> 30° ↑	Snow	Plow, treat intersections only	80	70	100*	Not recommended
	Freezing Rain	Apply Chemical	80 - 160	70 - 140	100 - 200*	Not recommended
30° ↓	Snow	Plow and apply chemical	80 - 160	70 - 140	100 - 200*	Not recommended
	Freezing Rain	Apply Chemical	150 - 200	130 - 180	180 - 240*	Not recommended
25° - 30° ↑	Snow	Plow and apply chemical	120 - 160	100 - 140	150 - 200*	Not recommended
	Freezing Rain	Apply Chemical	150 - 200	130 - 180	180 - 240*	Not recommended
25° - 30° ↓	Snow	Plow and apply chemical	120 - 160	100 - 140	150 - 200*	Not recommended
	Freezing Rain	Apply Chemical	160 - 240	140 - 210	200 - 300*	400
20° - 25° ↑	Snow or Freezing Rain	Plow and apply chemical	160 - 240	140 - 210	200 - 300*	400
20° - 25° ↓	Snow	Plow and apply chemical	200 - 280	175 - 250	250 - 350*	Not recommended
	Freezing Rain	Apply Chemical	240 - 320	210 - 280	300 - 400*	400
15° - 20° ↑	Snow	Plow and apply chemical	200 - 280	175 - 250	250 - 350*	Not recommended
	Freezing Rain	Apply Chemical	240 - 320	210 - 280	300 - 400*	400
15° - 20° ↓	Snow or Freezing Rain	Plow and apply chemical	240 - 320	210 - 280	300 - 400*	500 for freezing rain
0° - 15° ↑↓	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	300 - 400	Not recommended	500 - 750 spot treatment as needed
< 0°	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	400 - 600**	Not recommended	500 - 750 spot treatment as needed

* Dry salt is not recommended. It is likely to blow off the road before it melts ice.

** A blend of 6 - 8 gal/ton MgCl₂ or CaCl₂ added to NaCl can melt ice as low as -10°.

Anti-icing Route Data Form				
Truck Station:				
Date:				
Air Temperature	Pavement Temperature	Relative Humidity	Dew Point	Sky
Reason for applying:				
Route:				
Chemical:				
Application Time:				
Application Amount:				
Observation (first day):				
Observation (after event):				
Observation (before next application):				
Name:				

6.5 Invasive Species

With respect to a particular ecosystem, any species, including its seeds, eggs, spores, or other biological material capable of propagating that species, that is not native to that ecosystem is classified as an invasive species. Refer to the following fact sheet prepared by the University of New Hampshire Cooperative Extension entitled Methods for Disposing Non-Native Invasive Plants for recommended methods to dispose of invasive plant species.

6.6 Annual Updates and Log Requirements

The Owner and/or Contact/Responsible Party shall review this Operation and Maintenance Plan once per year for its effectiveness and adjust the plan and deed as necessary.

A log of all preventative and corrective measures for the stormwater system shall be kept on-site and be made available upon request by any public entity with administrative, health environmental or safety authority over the site including NHDES.

Copies of the Stormwater Maintenance report shall be submitted to the City of Portsmouth on an annual basis.

Stormwater Management Report						
Mixed Use Development		53 Green Street – Map 119, Lot 2				
BMP Description	Date of Inspection	Inspector	BMP Installed and Operating Properly?	Cleaning / Corrective Action Needed	Date of Cleaning / Repair	Performed By
Deep Sump CB's			<input type="checkbox"/> Yes <input type="checkbox"/> No			
Underground Detention			<input type="checkbox"/> Yes <input type="checkbox"/> No			
Jellyfish Filter 1			<input type="checkbox"/> Yes <input type="checkbox"/> No			

Stormwater Management Report						
City of Portsmouth		North Mill Pond Trail				
BMP Description	Date of Inspection	Inspector	BMP Installed and Operating Properly?	Cleaning / Corrective Action Needed	Date of Cleaning / Repair	Performed By
Porous Pavement			<input type="checkbox"/> Yes <input type="checkbox"/> No			

J:\C\C0960 Cathartes\C-0960-011 53 Green St, Portsmouth, NH\Report_Evaluation\Applications\City of Portsmouth\20210322 TAC Submission\Drainage\C-0960-011_Drainage Report.docx

APPENDIX A




Proposed Mixed Use Development
53 Green Street, Portsmouth, NH

SITE SPECIFIC SOIL MAP REPORT

CPI Management, LLC

March 2021



Tighe&Bond

1.0 Introduction

This report is provided in conjunction with a 1.81 +/- acre Site Specific Soil Map (SSSM) prepared by Tighe & Bond for a parcel at 53 Green Street in Portsmouth, NH. The purpose of the mapping was to assist in the evaluation of drainage and other soil-related uses associated with site improvements, and may be used as part of an Alteration of Terrain (AoT) permit application.

2.0 Methods

Fieldwork for the soil mapping was completed October 22 and December 2, 2019 based on *Site-Specific Soil Mapping Standards for New Hampshire and Vermont, Version 5.0*, (Society of Soil Scientists of Northern New England [SSSNNE] Special Publication No. 3, December 2017). The poorly and very poorly drained soil types under this system are based on the most recent version of *Field Indicators for Identifying Hydric Soils in New England, Version 4* (New England Interstate Water Pollution Control Commission, 2018).

The soil legend for this map is based on the soil series currently mapped in the State of New Hampshire as published in the *New Hampshire State-Wide Numerical Soils Legend* (USDA Natural Resources Conservation Service, Issue #10, 2011). Since this soil map includes disturbed soils and may be used for an AoT application, the map symbols are composed of two major parts separated by a forward slash (/). The first part of the soil symbol includes a numerical identifier from the state-wide soil legend, followed by a letter indicating the slope class (e.g., 299A). Slope class identifiers are as follows:

A	0-3%	D	15-25%
B	3-8%	E	25-50%
C	8-15%	F	>50%

The second part of the symbol is based on the SSSNNE Disturbed Soil Supplemental Symbols, which are included within the Site Specific Soil Map (SSSM) standards. This portion of the symbol translates as follows:

Character 1: Drainage Class

- a-Excessively Drained
- b-Somewhat Excessively Drained
- c-Well Drained
- d-Moderately Well Drained
- e-Somewhat Poorly Drained
- f-Poorly Drained
- g-Very Poorly Drained
- h-Not Determined

Character 2: Parent Material (of naturally formed soil only, if present)

- a-No natural soil within 60 inches
- b-Glaciofluvial deposits (outwash/terraces of sand or sand and gravel)
- c-Glacial till material (active ice)
- d-Glaciolacustrine very fine sand and silt deposits (glacial lakes)
- e-Loamy/sandy over silt/clay deposits
- f-Marine silt and clay deposits (ocean waters)
- g-Alluvial deposits (floodplains)
- h-Organic materials-fresh water wetlands
- i-Organic materials-tidal wetlands

Character 3: Restrictive Properties

- a-None
- b-Bouldery surface with more than 15% of the surface covered with boulders
- c-Mineral restrictive layer(s) are present in the soil profile less than 40 inches below the soil surface such as hard pan, platy structure or clayey texture with consistence of at least firm (i.e. more than 20 newtons).
- d-Bedrock in the soil profile; 0-20 inches
- e-Bedrock in the soil profile; 20-60 inches
- f-Areas where depth to bedrock is so variable that a single soil type cannot be applied, will be mapped as a complex of soil types
- g-Subject to flooding
- h-Manufactured impervious surface including pavement, concrete, or built-up surfaces (e.g. buildings) with no morphological restrictive layer within control section

Character 4: Estimated Ksat (most limiting layer excluding symbol 3h above)

- a-High
- b-Moderate
- c-Low
- d-Not determined *See "Guidelines for Ksat Class Placement" in Chapter 3 of the Soil Survey Manual, USDA

Character 5: Hydrologic Soil Group

- a-Group A
- b-Group B
- c-Group C
- d-Group D
- e-Not determined

SSSM report standards require estimates of the maximum size of *limiting* inclusions for the entire soil map and an estimate of the percentage of *dissimilar* inclusions within each map unit. *Limiting* inclusions are soils "...that differ appreciably in one or more soil properties from the named soil in a map unit. The difference in soil properties is more restrictive and may affect use and management." *Dissimilar* inclusions are "...soils that either do not share limits of some important diagnostic properties of the named taxon, or, in the professional judgment of the soil scientist, have different use or management requirements." The maximum size of any limiting inclusions in this soil map is estimated to be less than 2,000 square feet. Any dissimilar inclusions noted during the mapping are listed below within the map unit descriptions.

3.0 Site Features

The parcel is a highly disturbed site along the North Mill Pond. The property shows evidence of what appears to be very old filling and grading associated with the existing development.

4.0 Soil Map Unit Descriptions

Below are descriptions for the map unit found on the accompanying SSSM. The "*" after the numerical map unit symbol represents a placeholder for the slope class indicators described above.

100*/cfabb—Udorthents, wet substratum

Landscape Setting: Soils that have been filled over what was originally hydric soils

Drainage Class: Well drained

Parent Material: Fill over marine silts and clays at <60 inches.

Typical Textures: Gravelly sandy loam fill

Hydrologic Soil Group: B

Dissimilar Inclusions: None noted

Limiting Inclusions: Upper slopes along the shore are steeper than the mapped unit and are affected by tidal inundation. These areas comprise less than 10% of the unit

Additional Notes: Soils in these areas have properties that are similar to the Charlton soil series for Hydrologic Soil Group determination

100*/dfabb—Udorthents, wet substratum

Landscape Setting: Soils that have been filled and leveled over what was originally hydric soils

Drainage Class: Moderately well drained

Parent Material: Fill over marine silts and clays at <60 inches.

Typical Textures: Very gravelly sandy loam fill

Hydrologic Soil Group: B

Dissimilar Inclusions: None noted

Limiting Inclusions: Slopes along the shore are steeper than the mapped unit and are affected by tidal inundation. These areas comprise less than 10% of the unit

Additional Notes: Soils in these areas have properties that are similar to the Sutton soil series for Hydrologic Soil Group determination

100*/ffccc—Udorthents, wet substratum

Landscape Setting: Soils that have been filled over what was originally hydric soils

Drainage Class: Poorly drained

Parent Material: Fill over marine silts and clays at <60 inches.

Typical Textures: Gravelly and cobbly sandy loam fill with some anthropogenic debris, such as bricks, over silt loam

Hydrologic Soil Group: C

Dissimilar Inclusions: None noted

Limiting Inclusions: None noted

Additional Notes: Soils in these areas have properties that are similar to the Shaker soil series for Hydrologic Soil Group determination. These soils are regularly inundated by the tides.

Site Specific Soil Map Legend

53 Green Street, Portsmouth, NH

Slope Class Identifiers

A	0-3%	D	15-25%
B	3-8%	E	25-50%
C	8-15%	F	>50%

Map Unit Symbols




<u>Map Number* /Disturbed Soil Numerator**</u>	<u>Soil Map Unit Name</u>	<u>Hydrologic Soil Group</u>
100*/cfabb	Udorthents, wet substratum / well drained, fill over marine silts and clays, no restrictive layer within 40 inches, moderate Ksat, Hydrologic Soil Group B	B
100*/dfabb	Udorthents, wet substratum, 0-3% slopes / moderately well drained, fill over marine silts and clays, no restrictive layer within 40 inches, moderate Ksat, Hydrologic Soil Group B	B
100*/ffccc	Udorthents, wet substratum, 0-3% slopes / poorly drained, fill over marine silts and clays, restrictive layer is present within 40 inches, low Ksat, Hydrologic Soil Group C	C

*Indicates the location of the slope class identifier (A-F)

**Supplemental symbols are used to further characterize disturbed soils for Alteration of Terrain permits

Soil Mapping Notes:

1. Hydrologic soil groups for disturbed soils were based on most similar soil series listed in *Ksat Values for NH Soils*, SSSNNE Special Publication No. 5, 2009.
2. Fieldwork for this map was conducted by Leonard A. Lord, PhD, NHCSS #19 on October 22 and December 2, 2019.
3. This detailed Site Specific Soil Map conforms to the standards of SSSNNE Publication No. 3, as amended, *Site Specific Soil Mapping Standards for NH and VT*.
4. This map has been prepared to comply with soil mapping requirements of RSA 485 A:17 and NHDES Env-Wq, Alteration of Terrain.
5. See accompanying narrative report for methodology, map symbol legend, and interpretations.



TAX MAP 124 LOT 10
VAUGHAN STREET HOTEL LLC
1359 HOOKSETT ROAD
HOOKSETT, NH 03106
R.C.R.D. BOOK 5848, PAGE 129

TAX MAP 119
LOT 2
72,200 SQ. FT. ±
1.65 AC. ±
AREA CALCULATED TO
MEAN HIGH WATER LINE
(SEE EXISTING
CONDITIONS PLAN)

TAX MAP 119 LOT 3
BOSTON & MAINE CORP
IRON HORSE PARK
BILLERICA, MA 01862

SITE SPECIFIC SOIL MAP LEGEND
53 GREEN STREET, PORTSMOUTH, NH


SLOPE CLASS IDENTIFIERS

A	0-3%	B	3-8%
C	8-15%	D	15-25%
E	25-50%	F	>50%

MAP UNIT SYMBOLS

MAP NUMBER*/ DISTRIBUTED SOIL NUMERATOR**	SOIL MAP UNIT NAME	HSG
100*/CFABB	UDORTMENTS, WET SUBSTRATUM / WELL DRAINED, FILL OVER MARINE SILTS AND CLAYS, NO RESTRICTIVE LAYER WITHIN 40 INCHES, MODERATE KSAT, HYDROLOGIC SOIL GROUP B	B
100*/DFABB	UDORTMENTS, WET SUBSTRATUM / MODERATELY WELL DRAINED, FILL OVER MARINE SILTS AND CLAYS, NO RESTRICTIVE LAYER WITHIN 40 INCHES, MODERATE KSAT, HYDROLOGIC SOIL GROUP B	B
100*/FFCCC	UDORTMENTS, WET SUBSTRATUM / POORLY DRAINED, FILL OVER MARINE SILTS AND CLAYS, RESTRICTIVE LAYER WITHIN 40 INCHES LOW KSAT, HYDROLOGIC SOIL GROUP C	C

- NOTES:**
- * INDICATES THE LOCATION OF THE SLOPE CLASS IDENTIFIER (A-F)
 - ** SUPPLEMENTAL SYMBOLS ARE USED TO FURTHER CHARACTERIZE DISTRIBUTED SOILS FOR THE ALTERATION OF TERRAIN PERMITS
- SOIL MAPPING NOTES:**
1. HYDROLOGIC SOIL GROUPS FOR DISTRIBUTED SOILS WERE BASED ON MOST SIMILAR SOIL SERIES LISTED IN *KSAT VALUES FOR NH SOILS*, SSSNNE SPECIAL PUBLICATION NO. 5, 2019
 2. FIELDWORK FOR THIS MAP WAS CONDUCTED BY LEONARD A. LORD, PHD, NHCSS #19 ON OCTOBER 22 AND DECEMBER 2, 2019
 3. THIS DETAILED SITE SPECIFIC SOIL MAP CONFORMS TO THE STANDARDS OF SSSNNE PUBLICATION NO. 3, AS AMENDED, *SITE SPECIFIC SOIL MAPPING STANDARDS FOR NH AND VT*
 4. THIS MAP HAS BEEN PREPARED TO COMPLY WITH SOIL MAPPING REQUIREMENTS OF RSA 485 A:17 AND NHDES ENV-WQ, ALTERATION OF TERRAIN.
 5. SEE ACCOMPANYING NARRATIVE REPORT FOR METHODOLOGY, MAP SYMBOL LEGEND, AND INTERPRETATIONS



**Proposed
Mixed Use
Development**

CPI
Management,
LLC

53 Green Street
Portsmouth, NH

MARK	DATE	DESCRIPTION
PROJECT NO:	C0960-011	
DATE:	MARCH 22, 2021	
FILE:	C0960-011_SSSM.DWG	
DRAWN BY:	AFS	
CHECKED:	LAL	
APPROVED:	LAL	

SITE SPECIFIC SOIL MAP

SCALE: AS SHOWN

Last Saved: 3/19/2021
 Plotted On: Mar 19, 2021 1:31:58pm
 By: A.Selbir
 Tighe & Bond\21\C0960-C0960-011_53 Green St., Portsmouth, NH Drawings\Figures\AutoCAD\Sheet\C0960-011_SSSM.dwg

APPENDIX B

Extreme Precipitation Tables

Northeast Regional Climate Center

Data represents point estimates calculated from partial duration series. All precipitation amounts are displayed in inches.

Smoothing	Yes
State	New Hampshire
Location	
Longitude	70.764 degrees West
Latitude	43.080 degrees North
Elevation	0 feet
Date/Time	Fri, 24 Jul 2020 12:23:19 -0400

Extreme Precipitation Estimates

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.26	0.40	0.50	0.65	0.81	1.04	1yr	0.70	0.98	1.21	1.56	2.03	2.65	2.92	1yr	2.35	2.81	3.22	3.94	4.54	1yr
2yr	0.32	0.50	0.62	0.81	1.02	1.30	2yr	0.88	1.18	1.52	1.94	2.48	3.20	3.57	2yr	2.84	3.43	3.93	4.67	5.32	2yr
5yr	0.37	0.58	0.73	0.97	1.25	1.61	5yr	1.08	1.47	1.89	2.43	3.14	4.06	4.57	5yr	3.59	4.40	5.03	5.93	6.69	5yr
10yr	0.41	0.65	0.82	1.11	1.45	1.89	10yr	1.25	1.72	2.23	2.89	3.74	4.86	5.52	10yr	4.30	5.31	6.07	7.09	7.96	10yr
25yr	0.48	0.76	0.97	1.33	1.77	2.33	25yr	1.53	2.14	2.77	3.62	4.73	6.16	7.09	25yr	5.45	6.81	7.78	9.00	10.03	25yr
50yr	0.53	0.86	1.10	1.53	2.07	2.75	50yr	1.78	2.52	3.28	4.31	5.65	7.37	8.57	50yr	6.53	8.24	9.40	10.79	11.95	50yr
100yr	0.59	0.96	1.24	1.76	2.41	3.25	100yr	2.08	2.97	3.90	5.15	6.75	8.83	10.36	100yr	7.82	9.96	11.35	12.93	14.24	100yr
200yr	0.67	1.10	1.42	2.04	2.82	3.82	200yr	2.43	3.51	4.60	6.11	8.06	10.58	12.52	200yr	9.37	12.04	13.71	15.50	16.98	200yr
500yr	0.80	1.31	1.71	2.48	3.47	4.75	500yr	2.99	4.37	5.75	7.68	10.19	13.45	16.11	500yr	11.90	15.49	17.61	19.72	21.44	500yr

Lower Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.23	0.36	0.44	0.59	0.73	0.88	1yr	0.63	0.86	0.92	1.33	1.68	2.23	2.48	1yr	1.97	2.39	2.86	3.18	3.88	1yr
2yr	0.31	0.49	0.60	0.81	1.00	1.19	2yr	0.86	1.16	1.37	1.82	2.34	3.05	3.45	2yr	2.70	3.31	3.82	4.54	5.07	2yr
5yr	0.35	0.54	0.67	0.92	1.17	1.40	5yr	1.01	1.37	1.61	2.12	2.73	3.78	4.18	5yr	3.34	4.02	4.71	5.52	6.23	5yr
10yr	0.38	0.59	0.73	1.02	1.32	1.60	10yr	1.14	1.56	1.80	2.39	3.06	4.36	4.85	10yr	3.86	4.66	5.42	6.39	7.17	10yr
25yr	0.44	0.67	0.83	1.18	1.56	1.90	25yr	1.34	1.86	2.10	2.76	3.54	4.70	5.87	25yr	4.16	5.64	6.62	7.76	8.65	25yr
50yr	0.48	0.73	0.91	1.31	1.76	2.17	50yr	1.52	2.12	2.34	3.07	3.93	5.31	6.77	50yr	4.70	6.51	7.68	9.00	9.98	50yr
100yr	0.53	0.81	1.01	1.46	2.00	2.47	100yr	1.73	2.41	2.62	3.42	4.35	5.96	7.81	100yr	5.28	7.51	8.92	10.45	11.52	100yr
200yr	0.59	0.89	1.12	1.63	2.27	2.81	200yr	1.96	2.75	2.93	3.79	4.79	6.68	9.01	200yr	5.91	8.66	10.34	12.15	13.31	200yr
500yr	0.68	1.02	1.31	1.90	2.70	3.36	500yr	2.33	3.28	3.41	4.32	5.46	7.76	10.87	500yr	6.87	10.45	12.58	14.86	16.11	500yr

Upper Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
1yr	0.28	0.44	0.54	0.72	0.89	1.08	1yr	0.77	1.06	1.26	1.74	2.21	2.98	3.16	1yr	2.64	3.04	3.58	4.37	5.04	1yr
2yr	0.34	0.52	0.64	0.86	1.07	1.27	2yr	0.92	1.24	1.48	1.96	2.52	3.42	3.70	2yr	3.03	3.56	4.08	4.83	5.62	2yr
5yr	0.40	0.62	0.76	1.05	1.34	1.62	5yr	1.15	1.58	1.88	2.53	3.25	4.33	4.96	5yr	3.84	4.77	5.37	6.37	7.15	5yr
10yr	0.47	0.72	0.89	1.24	1.61	1.97	10yr	1.39	1.93	2.28	3.11	3.95	5.33	6.20	10yr	4.72	5.96	6.82	7.83	8.74	10yr
25yr	0.57	0.87	1.09	1.55	2.04	2.57	25yr	1.76	2.51	2.95	4.07	5.15	7.77	8.34	25yr	6.88	8.02	9.15	10.33	11.40	25yr
50yr	0.67	1.02	1.27	1.82	2.46	3.12	50yr	2.12	3.05	3.59	5.00	6.32	9.73	10.46	50yr	8.62	10.06	11.45	12.71	13.95	50yr
100yr	0.79	1.19	1.49	2.15	2.95	3.80	100yr	2.55	3.72	4.37	6.15	7.76	12.18	13.11	100yr	10.78	12.61	14.32	15.68	17.08	100yr
200yr	0.92	1.39	1.76	2.54	3.55	4.64	200yr	3.06	4.54	5.33	7.58	9.53	15.29	16.45	200yr	13.53	15.82	17.94	19.34	20.91	200yr
500yr	1.14	1.70	2.19	3.18	4.52	6.02	500yr	3.90	5.89	6.92	10.01	12.54	20.67	22.22	500yr	18.29	21.37	24.18	25.50	27.33	500yr



APPENDIX C

Examination of Thermal Impacts from Stormwater BMPs



In a study in Durham, New Hampshire, four years of runoff temperature data were examined for a range of stormwater best management practices (BMPs) in relation to established environmental indicators.

The stormwater BMPs examined included:

Conventional	Low Impact Development	Manufactured Treatment Devices
<ul style="list-style-type: none"> • Vegetated Swale • Detention Pond • Retention Pond 	<ul style="list-style-type: none"> • Bioretention • Gravel Wetland 	<ul style="list-style-type: none"> • Storm Tech Isolator Row • ADS Infiltration System • Hydrodynamic Separator



Surface systems that are exposed to direct sunlight have been shown to increase already elevated summer runoff temperatures, while systems that provide treatment by infiltration and filtration can moderate runoff temperatures by thermal exchange with cool subsurface materials.

The storm drain system in this study had an annual average event mean temperature (EMT) greater than the mean groundwater temperature of 47°F that commonly feeds coldwater streams.

The examination of BMPs indicates that outflow from the larger surface systems is warmer and more variable than from parking lots. The filtration and infiltration systems cooled stormwater runoff to temperatures close to groundwater temperature.



Top: A view of a healthy coldwater fishery. Center: Large parking areas store tremendous amounts of heat which is transferred into stormwater runoff. Bottom: Subsurface treatment systems such as gravel wetlands can buffer temperature impacts for stormwater runoff.

SURFACE SYSTEMS: Thermal Extremes

The summer temperatures of the two stormwater ponds, vegetated swale, and HDS (Hydrodynamic Separators) systems, indicate that they **provide little to no reduction of high runoff temperatures.**

The Retention and Detention ponds have the largest variation in temperature. The Retention Pond is the only system to exceed both the Upper Optimum Limit (UOL) and the Lethal Limit of 80°F, however, the Detention Pond with a maximum temperature of 79.4°F comes very close.

The permanent pool of water in the Retention Pond appears to act as a heat sink during periods of extreme heat.

FILTRATION & INFILTRATION SYSTEMS: Thermal Buffers

Filtration and infiltration systems **showed the strongest ability to reduce temperature variations.** The gravel wetland, the ADS (Advanced Drainage Systems™) Infiltration System, and the StormTech Isolator Row have a strong capacity to reduce temperatures of runoff.


The Bioretention system showed minor buffering capacity and was consistently cooler in the summer and warmer in the winter than the runoff. These filtration and infiltration systems are, on average, reducing the summer temperatures and increasing the winter temperatures of the runoff to near the average groundwater temperature of 47°F.

The two subsurface infiltration systems, ADS and STIR, are the only systems with mean July temperatures within the optimum zone of 45°F to 65°F for coldwater aquatic species. All other systems result in runoff within the stress zone for aquatic species, between 65°F and 80°F.

The Gravel Wetland, the ADS infiltration system, and the Isolator Row systems have the lowest exceedance values of the UOL at 13.0%, 5.0%, 1.5% respectively.



StormTech Isolator Row.



Comparison of summer temperatures for two streams: Wednesday Hill Brook (unimpacted) and College Brook (impacted); a wet and dry pond, a gravel wetland, and subsurface infiltration (Stormtech Isolator Row) with environmental indicators for cold water fisheries:

Average Annual Groundwater Temperature (GW) = 47°F

Lower Optimum Limit (LOL) = 45°F

Upper Optimum Limit (UOL) = 65°F

Lethal Limit (LL) = 80°F

53 Green Street, Portsmouth, NH: Wetland & Buffer Report

To: Patrick Crimmins, PE
FROM: Leonard A. Lord, PhD, CSS, CWS
DATE: January 6, 2020
PROJECT: P-0595-007

On October 29 and December 2, 2019, Tighe & Bond delineated and assessed tidal wetlands and their 100-foot buffers at 53 Green Street, Portsmouth, NH. This 1.81-acre parcel lies along the northwestern end of North Mill Pond.

Methods

The wetland delineation was based on criteria specified in the *Corps of Engineers Wetlands Delineation Manual, Technical Report Y-87-1* (January 1987) and the *Regional Supplement to the Corps of Engineers Wetland Delineation Manual: Northcentral and Northeast Region* (January 2012). The Highest Observable Tide Line (HOTL) was delineated based on the definition found in the NH Department of Environmental Services (NHDES) Wetland Rules, Env-Wt 101.49/Env-Wt 602.23. Wetlands were classified based on the *Classification of Wetlands and Deepwater Habitats of the United States* (Cowardin et al., 1979). The only wetlands located on the parcel are tidal wetlands (HOTL), which were delineated with sequentially-numbered flagging labelled 1A-1 to 1A-19.

Important wetland functions and values were also assessed and summarized in the vicinity of the parcel. The assessment was based on the *Maine Citizens Guide to Evaluating, Restoring, and Managing Tidal Marshes* (Bryan et al., 1997) and *The Highway Methodology Workbook Supplement—Wetland Functions and Values: A Descriptive Approach*, NAEPP-360-1-30a, US Army Corps of Engineers, New England Division, (September 1999).

Wetlands

Wetlands on this site were classified as estuarine intertidal rocky shore, rubble, and regularly flooded (E2RS2N). The wetland edge slopes sharply and is predominantly covered with angular stones and cobbles. Sparse halophytic vegetation along the upper portion of the tidal wetland edge includes seaside plantain (*Plantago maritima*), sea lavender (*Limonium carolinianum*), salt meadow grass (*Spartina patens*), and seaside goldenrod (*Solidago sempervirens*). Lower portions of the slopes were covered with rockweed (*Ascophyllum nodosum*) within the intertidal zone. Important wetland functions and values in this portion of North Mill Pond include recreation potential and aesthetic quality, though both are impacted by the density and character of the surrounding urban development.

Tidal Buffer

The 100-foot tidal buffer on this parcel consists primarily of maintained lawn, a commercial building, and a parking lot. There are small patches of shrubby vegetation and small trees at the tops of the slopes between the lawn and tidal wetlands, particularly near both ends of the wetland delineation. Species in these areas include black locust (*Robinia pseudoacacia*),

eastern red cedar (*Juniperus virginiana*), staghorn sumac (*Rhus typhina*), and black cherry (*Prunus serotina*). The highly-developed tidal buffer provides some vegetated permeable surfaces to help reduce and filter runoff but otherwise does little to enhance and protect the downgradient tidal wetland.

\\tighebond.com\data\Data\Projects\P\0595 Pro Con General Proposals\0595-007 Raynes Ave Hotel\Raynes+Green Wetlands+Soils\Green St Wetland-Buffer Rept- 2020-1-9.pdf

Photographic Log

Client: ProCon

Job Number: P-0595-007



Site: 53 Green Street, Portsmouth, NH

Photograph No.: 1	Date: 10/29/2019	Direction Taken: Northeast
Description: Intertidal rocky shore and tidal buffer viewed from the southwest end of the site.		
		


Photograph No.: 2	Date: 10/29/2019	Direction Taken: Northeast
Description: Intertidal rocky shore and narrow shrubby portion of the tidal buffer at the northeastern end of the site.		
		

**PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET**

**WETLAND BUFFER IMPERVIOUS
SURFACE EXHIBIT**



Impervious Surface Within Buffer Area		
Local Wetland Buffer Setback	Impervious Surface	
	Existing Condition	Proposed Development
0 - 25 FT	0 SF	0 SF
25 - 50 FT	745 SF	98 SF
50 - 100 FT	10,836 SF	8,425 SF
Total Impervious Surface	11,581 SF	8,523 SF
Net Impervious Surface	-3,058 SF	




Tighe & Bond

Last Save Date: March 22, 2021, 11:25 AM By: ASELLAR
 Plot Date: Monday, March 22, 2021 Plotted By: Alexander Sellar
 TSS File Location: J:\C0960\011_53 Green St, Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-FIGS.dwg Layout: Tab: BUFFER

PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET
PORTSMOUTH, NEW HAMPSHIRE

SITE OVERLAY EXHIBIT







Tighe & Bond


Last Save Date: March 22, 2021, 11:25 AM By: ASELAR
Plot Date: Monday, March 22, 2021 Plotted By: Alexander Sellar
T&B File Location: J:\C0960\011_53 Green St, Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-FIGS.dwg Layout Tab: SITE AERIAL

**PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET
PORTSMOUTH, NEW HAMPSHIRE**

COMMUNITY SPACE EXHIBIT



COMMUNITY OPEN SPACE:		REQUIRED	PROVIDED
	NORTH MILL POND GREENWAY COMMUNITY SPACE		10,532 SF
	GREENWAY CONNECTION COMMUNITY SPACE		5,105 SF
	WIDE SIDEWALK COMMUNITY SPACE		700 SF
TOTAL LOT AREA: 77,311 SF COMMUNITY OPEN SPACE (20% OF TOTAL)		15,462 SF	16,337 SF





Tighe & Bond


Last Save Date: March 22, 2021, 11:25 AM By: ASELLAR
 Plot Date: Monday, March 22, 2021 Plotted By: Alexander Sellar
 TSS File Location: J:\C0960 Cabarrus\C-0960-011 53 Green St, Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-FIGS.dwg Layout: Tab: C.SPACE

**PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET
PORTSMOUTH, NEW HAMPSHIRE**

FIRE TRUCK TURNING EXHIBIT



Portsmouth Fire Truck	
Overall Length	47.830ft
Overall Width	8.500ft
Overall Body Height	10.432ft
Min Body Ground Clearance	0.862ft
Track Width	8.000ft
Lock-to-lock time	6.00s
Max Steering Angle (Virtual)	38.00°



Tighe & Bond


Last Save Date: March 22, 2021, 11:22 AM By: ASELLAR
 Plot Date: Monday, March 22, 2021 Plotted By: Alexander Sellar
 TSS File Location: J:\C0960\011_53 Green St, Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C-DSGN.dwg Layout Tab: FIRE TRUCK

PROPOSED MIXED USE DEVELOPMENT
53 GREEN STREET
PORTSMOUTH, NEW HAMPSHIRE

PHOTO LOCATION PLAN



Last Save Date: January 27, 2021, 11:50 AM By: CML
Plot Date: Wednesday, January 27, 2021, Plotted By: Craig M. Langton
TSS File Location: J:\C0960\011_53 Green St., Portsmouth, NH\Drawings_Figures\AutoCAD\C0960-011_C_Photo Location.dwg Layout Tab: PHOTO LOCATION



0 20' 40'
GRAPHIC SCALE

Tighe & Bond

January 27, 2021
C0960-011_C_Photo Location.dwg



Photo #1: Looking northeast at existing utility towers and parking located in 100-foot tidal wetland buffer.



Photo #2: Looking northeast towards Market Street across existing maintained lawn area located in 100-foot tidal wetland buffer.



Photo #3: Looking southwest along existing building within 100-foot tidal wetland buffer.



Photo #4: Looking northeast toward existing building and parking located in 100-foot tidal wetland buffer.



Photo #5: Looking southwest towards existing building and maintained lawn area located in 100-foot tidal wetland buffer.



Photo #6: Looking west across existing maintained lawn area and North Mill Pond toward location of future City park.



Photo #7: Looking north toward existing parking lot.