APPLICANT

2219 LAFAYETTE ROAD LLC 549 US HIGHWAY 1 BY-PASS PORTSMOUTH, NH 03801 (603) 319-0440

PREPARED FOR

2219 LAFAYETTE ROAD LLC 549 US HIGHWAY 1 BY-PASS PORTSMOUTH, NH 03801 (603) 319-0440

RESOURCE LIST

| PLANNING / ZONING DEPARTMENT 1 JUNKINS AVENUE, 3RD FLOOR PORTSMOUTH, NH 03801

(603) 610-7296 JULIET WALKER, PLANNING DIRECTOR

BUILDING DEPARTMENT 1 JUNKINS AVENUE, 3RD FLOOR

PORTSMOUTH, NH 03801 (603) 610-7261 ROBERT MARSILIA, CHIEF BUILDING INSPECTOR

PUBLIC WORKS

680 PEVERLY HILL ROAD PORTSMOUTH, NH 03801 (603) 427-1530 PETER RICE, DIRECTOR

POLICE DEPARTMENT 3 JUNKINS AVENUE

PORTSMOUTH, NH 03801 (603) 427-1512 ROBERT MERNER, CHIEF

FIRE DEPARTMENT

170 COURT STREET PORTSMOUTH, NH 03801 (603) 427-1515 STEVEN E. ACHILLES, CHIEF

ARCHITECT

T|W DESIGNS LLC 254 DRAKE HILL ROAD STRAFFORD, NH 03884 VISIONS@TW-DESIGNS.COM (603) 664-2181JOHN TUTTLE, PRINCIPAL


LAND SURVEYORS

MSC ENGINEERS a division of TFMORAN 170 COMMERCE WAY, SUITE 102 PORTSMOUTH, NH 03801 (603) 431-2222J. COREY COLWELL, LSS

KEY ACURA OF PORTSMOUTH

PORTSMOUTH, NEW HAMPSHIRE

MAY 7, 2019 LAST REVISED JULY 9, 2019







| 170 Commerce Way, Suite 102 Phone (603) 431-2222 Fax (603) 431-0910

INDEX OF SHEETS

SHEET	SHEET TITLE
C-01	COVER
C-02	EXISTING CONDITIONS PLAN
C-03	NOTES SHEET
C-04	SITE PREPARATION AND DEMOLITION PLAN
C-05	SITE & LAYOUT PLAN
C-06	GRADING AND DRAINAGE PLAN
C-07	UTILITY PLAN
C-08	LANDSCAPE PLAN
C-09	LANDSCAPE NOTES, DETAILS AND SCHEDULES
C-10	LIGHTING PLAN
C-11	EROSION CONTROL PLAN
C-12	EROSION CONTROL NOTES AND DETAILS
C-13	TRUCK MOVEMENT
C-14 TO C-15	DETAIL SHEET
A1.1 TO A4.1	ARCHITECTURAL PLANS (TW DESIGNS)

PERMITS/APPROVALS

	NUMBER	APPROVED	EXPIRES
ZBA APPROVAL	PENDING	PENDING	PENDING
TOWN SITE PLAN	PENDING	PENDING	PENDING
NHDOT DRIVEWAY	PENDING	PENDING	PENDING

THESE PLANS ARE PERMIT DRAWINGS ONLY AND HAVE NOT BEEN DETAILED FOR CONSTRUCTION OR BIDDING.

SITE DEVELOPMENT PLANS


TAX MAP 272 LOT 1


COVER SHEET KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

OWNED BY

2219 LAFAYETTE ROAD LLC

MAY 7, 2019





A division of **TFMoran**, Inc.

170 Commerce Way, Suite 102 Structural Engineers Portsmouth, NH 03801 Traffic Engineers Phone (603) 431-2222 Land Surveyors Fax (603) 431-0910 Landscape Architects

CK CRR CADFILE 45407-80_Cover.dwg C-01




Copyright 2019 © Thomas F. Moran, Inc.

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of Thomas F. Moran, Inc.

This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.



PLANNING BOARD FILE # 48 Constitution Drive, Bedford, N.H. 03110



ENV-WQ 1500 AS APPLICABLE.

- AN ALTERATION OF TERRAIN PERMIT IS NOT REQUIRED SINCE THE DISTURBANCE IS LESS THAN 100,000 SF. THE SITE CONTRACTOR SHALL ENSURE THAT ALL WORK IS PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS OF NHDES
- 4. CONTACT EASEMENT OWNERS PRIOR TO COMMENCING ANY WORK WITHIN THE EASEMENTS.
- 5. ALL WORK SHALL CONFORM TO THE APPLICABLE REGULATIONS AND STANDARDS OF THE CITY OF PORTSMOUTH, AND SHALL BE BUILT IN A WORKMANLIKE MANNER IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS.
- ALL WORK TO CONFORM TO CITY OF PORTSMOUTH, DEPARTMENT OF PUBLIC WORKS STANDARD SPECIFICATIONS. ALL WORK WITHIN THE RIGHT-OF-WAY OF THE CITY AND/OR STATE SHALL COMPLY WITH APPLICABLE STANDARDS.
- ALL DEMOLITION SHALL INSURE MINIMUM INTERFERENCE WITH ROADS, STREETS, WALKWAYS AND ANY OTHER ADJACENT OPERATING FACILITIES. PRIOR WRITTEN PERMISSION FROM THE OWNER/DEVELOPER AND LOCAL PERMITTING AUTHORITY IS REQUIRED IF CLOSURE/OBSTRUCTIONS TO ROADS, STREET, WALKWAYS AND OTHERS IS DEEMED NECESSARY. CONTRACTOR TO PROVIDE ALTERNATE ROUTES AROUND CLOSURES/OBSTRUCTIONS PER CITY/GOVERNMENTAL
- REFER TO ARCHITECTURAL PLANS FOR LAYOUT OF BUILDING FOUNDATIONS AND CONCRETE ELEMENTS WHICH ABUT THE BUILDING SUCH AS STAIRS, SIDEWALKS, LOADING DOCK RAMPS, PADS AND COMPACTOR PADS. DO NOT USE SITE PLANS FOR LAYOUT OF FOUNDATIONS.
- 9. SNOW SHALL NOT BE STOCKPILED IN SEDIMENT FOREBAYS, WETLAND BUFFERS OR WETLANDS. SEE SNOW STORAGE LOCATIONS. IN THE EVENT THAT THE SNOW STORAGE AREAS PROVIDED ON THE SITE ARE COMPLETELY UTILIZED, EXCESS SNOW SHALL BE TRANSPORTED OFF SITE FOR DISPOSAL IN ACCORDANCE WITH NHDES REGULATION. IF SNOW IS STORED WITHIN PARKING AREA, KEEP CATCH BASINS CLEAR.
- 10. TEMPORARY FENCING SHALL BE PROVIDED AND COVERED WITH A FABRIC MATERIAL TO CONTROL DUST MITIGATION.
- 11. IN THE EVENT OF A CONFLICT BETWEEN PLANS, SPECIFICATIONS, AND DETAILS, THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY FOR CLARIFICATION.
- 12. IF CONDITIONS AT THE SITE ARE DIFFERENT THAN SHOWN ON THE PLANS, THE ENGINEER SHALL BE NOTIFIED PRIOR TO PROCEEDING WITH THE AFFECTED WORK.
- 13. CONTRACTOR TO NOTIFY ENGINEER IN WRITING OF ANY DISCREPANCIES OF PROPOSED LAYOUT AND EXISTING FEATURES.
- 14. THESE PLANS WERE PREPARED UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER. MSC A DIVISION OF TFMORAN, INC. ASSUMES NO LIABILITY AS A RESULT OF ANY CHANGES OR NON-CONFORMANCE WITH THESE PLANS EXCEPT UPON THE WRITTEN APPROVAL OF THE ENGINEER OF RECORD.
- 15. MSC A DIVISION OF TEMORAN, INC. ASSUMES NO LIABILITY FOR WORK PERFORMED WITHOUT AN ACCEPTABLE PROGRAM OF TESTING AND INSPECTION AS APPROVED BY THE ENGINEER OF RECORD.
- 16. AT COMPLETION OF CONSTRUCTION, THE SITE CONTRACTOR SHALL PROVIDE A LETTER CERTIFYING THAT THE PROJECT WAS COMPLETED IN ACCORDANCE WITH THE APPROVED PLANS AND SPECIFICATIONS, AND A LETTER STAMPED BY A QUALIFIED ENGINEER THAT THEY HAVE OBSERVED ALL UNDERGROUND DETENTION SYSTEMS, INFILTRATION SYSTEMS, OR FILTERING SYSTEMS PRIOR TO BACKFILL, AND THAT SUCH SYSTEMS CONFORM TO THE APPROVED PLANS AND
- 17. IF ANY DEVIATIONS FROM THE APPROVED PLANS AND SPECIFICATIONS HAVE BEEN MADE, THE SITE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWING STAMPED BY A LICENSED SURVEYOR OR QUALIFIED ENGINEER ALONG WITH A LETTER STAMPED BY A QUALIFIED ENGINEER DESCRIBING ALL SUCH DEVIATIONS, AND BEAR ALL COSTS FOR PREPARING AND FILING ANY NEW PERMITS OR PERMIT AMENDMENTS THAT MAY BE REQUIRED.
- 18. THE SITE PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY OF REGISTRY OF DEEDS.
- 19. ALL IMPROVEMENTS SHOWN ON THE SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE PORTSMOUTH PLANNING DIRECTOR.
- 20. CONTRACTOR'S RESPONSIBILITIES:
- A. TO NOTIFY ENGINEER IN WRITING OF ANY DISCREPANCIES OF PROPOSED LAYOUT AND/OR EXISTING FEATURES.
- B. THE CONTRACTOR SHALL EMPLOY A LICENSED LAND SURVEYOR TO DETERMINE ALL LINES AND GRADES.
- C. EMPLOY A LICENSED SURVEYOR TO DETERMINE ALL LINES AND GRADES AND LAYOUT OF SITE ELEMENTS AND
- D. PROVIDE AN AS-BUILT PLAN AT THE COMPLETION OF THE PROJECT TO THE PLANNING DIRECTOR AND PER CITY REGULATIONS.
- E. PROTECTING NEW AND EXISTING BURIED UTILITIES DURING INSTALLATION OF ALL SITE ELEMENTS. DAMAGED UTILITIES SHALL BE REPAIRED OR REPLACED AT NO ADDITIONAL COST TO THE OWNER.
- TAKE APPROPRIATE MEASURES TO REDUCE, TO THE FULLEST EXTENT POSSIBLE, NOISE, DUST AND UNSIGHTLY
- . COORDINATE WITH ALL UTILITY COMPANIES AND CONTACT DIGSAFE (811 OR 888-344-7233) AT LEAST 72 HOURS
- H. THE CONTRACTOR IS RESPONSIBLE FOR THE MEANS AND METHODS OF CONSTRUCTION AND FOR CONDITIONS AT THE SITE. THESE PLANS, PREPARED BY MSC A DIVISION OF TFMORAN, INC., DO NOT EXTEND TO OR INCLUDE SYSTEMS PERTAINING TO THE SAFETY OF THE CONSTRUCTION CONTRACTOR OR THEIR EMPLOYEES, AGENTS OR REPRESENTATIVES IN THE PERFORMANCE OF THE WORK. THE SEAL OF THE SURVEYOR OR ENGINEER HEREON DOES NOT EXTEND TO ANY SUCH SAFETY SYSTEMS THAT MAY NOW OR HEREAFTER BE INCORPORATED INTO THESE PLANS. THE CONSTRUCTION CONTRACTOR SHALL PREPARE OR OBTAIN THE APPROPRIATE SAFETY SYSTEMS WHICH MAY BE REQUIRED BY THE US OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) AND/OR LOCAL REGULATIONS.
- VERIFY LAYOUT OF PROPOSED BUILDING FOUNDATIONS WITH ARCHITECT AND THAT PROPOSED FOUNDATION MEETS PROPERTY LINE SETBACKS PRIOR TO COMMENCING ANY FOUNDATION CONSTRUCTION.
- J. THE CONTRACTOR SHALL BID AND PERFORM THE WORK IN ACCORDANCE WITH ALL LOCAL, STATE AND NATIONAL CODES, SPECIFICATIONS, REGULATIONS AND STANDARDS.
- K. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO BECOME FAMILIAR WITH THE SITE AND ALL SURROUNDING CONDITIONS. THE CONTRACTOR SHALL ADVISE THE APPROPRIATE AUTHORITY OF INTENTIONS AT LEAST 48 HOURS
- L. THE CONTRACTOR SHALL MAINTAIN EMERGENCY ACCESS TO ALL AREAS AFFECTED BY WORK AT ALL TIMES.
- . ALL CONDITIONS ON THIS PLAN SHALL REMAIN IN EFFECT IN PERPETUITY PURSUANT TO THE REQUIREMENTS OF THE SITE PLAN REVIEW REGULATIONS.

PAVEMENT NOTES

- 1. WHERE PROPOSED PAVEMENT MEETS EXISTING PAVEMENT, THE SEAM SHALL BE A SAW CUT EDGE AND TREATED WITH EMULSION
- 2. ADJUST ALL MANHOLES, CATCHBASINS, CURB BOXES, MONITORING WELL BOXES, ETC. WITHIN LIMITS OF WORK TO FINISH GRADE PRIOR TO INSTALLATION OF SURFACE PAVEMENT LAYER.
- 3. CONTRACTOR SHALL PROVIDE A FINISH PAVEMENT SURFACE FREE OF LOW SPOTS AND PONDING AREAS. CRITICAL AREAS INCLUDE STOREFRONT, ACCESSIBLE PARKING, LOADING AREA AND FRONT
- 4. WHERE EXISTING PAVEMENT THAT IS OVERLAID MEETS EXISTING PAVEMENT TO REMAIN, THE LIMITS SHALL BE MILLED TO CREATE A 5' WIDE BY 1.5" DEEP KEY JOINT (SEE DETAIL).
- 5. THE GRADE SURFACE TOLERANCE AT THE INTERFACE BETWEEN EXISTING PAVEMENT TO REMAIN AND PROPOSED NEW PAVEMENT SHALL NOT VARY MORE THEN 3/8" FROM A 10' STRAIGHT EDGE. MEASURED IN ANY DIRECTION PLACED AT ANY LOCATION ALONG THE INTERFACE.
- 6. THE FINISHED GRADE AT BOTTOM OF ALL ACCESSIBLE RAMPS SHALL BE FLUSH WITH PAVEMENT WITH A TOLERANCE OF PLUS OR MINUS 1/4".
- 7. COMPLETE PERMANENT PAVEMENT TRENCH PATCH FOR UTILITY INSTALLATION PRIOR TO OVERLAY.

VARIANCES

ZONING RELIEF HAS BEEN GRANTED FROM THE FOLLOWING ARTICLES OF THE CITY OF PORTSMOUTH ZONING ORDINANCE:

1. SECTION 10.1114.20-PARKING STALL LAYOUT; REQUIRED: 19 FEET, PROVIDED; 18 FEET.

CONSTRUCTION SEQUENCE

TO MINIMIZE EROSION AND SEDIMENTATION DUE TO CONSTRUCTION, CONSTRUCTION SHALL FOLLOW THIS GENERAL CONSTRUCTION SEQUENCE.

MODIFICATIONS TO THE SEQUENCE NECESSARY DUE TO THE CONTRACTOR'S SCHEDULE SHALL INCLUDE APPROPRIATE TEMPORARY AND PERMANENT EROSION AND SEDIMENTATION CONTROL MEASURES.

THE CONTRACTOR SHALL SCHEDULE WORK SUCH THAT ANY CONSTRUCTION AREA IS STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE EXCEPT AS NOTED BELOW. NO MORE THAN 5 ACRES OF DISTURBED LAND SHALL BE UNSTABILIZED AT ANY ONE TIME.

THE PROJECT SHALL BE MANAGED SO THAT IT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER ARG 3800 RELATIVE TO INVASIVE SPECIES.

- 1. NOTIFY EASEMENT OWNERS PRIOR TO COMMENCEMENT OF WORK.
- 2. INSTALL ALL PERIMETER EROSION PROTECTION MEASURES AS INDICATED ON THE PLANS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION.
- 3. PONDS AND SWALES SHALL BE INSTALLED BEFORE ROUGH GRADING THE SITE.
- 4. DURING CONSTRUCTION EVERY EFFORT SHALL BE MADE TO MANAGE SURFACE RUNOFF QUALITY.
- 5. DAILY, OR AS REQUIRED, CONSTRUCT TEMPORARY BERMS, DRAINS, DITCHES, SILT BARRIERS, SEDIMENT TRAPS, ETC.. MULCH AND SEED AS REQUIRED (TEMPORARY SEED MIXTURE OF WINTER RYE APPLIED AT A RATE OF 2.5 LBS/1000 SF SHALL BE USED).
- 6. CONDUCT MAJOR EARTHWORK, INCLUDING CLEARING AND GRUBBING, WITHIN THE LIMITS OF WORK. ALL CUT AND FILL SLOPES SHALL BE SEEDED WITHIN 72 HOURS AFTER GRADING.
- 7. ALL STRIPPED TOPSOIL AND OTHER EARTH MATERIALS SHALL BE STOCKPILED OUTSIDE THE IMMEDIATE WORK AND WETLAND AREAS. A SILT BARRIER SHALL BE CONSTRUCTED AROUND THESE PILES IN A MANNER TO PROVIDE ACCESS AND AVOID SEDIMENT OUTSIDE OF THE WORK AREA.
- 8. CONSTRUCT BUILDING PAD AND COMMENCE NEW BUILDING ADDITIONS CONSTRUCTION.
- 9. CONSTRUCT TEMPORARY CULVERTS AND DIVERSIONS AS REQUIRED.
- 10. BEGIN PERMANENT AND TEMPORARY INSTALLATION OF SEED AND MULCH.
- 11. PERFORM EARTHWORK NECESSARY TO ESTABLISH ROUGH GRADING AROUND PARKING FIELDS AND ACCESS DRIVES. MANAGE EXPOSED SOIL SURFACES TO AVOID TRANSPORTING SEDIMENTS INTO WETLANDS. PARKING LOTS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.
- 12. INSTALL SUBSURFACE UTILITIES (WATER, SEWER, GAS, ELECTRIC, COMMUNICATIONS, DRAINAGE, DRAINAGE FACILITIES, ETC.).
- 13. CONSTRUCT PROPOSED PARKING AREAS, DISPLAY AREAS, AND AISLES. ALL DITCHES, SWALES, AND GRAVEL WETLANDS SHALL BE FULLY STABILIZED PRIOR TO DIRECTING FLOW TO THEM.
- 14. COMPLETE BUILDING AND ALL OFF-SITE IMPROVEMENTS.
- 15. COMPLETE SEEDING AND MULCHING. SEED TO BE APPLIED WITH BROADCAST SPREADER OR BY HYDRO-SEEDING, THEN ROLLED, RAKED OR DRAGGED TO ASSURE SEED/SOIL CONTACT.
- 16. REMOVE TEMPORARY EROSION CONTROL MEASURES AFTER SEEDED AREAS HAVE BECOME FIRMLY ESTABLISHED AND SITE IMPROVEMENTS ARE COMPLETE.
- 17. DURING THE COURSE OF THE WORK AND UPON COMPLETION, THE CONTRACTOR SHALL REMOVE ALL SEDIMENT DEPOSITS, EITHER ON OR OFF SITE, INCLUDING CATCH BASINS AND SUMPS, DRAIN PIPES AND DITCHES, CURB LINES, ALONG SILT BARRIERS, ETC. RESULTING FROM SOIL AND/OR CONSTRUCTION

18. SEE WINTER CONSTRUCTION SEQUENCE FOR WORK CONDUCTED AFTER OCTOBER 15TH.

CITY NOTES

- 1. THIS SITE PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.
- 2. ALL IMPROVEMENTS SHOWN ON THIS SITE PLAN SHALL BE CONSTRUCTED AND MAINTAINED IN ACCORDANCE WITH THE PLAN BY THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS. NO CHANGES SHALL BE MADE TO THIS SITE PLAN WITHOUT THE EXPRESS APPROVAL OF THE CITY PLANNING DIRECTOR.

LAYOUT & MATERIAL NOTES

- 1. ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO APPLICABLE CITY, STATE, AND FEDERAL CODES.
- 2. ALL ON-SITE CURBING SHALL BE VERTICAL GRANITE CURBING. ALL DIMENSIONS ARE TO THE FACE OF CURB UNLESS NOTED OTHERWISE.
- 3. ALL SIDEWALK AND OTHER CURB REVEALS NOT IDENTIFIED TO BE FLUSH SHALL BE 6" WITH A TOLERANCE OF PLUS OR MINUS 3/8".
- 4. CURBING ALIGNMENT SHALL BE MODIFIED TO AVOID CONFLICTS WITH ALL UTILITY MANHOLES OR POLES AND OTHER CASTINGS. ALL CONFLICTS SHALL BE REVIEWED WITH THE OWNER PRIOR TO PLACEMENT OF CURB FOR APPROVAL OF MODIFIED
- 5. WHERE NEW CURB MEETS EXISTING CURB OR CURBING OF A DIFFERENT MATERIAL OR CONFIGURATION, A TRANSITION PIECE SHALL BE INCLUEDED SO THAT CONNECTION IS FLUSH IN ALIGNMENT, WIDTH AND REVEAL.
- 6. ALL TRAFFIC PAINT SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F".
- 7. ALL PAINTED ISLANDS SHALL BE 4" WIDE DIAGONAL LINES AT 3'-0" O.C. BORDERED BY 4" WIDE LINES.
- 8. ALL PAVEMENT MARKINGS AND SIGNS TO CONFORM TO THE LATEST EDITIONS OF "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", "STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS" AND THE AMERICANS WITH DISABILITIES ACT REQUIREMENTS.
- 9. REFER TO ARCHITECTURAL PLANS FOR LAYOUT OF BUILDING FOUNDATIONS AND CONCRETE ELEMENTS WHICH ABUT THE BUILDING SUCH AS STAIRS, SIDEWALKS, LOADING DOCK RAMPS AND PADS. DO NOT USE SITE PLANS FOR LAYOUT OF FOUNDATIONS.
- 10. WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS. THE CONTRACTOR SHALL USE CAUTION WHEN SCALING REPRODUCED PLANS. IN CASE OF CONFLICT BETWEEN THIS PLAN SET AND ANY OTHER DRAWING AND/OR SPECIFICATION, THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY FOR

SITE DEVELOPMENT PLANS

TAX MAP 272 LOT 1


NOTES SHEET KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE


OWNED BY

2219 LAFAYETTE ROAD LLC

MAY 7, 2019

C-03





Civil Engineers Scientists A division of TFMoran, Inc.

| 170 Commerce Way, Suite 102 Structural Engineers Portsmouth, NH 03801 Traffic Engineers Phone (603) 431-2222 Land Surveyors Fax (603) 431-0910 Landscape Architects www.TFMoran.com

CK XXX CADFILE 45407-80_Notes.dwg

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110


Thomas F. Moran, Inc.


PLANNING BOARD FILE #

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of Thomas F. Moran, Inc. This plan is not effective unless signed by a duly authorized officer of









3. PROPOSED BUILDING ADDITIONS WILL HAVE NEW FOUNDATIONS.

TO BUILDING PERMIT APPLICATION.

5. SEE SHEET C-03 FOR ADDITIONAL SITE NOTES.

4. SITE IS INTENDED TO BE OPEN DURING CONSTRUCTION: A LIFE-SAFETY PLAN WILL BE REQUIRED PRIOR

48 Constitution Drive, Bedford, N.H. 03110

Thomas F. Moran, Inc.

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever

This plan is not effective unless signed by a duly authorized officer of

CONTACT DIG SAFE 72 BUSINESS

HOURS PRIOR TO CONSTRUCTION

without the prior written permission of Thomas F. Moran, Inc.

Traffic Engineers Land Surveyors Landscape Architects Scientists A division of TFMoran, Inc.

2 7/8/19 REVISED PER TAC COMMENTS

1 6/17/19 REVISED PER TAC COMMENTS

REV. DATE

Graphic Scale in Feet

RCK CRR


RCK CRR


DR CK

170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

MAY 7, 2019

DR RCK FB 45407.80 C-05 CK CRR CADFILE 45407-80_Site.dwg





UTILITY NOTES

- 1. ALL WORK SHALL CONFORM TO THE APPLICABLE REGULATIONS AND STANDARDS OF THE CITY OF PORTSMOUTH, AND SHALL BE BUILT IN A WORKMANLIKE MANNER IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS. COORDINATE ALL WORK WITHIN THE RIGHT-OF-WAY WITH APPROPRIATE TOWN, COUNTY AND/OR STATE AGENCY.
- 2. ALL PROPOSED UTILITY WORK, INCLUDING MATERIAL, INSTALLATION, TERMINATION, EXCAVATION, BEDDING, BACKFILL, COMPACTION, TESTING, CONNECTIONS, AND CONSTRUCTION SHALL BE COORDINATED WITH AND COMPLETED IN ACCORDANCE WITH THE APPROPRIATE REQUIREMENTS, CODES AND STANDARDS OF ALL CORRESPONDING UTILITY ENTITIES AND SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 3. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO BECOME FAMILIAR WITH THE SITE AND ALL SURROUNDING CONDITIONS.
- EXCEPT FOR THE RELOCATION OF THE EXISTING WATER SERVICE, ALL UTILITY CONNECTIONS FOR THE PROPOSED ADDITIONS ARE FROM THE EXISTING BUILDING. NO NEW SEWER CONNECTIONS ARE PROPOSED. (SEE ARCHITECTURAL PLANS FOR MORE DETAIL).
- 5. THE CONTRACTOR IS RESPONSIBLE FOR THE MEANS AND METHODS OF CONSTRUCTION AND FOR THE CONDITIONS AT THE SITE. WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND REPORT DISCREPANCIES TO THE ENGINEER.
- 6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION, SIZE AND ELEVATION OF ALL EXISTING UTILITIES, SHOWN OR NOT SHOWN ON THESE PLANS, PRIOR TO THE START OF ANY CONSTRUCTION. THE ENGINEER SHALL BE NOTIFIED IN WRITING OF ANY UTILITIES FOUND INTERFERING WITH THE PROPOSED CONSTRUCTION AND APPROPRIATE REMEDIAL ACTION BE AGREED TO BY THE ENGINEER BEFORE PROCEEDING WITH THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTACT "DIGSAFE" (811) AT LEAST 72 HOURS BEFORE DIGGING.
- 7. THE CONTRACTOR SHALL CONTACT ALL UTILITY COMPANIES OWNING UTILITIES, EITHER OVERHEAD OR UNDERGROUND, WITHIN THE CONSTRUCTION AREA AND SHALL COORDINATE AS NECESSARY WITH THE UTILITY COMPANIES OF SAID UTILITIES. THE PROTECTION OR RELOCATION OF UTILITIES IS ULTIMATELY THE RESPONSIBILITY OF THE CONTRACTOR.
- 8. PROVIDE PERMANENT PAVEMENT REPAIR FOR ALL UTILITY TRENCHES IN EXISTING ROAD OR PAVEMENT TO REMAIN. SAW CUT TRENCH, PAVEMENT AND GRANULAR BASE THICKNESS TO MATCH EXISTING PAVEMENT. OBTAIN ALL PERMITS REQUIRED FOR TRENCHING.
- 9. THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MANHOLES, BOXES, FITTINGS, CONNECTORS, COVER PLATES AND OTHER MISCELLANEOUS ITEMS NOT NECESSARILY DETAILED ON THESE DRAWINGS TO RENDER THE UTILITY INSTALLATION COMPLETE AND OPERATIONAL.
- 10. SEE EXISTING FEATURES PLAN FOR ANY KNOWN EXISTING UTILITY EASEMENTS. CONTACT ALL EASEMENT OWNERS PRIOR TO COMMENCING ANY WORK WITHIN THE EASEMENT.
- 11. ALL UTILITY STRUCTURES IN PAVEMENT SHALL BE SET TO FINISH GRADE REGARDLESS OF ANY ELEVATIONS OTHERWISE SHOWN.
- 12. LENGTH OF PIPE IS FOR CONVENIENCE ONLY. ACTUAL PIPE LENGTH SHALL BE DETERMINED IN THE
- 13. UNLESS OTHERWISE SPECIFIED, ALL UNDERGROUND STRUCTURES, PIPES, CHAMBERS, ETC. SHALL BE COVERED WITH A MINIMUM OF 18" OF COMPACTED SOIL BEFORE EXPOSURE TO VEHICLE LOADS.
- 14. THE CONTRACTOR SHALL ARRANGE AND PAY FOR ALL INSPECTIONS, TESTING AND RELATED SERVICES AND SUBMIT COPIES OF ACCEPTANCE TO THE OWNER, UNLESS OTHERWISE INDICATED.
- 15. COORDINATE ALL WORK ADJACENT TO PROPOSED BUILDINGS WITH ARCHITECTURAL BUILDING DRAWINGS. CONFIRM UTILITY PENETRATIONS AND INVERT ELEVATIONS ARE COORDINATED PRIOR TO
- 16. THE EXACT LOCATION OF NEW UTILITY CONNECTIONS SHALL BE DETERMINED BY THE CONTRACTOR IN COORDINATION WITH UTILITY COMPANY, COUNTY AGENCY AND/OR PRIVATE UTILITY COMPANY.
- 17. SANITARY SEWER FOR PROPOSED ADDITIONS WILL CONNECT INTERNALLY TO THE EXISTING STRUCTURE, AND USE EXISTING SEWER SERVICE.
- 18. ON-SITE WATER DISTRIBUTION SHALL BE TO THE CITY OF PORTSMOUTH STANDARDS AND SPECIFICATIONS. WATER MAINS SHALL HAVE A MINIMUM OF 5.5 FEET COVER. WHERE WATER PIPES CROSS SEWER LINES A MINIMUM OF 18" VERTICAL SEPARATION BETWEEN THE TWO OUTSIDE PIPE WALLS SHALL BE OBSERVED. HORIZONTAL SEPARATION BETWEEN WATER AND SEWER SHALL BE 10 FEET MINIMUM. WHERE A SANITARY LINE CROSSES A WATER LINE, ENCASE THE SANITARY LINE IN 6" THICK CONCRETE FOR A DISTANCE OF 10' EITHER SIDE OF THE CROSSING, OR SUBSTITUTE RUBBER-GASKETED PRESSURE PIPE FOR THE SAME DISTANCE. WHEN SANITARY LINES PASS BELOW WATER LINES, LAY PIPE SO THAT NO JOINT IN THE SANITARY LINE WILL BE CLOSER THAN 3' HORIZONTALLY TO THE WATER LINE.
- 19. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR CONDUIT AND WIRING TO ALL SIGNS AND LIGHTS. CONDUIT TO BE A MINIMUM OF 24" BELOW FINISH GRADE.
- 20. ALL PROPOSED UTILITIES SHALL BE UNDERGROUND. ALL UNDERGROUND CONDUITS SHALL HAVE NYLON PULL ROPES.
- 21. ALL UTILITY COMPANIES REQUIRE INDIVIDUAL CONDUITS. CONTRACTOR TO COORDINATE WITH TELEPHONE, CABLE AND ELECTRIC COMPANIES REGARDING NUMBER, SIZE AND TYPE OF CONDUITS REQUIRED PRIOR TO INSTALLATION OF ANY CONDUIT.
- 22. THRUST BLOCKS SHALL BE PROVIDED AT ALL LOCATIONS WHERE WATER LINE CHANGES DIRECTIONS OR CONNECTS TO ANOTHER WATER LINE.
- 23. SDR-11 PIPE SHALL CONFORM WITH ASTM 3035 PER ENV-WQ 704.08 (D).
- THE PROPERTY WILL CONTINUE TO BE SERVICED BY THE FOLLOWING:

DRAINAGE	PRIVATE	
SEWER	MUNICIPAL	(603) 427-1530
WATER	MUNICIPAL	(603) 427-1530
GAS	UNITIL	(603) 772-0775
ELECTRIC	EVERSOURCE	(800) 662-7764
TELEPHONE	CONSOLIDATED COMMUNICATIONS	(800) 240-5019
CABLE	COMCAST	(800) 266 2278

24. THE FIRE DEPARTMENT MUST BE NOTIFIED DURING THE WATER PIPE CONSTRUCTION THAT THE FIRE

SITE DEVELOPMENT PLANS

TAX MAP 272 LOT 1

UTILITY PLAN KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

OWNED BY

2219 LAFAYETTE ROAD LLC

SCALE:1' = 40'(22X34) 1' = 80'(11X17)

MAY 7, 2019



DR CK

MSC
A division of TFMoran, Inc


Civil Engineers Structural Engineers Traffic Engineers Land Surveyors Landscape Architects Scientists

170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

DR RCK 45407.80 C-07 CK CRR CADFILE 45407-80_Utility.dwg

Graphic Scale in Feet

REV. DATE



- 2. CONTRACTOR WILL LOCATE, VERIFY AND MARK ALL EXISTING AND NEWLY INSTALLED UNDERGROUND UTILITIES PRIOR TO ANY LAWNWORK OR PLANTING. ANY CONFLICTS WHICH MIGHT OCCUR BETWEEN PLANTING AND UTILITIES WILL IMMEDIATELY BE REPORTED TO THE LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE, SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
- 3. CONTRACTOR WILL FURNISH AND PLANT ALL PLANTS IN QUANTITIES AS SHOWN ON THIS PLAN. IN CASES OF DISCREPANCY BETWEEN PLAN AND LIST CLARIFY WITH LANDSCAPE ARCHITECT PRIOR TO PLACING PURCHASE ORDER AND AGAIN PRIOR TO PLANTING.
- 4. SEE PLANTING DETAILS AND IF INCLUDED, SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- 5. NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT PRIOR WRITTEN APPROVAL OF THE LANDSCAPE ARCHITECT OR OWNER'S
- 6. PLANTING SHALL BE COMPLETED FROM APRIL 15TH THROUGH OCTOBER 15TH UNLESS OTHERWISE NOTED IN SPECIFICATIONS. THERE WILL BE NO PLANTING DURING JULY AND AUGUST UNLESS SPECIAL PROVISIONS ARE MADE FOR DROUGHT BY PROVIDING ADDITIONAL WATERING.
- 7. ALL PLANTS WILL BE NURSERY GROWN.
- 8. PLANTS WILL BE IN ACCORDANCE, AT A MINIMUM, WITH CURRENT EDITION OF "AMERICAN STANDARDS FOR NURSERY STOCK" AS PUBLISHED BY THE AMERICAN HORTICULTURE INDUSTRY ASSOCIATION.
- 9. TREES WILL BE PRUNED IN ACCORDANCE WITH THE LATEST EDITION OF ANSI A300 PART 1, "TREE, SHRUB AND OTHER WOODY PLANT MAINTENANCE STANDARD PRACTICES".
- 10. PLANTS MATERIAL IS SUBJECT TO APPROVAL / REJECTION BY THE LANDSCAPE ARCHITECT AT THE SITE AND AT THE NURSERY.
- 11. ALL PLANTS WILL BE MOVED WITH ROOT SYSTEMS AS SOLID UNITS AND WITH BALLS OF EARTH FIRMLY WRAPPED WITH BURLAP. NO PLANT WILL BE ACCEPTED WHEN BALL OF EARTH SURROUNDING ITS ROOTS HAS BEEN BADLY CRACKED OR BROKEN BEFORE PLANTING. ALL PLANTS THAT CANNOT BE PLANTED AT ONCE WILL BE HEELED-IN BY SETTING IN THE GROUND AND COVERING THE BALLS WITH SOIL AND THEN WATERING. DURING TRANSPORT, ALL PLANT MATERIALS WILL BE WRAPPED WITH WIND PROOF COVERING.
- 12. PROPOSED TREES OVERHANGING SIDEWALKS, ROADS OR PARKING WILL BEGIN BRANCHING NATURALLY (NOT PRUNED) AT 6' HEIGHT.
- 13. MULCH FOR PLANTED AREAS (NOT INCLUDING RAIN GARDENS) WILL BE AGED SHREDDED PINE BARK, PARTIALLY DECOMPOSED, DARK BROWN IN COLOR AND FREE OF WOOD CHIPS UNLESS OTHERWISE SHOWN.
- 14. PLANT MATERIAL WILL BE LOCATED OUTSIDE BUILDING DRIPLINES AND ROOF VALLEY POINTS OF CONCENTRATION TO PREVENT DAMAGE TO PLANTS. CLARIFY RELOCATION WITH LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- 15. ALL DISTURBED AREAS NOT TO BE PAVED OR OTHERWISE TREATED, WILL RECEIVE FIVE (5) INCH LOAM AND SEED.
- 16. TREE STAKES AND WRAP WILL REMAIN IN PLACE FOR NO MORE THAN 1 YEAR. CONTRACTOR WILL REMOVE.
- 17. ALL PLANT GROUPINGS WILL BE IN MULCH BEDS UNLESS OTHERWISE SPECIFIED OR NOTED ON PLANS. WHERE MULCHED PLANT BED ABUTS LAWN, PROVIDE TURF CUT EDGE.
- 18. ALL PLANT BEDS WILL INTERSECT WITH PAVEMENT AT 90 DEGREES UNLESS OTHERWISE NOTED ON PLANS.
- 19. ALL PLANT BED EDGES WILL BE SMOOTH AND CONSISTENT IN LAYOUT OF RADII AND TANGENTS. IRREGULAR, WAVY EDGES WILL NOT BE ACCEPTED.
- 20. CONTRACTOR WILL VERIFY PRIOR TO PRICING IF SITE SOILS ARE VERY POORLY DRAINING OR IF LEDGE IS PRESENT. IF CONTRACTOR ENCOUNTERS VERY POORLY DRAINING SOILS (BATH TUB EFFECT) OR LEDGE THAT IMPACTS PROPOSED PLANTING PLAN, NOTIFY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE FOR DIRÈCTION PRIOR TO PRICING AND AGAIN PRIOR TO PERFORMING ANY WORK.
- 21. PARKING AREA PLANTED ISLANDS WILL HAVE MINIMUM OF 1'-0" TOPSOIL PLACED TO THE TOP OF CURB ELEVATION. REMOVE ALL CONSTRUCTION DEBRIS BEFORE PLACING TOPSOIL.
- 22. EXISTING TREES SHOWN ON THE PLAN WILL REMAIN UNDISTURBED. ALL EXISTING TREES SHOWN TO REMAIN WILL BE PROTECTED WITH A 4-FOOT SNOW FENCE PLACED AT THE DRIP LINE OF THE BRANCHES OR AT 8 FEET MINIMUM FROM THE TREE TRUNK.
- 23. CONTRACTOR WILL STAKE OR PLACE ON GROUND ALL PROPOSED PLANT MATERIALS PER PLAN. CONTACT LANDSCAPE ARCHITECT FOR REVIEW AND APPROVAL PRIOR TO INSTALLATION.
- 24. CONTRACTOR WILL BE RESPONSIBLE FOR ALL MEANS, METHODS AND TECHNIQUES OF WATERING.
- 25. CONTRACTOR WILL BEGIN WATERING IMMEDIATELY AFTER PLANTING. ALL PLANTS WILL BE THOROUGHLY WATERED TWICE DURING THE FIRST 24 HOUR PERIOD AFTER PLANTING. ALL PLANTS WILL BE WATERED WEEKLY, OR MORE OFTEN, IF NECESSARY DURING THE FIRST GROWING SEASON BUT NOT LESS THAN ONE YEAR.
- 26. WATER ALL LAWNS AS REQUIRED. DO NOT LET NEWLY PLANTED LAWNS DRY OUT DURING THE FIRST FOUR WEEKS MINIMUM.
- 27. ALL GENERAL LAWN SEEDED AREAS WILL BE MAINTAINED AND MOWED A MINIMUM THREE (3) TIMES BEFORE REQUESTING REVIEW BY LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE FOR ACCEPTANCE. MAINTENANCE AND MOWING WILL CONTINUE UNTIL ACCEPTED BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE IS ISSUED IN WRITING.
- 28. THE CONTRACTOR WILL MAINTAIN AND GUARANTEE ALL PLANTINGS TO BE IN GOOD HEALTHY, FLOURISHING AND ACCEPTABLE CONDITION FOR A PERIOD OF ONE (1) YEAR OR TWO (2) GROWING SEASONS, WHICHEVER IS GREATER, BEGINNING AT THE DATE OF ACCEPTANCE BY THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE. ALL GRASSES, TREES AND SHRUBS THAT, IN THE OPINION OF THE LANDSCAPE ARCHITECT OR OWNER'S REPRESENTATIVE SHOWING LESS THAN 80% HEALTHY GROWTH AT THE END OF ONE (1) YEAR PERIOD WILL BE IMMEDIATELY REPLACED BY THE CONTRACTOR.
- 29. DECIDUOUS PLANT MATERIAL INSTALLED AFTER SEPTEMBER 30 AND BEFORE APRIL 15 WILL NOT BE REVIEWED THAT SEASON FOR ACCEPTANCE DUE TO STAGE OF LEAF PHYSIOLOGY. THIS PLANT MATERIAL WILL NOT BE REVIEWED UNTIL FOLLOWING GROWING SEASON. GUARANTEE PERIOD WILL BEGIN ONLY AFTER ACCEPTANCE BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE.
- 30. EVERGREEN PLANT MATERIAL INSTALLED AFTER OCTOBER 30 AND BEFORE APRIL 15 WILL NOT BE REVIEWED THAT SEASON FOR ACCEPTANCE DUE TO END OF GROWTH SEASON. THIS PLANT MATERIAL WILL NOT BE REVIEWED UNTIL FOLLOWING GROWING SEASON. GUARANTEE PERIOD WILL BEGIN ONLY AFTER ACCEPTANCE BY LANDSCAPE ARCHITECT OR OWNERS' REPRESENTATIVE.

SEEDING NOTES


1. GENERAL LAWN SEED WILL BE NHDOT SPECIFICATION SECTION 644, TABLE 644-1-PARK SEED TYPE 15, INCLUDING NOTES TO TABLE 1, 2

STAKE - SEE NOTES BELOW-REINFORCED NEW RUBBER HOSE, BLACK, 1/2" I.D., TYF DOUBLE STRAND 12 GA. WIRE TWISTED OR PVC CHAINLOCK ROOTBALL — TREE PIT — - DO NOT CUT MAIN LEADER. ANY TREES DISPLAYING CUT MAIN LEADER WILL BE REJECTED. - SECURE TREE WRAPPING ABOVE FIRST BRANCH - GUY ALL TREES GREATER THAN 2 1/2" CALIPER. USE 12 GAUGE TWISTED GALVANIZED WIRE OR PVC CHAINLOCK. STAKES (3) TO BE 2"x 2"x8' SQUARE HARDWOOD - SEE PLAN VIEW. WRAP THIN BARKED TREE TRUNKS ONLY WITH TREE WRAP, LAP ENDS DO NOT STAPLE. -3" DEPTH SHREDDED PINE BARK MULCH IN SAUCER. KEEP MULCH AWAY FROM TRUNK. - WATERING SAUCER, 4" CONTINUOUS FINISH GRADE. ROOT BALL TO BE LEVEL OR 1-2" ABOVE FINISHED GRADE -CUT & REMOVE BURLAP AND WIRE FROM TOP 2/3 OF ROOTBALL. REMOVE ALL STRING. FOLD REMAINING BURLAP & WIRE DOWN INTO PLANT PIT. IF BURLAP IS SYNTHETIC REMOVE COMPLETELY. -PLANTING MIXTURE: 20 PARTS TOPSOIL, 4 PARTS PEAT MOSS AND ONE PART WELL ROTTED MANURE OR OTHER ROOTBALL COMPOSTED ORGANIC MATTER OF LOW PH. BACKFILL IN LOOSE LIFTS OF 6"-8" DEPTH. SETTLE WITH THOROUGH -DIG TREE PIT TO BE AS DEEP AS THE ROOT BALL AND -COMPACTED OR UNDISTURBED SUBGRADE, BY OTHERS.

1. PROVIDE ALL DECIDUOUS TREES WITH "IRREGATOR" 20 GALLON IRRIGATION BAGS OR APPROVED EQUAL.

DECIDUOUS TREE PLANTING

NOT TO SCALE



NOTE:


1. IF SEEDING OPERATIONS ARE COMPLETED TOO LATE IN THE FALL FOR ADEQUATE GERMINATION AND GROWTH OF GRASS, MAINTENANCE SHALL CONTINUE INTO FOLLOWING SPRING AND UNTIL FINAL ACCEPTANCE BY THE LAND. ARCH. AT NO ADDITIONAL COST TO OWNER.

LOAM AND SEED

NOT TO SCALE

C-09 NOTE

1. SEE C-08 FOR LANDSCAPE PLAN.



EVERGREEN TREE PLANTING

NOT TO SCALE

HOOVER

SITE DEVELOPMENT PLANS

TAX MAP 272 LOT 1


LANDSCAPE NOTES, DETAILS, AND SCHEDULES KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE


OWNED BY

2219 LAFAYETTE ROAD LLC

SCALE: 1" = 40' 1" = 80'

MAY 7, 2019





A division of TFMoran, Inc.

Civil Engineers Structural Engineers Traffic Engineers Land Surveyors Landscape Architects Scientists

| 170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

C-09 CK CRR CADFILE 45407-80_Landscape.dwg

PLANNING BOARD FILE

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110


All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of Thomas F. Moran, Inc.

This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.



RECORDING NOTES

- 1. THIS LANDSCAPE PLAN SHALL BE RECORDED IN THE ROCKINGHAM COUNTY REGISTRY OF DEEDS.
- 2. THE PROPERTY OWNER AND ALL FUTURE PROPERTY OWNERS SHALL BE RESPONSIBLE FOR THE MAINTENANCE, REPAIR AND REPLACEMENT OF ALL REQUIRED SCREENING AND LANDSCAPE MATERIALS.
- 3. ALL REQUIRED PLANT MATERIALS SHALL BE TENDED AND MAINTAINED IN A HEALTHY GROWING CONDITION, REPLACED WHEN NECESSARY, AND KEPT FREE OF REFUSE AND DEBRIS. ALL REQUIRED FENCES AND WALLS SHALL BE MAINTAINED IN GOOD REPAIR.
- 4. THE PROPERTY OWNER SHALL BE RESPONSIBLE TO REMOVE AND REPLACE DEAD OR DISEASED PLANT MATERIALS IMMEDIATELY WITH THE SAME TYPE, SIZE AND QUANTITY OF PLANT MATERIALS AS ORIGINALLY INSTALLED, UNLESS ALTERNATIVE PLANTINGS ARE REQUESTED, JUSTIFIED AND APPROVED BY THE PLANNING BOARD OR PLANNING DIRECTOR.



Graphic Scale in Feet


REV. DATE

DR CK

MAY 7, 2019

C-10

CONTACT DIG SAFE 72 BUSINESS



<u>DISTURBED AREA</u>

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 24,000 SQUARE FEET (0.55 ACRES).

CRITICAL NOTE: THIS DRAWING IS PROVIDED FOR GENERAL GUIDANCE. ALL SPECIAL EROSION CONTROL MEASURES MUST BE EXECUTED IN ACCORDANCE WITH CURRENT STATE AND LOCAL REGULATIONS, APPROVED SWPPP AND PERMIT REQUIREMENTS.

SEQUENCE OF MAJOR ACTIVITIES

INSTALL TEMPORARY EROSION CONTROL MEASURES. DEMOLISH EXISTING SITE WORK DESIGNATED FOR REMOVAL.

DRAINAGE PIPES WHERE EROSIVE VELOCITIES ARE ENCOUNTERED.

- COMPLETE MAJOR GRADING OF SITE.
- CONSTRUCT BUILDING PAD, STORMWATER SYSTEM, AND SITE UTILITIES.
- CONSTRUCT PARKING LOT
- WHEN ALL CONSTRUCTION ACTIVITY IS COMPLETE AND SITE IS STABILIZED, REMOVE ALL INLET PROTECTION, SILT BARRIERS AND SEDIMENT THAT HAS BEEN TRAPPED BY THESE DEVICES.

EROSION AND SEDIMENT CONTROLS AND STABILIZATION PRACTICES

STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES AND DISTURBED AREAS WHERE CONSTRUCTION ACTIVITY WILL NOT OCCUR FOR MORE THAN TWENTY ONE (21) CALENDAR DAYS BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR TEMPÓRARILY CEASED IN THAT AREA. ALL DISTURBED AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:

- BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED: 2. A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED;
- . A MINIMUM OF 3" OF NON—EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED; OR 4. EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.

DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STABILIZED CHANNELS WHERE POSSIBLE. SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILT BARRIERS. ALL STORM

DRAIN INLETS SHALL BE PROVIDED WITH BARRIER FILTERS. STONE RIPRAP SHALL BE PROVIDED AT THE OUTLETS OF

OFF SITE VEHICLE TRACKING

CONTRACTOR TO SWEEP AS NEEDED TO PREVENT ANY VEHICLES TRACKING ON CITY STREETS

<u>INSTALLATION, MAINTENANCE AND INSPECTION OF EROSION AND SEDIMENT CONTROLS</u>

THESE ARE THE GENERAL INSPECTION AND MAINTENANCE PRACTICES THAT WILL BE USED TO IMPLEMENT THE PLAN.

- 1. STABILIZATION OF ALL SWALES, DITCHES AND PONDS IS REQUIRED PRIOR TO DIRECTING FLOW TO THEM.
- 2. THE SMALLEST PRACTICAL PORTION OF THE SITE WILL BE DENUDED AT ONE TIME. (5 AC MAX)
- 3. ALL CONTROL MEASURES WILL BE INSPECTED AT LEAST ONCE EACH WEEK AND FOLLOWING ANY STORM EVENT
- OF 0.10 INCHES OR GREATER.
- 4. ALL MEASURES WILL BE MAINTAINED IN GOOD WORKING ORDER. IF A REPAIR IS NECESSARY, IT WILL BE INITIATED WITHIN 24 HOURS OF REPORT.
- 5. BUILT UP SEDIMENT WILL BE REMOVED FROM SILT BARRIER WHEN IT HAS REACHED ONE THIRD THE HEIGHT OF
- 6. ALL DIVERSION DIKES WILL BE INSPECTED AND ANY BREACHES PROMPTLY REPAIRED.
- 7. TEMPORARY SEEDING AND PLANTING WILL BE INSPECTED FOR BARE SPOTS, WASHOUTS, AND UNHEALTHY GROWTH.
- 8. A MAINTENANCE INSPECTION REPORT WILL BE MADE AFTER EACH INSPECTION.
- 9. THE CONTRACTOR'S SITE SUPERINTENDENT WILL BE RESPONSIBLE FOR INSPECTIONS, MAINTENANCE AND REPAIR ACTIVITIES, AND FILLING OUT THE INSPECTION AND MAINTENANCE REPORT.

B. <u>FILTERS / BARRIERS</u>

- A. KNOTTED MESH NETTING MATERIAL SHALL BE DELIVERED TO SITE IN A 5 MIL CONTINUOUS, TUBULAR, HDPE 3/8" MATERIAL, FILLED WITH COMPOST CONFORMING TO THE FOLLOWING REQUIREMENTS:

PHYSICAL PROPERTY

TMECC 02.02-B 2" SIEVE AND MIN. 60% GREATER PARTICLE SIZE

THAN THE 3 SIEVE

MOISTURE CONTENT STND TESTING < 60%

THE UPSLOPE AREAS HAS BEEN PERMANENTLY STABILIZED.

MATERIAL SHALL BE RELATIVELY FREE OF INERT OR FOREIGN MAN-MADE MATERIALS

MATERIAL SHALL BE WEED FREE AND DERIVED FROM A WELL-DECOMPOSED SOURCE OF ORGANIC MATTER,

FREE FROM ANY REFUSE, CONTAMINANTS OR OTHER MATERIALS TOXIC TO PLANT GROWTH.

- B. SEDIMENT COLLECTED AT THE BASE OF THE SILT SOCK SHALL BE REMOVED ONCE IT HAS REACHED 1/3 OF THE EXPOSED HEIGHT OF THE SILT SOCK.
- C. SILT BARRIER SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFUL PURPOSE, BUT NOT BEFORE
- 2. SEQUENCE OF INSTALLATION

SEDIMENT BARRIERS SHALL BE INSTALLED PRIOR TO ANY SOIL DISTURBANCE OF THE CONTRIBUTING DRAINAGE AREA ABOVE THEM.

MAINTENANCE

- A. SILT BARRIERS SHALL BE INSPECTED WEEKLY AND IMMEDIATELY AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL. THEY SHALL BE REPAIRED IF THERE ARE ANY SIGNS OF EROSION OR SEDIMENTATION BELOW THEM. ANY REQUIRED REPAIRS SHALL BE MADE IMMEDIATELY. IF THERE ARE SIGNS OF UNDERCUTTING AT THE CENTER OR THE EDGES, OR IMPOUNDING OF LARGE VOLUMES OF WATER BEHIND THEM, SEDIMENT BARRIERS SHALL BE REPLACED WITH A TEMPORARY CHECK DAM.
- B. SHOULD THE FABRIC DECOMPOSE OR BECOME INEFFECTIVE PRIOR TO THE END OF THE EXPECTED USABLE LIFE AND THE BARRIER STILL IS NECESSARY, THE FABRIC SHALL BE REPLACED PROMPTLY.
- C. SEDIMENT DEPOSITS SHOULD BE REMOVED AFTER EACH STORM EVENT. THEY MUST BE REMOVED WHEN DEPOSITS REACH APPROXIMATELY ONE THIRD (1/3) THE HEIGHT OF THE BARRIER.
- D. ANY SEDIMENT DEPOSITS REMAINING IN PLACE AFTER THE SILT BARRIER IS NO LONGER REQUIRED SHALL BE DRESSED TO CONFIRM WITH THE EXISTING GRADE, PREPARED AND SEEDED.

C. <u>MULCHING</u>

PLANNING BOARD FILE

Copyright 2019 © Thomas F. Moran, Inc. 48 Constitution Drive, Bedford, N.H. 03110

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of Thomas F. Moran, Inc.

This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.



IN ORDER FOR MULCH TO BE EFFECTIVE, IT MUST BE IN PLACE PRIOR TO MAJOR STORM EVENTS. THERE ARE TWO (2) TYPES OF STANDARDS WHICH SHALL BE USED TO ASSURE THIS:

A. APPLY MULCH PRIOR TO ANY STORM EVENT.

THIS IS APPLICABLE WHEN WORKING WITHIN 100 FEET OF WETLANDS. IT WILL BE NECESSARY TO CLOSELY MONITOR WEATHER PREDICTIONS, USUALLY BY CONTACTING THE NATIONAL WEATHER SERVICE, TO HAVE ADEQUATE WARNING OF SIGNIFICANT STORMS.

B. REQUIRED MULCHING WITHIN A SPECIFIED TIME PERIOD.

THE TIME PERIOD CAN RANGE FROM 14 TO 21 DAYS OF INACTIVITY ON AN AREA, WHERE THE LENGTH OF TIME VARIES WITH SITE CONDITIONS. PROFESSIONAL JUDGMENT SHALL BE USED TO EVALUATE THE INTERACTION OF SITE CONDITIONS (SOIL ERODIBILITY, SEASON OF YEAR, EXTENT OF DISTURBANCE, PROXIMITY TO SENSITIVE RESOURCES, ETC.) AND THE POTENTIAL IMPACT OF EROSION ON ADJACENT AREAS TO CHOOSE AN APPROPRIATE TIME RESTRICTION.

2. GUIDELINES FOR WINTER MULCH APPLICATION.

WHEN MULCH IS APPLIED TO PROVIDE PROTECTION OVER WINTER (PAST THE GROWING SEASON) IT SHALL BE AT A RATE OF 6,000 POUNDS OF HAY OR STRAW PER ACRE. A TACKIFIER MAY BE ADDED TO THE MULCH.

ALL MULCHES MUST BE INSPECTED PERIODICALLY, IN PARTICULAR AFTER RAINSTORMS, TO CHECK FOR RILL EROSION. IF LESS THAN 90% OF THE SOIL SURFACE IS COVERED BY MULCH, ADDITIONAL MULCH SHALL BE IMMEDIATELY APPLIED.

D. VEGETATIVE PRACTICE

- 1. AFTER ROUGH GRADING OF THE SUBGRADE HAS BEEN COMPLETED AND APPROVED, THE SUB GRADE SURFACE SHALL BE SCARIFIED TO A DEPTH OF FOUR INCHES. THEN, FURNISH AND INSTALL A LAYER OF LOAM PROVIDING A ROLLED THICKNESS AS SPECIFIED IN THESE PLANS. ANY DEPRESSIONS WHICH MAY OCCUR DURING ROLLING SHALL BE FILLED WITH ADDITIONAL LOAM, REGRADED AND REROLLED UNTIL THE SURFACE IS TRUE TO THE FINISHED LINES AND GRADES. ALL LOAM NECESSARY TO COMPLETE THE WORK UNDER THIS SECTION SHALL BE SUPPLIED BY THE SITE SUBCONTRACTOR.
- 2. ALL LARGE STIFF CLODS, LUMPS, BRUSH, ROOTS, DEBRIS, GLASS, STUMPS, LITTER AND OTHER FOREIGN MATERIAL, AS WELL AS STONES OVER ONE INCH IN DIAMETER, SHALL BE REMOVED FROM THE LOAM AND DISPOSED OF OFF SITE. THE LOAM SHALL BE RAKED SMOOTH AND EVEN.
- 3. THE LOAM SHALL BE PREPARED TO RECEIVE SEED BY REMOVING STONES, FOREIGN OBJECTS AND GRADING TO ELIMINATE WATER POCKETS AND IRREGULARITIES PRIOR TO PLACING SEED. FINISH GRADING SHALL RESULT IN STRAIGHT UNIFORM GRADES AND SMOOTH, EVEN SURFACES WITHOUT IRREGULARITIES TO LOW POINTS.
- 4. SHAPE THE AREAS TO THE LINES AND GRADES REQUIRED. THE SITE SUBCONTRACTOR'S ATTENTION IS DIRECTED TO THE SCHEDULING OF LOAMING AND SEEDING OF GRADED AREAS TO PERMIT SUFFICIENT TIME FOR THE STABILIZATION OF THESE AREAS. IT SHALL BE THE SITE SUBCONTRACTOR'S RESPONSIBILITY TO MAINTAIN THE AREAS DURING THE CONSTRUCTION PERIOD AND REGRADE, LOAM AND RESEED ANY DAMAGED AREAS.
- 5. ALL AREAS DISTURBED BY CONSTRUCTION WITHIN THE PROPERTY LINES AND NOT COVERED BY STRUCTURES, PAVEMENT, OR MULCH SHALL BE LOAMED AND SEEDED.
- 6. LIMESTONE SHALL BE THOROUGHLY INCORPORATED INTO THE LOAM LAYER AT A RATE OF 2 TONS PER ACRE IN ORDER TO PROVIDE A PH VALUE OF 5.5 TO 6.5.
- 7. FERTILIZER SHALL BE SPREAD ON THE TOP LAYER OF LOAM AND WORKED INTO THE SURFACE. FERTILIZER APPLICATION RATE SHALL BE 500 POUNDS PER ACRE OF 10-20-20 FERTILIZER.
- 8. SOIL CONDITIONERS AND FERTILIZER SHALL BE APPLIED AT THE RECOMMENDED RATES AND SHALL BE THOROUGHLY WORKED INTO THE LOAM. LOAM SHALL BE RAKED UNTIL THE SURFACE IS FINELY PULVERIZED, SMOOTH AND EVEN, AND THEN COMPACTED TO AN EVEN SURFACE CONFORMING TO THE REQUIRED LINES AND GRADES WITH APPROVED ROLLERS WEIGHING BETWEEN 4 1/2 POUNDS AND 5 1/2 POUNDS PER INCH OF WIDTH.
- 9. SEED SHALL BE SOWN AT THE RATE SHOWN BELOW. SOWING SHALL BE DONE ON A CALM, DRY DAY, PREFERABLY BY MACHINE, BUT IF BY HAND, ONLY BY EXPERIENCED WORKMEN. IMMEDIATELY BEFORE SEEDING, THE SOIL SHALL BE LIGHTLY RAKED. ONE HALF THE SEED SHALL BE SOWN IN ONE DIRECTION AND THE OTHER HALF AT RIGHT ANGLES TO THE ORIGINAL DIRECTION. IT SHALL BE LIGHTLY RAKED INTO THE SOIL TO A DEPTH NOT OVER 1/4 INCH INCH AND ROLLED WITH A HAND ROLLER WEIGHING NOT OVER 100 POUNDS PER LINEAR
- 10. HAY MULCH SHALL BE APPLIED IMMEDIATELY AFTER SEEDING AT A RATE OF 1.5 TO 2 TONS PER ACRE. MULCH THAT BLOWS OR WASHES AWAY SHALL BE REPLACED IMMEDIATELY AND ANCHORED USING APPROPRIATE TECHNIQUES FROM THE EROSION AND SEDIMENT CONTROL HANDBOOK.
- 11. THE SURFACE SHALL BE WATERED AND KEPT MOIST WITH A FINE SPRAY AS REQUIRED, WITHOUT WASHING AWAY THE SOIL, UNTIL THE GRASS IS WELL ESTABLISHED. ANY AREAS WHICH ARE NOT SATISFACTORILY COVERED WITH GRASS SHALL BE RESEEDED, AND ALL NOXIOUS WEEDS REMOVED.
- 12. THE SITE SUBCONTRACTOR SHALL PROTECT AND MAINTAIN THE SEEDED AREAS UNTIL ACCEPTED, INCLUDING CUTTING, AS SPECIFIED HEREIN AFTER UNDER MAINTENANCE AND PROTECTION.
- 13. UNLESS OTHERWISE APPROVED, SEEDING SHALL BE DONE DURING THE APPROXIMATE PERIODS OF EARLY SPRING TO SEPTEMBER 30, WHEN SOIL CONDITIONS AND WEATHER ARE SUITABLE FOR SUCH WORK. IN NO CASE SHALL THE WEED CONTENT EXCEED 1 PERCENT BY WEIGHT. ALL SEED SHALL COMPLY WITH STATE AND FEDERAL SEED LAWS. FOR TEMPORARY PLANTINGS AFTER SEPTEMBER 30, TO EARLY SPRING AND FOR TEMPORARY PROTECTION OF DISTURBED AREAS:
- A. FOLLOW ABOVE SLOPE, LOAM DEPTH AND GRADING REQUIREMENTS. B. FERTILIZER SHALL BE SPREAD AND WORKED INTO THE SURFACE AT A RATE OF 300 POUNDS PER ACRE.

MULCHING AND SEEDING SHALL BE APPLIED AT THE FOLLOWING RATES:

WINTER RYE (FALL SEEDING) OATS (SPRING SEEDING)

MULCH

2.5 LBS/1,000 SF 2.0 LBS/1,000 SF 1.5 TONS/ACRE

FLEXSTORM CATCH-IT FILTERS

TYPICAL RECTANGULAR INLET FILTER

INSTALL PER MANUFACTURER'S SPECIFICATIONS. INSPECTION SHOULD OCCUR FOLLOWING ANY RAIN EVENT $>_{1}^{1}$ ".

STANDARD 2"

OVERFLOW AREA

REMOVED CAKED ON SILT FROM SEDIMENT BAG AND FLUSH WITH MEDIUM SPRAY WITH OPTIMAL FILTRATION. REPLACE BAG IF TORN OR PUNCTURED TO > 1" DIAMETER ON LOWER

EMPTY THE SEDIMENT BAG PER MANUFACTURER'S SPECIFICATIONS.

ALL PRODUCTS MANUFACTURED BY INLET & PIPE PROTECTION, INC. A DIVISION OF ADS, INC. WWW.INI FTFIL TFRS.COM (866) 287-8655 INFO@INLETFILTERS.COM

INLET PROTECTION

E. CATCH BASIN INLET PROTECTION

- 1. INLET BASKET STRUCTURE
- A. INLET PROTECTION SHALL BE INSTALLED IMMEDIATELY PRIOR TO DISTURBING PAVEMENT AND SHALL REMAIN IN PLACE AND MAINTAINED UNTIL PAVEMENT BINDER COURSE IS COMPLETE.
- B. MOLD 6X6, 42 LB. WIRE SUPPORT AROUND INLET FRAME AND GRATE AND EXTEND 6" BEYOND SIDES. SECURE FILTER FABRIC TO WIRE SUPPORT
- C. THE FILTER FABRIC SHALL BE A GEOTEXTILE FABRIC; POLYESTER, POLYPROPYLENE, STABILIZED NYLON,
- POLYETHYLENE OR POLYVINYLIDENE CHLORIDE MEETING THE FOLLOWING SPECIFICATIONS:
- GRAB STRENGTH: 45 LB. MINIMUM IN ANY PRINCIPAL DIRECTION (ASTM D1682) MULLEN BURST STRENGTH: MIN. 60PSI (ASTM D774)
- D. THE FABRIC SHALL HAVE AN OPENING NO GREATER THAN A NUMBER 20 U.S. STANDARD SIEVE AND A MINIMUM PERMEABILITY OF 120 GPM.
- E. THE INLET PROTECTION SHALL BE INSPECTED WITHIN 24 HOURS AFTER EACH RAINFALL OR DAILY DURING EXTENDED PERIODS OF PRECIPITATION. REPAIRS SHALL BE MADE IMMEDIATELY, AS NECESSARY, TO PREVENT PARTICLES FROM REACHING THE DRAINAGE SYSTEM AND/OR CAUSING SURFACE FLOODING.
- F. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT, OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED

F. <u>WINTER CONSTRUCTION SEQUENCE</u>

- 1. ALL PROPOSED POST-DEVELOPMENT LANDSCAPED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH, OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1 AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE PLACEMENT OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENT.
- 2. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15TH. OR WHICH ARE DISTURBED AFTER OCTOBER 15TH, SHALL BE STABILIZED WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.
- 3. AFTER OCTOBER 15TH, ALL TRAVEL SURFACES SHALL BE PROTECTED WITH A MINIMUM OF 3-INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOWFALL AFTER EACH STORM EVENT.

TIMING OF CONTROLS/MEASURES

AS INDICATED IN THE SEQUENCE OF MAJOR ACTIVITIES, SILT BARRIERS SHALL BE INSTALLED PRIOR TO COMMENCING ANY CLEARING OR GRADING OF THE SITE. STRUCTURAL CONTROLS SHALL BE INSTALLED CONCURRENTLY WITH THE APPLICABLE ACTIVITY. AREAS WHERE CONSTRUCTION ACTIVITY TEMPORARILY CEASES FOR MORE THAN TWENTY ONE (21) DAYS WILL BE STABILIZED WITH A TEMPORARY SEED AND MULCH WITHIN FOURTEEN (14) DAYS OF THE LAST DISTURBANCE. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN AN AREA, SILT BARRIERS AND ANY EARTH/DIKES WILL BE REMOVED ONCE PERMANENT MEASURES ARE ESTABLISHED.

ALL WASTE MATERIALS WILL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE WILL BE DEPOSITED IN A DUMPSTER. NO CONSTRUCTION WASTE MATERIALS WILL BE BURIED ON SITE. ALL PERSONNEL WILL BE INSTRUCTED REGARDING THE CORRECT PROCEDURE FOR WASTE

- HAZARDOUS WASTE ALL HAZARDOUS WASTE MATERIALS WILL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE
- REGULATION OR BY THE MANUFACTURER. SITE PERSONNEL WILL BE INSTRUCTED IN THESE PRACTICES BY THE

SANITARY WASTE ALL SANITARY WASTE WILL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

SPILL PREVENTION

- MATERIAL MANAGEMENT PRACTICES THE FOLLOWING ARE THE MATERIAL MANAGEMENT PRACTICES THAT WILL BE USED TO REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES DURING CONSTRUCTION TO STORMWATER RUNOFF:
- THE FOLLOWING GOOD HOUSEKEEPING PRACTICES WILL BE FOLLOWED ON SITE DURING THE CONSTRUCTION
- A. AN EFFORT WILL BE MADE TO STORE ONLY SUFFICIENT AMOUNTS OF PRODUCTS TO DO THE JOB.
- ALL MATERIALS STORED ON SITE WILL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR PROPER (ORIGINAL IF POSSIBLE) CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE.
- C. MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL WILL BE FOLLOWED.
- D. THE SITE SUPERINTENDENT WILL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS.
- E. SUBSTANCES WILL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER. F. WHENEVER POSSIBLE ALL OF A PRODUCT WILL BE USED UP BEFORE DISPOSING OF THE CONTAINER.
- THE FOLLOWING PRACTICES WILL BE USED TO REDUCE THE RISKS ASSOCIATED WITH HAZARDOUS MATERIALS:
- A. PRODUCTS WILL BE KEPT IN THEIR ORIGINAL CONTAINERS UNLESS THEY ARE NOT RESEALABLE. B. ORIGINAL LABELS AND MATERIAL SAFETY DATA WILL BE RETAINED FOR IMPORTANT PRODUCT
- INFORMATION C. SURPLUS PRODUCT THAT MUST BE DISPOSED OF WILL BE DISCARDED ACCORDING TO THE
- 2. PRODUCT SPECIFICATION PRACTICES

MANUFACTURER'S RECOMMENDED METHODS OF DISPOSAL.

MANUFACTURER'S RECOMMENDATIONS.

THE FOLLOWING PRODUCT SPECIFIC PRACTICES WILL BE FOLLOWED ON SITE:

WILL BE TRANSFERRED TO A SEALABLE PLASTIC BIN TO AVOID SPILLS.

REDUCE LEAKAGE. PETROLEUM PRODUCTS WILL BE STORED IN TIGHTLY SEALED CONTAINERS WHICH ARE CLEARLY LABELED. ANY ASPHALT BASED SUBSTANCES USED ON SITE WILL BE APPLIED ACCORDING TO THE

FERTILIZERS USED WILL BE APPLIED ONLY IN THE MINIMUM AMOUNTS DIRECTED BY THE SPECIFICATIONS. ONCE APPLIED FERTILIZER WILL BE WORKED INTO THE SOIL TO LIMIT EXPOSURE TO STORMWATER. STORAGE WILL BE IN A COVERED SHED OR ENCLOSED TRAILERS. THE CONTENTS OF ANY PARTIALLY USED BAGS OF FERTILIZER

ALL ON SITE VEHICLES WILL BE MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO

ALL CONTAINERS WILL BE TIGHTLY SEALED AND STORED WHEN NOT REQUIRED FOR USE. EXCESS PAINT WILL NOT BE DISCHARGED TO THE STORM SEWER SYSTEM BUT WILL BE DISPOSED OF PROPERLY ACCORDING TO MANUFACTURER'S INSTRUCTIONS OR STATE AND LOCAL REGULATIONS.

CONCRETE TRUCKS WILL DISCHARGE AND WASH OUT SURPLUS CONCRETE OR DRUM WASH WATER IN A CONTAINED AREA DESIGNATED ON SITE.

2 7/8/19 REVISED PER TAC COMMENTS

1 6/17/19 REVISED PER TAC COMMENTS

DESCRIPTION

REV. DATE


SPILL CONTROL PRACTICES

SPECIFICALLY FOR THIS PURPOSE.

- IN ADDITION TO GOOD HOUSEKEEPING AND MATERIAL MANAGEMENT PRACTICES DISCUSSED IN THE PREVIOUS SECTION THE FOLLOWING PRACTICES WILL BE FOLLOWED FOR SPILL PREVENTION AND CLEANUP:
- A. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP WILL BE CLEARLY POSTED AND SITE PERSONNEL WILL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND
 - B. MATERIALS AND EQUIPMENT NECESSARY FOR SPILL CLEANUP WILL BE KEPT IN THE MATERIAL STORAGE AREA ON SITE. EQUIPMENT AND MATERIALS WILL INCLUDE BUT NOT BE LIMITED TO BROOMS, DUSTPANS, MOPS, RAGS, GLOVES, GOGGLES, KITTY LITTER, SAND, SAWDUST AND PLASTIC OR METAL TRASH CONTAINERS
 - C. ALL SPILLS WILL BE CLEANED UP IMMEDIATELY AFTER DISCOVERY.
 - D. THE SPILL AREA WILL BE KEPT WELL VENTILATED AND PERSONNEL WILL WEAR APPROPRIATE PROTECTIVE CLOTHING TO PREVENT INJURY FROM CONTACT WITH A HAZARDOUS SUBSTANCE.
 - E. SPILLS OF TOXIC OR HAZARDOUS MATERIAL WILL BE REPORTED TO THE APPROPRIATE STATE OR LOCAL GOVERNMENT AGENCY, REGARDLESS OF THE SIZE.
 - F. THE SPILL PREVENTION PLAN WILL BE ADJUSTED TO INCLUDE MEASURES TO PREVENT THIS TYPE OF SPILL FROM RECURRING AND HOW TO CLEANUP THE SPILL IF IT RECURS. A DESCRIPTION OF THE SPILL, ITS CAUSE, AND THE CLEANUP MEASURES WILL BE INCLUDED.
- G. THE SITE SUPERINTENDENT RESPONSIBLE FOR DAY-TO-DAY SITE OPERATIONS WILL BE THE SPILL PREVENTION AND CLEANUP COORDINATOR.

DUST CONTROL

THE CONTRACTOR SHALL BE RESPONSIBLE TO CONTROL DUST THROUGHOUT THE CONSTRUCTION PERIOD. DUST CONTROL METHODS SHALL INCLUDE, BUT NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY MULCHING. DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ABUTTING AREAS.



SITE DEVELOPMENT PLANS


TAX MAP 272 LOT 1

EROSION CONTROL NOTES AND DETAILS KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

OWNED BY

2219 LAFAYETTE ROAD LLC

MAY 7, 2019




A division of TFMoran, Inc.


Civil Engineers Structural Engineers Traffic Engineers Land Surveyors Landscape Architects Scientists

170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

CK CRR CADFILE 45407-80_Details.dwg

C-12





- WHITE BORDER

- 1. TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F". APPLY TWO COATS.
- 2. SYMBOLS & PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT, LATEST EDITION.
- 3. 2% MAXIMUM CROSS SLOPE ALLOWED IN ACCESSIBLE PARKING SPACES AND ACCESS AISLES.

STEEL TO PVC CONNECTOR THEN NEXT PIER. - SCHEDULE 40 PVC RIGID STEEL - RIGID STEEL ELBOW (SEE SITE PLAN FOR SIZE) -3/4" Ø MIN. COPPER CLAD STEEL GROUND ROD MIN. 2'-0" BELOW BOTTOM OF PIER -#3 TIES AT 12" ON CENTER CONCRETE TO BE 4000 PSI. 2. BASE SHALL BE USED FOR ALL POLES WITH FIXTURE MOUNTING HEIGHT LESS THAN 16-FEET.

BASE COVER -

1" RIGID STEEL

TO POLE -

—BOND GROUND ROD TO LIGHT STANDARD

FOUR 3/4"ø ANCHOR BOLTS WITH 4"

POLES IDENTIFIED TO BE RELOCATED

HOOK. BURR THREADS AFTER SETTING

POLE. BOLT TEMPLATE TO PROVIDE FOR


RIGID STEEL CONDUIT - EXTEND


MIN. 10'-0" OUT OF PIER. USE

AND EACH RACEWAY WITH #8CU MIN.

GROUT AFTER POLE IS SET AND

┼┼╫╟ PLUMBED.






PLAN VIEW

VERTICAL GRANITE CURB NOT TO SCALE

MORTAR JOINTS AND OTHER INSTALLATION TO BE AS SPECIFIED IN

2. ADJOINING STONES SHALL HAVE THE SAME OR APPROXIMATELY THE



<u>NOTES</u>

1. TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F". APPLY TWO COATS.

STOP BAR & LEGEND

NOT TO SCALE

VERTICAL GRANITE CURB

PAVEMENT

(SEE DETAIL)

SECTION -

(NHDOT ITEM 609.0X)

CLASS B CONCRETE

(NHDOT ITEM 520.2X)

NHDOT SECTION 609.

SAME LENGTH.


<u>NOTES</u>

TYPICAL PARKING LAYOUT

- BLUE BACKGROUND

WHITE SYMBOL

NOT TO SCALE



1/8"x1" DEEP HAND TOOLED JOINT

WITH 1/4" RADII

PAVEMENT SECTION , (SEE DETAIL) -8" GRAVEL BASE (NHDOT 304.3)

FILLED WITH

SEALAN⁻

<u>NOTES</u>

1. PROVIDE CLEAN BUTT TO EXISTING PAVEMENT - USE TACK COAT.

2-1/2" VALVE OPENING

4-1/2" PUMPER

OPENING (1)

SECTION VIEW

CONCRETE PAD NOT TO SCALE


LIGHT POLE BASE

(24" MOUNTING HEIGHT

NOT TO SCALE

- 1. TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F". APPLY TWO COATS.
- 2. SYMBOLS AND PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT, LATEST EDITION.


PAINTED ARROW NOT TO SCALE



NOTES:


- DIAMETER 14 GAUGE. TOP RAIL SHOULD BE 1 1/2" DIAMETER 16 GAUGE. ALL PER

CHAIN LINK FENCE NOT TO SCALE



1. BOLLARD SHALL BE PAINTED WITH PRIMER & 2 COATS OF SAFETY YELLOW PAINT.

BOLLARD NOT TO SCALE



SITE DEVELOPMENT PLANS

TAX MAP 272 LOT 1

DETAIL SHEET KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

OWNED BY

2219 LAFAYETTE ROAD LLC

MAY 7, 2019

CONCRETE CURB

- COMPACTED SUBGRAI

PAVEMENT SECTION

CRUSHED GRAVEL

(NHDOT ITEM 304.3)

(SEE DETAIL)

AGGREGATE BASE

1/3 POST HEIGHT

(SEE NOTE 1)

<u>LENGTH:</u> AS REQUIRED

MINIMUM OF 2'.

WEIGHT PER LINEAR FOOT: 2.50 LBS (MIN)

HOLES: 3/8" DIAMETER, 1" C-C FULL LENGTH

ASTM A-576 (GRADE 1070 - 1080)

BE COMPLETE BEFORE PAINTING.

STEEL: SHALL CONFORM TO ASTM A-499 (GRADE 60) OR

NOTE: 1. Where ledge application exists, drill & grout to a

3. SIGN, HARDWARE, AND INSTALLATION SHALL CONFORM TO THE LATEST NHDOT STANDARD SPECIFICATIONS.

2. ALL SIGNAGE SHALL FOLLOW THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES STANDARDS AND NHDOT

SIGN POST

NOT TO SCALE

MEDIUM GREEN BAKED-ON OR AIR-DRIED PAINT OF

WEATHER RESISTANT QUALITY. ALL FABRICATION SHALL


FINISH: SHALL BE PAINTED WITH 2 COATS OF AN APP

CAST-IN-PLACE CONCRETE CURB

NOT TO SCALE

GALVANIZED

STEEL POST



DESCRIPTION

REV. DATE



45407.80

DR CK

Civil Engineers Structural Engineers Traffic Engineers Land Surveyors Landscape Architects Scientists A division of TFMoran, Inc.

170 Commerce Way, Suite 102 Portsmouth, NH 03801 Phone (603) 431-2222 Fax (603) 431-0910 www.TFMoran.com

DR XXX FB C-14 CK XXX CADFILE 45407-80_Details.dwg

- 1. TRAFFIC PAINT SHALL BE APPLIED AS SPECIFIED BY THE MANUFACTURER AND SHALL MEET THE REQUIREMENTS OF AASHTO M248 TYPE "F". APPLY TWO COATS.
- SYMBOLS AND PARKING STALLS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT, LATEST EDITION.

ACCESSIBLE GRAPHIC SYMBOL

NOT TO SCALE

PLANNING BOARD FILE # Copyright 2019 © Thomas F. Moran, Inc. All rights reserved. These plans and materials may not be copied,

48 Constitution Drive, Bedford, N.H. 03110 duplicated, replicated or otherwise reproduced in any form whatsoever

without the prior written permission of Thomas F. Moran, Inc. This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.



NOT TO SCALE

PORTSMOUTH FIRE HYDRANT

THREE-WAY HYDRANT KENNEDY K-81A <u>SPECIFICATIONS</u> 1. 150 PSI WORKING PRESSURE 2. 300 PSI TEST PRESSURE 3. HYDRANT DRAIN SHALL BE PLUGGED 4. DRY TOP DESIGN VALVE SHALL OPEN WHEN OPERATING NUT IS TURNED CLOCKWISE AND BE SO INDICATED ON


6. THREADS SHALL BE NATIONAL STANDARD HOSE THREAD

GUARDIAN ELMIRA, N.Y.

5. OPERATING NUT SHALL BE STANDARD AWWA PENTAGON

OPERATING NUT WITH 1 1/2" POINT TO FLAT DIMENSION


- 1. 2" MESH FABRIC, 9 GAUGE WIRE FOR FENCE. LINE POSTS ARE TO BE A 2 1/2"
- 2. INSTALL DARK BROWN VINYL PRIVACY SLATS IN FENCE & GATES WHERE INDICATED.
- 3. BARB WIRE SHALL BE PROVIDED ALONG TOP OF FENCE.



- 1. SEE GRADING & EROSION CONTROL PLAN FOR PAVEMENT SLOPE AND CROSS-SLOPE.
- PROVIDE CLEAN BUTT TO EXISTING PAVEMENT- USE TACK COAT. A TACK COAT SHALL ALSO BE PLACED BETWEEN GRAVEL COURSE AND SUCCESSIVE LAYERS OF BITUMINOUS CONCRETE. SPECIFICALLY, A TACK COAT SHALL BE PLACED ATOP THE BINDER COURSE PAVEMENT PRIOR TO PLACING THE WEARING COURSE.
- 3. REMOVE ALL LOAM AND/OR YIELDING MATERIAL BELOW PAVEMENT.
- 4. BITUMINOUS MATERIALS SHALL CONFORM TO NHDOT SPECIFICATION SECTION 401.
- BITUMINOUS CONCRETE SHALL BE COMPACTED TO AT LEAST 92-97% OF THEORETICAL MAXIMUM DENSITY AS DETERMINED BY ASTM D2041. PLACEMENT TEMPERATURES OF BITUMINOUS CONCRETE MIXES, IN GENERAL, RANGE BETWEEN 270 AND 310 DEGREES
- 6. PAVEMENT BASE COURSE AGGREGATE SHALL CONFORM TO NHDOT SPECIFICATION SECTION 304, ITEM 304.3 AND COMPACTED TO A MINIMUM OF 95% OF ASTM D-1557.
- 7. PAVEMENT SUBBASE COURSE AGGREGATE AND AGGREGATE FOR SUBGRADE REPAIR AREAS SHALL BE SUITABLE FOR USE AS STRUCTURAL FILL AND BE PROOF ROLLED AND COMPACTED TO 95% OF ASTM D-1557.
- 8. THE EXPOSED SOIL SUBGRADE SHOULD BE PROOF ROLLED PRIOR TO THE PLACEMENT OF SUBBASE GRAVEL, AND SOFT AREAS SHOULD BE REPAIRED AND REPLACED.
- 9. LOCATION OF HEAVY DUTY PAVEMENT SHALL BE AS SHOWN ON THE LAYOUT PLAN. ALL OTHER LOCATIONS SHALL BE STANDARD DUTY PAVEMENT.
- 10. EXACT AREAS TO RECEIVE FULL-DEPTH PAVEMENT SECTION BASE AND SUB-BASE SHALL BE DETERMINED IN FIELD AT THE TIME OF CONSTRUCTION.

PAVEMENT SECTION

NOT TO SCALE




- 1. ALL SECTIONS SHALL BE PRECAST CONCRETE NHDOT CLASS AA, 4,000 PSI. 2. CATCH BASINS SHALL MEET NHDOT SPECIFICATIONS. ALL COMPONENTS SHALL BE DESIGNED FOR HS-20 LOADING. 4. LARGER DIAMETER STRUCTURES SHALL BE USED AS REQUIRED DUE TO NUMBER, ANGLE OR SIZE OF PIPES AT THE STRUCTURE.
- **ECCENTRIC CATCH BASIN WITH SNOUT**


NOT TO SCALE

Copyright 2019 © Thomas F. Moran, Inc.





SECTION (WITHOUT CURB)



WOODEN -

FILTREXX™ FILTERSOXX™ SECTION

PLAN VIEW

Filtrexx™

FilterSoxx™

_ FILTREXX™

1. ALL MATERIAL TO MEET FILTREXX™SPECIFICATIONS


FILTERSOXX™

2. FILTERSOXX COMPOST/SOIL/ROCK/SEED FILL TO MEET APPLICATION

FILTREXX[™] FILTERSOXX[™] STAKING

NOT TO SCALE

3. COMPOST MATERIAL TO BE DISPERSED ON SITE, AS DETERMINED BY ENGINEER.



<u>NOTES</u>


- 1. MANHOLE FRAME & COVER: SHALL BE NEENAH R-1653-A OR APPROVED
- MANHOLES SHALL MEET NHDOT SPECIFICATIONS. ALL COMPONENTS SHALL BE DESIGNED FOR HS-20 LOADING
- 4. REINFORCING SHALL CONFORM TO ASTM 185 OR ASTM 1497 & ASTM

NUMBER, ANGLE OR SIZE OF PIPES AT THE STRUCTURE.

A615, GRADE 60. 5. ALL CONCRETE SHALL BE NHDOT CLASS A. 6. LARGER DIAMETER STRUCTURES SHALL BE USED AS REQUIRED DUE TO

DRAIN MANHOLE

NOT TO SCALE



1. USE KEY JOINT AT ALL LOCATIONS WHERE OVERLAY MEETS EXISTING PAVEMENT.

2. NEW PAVEMENT SHALL BE FLUSH WITH EXISITING PAVEMENT AND SHALL MEET OVERLAY GRADE WHERE IT ABUTS EXISTING PAVEMENT TO BE OVERLAYED.

KEY JOINT DETAIL


(SEE SITE PLAN) -VERTICAL GRANITE CURB BROOM ~ CROSS SLOPE=1.5% \pm 0.5% **FINISH** CONCRETE WALK (4,000 PSI, AIR ENTRAINED) -PAVEMENT 6x6~10/10 MESH -6" AGGREGATE BASE COMPACTED -SUBGRADE

SECTION (WITH GRANITE CURB)

1. SIDEWALKS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICAN WITH DISABILITIES ACT, LATEST EDITION.

CONCRETE SIDEWALK

NOT TO SCALE



DETAIL PROVIDED BY SHEA CONCRETE PRODUCTS 87 HAVERHILL ROAD AMESBURY, MA (800) 696-7432

> 1. CONCRETE: 5,000 PSI MINIMUM AFTER 28 DAYS. 2. DESIGNED FOR H-20 LOADING 3. TONGUE & GROOVE JOINT SEALED WITH BUTYL RESIN.

1,500 GALLON SEDIMENT & OIL SEPARATOR

NOT TO SCALE

SECTION SIDE VIEW

FINISH GRADE. o" TOLERANCE. - CURB TIP DOWN CURB AS PLAN NOTE. 1. RAMPS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE AMERICAN WITH DISABILITIES ACT, LATEST EDITION.

SIDEWALK TIP DOWN RAMP

NOT TO SCALE

7/8/19 REVISED PER TAC COMMENTS RCK CRR 1 6/17/19 REVISED PER TAC COMMENTS RCK CRR REV. DATE DESCRIPTION DR CK

SITE DEVELOPMENT PLANS


TAX MAP 272 LOT 1

DETAIL SHEET KEY ACURA OF PORTSMOUTH 2219 LAFAYETTE ROAD PORTSMOUTH, NEW HAMPSHIRE

OWNED BY

2219 LAFAYETTE ROAD LLC

MAY 7, 2019



PLANNING BOARD FILE

48 Constitution Drive, Bedford, N.H. 03110

All rights reserved. These plans and materials may not be copied, duplicated, replicated or otherwise reproduced in any form whatsoever without the prior written permission of Thomas F. Moran, Inc. This plan is not effective unless signed by a duly authorized officer of Thomas F. Moran, Inc.



SECTION B-B VIEW BAFFLE WALL DETAIL

FLUSH LANDING (2% MAX SLOPE) 1:20 (MAX.) - GUTTER LINE (6" REVEAL — MAX.) -0" REVEAL -START TIP - DOWN (TYPICAL) _ SCORELINE DOWN
MAX SLOPE 1: 20 (MAX.) VARIES

STAKE ON 10'


FILTREXX™ SILTSOXX™

PLAN VIEW

LINEAL SPACING

1:12 DETECTABLE 2% MAX WARNING STRIF (FULL WIDTH) MATCH PAVEMENT -(MIN.) └─ 6" (MAX.) REVEAL SPECIFIED ON DRAWINGS

Fax (603) 431-0910



DESIGN | BUILD Architectural Document Set-Prepared For Exclusive Use By:

No. Description

Revision Schedule

Key Acura of Portsmouth

2219 Lafayette Rd. Portsmouth, NH

Sheet Status:

Latest Release:
Issued For: Progress Set
Org. Issue Date: N.F.C.

JOB NO:
DRAFTED: MLN
CHECKED: JMT


SCALE: As indicated

Sheet Title:
First Floor Plan

First Floor Plan

Sheet Number:

Printed on: 4/11/2019 7:40:48 AM





Revision Schedule

Project Info: **Key Acura Portsmouth**

2219 Lafayette Portsmouth, NH

Sheet Status: Issued For: Progress Set
Org. Issue Date: N.F.C.

> DRAFTED: CHECKED:


As indicated

Sheet Title:

Shop Floor Plan

Sheet Number:

1/8" = 1'-0"





Revision Schedule

Project Info: **Key Acura Portsmouth**

2219 Lafayette Portsmouth, NH

Sheet Status: Issued For: Progress Set Org. Issue Date: N.F.C.


DRAFTED: CHECKED:

As indicated Sheet Title:

Second Floor Plan








T:\3.Projects\18039-Acura\18039-A

Printed on: 4/11/2019 7:40:53 AM





Revision Schedule

Project Info: **Key Acura Portsmouth**

2219 Lafayette Portsmouth, NH

Sheet Status:

Issued For: Progress Set
Org. Issue Date: N.F.C. Issued For:

JOB NO: DRAFTED:

MLN CHECKED: JMT 1/8" = 1'-0"


Sheet Title:

First Floor Reflected Ceiling Plan

Sheet Number:

Printed on: 4/11/2019 7:40:56 AM





ELEVATION NOTES:

1) REFER TO SHEET A3.3 FOR ALL LOCATIONS OF E.I.F.S. 3/4" REVEALS & 1/2" "V" GROOVES

2) REFER TO SHEET A3.3 FOR ALL CURTAIN WALL & STOREFRONT MULLION GRID DIMENSIONS

3) REFER TO SHEET A6.1 FOR DOOR & WINDOW SCHEDULES & LEGENDS

4) REFER TO FLOOR PLANS FOR ALL EXTERIOR WALL TYPES

5) REFER TO SHEET A4.0 FOR ALL WALL TYPES

6) ALL EXTERIOR FINISH MATERIALS & COLORS ARE PER ACURA DESIGN STANDARDS

7) LIGHTING LAYOUT FOR DESIGN INTENT ONLY. ALL FIXTURE PLACEMENTS TO BE BY ELECTRICAL CONTRACTOR'S DESIGN / BUILD ENGINEER

8) ALL ALPOLIC ACM PANELS TO BE DRY-JOINT SYSTEM


EXTERIOR FINISH SCHEDULE

1. CM-1 = COMPOSITE METAL PANEL - "CHAMPAGNE METALLIC" COLOR (ALPOLIC OR APROVED EQ.)

2. CM-2 = COMPOSITE METAL PANEL - "AUB BLUE" COLOR (ALPOLIC OR APROVED EQ.)

3. EIFS-1 = EXTERIOR INSULATING FINISH SYSTEM - "WHITE ASH" COLOR (DRYVIT AMERISTONE SERIES)

4. EIFS-2 = EXTERIOR INSULATING FINISH SYSTEM - "KING'S GRAY" COLOR (DRYVIT QUARZPUTZ SERIES)



Revision Schedule

Key Acura of Portsmouth

2219 Lafayette Rd. Portsmouth, NH

Issued For: Progress Set N.F.C.

JOB NO: DRAFTED: MLN

Sheet Status:

DRAFTED: MLN
CHECKED: JMT

SCALE: 1/8" = 1'-0"

Sheet Title:


Proposed

Proposed Exterior Elevations

Sheet Number:

Printed on: 4/11/2019 7:41:15 AM





ELEVATION NOTES:

1) REFER TO SHEET A3.3 FOR ALL LOCATIONS OF E.I.F.S. 3/4" REVEALS & 1/2" "V" GROOVES

2) REFER TO SHEET A3.3 FOR ALL CURTAIN WALL & STOREFRONT MULLION GRID DIMENSIONS

3) REFER TO SHEET A6. I FOR DOOR & WINDOW SCHEDULES & LEGENDS

4) REFER TO FLOOR PLANS FOR ALL EXTERIOR WALL TYPES

5) REFER TO SHEET A4.0 FOR ALL WALL TYPES

6) ALL EXTERIOR FINISH MATERIALS & COLORS ARE PER ACURA DESIGN STANDARDS

LIGHTING LAYOUT FOR DESIGN INTENT ONLY. ALL FIXTURE PLACEMENTS TO BE BY

ELECTRICAL CONTRACTOR'S DESIGN / BUILD ENGINEER ALL ALPOLIC ACM PANELS TO BE DRY-JOINT SYSTEM


EXTERIOR FINISH SCHEDULE


1. CM-1 = COMPOSITE METAL PANEL - "CHAMPAGNE METALLIC" COLOR (ALPOLIC OR APROVED EQ.)


2. CM-2 = COMPOSITE METAL PANEL - "AUB BLUE" COLOR (ALPOLIC OR APROVED EQ.)


3. EIFS-1 = EXTERIOR INSULATING FINISH SYSTEM - "WHITE ASH" COLOR (DRYVIT AMERISTONE SERIES)

4. EIFS-2 = EXTERIOR INSULATING FINISH SYSTEM - "KING'S GRAY" COLOR (DRYVIT QUARZPUTZ SERIES)










D E S I G N S LLC
P.O. BOX 69 STRAFFORD, NH 03884
P: 603.664.2181 | F: 603.664.9508

DESIGN | BUILD Architectural Document SetPrepared For Exclusive Use By:


HITCHER
BUILDERS

3 NEW VS. EXISTING KEY SECTION "A"
1" = 30'-0"

4 NEW VS. EXISTING KEY SECTION "B"
1" = 30'-0"



1 BUILDING SECTION "A"
1/8" = 1'-0"



No. Description

Revision Schedule

Key Acura
of
Project Info:

Ney Acura
Project Info:

Portsmouth

2219 Lafayette Rd. Portsmouth, NH

Sheet Status:

Latest Release:

Issued For: Progress Set

Org. Issue Date: N.F.C.

JOB NO:
DRAFTED: MLN
CHECKED: JMT

SCALE: As indicated

Sheet Title:

Building Sections

Sheet Number:

Printed on: 4/11/2019 7:41:46 AM

T:\3.Projects\18039-Acura\18039-A.rvt