



HALEY WARD.®

## APPLICATION FOR SITE PLAN REVIEW

TO THE CITY OF PORTSMOUTH  
FOR 1151 SAGAMORE AVENUE

Map 224, Lot 19 | Portsmouth, NH

**APPLICANT:**

**1151 Sagamore Avenue CBC LLC**  
76 State Street, Newburyport, ME 01950



December 22, 2025  
JN: 5010314.002

---

**REPORT PREPARED BY:**

**Haley Ward, Inc.**

200 Griffin Road, Unit 14 | Portsmouth, NH 03801

December 22, 2025

Peter Stith, TAC Committee Chair  
City of Portsmouth  
1 Junkins Avenue  
Portsmouth, New Hampshire 03801

**Re: Request for Site Plan Review at 1151 Sagamore Avenue, Tax Map 224, Lot 19**

Dear Mr. Stith and Technical Advisory Committee (TAC) Members:

On behalf of 1151 Sagamore CBC LLC we are pleased to submit the attached plan set for **Site Plan Review and Approval** for the above-mentioned project and request that we be placed on the agenda for your **January 6, 2026**, meeting. The project is the demolition of the existing building and proposed new construction of four (4) standalone residential condominium units with the associated and required site improvements.

Within this application we have provided a drawing set that includes depictions of both the parcel's existing and proposed conditions. The proposed conditions include the four buildings, driveways, utilities, grading/stormwater, landscaping, and typical notes/details. This application includes submission items as required for Site Plan review per the City's Site Plan Review Checklist.

We look forward to TAC review of this submission and the Committees feedback on the proposed design.

Sincerely,  
Haley Ward, Inc.



Drew Olehowski, PE  
Project Manager  
DJO-cba



# City of Portsmouth, New Hampshire

## *Site Plan Application Checklist*

This site plan application checklist is a tool designed to assist the applicant in the planning process and for preparing the application for Planning Board review. The checklist is required to be completed and uploaded to the Site Plan application in the City's online permitting system. A pre-application conference with a member of the planning department is strongly encouraged as additional project information may be required depending on the size and scope. The applicant is cautioned that this checklist is only a guide and is not intended to be a complete list of all site plan review requirements. Please refer to the Site Plan review regulations for full details.

**Applicant Responsibilities (Section 2.5.2):** Applicable fees are due upon application submittal along with required attachments. The application shall be complete as submitted and provide adequate information for evaluation of the proposed site development. Waiver requests must be submitted in writing with appropriate justification.

Name of Applicant: 1151 Sagamore Ave CBC, LLC Date Submitted: 12/12/2025

Application # (in City's online permitting): TBD

Site Address: 1151 Sagamore Avenue Portsmouth, NH 03801 Map: 224 Lot: 19

Application Requirements			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Complete <a href="#">application</a> form submitted via the City's web-based permitting program (2.5.2.1(2.5.2.3A))	Online	N/A
<input type="checkbox"/>	All application documents, plans, supporting documentation and other materials uploaded to the application form in viewpoint in digital Portable Document Format (PDF). One hard copy of all plans and materials shall be submitted to the Planning Department by the published deadline. <b>(2.5.2.8)</b>	Online and Delivered	N/A

Site Plan Review Application Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Statement that lists and describes "green" building components and systems. <b>(2.5.3.1B)</b>	TBD	
<input type="checkbox"/>	Existing and proposed gross floor area and dimensions of all buildings and statement of uses and floor area for each floor. <b>(2.5.3.1C)</b>	Architects Plans	N/A
<input type="checkbox"/>	Tax map and lot number, and current zoning of all parcels under Site Plan Review. <b>(2.5.3.1D)</b>	Proposed Site Plan	N/A

Site Plan Review Application Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Owner's name, address, telephone number, and signature. Name, address, and telephone number of applicant if different from owner. <b>(2.5.3.1E)</b>	Cover Page	N/A
<input type="checkbox"/>	Names and addresses (including Tax Map and Lot number and zoning districts) of all direct abutting property owners (including properties located across abutting streets) and holders of existing conservation, preservation or agricultural preservation restrictions affecting the subject property. <b>(2.5.3.1F)</b>	Proposed Site Plan	N/A
<input type="checkbox"/>	Names, addresses and telephone numbers of all professionals involved in the site plan design. <b>(2.5.3.1G)</b>	Cover Page	N/A
<input type="checkbox"/>	List of reference plans. <b>(2.5.3.1H)</b>	Cover Page	N/A
<input type="checkbox"/>	List of names and contact information of all public or private utilities servicing the site. <b>(2.5.3.1I)</b>	Cover Page	N/A

Site Plan Specifications			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Full size plans shall not be larger than 22 inches by 34 inches with match lines as required, unless approved by the Planning Director.. <b>(2.5.4.1A)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Scale: Not less than 1 inch = 60 feet and a graphic bar scale shall be included on all plans. <b>(2.5.4.1B)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	GIS data should be referenced to the coordinate system New Hampshire State Plane, NAD83 (1996), with units in feet. <b>(2.5.4.1C)</b>	Complies	N/A
<input type="checkbox"/>	Plans shall be drawn to scale and stamped by a NH licensed civil engineer. <b>(2.5.4.1D)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Wetlands shall be delineated by a NH certified wetlands scientist and so stamped. <b>(2.5.4.1E)</b>	N/A	N/A
<input type="checkbox"/>	Title (name of development project), north point, scale, legend. <b>(2.5.4.2A)</b>	All Pages	N/A
<input type="checkbox"/>	Date plans first submitted, date and explanation of revisions. <b>(2.5.4.2B)</b>	All Pages	N/A
<input type="checkbox"/>	Individual plan sheet title that clearly describes the information that is displayed. <b>(2.5.4.2C)</b>	Required on all plan sheets	N/A
<input type="checkbox"/>	Source and date of data displayed on the plan. <b>(2.5.4.2D)</b>	On Site Survey	N/A

Site Plan Specifications – Required Exhibits and Data			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	<p><b>1. Existing Conditions: (2.5.4.3A)</b></p> <ul style="list-style-type: none"> <li>Surveyed plan of site showing existing natural and built features;</li> <li>Existing building footprints and gross floor area;</li> <li>Existing parking areas and number of parking spaces provided;</li> <li>Zoning district boundaries;</li> <li>Existing, required, and proposed dimensional zoning requirements including building and open space coverage, yards and/or setbacks, and dwelling units per acre;</li> <li>Existing impervious and disturbed areas;</li> <li>Limits and type of existing vegetation;</li> <li>Wetland delineation, wetland function and value assessment (including vernal pools);</li> <li>SFHA, 100-year flood elevation line and BFE data, as required.</li> </ul>	Existing Conditions Plan	
<input type="checkbox"/>	<p><b>2. Buildings and Structures: (2.5.4.3B)</b></p> <ul style="list-style-type: none"> <li>Plan view: Use, size, dimensions, footings, overhangs, 1st fl. elevation;</li> <li>Elevations: Height, massing, placement, materials, lighting, façade treatments;</li> <li>Total Floor Area;</li> <li>Number of Usable Floors;</li> <li>Gross floor area by floor and use.</li> </ul>	Architects Plans	
<input type="checkbox"/>	<p><b>3. Access and Circulation: (2.5.4.3C)</b></p> <ul style="list-style-type: none"> <li>Location/width of access ways within site;</li> <li>Location of curbing, right of ways, edge of pavement and sidewalks;</li> <li>Location, type, size and design of traffic signing (pavement markings);</li> <li>Names/layout of existing abutting streets;</li> <li>Driveway curb cuts for abutting prop. and public roads;</li> <li>If subdivision; Names of all roads, right of way lines and easements noted;</li> <li>AASHTO truck turning templates, description of minimum vehicle allowed being a WB-50 (unless otherwise approved by TAC).</li> </ul>	Proposed Site Plan	
<input type="checkbox"/>	<p><b>4. Parking and Loading: (2.5.4.3D)</b></p> <ul style="list-style-type: none"> <li>Location of off street parking/loading areas, landscaped areas/buffers;</li> <li>Parking Calculations (# required and the # provided).</li> </ul>	Proposed Site Plan	
<input type="checkbox"/>	<p><b>5. Water Infrastructure: (2.5.4.3E)</b></p> <ul style="list-style-type: none"> <li>Size, type and location of water mains, shut-offs, hydrants &amp; Engineering data;</li> <li>Location of wells and monitoring wells (include protective radii).</li> </ul>	Utility Plan	
<input type="checkbox"/>	<p><b>6. Sewer Infrastructure: (2.5.4.3F)</b></p> <ul style="list-style-type: none"> <li>Size, type and location of sanitary sewage facilities &amp; Engineering data, including any onsite temporary facilities during construction period.</li> </ul>	Utility Plan	

<input type="checkbox"/>	<b>7. Utilities: (2.5.4.3G)</b> <ul style="list-style-type: none"> <li>The size, type and location of all above &amp; below ground utilities;</li> <li>Size type and location of generator pads, transformers and other fixtures.</li> </ul>	Utility Plan	
<input type="checkbox"/>	<b>8. Solid Waste Facilities: (2.5.4.3H)</b> <ul style="list-style-type: none"> <li>The size, type and location of solid waste facilities.</li> </ul>		
		City Pick Up General Notes Sheet	
<input type="checkbox"/>	<b>9. Storm water Management: (2.5.4.3I)</b> <ul style="list-style-type: none"> <li>The location, elevation and layout of all storm-water drainage.</li> <li>The location of onsite snow storage areas and/or proposed off-site snow removal provisions.</li> <li>Location and containment measures for any salt storage facilities</li> <li>Location of proposed temporary and permanent material storage locations and distance from wetlands, water bodies, and stormwater structures.</li> </ul>	Grading & Drainage Plan C6	
<input type="checkbox"/>	<b>10. Outdoor Lighting: (2.5.4.3J)</b> <ul style="list-style-type: none"> <li>Type and placement of all lighting (exterior of building, parking lot and any other areas of the site) and photometric plan.</li> </ul>	No Exterior Lighting	
<input type="checkbox"/>	<b>11. Indicate where dark sky friendly lighting measures have been implemented. (10.1)</b>	N/A	
<input type="checkbox"/>	<b>12. Landscaping: (2.5.4.3K)</b> <ul style="list-style-type: none"> <li>Identify all undisturbed area, existing vegetation and that which is to be retained;</li> <li>Location of any irrigation system and water source.</li> </ul>	Landscape Plan	
<input type="checkbox"/>	<b>13. Contours and Elevation: (2.5.4.3L)</b> <ul style="list-style-type: none"> <li>Existing/Proposed contours (2 foot minimum) and finished grade elevations.</li> </ul>	Grading Plan	
<input type="checkbox"/>	<b>14. Open Space: (2.5.4.3M)</b> <ul style="list-style-type: none"> <li>Type, extent and location of all existing/proposed open space.</li> </ul>	Proposed Site Plan	
<input type="checkbox"/>	<b>15. All easements, deed restrictions and non-public rights of ways. (2.5.4.3N)</b>	N/A	
<input type="checkbox"/>	<b>16. Character/Civic District (All following information shall be included): (2.5.4.3P)</b> <ul style="list-style-type: none"> <li>Applicable Building Height (10.5A21.20 &amp; 10.5A43.30);</li> <li>Applicable Special Requirements (10.5A21.30);</li> <li>Proposed building form/type (10.5A43);</li> <li>Proposed community space (10.5A46).</li> </ul>	N/A	
<input type="checkbox"/>	<b>17. Special Flood Hazard Areas (2.5.4.3Q)</b> <ul style="list-style-type: none"> <li>The proposed development is consistent with the need to minimize flood damage;</li> <li>All public utilities and facilities are located and construction to minimize or eliminate flood damage;</li> <li>Adequate drainage is provided so as to reduce exposure to flood hazards.</li> </ul>	N/A	

Other Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	Traffic Impact Study or Trip Generation Report, as required. <b>(3.2.1-2)</b>	Online	
<input type="checkbox"/>	Indicate where Low Impact Development Design practices have been incorporated. <b>(7.1)</b>	Drainage Analysis	
<input type="checkbox"/>	Indicate whether the proposed development is located in a wellhead protection or aquifer protection area. Such determination shall be approved by the Director of the Dept. of Public Works. <b>(7.3.1)</b>	N/A	
<input type="checkbox"/>	Stormwater Management and Erosion Control Plan. <b>(7.4)</b>	General Notes Sheet	
<input type="checkbox"/>	Inspection and Maintenance Plan <b>(7.6.5)</b>	Drainage Analysis	

Final Site Plan Approval Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	All local approvals, permits, easements and licenses required, including but not limited to: <ul style="list-style-type: none"> <li>• Waivers;</li> <li>• Driveway permits;</li> <li>• Special exceptions;</li> <li>• Variances granted;</li> <li>• Easements;</li> <li>• Licenses.</li> </ul> <b>(2.5.3.2A)</b>	Cover Sheet	
<input type="checkbox"/>	Exhibits, data, reports or studies that may have been required as part of the approval process, including but not limited to: <ul style="list-style-type: none"> <li>• Calculations relating to stormwater runoff;</li> <li>• Information on composition and quantity of water demand and wastewater generated;</li> <li>• Information on air, water or land pollutants to be discharged, including standards, quantity, treatment and/or controls;</li> <li>• Estimates of traffic generation and counts pre- and post-construction;</li> <li>• Estimates of noise generation;</li> <li>• A Stormwater Management and Erosion Control Plan;</li> <li>• Endangered species and archaeological / historical studies;</li> <li>• Wetland and water body (coastal and inland) delineations;</li> <li>• Environmental impact studies.</li> </ul> <b>(2.5.3.2B)</b>	Online	
<input type="checkbox"/>	A document from each of the required private utility service providers indicating approval of the proposed site plan and indicating an ability to provide all required private utilities to the site. <b>(2.5.3.2D)</b>	TBD	

Final Site Plan Approval Required Information			
<input checked="" type="checkbox"/>	Required Items for Submittal	Item Location (e.g. Page/line or Plan Sheet/Note #)	Waiver Requested
<input type="checkbox"/>	A list of any required state and federal permit applications required for the project and the status of same. <b>(2.5.3.2E)</b>	Cover Sheet	
<input type="checkbox"/>	A note shall be provided on the Site Plan stating: "All conditions on this Plan shall remain in effect in perpetuity pursuant to the requirements of the Site Plan Review Regulations." <b>(2.5.4.2E)</b>	Proposed Site Plan	N/A
<input type="checkbox"/>	For site plans that involve land designated as "Special Flood Hazard Areas" (SFHA) by the National Flood Insurance Program (NFIP) confirmation that all necessary permits have been received from those governmental agencies from which approval is required by Federal or State law, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334. <b>(2.5.4.2F)</b>	N/A	
<input type="checkbox"/>	Plan sheets submitted for recording shall include the following notes: <ol style="list-style-type: none"> <li>"This Site Plan shall be recorded in the Rockingham County Registry of Deeds."</li> <li>"All improvements shown on this Site Plan shall be constructed and maintained in accordance with the Plan by the property owner and all future property owners. No changes shall be made to this Site Plan without the express approval of the Portsmouth Planning Director."</li> </ol> <b>(2.13.3)</b>	Proposed Site Plan	N/A

Applicant's Signature: 

Date: 12/22/2025

August 22, 2025

To Whom It May Concern:

Please be advised that Haley Ward, Inc. is hereby authorized to act on behalf of 1151 Sagamore Avenue CBC, LLC, regarding the proposed residential development at 1151 Sagamore Avenue in Portsmouth, NH.


David Kennedy, its manager

---

Printed Name and Title



Signature



Date

**Property Information**

Property ID 0224-0019-0000  
Location 1151 SAGAMORE AVE  
Owner 1151 SAGAMORE AVENUE CBC LLC




**MAP FOR REFERENCE ONLY  
NOT A LEGAL DOCUMENT**

City of Portsmouth, NH makes no claims and no warranties, expressed or implied, concerning the validity or accuracy of the GIS data presented on this map.

Geometry updated 10/23/2025

Print map scale is approximate.  
Critical layout or measurement  
activities should not be done using  
this resource.

**Property Information**

**Property ID** 0224-0019-0000  
**Location** 1151 SAGAMORE AVE  
**Owner** 1151 SAGAMORE AVENUE CBC LLC

**MAP FOR REFERENCE ONLY  
NOT A LEGAL DOCUMENT**

City of Portsmouth, NH makes no claims and no warranties, expressed or implied, concerning the validity or accuracy of the GIS data presented on this map.

Geometry updated 10/23/2025

Print map scale is approximate.  
Critical layout or measurement  
activities should not be done using  
this resource.

## Map Theme Legends

### Zoning

#### Residential Districts

	R	Rural
	SRA	Single Residence A
	SRB	Single Residence B
	GRA	General Residence A
	GRB	General Residence B
	GRC	General Residence C
	GA/MH	Garden Apartment/Mobile Home Park

#### Mixed Residential Districts

	MRO	Mixed Residential Office
	MRB	Mixed Residential Business
	G1	Gateway Corridor
	G2	Gateway Center

#### Business Districts

	GB	General Business
	B	Business
	WB	Waterfront Business

#### Industrial Districts

	OR	Office Research
	I	Industrial
	WI	Waterfront Industrial

#### Airport Districts

	AIR	Airport
	AI	Airport Industrial
	PI	Pease Industrial
	ABC	Airport Business Commercial

#### Conservation Districts

	M	Municipal
	NRP	Natural Resource Protection

#### Character Districts

	CD5	Character District 5
	CD4	Character District 4
	CD4 W	Character District 4-W
	CD4-L1	Character District 4-L1
	CD4-L2	Character District 4-L2

#### Civic District

	Civic District
--	----------------

#### Municipal District

	Municipal District
--	--------------------

#### Overlay Districts

	OLOD	Osprey Landing Overlay District
	Downtown	Overlay District
	Historic	District

City of Portsmouth



# Environment One Corporation

# Pressure Sewer Preliminary Cost and Design Analysis

## For

### 1151 Sagamore Ave Portsmouth, NH

**Prepared For:  
Drew Olehowski Haley Ward  
120 Main St Suite 132  
Saco  
Tel: 207-576-6488  
Fax:  
Prepared By: D.Coppola  
November 26, 2025**

## PRELIMINARY PRESSURE SEWER - PIPE SIZING AND BRANCH ANALYSIS

Prepared By:

D.Coppola

1151 Sagamore Ave

Portsmouth, NH

November 26, 2025

Zone Number	Connects to Zone	Number of Pumps in Zone	Accum Pumps in Zone	Gals/day per Pump	Max Flow Per Pump (gpm)	Max Sim Ops	Max Flow (GPM)	Pipe Size (inches)	Max Velocity (FPS)	Length of Main this Zone	Friction Factor (ft/100 ft)	Friction Loss This Zone	Accum Fric Loss (feet)	Max Main Elevation	Minimum Pump Elevation	Static Head (feet)	Total Dynamic Head (ft)
This spreadsheet was calculated using pipe diameters for: SDR11HDPE																	
1.00	1.00	4	4	200	11.00	3	33.00	2.00	3.57	274.00	2.52	6.90	6.90	32.00	28.00	4.00	10.90

## PRELIMINARY PRESSURE SEWER - ACCUMULATED RETENTION TIME (HR)

Prepared By:

D.Coppola

1151 Sagamore Ave

Portsmouth, NH

November 26, 2025

Zone Number	Connects to Zone	Accumulated Total of Pumps this Zone	Pipe Size (inches)	Gallons per 100 lineal feet	Length of Zone	Capacity of Zone	Average Daily Flow	Average Fluid Changes per Day	Average Retention Time (Hr)	Accumulated Retention Time (Hr)
This spreadsheet was calculated using pipe diameters for: SDR11HDPE										Gals per Day per Dwelling
1.00	1.00	4	2.00	15.40	274.00	42.20	800	18.96	1.27	200

**“Green” Building Statement, 1155 Sagamore Ave., Portsmouth**

**Location and Transportation**

**Walkable Destinations:** 1155 Sagamore is two miles from Wentworth-By-The-Sea, two miles from downtown Portsmouth, and less than one mile to the Rye border and the Atlantic Grill.

**Bicycles:** This area is a frequently used bicycle traffic route to beaches, downtown amenities, other points north and south and other popular locations. Hanging bicycle storage is provided within each garage space.

**Ride sharing:** Although this location is not serviced directly by public transportation, it enjoys easy access and is a quickly identifiable address for cabs or shared transportation services.

**Site**

**Stormwater:** Stormwater will be collected and treated in a proposed Rain Garden before discharge from the property. This Rain Garden provides advanced stormwater treatment where no treatment is currently provided.

**Reuse:** This site requires demolition of an outdated and underutilized structure. The new 4-unit townhouse structure will better utilize this location with a modern design, defined parking areas, non-polluting HVAC systems, and elimination of an existing multi-unit septic disposal system.

**Landscaping:** A professionally produced landscaping plan includes shrubbery, grass, and a multitude of trees that currently do not exist. An irrigation system to maintain grass and plantings is included.

**Zoning:** This project meets requirements in the MRO zone where it is located. No variances have been requested.

**Utilities and fire protection**

**Water:** All new water-saving plumbing fixtures will be installed as per the current plumbing code. Frost-free outside water taps are included at each living unit.

**Sewer:** The existing septic system is being replaced by a common E-one grinder/ejector system connected to the public sewer.

**Electric:** Eversource has indicated they will be installing a new transformer to service this property. All connections from the pole to this transformer and transformer to the electric meter bank will be underground. The current electric service is overhead. The transformer will be partially screened with landscaping.

**Fire Protection:** A fire suppression system governed by requirements of NFPA 13 will be installed in each townhouse. Additionally, full foundation to ridge firewalls will be installed between living units.

**Gas or heating oil:** None.

**Energy:**


**Heating and Air Conditioning:** HVAC will be via either air-source or ground-source (geothermal) heat pump. No natural gas, propane gas or heating oil facilities are included in this design. No exhaust flues are required, nor greenhouse gases emitted. Further, the potential for carbon monoxide poisoning from a malfunctioning heating system is eliminated.

**Insulation:** The heated envelope will be insulated with spray-foam insulation to maximize insulation R-values, minimize air penetration and minimize acoustic noise from outdoors and between living units.

**Lighting:** LED lighting will be used throughout.

**Kitchen Appliances:** All kitchen appliances will be energy-star certified.

**Fenestration:** Very substantial windows and doors are state-of-the-art and shall have a U-value below .30, meeting or exceeding energy-star requirements.



1 0.0 BSMT  
1/4" = 1'-0"

# William Frangos Architect

0 Cummings Center, Suite 6500  
Wellesley MA 01915  
8 927 9419  
8 927 9417 fax

## CONSULTANTS

# PROGRESS PRINT

NOT FOR CONSTRUCTION

151 SAGAMORE  
AVENUE

PORTSMOUTH NH

OWNER

## REVISION SCHEDULE

Object Phase SCHEMATIC  
Obj Issue Date N/A  
Object No. 2511

OPYRIGHT  
William Frangos Architect 2025

**SHEET TITLE**

## Assessment Plan

## **Basement Plan**

HEET ISSUE DATE: 12/18/25


12.10.2020

A 101

A-101

A-101

HEET 4 OF



William Frangos  
Architect

500 Cummings Center, Suite 6500  
Beverly MA 01915  
978 927 9419  
978 927 9417 fax

CONSULTANTS

**PROGRESS  
PRINT**

NOT FOR CONSTRUCTION

PROJECT  
1151 SAGAMORE  
AVENUE

PORTSMOUTH NH

OWNER  
Owner

REVISION SCHEDULE		
No.	Date	Description

Project Phase SCHEMATIC  
Proj Issue Date N/A  
Project No. 2511

COPYRIGHT  
William Frangos Architect 2025


SHEET TITLE

First Floor Plan

SHEET ISSUE DATE: 12/18/25

A-102

SHEET 1 OF 4



William Frangos  
Architect

500 Cummings Center, Suite 6500  
Beverly MA 01915  
978 927 9419  
978 927 9417 fax

CONSULTANTS

A-103

SHEET 2 OF 4



**PROGRESS  
PRINT**

NOT FOR CONSTRUCTION

PROJECT  
1151 SAGAMORE  
AVENUE

PORTSMOUTH NH

OWNER  
Owner

REVISION SCHEDULE  
No. Date Description

Project Phase SCHEMATIC  
Proj Issue Date N/A  
Project No. 2511


COPYRIGHT  
William Frangos Architect 2025

SHEET TITLE

Elevations

② NORTH  
1/4" = 1'-0"

① SOUTH - FAÇADE  
1/4" = 1'-0"



SHEET ISSUE DATE: 12/18/25

A-201

SHEET 3 OF 4

William Frangos  
Architect

500 Cummings Center, Suite 6500  
Beverly MA 01915  
978 927 9419  
978 927 9417 fax

CONSULTANTS

**PROGRESS  
PRINT**

NOT FOR CONSTRUCTION

PROJECT  
1151 SAGAMORE  
AVENUE

PORTSMOUTH NH

OWNER

Owner

REVISION SCHEDULE		
No.	Date	Description

Project Phase SCHEMATIC  
Proj Issue Date N/A  
Project No. 2511

COPYRIGHT  
William Frangos Architect 2025

SHEET TITLE

**Elevations**

SHEET ISSUE DATE: 12/18/25

**A-202**

SHEET 4 OF 4



**PROJECT NAME & ADDRESS:**

1151 Sagamore Ave

**DATE:**

11/7/2025

**MAP & LOT:**

224/19

**Description****Quantity** **Unit** **Unit Price** **Total***\*Yellow cells are the ONLY editable items***Site Preparation**

	Quantity	Unit	Unit Price	Total
<b>Site Preparation</b>			\$	<b>17,406.20</b>
Clearing & Grubbing	0	AC	\$ 12,000.00	\$ -
Removal of Pipe Lines ≤ 24"		LF	\$ 18.00	\$ -
Removal of Pipe Lines > 24"		LF	\$ 36.00	\$ -
Common Excavation	500	CY	\$ 16.00	\$ 8,000.00
Unsuitable Excavation		CY	\$ 36.00	\$ -
Ledge Excavation	75	CY	\$ 125.00	\$ 9,375.00
Saw Cut Pavement	12	LF	\$ 2.60	\$ 31.20

**Roads**

Screened Sand	420	CY	\$ 25.00	\$ 10,500.00	Utility Trench fill material
Granular/Common Fill	2200	CY	\$ 32.00	\$ 70,400.00	Fill material to leve and grade site
Gravel Backfill (304.2)	700	CY	\$ 36.00	\$ 25,200.00	See Below*
Crushed Gravel (304.3)	131	CY	\$ 36.00	\$ 4,716.00	Asphalt sub base
Crushed Stone - Fine Gradation (304.4)		CY	\$ 40.00	\$ -	
Crushed Stone - Coarse Gradation (304.5)		CY	\$ 42.00	\$ -	
Hot Bituminous Pavement - Hand Method		TON	\$ 170.00	\$ -	
Hot Bituminous Pavement - Machine Method	220	TON	\$ 150.00	\$ 33,000.00	
Pavement Prep for Top Coat if placed over 1-yr after Base Coat		SY	\$ 1.00	\$ -	
Cold Plane		SY	\$ 6.50	\$ -	
Reclaim Pavement		SY	\$ 4.00	\$ -	
Fine Grading	790	SY	\$ 3.00	\$ 2,370.00	
Concrete Sidewalk 4"		SY	\$ 62.00	\$ -	
Bituminous Sidewalk 3"		SY	\$ 44.00	\$ -	
Straight Granite Curb	250	LF	\$ 40.00	\$ 10,000.00	
Curved Granite Curb		LF	\$ 50.00	\$ -	
Reset Granite Curb		LF	\$ 21.00	\$ -	
Bituminous Curb, Type B 6" Reveal		LF	\$ 12.00	\$ -	
Traffic Sign with Post		EA	\$ 320.00	\$ -	
Lightpole Base and Fixture		EA	\$ 12,000.00	\$ -	
Cobra Head Light onto Existing Pole		EA	\$ 1,170.00	\$ -	
Conduit Duct Bank (4" SCH 80 - 2 Pipes)		LF	\$ 80.00	\$ -	
Conduit Duct Bank (4" SCH 80 - 3 Pipes)		LF	\$ 100.00	\$ -	
Conduit Duct Bank (4" SCH 80 - 4 Pipes)		LF	\$ 120.00	\$ -	
Traffic Loop Detectors		EA	\$ 1,000.00	\$ -	
Retroreflective Paint Marking - 4" Line	310	LF	\$ 1.20	\$ 372.00	
Retroreflective Paint Pavement Marking - Symbol or Word	6	EA	\$ 51.00	\$ 306.00	
Retroreflective Thermoplastic Pavement Marking - ≤ 12" Line		LF	\$ 3.20	\$ -	
Retroreflective Thermoplastic Pavement Marking - Symbol		EA	\$ 130.00	\$ -	
Obliterate Pavement Marking - ≤12" Line		LF	\$ 1.00	\$ -	
Guardrail (Steel rail and posts)	20	LF	\$ 45.00	\$ 900.00	

**Structural**

	Quantity	Unit	Unit Price	Total
Mechanically Stabilized Earth Retaining Wall		SF	\$ 50.00	\$ -
Retaining Wall - Modular Block		SF	\$ 54.00	\$ -

**Utilities**

	Quantity	Unit	Unit Price	Total
Catch Basin with Frame, Grate & Hood	2	EA	\$ 4,800.00	\$ 9,600.00
Special Catch Basins (i.e. Tree Box Filters)		EA	\$ 5,600.00	\$ -
Box Culvert ≤ 36' x 60'		LF	\$ 500.00	\$ -

Box Culvert ≥ 36' x 60'		LF	\$	680.00	\$	-
Drop Inlet		EA	\$	3,200.00	\$	-
MH - 4' Dia. w/ Base and Top		VF	\$	480.00	\$	-
MH - 5' Dia. w/ Base and Top		VF	\$	520.00	\$	-
MH - 6' Dia. w/ Base and Top		VF	\$	640.00	\$	-
MH - 8' Dia. w/ Base and Top		VF	\$	940.00	\$	-
Remove and Reset CB, DI Grate and Frame		EA	\$	500.00	\$	-
Reconstruct / Adjust Drainage Manholes	1	EA	\$	1,000.00	\$	-
Outlet/Inlet Control Structure		EA	\$	6,100.00	\$	6,100.00
Riprap		CY	\$	64.00	\$	-
Perf Underdrain ≤ 6"	375	LF	\$	58.00	\$	21,750.00
Perf Underdrain > 6"		LF	\$	90.00	\$	-
12" RC Pipe - Class III		LF	\$	125.00	\$	-
15" RC Pipe - Class IV		LF	\$	140.00	\$	-
18" RC Pipe - Class IV		LF	\$	156.00	\$	-
24" RC Pipe - Class IV		LF	\$	204.00	\$	-
30" RC Pipe - Class IV		LF	\$	240.00	\$	-
36" RC Pipe - Class IV		LF	\$	285.00	\$	-
48" RC Pipe - Class V		LF	\$	400.00	\$	-
12" RCP - End Sections		EA	\$	780.00	\$	-
15" RCP - End Sections		EA	\$	880.00	\$	-
18" RCP - End Sections		EA	\$	980.00	\$	-
24" RCP - End Sections		EA	\$	1,200.00	\$	-
30" RCP - End Sections		EA	\$	1,300.00	\$	-
36" RCP - End Sections		EA	\$	1,500.00	\$	-
48" RCP - End Sections		EA	\$	1,800.00	\$	-
12" Plastic Corrugated/Smooth Pipe	250	LF	\$	85.00	\$	21,250.00
15" Plastic Corrugated/Smooth Pipe		LF	\$	98.00	\$	-
18" Plastic Corrugated/Smooth Pipe		LF	\$	120.00	\$	-
24" Plastic Corrugated/Smooth Pipe		LF	\$	180.00	\$	-
30" Plastic Corrugated/Smooth Pipe		LF	\$	200.00	\$	-
36" Plastic Corrugated/Smooth Pipe		LF	\$	260.00	\$	-
12" Plastic Flared End Sections		EA	\$	300.00	\$	-
15" Plastic Flared End Sections		EA	\$	310.00	\$	-
18" Plastic Flared End Sections		EA	\$	340.00	\$	-
24" Plastic Flared End Sections		EA	\$	400.00	\$	-
30" Plastic Flared End Sections		EA	\$	540.00	\$	-
36" Plastic Flared End Sections		EA	\$	610.00	\$	-
PVC Sewer Gravity Main ≤ 8"		LF	\$	130.00	\$	-
PVC Sewer Gravity Main > 8"		LF	\$	180.00	\$	-
PVC Sewer Service Pipe and Fittings		LF	\$	120.00	\$	-
PVC Sewer Force main Pipe ≤ 3"	280	LF	\$	36.00	\$	10,080.00
PVC Sewer Force main Pipe > 3"		LF	\$	61.00	\$	-
Reconstruct / Adjust Sewer Manholes		EA	\$	1,000.00	\$	-
Manhole Covers and Frames (Drainage and Sewer)		EA	\$	1,200.00	\$	-
6" Cement Lined Ductile Iron Water Pipe CL 52		LF	\$	150.00	\$	-
8" Cement Lined Ductile Iron Water Pipe CL 52		LF	\$	180.00	\$	-
12" Cement Lined Ductile Iron Water Pipe CL 52		LF	\$	210.00	\$	-
20" Cement Lined Ductile Iron Water Pipe CL 52		LF	\$	280.00	\$	-
3/4" Copper Water Pipe		LF	\$	65.00	\$	-
1" Copper Water Pipe	36	LF	\$	84.00	\$	3,024.00
2" Copper Water Pipe		LF	\$	120.00	\$	-
3/4" PE Water Pipe	375	LF	\$	45.00	\$	16,875.00
1" PE Water Pipe		LF	\$	81.00	\$	-
2" PE Water Pipe	375	LF	\$	100.00	\$	37,500.00
Curb Stop w/ Box & Rod	6	EA	\$	385.00	\$	2,310.00
6" Gate Valve		EA	\$	2,100.00	\$	-
8" Gate Valve		EA	\$	2,750.00	\$	-
12" Gate Valve		EA	\$	3,800.00	\$	-

1" Water Service Tap & Corporation	2	EA	\$ 425.00	\$ 850.00
Chlorine Injection Tap		EA	\$ 1,400.00	\$ -
Hydrant		EA	\$ 6,800.00	\$ -
Subdivision Electrification (Cost from Utility)	1	LS	\$ -	\$ -

### **Site Stabilization/Stormwater/Landscaping**

Silt Fence (or equal)	800	LF	\$ 4.70	\$ 3,760.00
Storm Water Pollution Prevention Plan (SWPPP)		EA	\$ 5,400.00	\$ -
Monitor SWPPP		HR	\$ 90.00	\$ -
Chain Link/Stockade Fence - 5'		LF	\$ 85.00	\$ -
Permanent Dumpster Pad & Enclosure		EA	\$ 2,900.00	\$ -
New Trees - Deciduous - General		EA	\$ 510.00	\$ -
New Trees - Evergreen Cedar		EA	\$ 510.00	\$ -
Shrubs - Large		EA	\$ 150.00	\$ -
Shrubs - Small		EA	\$ 80.00	\$ -
Rain Garden/Gravel Wetland (Volume of Storage)	2100	CF	\$ 15.30	\$ -
Infiltration/Detention Basin (Volume of Storage)		CF	\$ 8.30	\$ 17,430.00
Subsurface Infiltration Chamber (Volume of Storage)		CF	\$ 85.60	\$ -
Loam and Seed	1611	SY	\$ 9.50	\$ 15,304.50
Sod		SY	\$ 9.40	\$ -
Mulch		CY	\$ 80.00	\$ -
Hay Bales - Temporary Erosion Control		LF	\$ 22.00	\$ -

### **Quality Control**

Physical Testing Laboratory Services	0	AC	\$ 3,400.00	\$ -
Officers - 4 hr min	8	HR	\$ 98.00	\$ 784.00
Flagger	16	HR	\$ 44.00	\$ 704.00

### **Project Documentation**

As-Built Drawing (\$3,000 min)	1	LS	\$ 5,000.00	\$ 5,000.00
Staking/Monumentation/Record Drawings Prep (\$2,500 Min)	1	LS	\$ -	\$ -

### **Site Maintenance**

Site Clean Up (Removal of Construction Materials/Debris)	0.7	AC	\$ 6,400.00	\$ 4,480.00
Clean Out Catch Basins (\$400 Min)		EA	\$ 80.00	\$ -
Dumpster (10 CY - 4 Ton)		WK	\$ 675.00	\$ -

### **Demolition**

Specialized or Site Specific Demolition (\$1,200 Min)	1	LS	\$ -	\$ -
---	---	----	------	------

### **Specialty Requirements per N.O.D.**

Requirement or Other Cost not Listed Above	1	LS	\$ -	\$ -
E-One grinder pumps	4	EA	\$ 4,000.00	\$ 16,000.00
	1	LS	\$ -	\$ -
	1	LS	\$ -	\$ -
	1	LS	\$ -	\$ -
	1	LS	\$ -	\$ -

### **Mobilization/Demobilization**

		5% of total	\$	17,873.59
--	--	-------------	----	-----------

**Subtotal:** \$ 375,345.29

**10% Contingency:** \$ 37,534.53

**Performance Guarantee (10% of total cost including 10% contingency):** \$ 41,287.98

**Surety = 110% of the Uncompleted Work:** \$ 412,879.81

\*Sub grade for building foundations. Stone backfill for sewer. Under drain. Roadway

## Site Plan Review Application Fee – FY25

**Project:**

**Map/Lot:**

**Applicant:**

All development

*Base fee \$600*

**\$600.00**

*Plus \$5.00 per \$1,000 of site costs*

Site costs

**\$412,287**

**+ \$2,061.44**

*Plus \$10.00 per 1,000 S.F. of site development area*

Site development area

**30,200 S.F.**

**+ \$302.00**

**Fee \$2,963.44**

Maximum fee: \$20,000.00

Fee received by: \_\_\_\_\_

Date: \_\_\_\_\_

*Note: Initial application fee may be based on the applicant's estimates of site costs and site development area. Following site plan approval, the application fee will be recalculated based on the approved site plan and site engineer's corresponding site cost estimate as approved by the Department of Public Works, and any additional fee shall be paid prior to the issuance of a building permit.*

# 1151 SAGAMORE AVENUE CBC, LLC SITE PLAN REVIEW

## 1151 SAGAMORE AVENUE, PORTSMOUTH, NEW HAMPSHIRE

### PROJECT INFORMATION

**CIVIL ENGINEER**  
HALEY WARD, INC.  
ATTN: DREW OLEHOWSKI, PE.  
200 GRIFFIN ROAD, UNIT 14  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.430.9282

**OWNER / APPLICANT**  
1151 SAGAMORE AVENUE CBC, LLC  
76 STATE STREET  
NEWBURYPORT, MASSACHUSETTS 01950

**SURVEYOR**  
HALEY WARD, INC.  
ATTN: CHARLES ADAMS, LLS, PLS  
200 GRIFFIN ROAD, UNIT 14  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.430.9282

**LANDSCAPE ARCHITECT**  
TERRA FIRMA LANDSCAPE ARCHITECTURE  
ATTN: TERENCE PARKER  
163A COURT STREET  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.531.9109


**UTILITY PROVIDERS**  
WATER & SEWER  
CITY OF PORTSMOUTH DEPT. OF  
PUBLIC WORKS  
ATTN: JIM TOW  
680 PEVERLY HILL ROAD  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.427.1530

**ELECTRIC**  
EVERSOURCE  
ATTN: MICHAEL BUSBY, P.E.  
1700 LAFAYETTE ROAD  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.436.7708, EXT. 555.5678

**CABLE**  
COMCAST  
ATTN: MIKE COLLINS  
155 COMMERCE WAY  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.679.5695, EXT. 1037

**COMMUNICATIONS**  
CONSOLIDATED COMMUNICATIONS  
ATTN: JOE CONSIDINE  
1575 GREENLAND ROAD  
GREENLAND, NEW HAMPSHIRE 03840  
T: 603.427.5525

**NATURAL GAS**  
UNITIL  
ATTN: DAVE BEAULIEU  
325 WEST ROAD  
PORTSMOUTH, NEW HAMPSHIRE 03801  
T: 603.294.5144



LOCATION MAP

### ISSUED FOR PERMITTING DECEMBER 22, 2025

### INDEX OF DRAWINGS

C000	COVER SHEET
C001	GENERAL NOTES, LEGEND & ABBREVIATIONS
V101	EXISTING CONDITIONS
C101	SITE PLAN
C102	UTILITY PLAN
C103	GRADING PLAN
C201	PROPOSED DRIVEWAY PLAN & PROFILE
C202	SITE DISTANCE PLAN & PROFILE
C501	SITE DETAILS
C502	SITE DETAILS
C503	SITE DETAILS
C701	PRE-DEVELOPMENT HYDROLOGY PLAN
C702	POST-DEVELOPMENT HYDROLOGY PLAN
TR-1	TURNING DIAGRAM
TR-2	TURNING DIAGRAM
TR-3	TURNING DIAGRAM
TR-4	TURNING DIAGRAM

PLANS BY TERRA FIRMA LANDSCAPE ARCHITECTURE:

L-1 LANDSCAPE PLAN  
L-2 LANDSCAPE DETAILS

### PERMITS & APPROVALS

CITY OF PORTSMOUTH - SITE PLAN REVIEW: IN PROGRESS

### PLAN REFERENCE

1. EXISTING CONDITIONS PLAN FOR BUILD AMERICA, PREPARED FEBRUARY 2025 BY HALEY WARD, INC.
2. AS-BUILT SITE PLAN FOR BUILD AMERICA, PREPARED NOVEMBER 2025 BY AMBIT ENGINEERING, INC., A DIVISION OF HALEY WARD, INC.
3. SUPPLEMENTAL LIDAR TOPOGRAPHY OBTAINED FROM THE NOAA DIGITAL COAST DATA ACCESS VIEWER.



HALEY WARD

[www.haleyward.com](http://www.haleyward.com)

**CONSTRUCTION SEQUENCE**

DO NOT BEGIN CONSTRUCTION UNTIL ALL LOCAL, STATE AND FEDERAL PERMITS HAVE BEEN APPLIED FOR AND RECEIVED.

INSTALL SILT SOXX TO CONTROL EROSION AND SEDIMENTATION PRIOR TO ANY EARTH MOVING ACTIVITIES.

REMOVE EXISTING BUILDINGS AND OTHER SITE FEATURES TO BE REMOVED.

CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE.

CUT AND REMOVE ALL TREES, SHRUBS, SAPLINGS, BRUSH, VINES AND OTHER DEBRIS AND RUBBISH AS REQUIRED.

STRIP AND STOCKPILE LOAM FROM SITE. STOCKPILES SHALL BE SURROUNDED WITH SILT SOXX TO CONTROL SEDIMENT RUN OFF.

D ROUGH GRADE SITE AND CONSTRUCT DRAINAGE STRUCTURES, RAIN GARDEN AND SWALES. INSTALL AND MAINTAIN EROSION CONTROL DEVICES AS SHOWN ON THE PLANS. ALL PERMANENT DITCHES, AND SWALES SHALL BE STABILIZED PRIOR TO DIRECTING RUNOFF TO THEM. CONSTRUCT BUILDING FOUNDATIONS.

LOAM AND SEED DISTURBED AREAS IN ACCORDANCE WITH VEGETATIVE PRACTICE AND GENERAL CONSTRUCTION NOTES. CUT AND FILL SLOPES SHALL BE SEDED IMMEDIATELY AFTER THEIR CONSTRUCTION.

CONSTRUCT UTILITIES, BUILDINGS AND PAVEMENT BASE COURSE.

PLANT LANDSCAPING.

CONSTRUCT PAVEMENT WEARING COURSE.

REMOVE TRAPPED SEDIMENTS FROM COLLECTION DEVICES AS APPROPRIATE, AND THEN REMOVE TEMPORARY EROSION CONTROL MEASURES.

**PROJECT DESCRIPTION**

THE PROJECT CONSISTS OF FOUR HOUSING UNITS WITH ASSOCIATED PARKING AND UTILITIES.

THE TOTAL AREA TO BE DISTURBED IS APPROXIMATELY 0.695 ACRES.

BASED ON THE USCS WEB SOIL SURVEY THE SOILS ON SITE CONSIST OF CHATFIELD-HOLLIS-CANTON COMPLEX WHICH IS WELL DRAINED SOILS WITH A HYDROLOGIC SOIL GROUP RATING OF B.

THE STORMWATER RUNOFF FROM THE SITE WILL BE DISCHARGED VIA OVERLAND DRAINAGE PATHWAYS WHICH ULTIMATELY FLOW TO THE SAGAMORE CREEK.

**GENERAL CONSTRUCTION NOTES**

THE EROSION CONTROL PROCEDURES SHALL CONFORM TO SECTION 645 OF THE "STANDARD SPECIFICATION FOR ROAD AND BRIDGE CONSTRUCTION" OF THE NH DOT, AND "STORM WATER MANAGEMENT AND EROSION AND SEDIMENT CONTROL HANDBOOK FOR URBAN AND DEVELOPING AREAS IN NEW HAMPSHIRE". THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

C DURING CONSTRUCTION AND THEREAFTER, EROSION CONTROL MEASURES ARE TO BE IMPLEMENTED AS NOTED. THE SMALLEST PRACTICAL AREA OF LAND SHOULD BE EXPOSED AT ANY ONE TIME DURING DEVELOPMENT. NO DISTURBED AREA SHALL BE LEFT UNSTABILIZED FOR MORE THAN 45 DAYS.

ANY DISTURBED AREAS WHICH ARE TO BE LEFT TEMPORARILY, AND WHICH WILL BE REGRADED LATER DURING CONSTRUCTION SHALL BE MACHINE HAY MULCHED AND SEDED WITH RYE GRASS TO PREVENT EROSION.

THE PROJECT IS TO BE MANAGED IN A MANNER THAT MEETS THE REQUIREMENTS AND INTENT OF RSA 430:53 AND CHAPTER AGR 3800 RELATIVE TO INVASIVE SPECIES.

DUST CONTROL - DUST CONTROL MEASURES SHALL INCLUDE BUT ARE NOT LIMITED TO SPRINKLING WATER ON EXPOSED AREAS, COVERING LOADED DUMP TRUCKS LEAVING THE SITE, AND TEMPORARY MULCHING. DUST CONTROL MEASURES SHALL BE UTILIZED SO AS TO PREVENT THE MIGRATION OF DUST FROM THE SITE TO ADJACENT AREAS.

IF TEMPORARY STABILIZATION PRACTICES, SUCH AS TEMPORARY VEGETATION AND MULCHING, DO NOT ADEQUATELY REDUCE DUST GENERATION, APPLICATION OF WATER OR CALCIUM CHLORIDE SHALL BE APPLIED IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES.

SILTSOXX SHALL BE PERIODICALLY INSPECTED DURING THE LIFE OF THE PROJECT AND AFTER EACH STORM. ALL DAMAGED SILTSOXX SHALL BE REPAIRED. SEDIMENT DEPOSITS SHALL PERIODICALLY BE REMOVED AND DISPOSED IN A SECURED LOCATION.

ALL FILLS SHALL BE PLACED AND COMPAKTED TO REDUCE EROSION, SLIPPAGE, SETTLEMENT, SUBSIDENCE OR OTHER RELATED PROBLEMS.

ALL NON-STRUCTURAL, SITE-FILL SHALL BE PLACED AND COMPAKTED TO 90% MODIFIED PROCTOR DENSITY IN LAYERS NOT EXCEEDING 18 INCHES IN THICKNESS UNLESS OTHERWISE NOTED.

FROZEN MATERIAL OR SOFT, MUCKY OR HIGHLY COMPRESSIBLE MATERIAL, TRASH, WOODY DEBRIS, LEAVES, BRUSH OR ANY DELETERIOUS MATTER SHALL NOT BE INCORPORATED INTO FILLS.

FILL MATERIAL SHALL NOT BE PLACED ON FROZEN FOUNDATION SUBGRADE.

DURING CONSTRUCTION AND UNTIL ALL DEVELOPED AREAS ARE FULLY STABILIZED, ALL EROSION CONTROL MEASURES SHALL BE INSPECTED WEEKLY AND AFTER EACH ONE HALF INCH OF RAINFALL.

THE CONTRACTOR SHALL MODIFY OR ADD EROSION CONTROL MEASURES AS NECESSARY TO ACCOMMODATE PROJECT CONSTRUCTION.

B ALL ROADWAYS AND PARKING AREAS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. ALL CUT AND FILL SLOPES SHALL BE SEDED/LOAMED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE.

AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:

- BASE COURSE GRAVELS HAVE BEEN INSTALLED ON AREAS TO BE LEVEVED
- A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED
- A MINIMUM OF 3 INCHES OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED
- EROSION CONTROL BLANKETS HAVE BEEN INSTALLED
- IN AREAS TO BE PAVED, "STABLE" MEANS THAT BASE COURSE GRAVELS MEETING THE REQUIREMENTS OF NH DOT STANDARD FOR ROAD AND BRIDGE CONSTRUCTION, 2016, ITEM 304.2 HAVE BEEN INSTALLED.

STABILIZATION SHALL BE INITIATED ON ALL LOAM STOCKPILES, AND DISTURBED AREAS, WHERE CONSTRUCTION ACTIVITY SHALL NOT OCCUR FOR MORE THAN TWENTY-ONE (21) CALENDAR DAYS BY THE FOURTEENTH (14TH) DAY AFTER CONSTRUCTION ACTIVITY HAS PERMANENTLY OR TEMPORARILY CEASED IN THAT AREA.

STABILIZATION MEASURES TO BE USED INCLUDE:

- TEMPORARY SEEDING;
- MULCHING.

1. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS OF INITIAL DISTURBANCE.
2. WHEN CONSTRUCTION ACTIVITY PERMANENTLY OR TEMPORARILY CEASES WITHIN 100 FEET OF NEARBY SURFACE WATERS OR DELINQUENT WETLANDS, THE AREA SHALL BE STABILIZED WITHIN SEVEN (7) DAYS OR PRIOR TO A RAIN EVENT. ONCE CONSTRUCTION ACTIVITY CEASES PERMANENTLY IN THESE AREAS, SILTSOXX, MULCH BERMIS, HAY BALE BARRIERS AND ANY EARTHDIKES SHALL BE REMOVED ONCE PERMANENT MEASURES ARE ESTABLISHED.
3. DURING CONSTRUCTION, RUNOFF WILL BE DIVERTED AROUND THE SITE WITH EARTH DIKES, PIPING OR STONE CHAMBERS WHERE POSSIBLE. SHEET RUNOFF FROM THE SITE WILL BE FILTERED THROUGH SILTSOXX, MULCH BERMIS, HAY BALE BARRIERS, OR SILT SOCKS. ALL STORM DRAIN BASIN INLETS SHALL BE PROVIDED WITH FLARED END SECTIONS AND TRASH RACKS. THE SITE SHALL BE STABILIZED FOR THE WINTER BY OCTOBER 15.

**MAINTENANCE AND PROTECTION**

A THE SILTSOXX BARRIER SHALL BE CHECKED AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL.

SILTSOXX SHALL BE REMOVED ONCE SITE IS STABILIZED, AND DISTURBED AREAS RESULTING FROM SILTSOXX REMOVAL SHALL BE PERMANENTLY SEDED.

THE CATCH BASIN INLET BASKET SHALL BE INSPECTED WITHIN 24 HOURS AFTER EACH RAINFALL OR DURING EXCESSIVE PERIODS OF PRECIPITATION. REPAIRS SHALL BE MADE IMMEDIATELY, AS NECESSARY, TO PREVENT PARTICLES FROM REACHING THE DRAINAGE SYSTEM AND/OR CAUSING SURFACE FLOODING. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT, OR MORE OFTEN IF THE FABRIC BECOMES CLOGGED.

**WINTER NOTES**

ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHIBIT A MINIMUM OF 85% VEGETATED GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.

ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15, OR WHICH ARE DISTURBED AFTER OCTOBER 15, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS;

AFTER OCTOBER 15, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NH DOT ITEM 304.3, OR IF CONSTRUCTION IS TO CONTINUE THROUGH THE WINTER SEASON BE CLEARED OF ANY ACCUMULATED SNOW AFTER EACH STORM EVENT;

**STOCKPILES**

1. LOCATE STOCKPILES A MINIMUM OF 50 FEET AWAY FROM CATCH BASINS, SWALES, AND CULVERTS.
2. ALL STOCKPILES SHOULD BE SURROUNDED WITH TEMPORARY EROSION CONTROL MEASURES PRIOR TO THE ONSET OF PRECIPITATION.
3. PERIMETER BARRIERS SHOULD BE MAINTAINED AT ALL TIMES, AND ADJUSTED AS NEEDED TO ACCOMMODATE THE DELIVERY AND REMOVAL OF MATERIALS FROM THE STOCKPILE. THE INTEGRITY OF THE BARRIER SHOULD BE INSPECTED AT THE END OF EACH WORKING DAY.
4. PROTECT ALL STOCKPILES FROM STORMWATER RUN-OFF USING TEMPORARY EROSION CONTROL MEASURES SUCH AS BERMIS, SILT SOCKS, OR OTHER APPROVED PRACTICE TO PREVENT MIGRATION OF MATERIAL BEYOND THE IMMEDIATE CONFINES OF THE STOCKPILES.

**CONCRETE WASHOUT AREA**

THE FOLLOWING ARE THE ONLY NON-STORMWATER DISCHARGES ALLOWED. ALL OTHER NON-STORMWATER DISCHARGES ARE PROHIBITED ON SITE:

1. THE CONCRETE DELIVERY TRUCKS SHALL, WHENEVER POSSIBLE, USE WASHOUT FACILITIES AT THEIR OWN PLANT OR DISTRIBUTOR.
2. IF NECESSARY, SITE CONTRACTOR SHALL DESIGNATE SPECIFIC WASHOUT AREAS AND DESIGN FACILITIES TO HANDLE ANTICIPATED WASHOUT WATER.
3. CONTRACTOR SHALL LOCATE WASHOUT AREAS AT LEAST 150 FEET AWAY FROM STORM DRAINS, SWALES AND SURFACE WATERS OR DELINQUENT WETLANDS.
4. INSPECT WASHOUT FACILITIES DAILY TO DETECT LEAKS OR TEARS AND TO IDENTIFY WHEN MATERIALS NEED TO BE REMOVED.

**ALLOWABLE NON-STORMWATER DISCHARGES**

1. FIRE-FIGHTING ACTIVITIES;
2. FIRE HYDRANT FLUSHING;
3. WATERS USED TO WASH VEHICLES WHERE DETERGENTS ARE NOT USED;
4. WATER USED TO CONTROL DUST;
5. PORTABLE CONCRETE WASHING UNMOUNTED WATER LINE FLUSHING;
6. ROUTINE EXTERNAL BUILDING WASH DOWN WHERE DETERGENTS ARE NOT USED;
7. PAVEMENT WASH WATERS WHERE DETERGENTS ARE NOT USED;
8. UNCONTAMINATED AIR CONDITIONING/COMPRESSOR CONDENSATION;
9. UNCONTAMINATED GROUND WATER OR SPRING WATER;
10. FOUNDATION OR FOOTING DRAINS WHICH ARE UNCONTAMINATED;
11. UNCONTAMINATED EXCAVATION DEWATERING;
12. LANDSCAPE IRRIGATION;

**WASTE DISPOSAL**

1. WASTE MATERIAL
  - ALL WASTE MATERIALS SHALL BE COLLECTED AND STORED IN SECURELY LIDDED RECEPTACLES. ALL TRASH AND CONSTRUCTION DEBRIS FROM THE SITE SHALL BE DEPOSITED IN A DUMPSTER;
  - NO CONSTRUCTION WASTE MATERIALS SHALL BE BURIED ON SITE;
  - ALL CONSTRUCTION WASTE MATERIALS SHALL BE BURIED IN THE CORRECT PROCEDURE FOR WASTE DISPOSAL BY THE SUPERINTENDENT.
2. HAZARDOUS WASTE
  - ALL HAZARDOUS WASTE MATERIALS SHALL BE DISPOSED OF IN THE MANNER SPECIFIED BY LOCAL OR STATE REGULATION OR BY THE MANUFACTURER;
  - SUPERINTENDENT SHALL BE INSTRUCTED IN THESE PRACTICES BY THE SUPERINTENDENT.
3. SANITARY WASTE
  - ALL SANITARY WASTE SHALL BE COLLECTED FROM THE PORTABLE UNITS A MINIMUM OF ONCE PER WEEK BY A LICENSED SANITARY WASTE MANAGEMENT CONTRACTOR.

**BLASTING NOTES**

1. CONTRACTOR SHALL CONTACT THE NHDES AND/OR LOCAL JURISDICTION PRIOR TO COMMENCING ANY BLASTING ACTIVITIES.
2. FOR ANY PROJECT FOR WHICH BLASTING OF BEDROCK IS ANTICIPATED, THE APPLICANT SHALL SUBMIT A BLASTING PLAN THAT IDENTIFIES:
  - WHERE THE BLASTING ACTIVITIES ARE ANTICIPATED TO OCCUR;
  - THE ESTIMATED QUANTITY OF BLAST ROCK IN CUBIC YARDS; AND
  - SITE-SPECIFIC BLASTING BEST MANAGEMENT PRACTICES.

**ABBREVIATIONS**

@	AT	MAX.	MAXIMUM	
ANSI APPROX.±	AMERICAN NATIONAL STANDARDS INSTITUTE APPROXIMATELY	MDOT MH MIN	MAINE DEPT. OF TRANSPORTATION MANHOLE MINIMUM	
BLDG	BUILDING	N	NORTHERN	PROPERTY LINE
CL	CENTERLINE	NE	NORTHEAST	BENCHMARK
CB	CATCH BASIN	N.T.S.	NOT TO SCALE	SURVEY STATION
CLR	CLEAR	OD	OUTSIDE DIAMETER	IRON PIN
CMP	CORRUGATED METAL PIPE	O.C.	ON CENTER	DRILL HOLE
CO	CLEANOUT	OH	OVERHEAD	BOUND
CPE	CORRUGATED POLYETHYLENE	OZ	ONCE	TEST PIT
DI	DUCTILE IRON DIA. METER	PERF	PERFORATED	SEWER MANHOLE
DIA.	DIA. DIA. METER	PSF	POUNDS PER SQUARE FOOT	GAS VALVE
E	EASTING	PSI	POUNDS PER SQUARE INCH	UTILITY POLE
EL	ELEVATION	PVC	POLYVINYL CHLORIDE	GUY ANCHOR
EFM	EXISTING FORCE MAIN	PROPERTY LINE	PROPOSED OVERHEAD ELECTRIC	ELECTRICAL MANHOLE
EPS	EXTRUDED POLYSTYRENE	POH	PROPOSED UNDERGROUND ELECTRIC	TRANSFORMER
FM	FORCEMAN	PUBE	UNDERGROUND ELECTRIC	PULLBOX
GAL	GALLON	R	RADIUS	PARKING LIGHT
GALV	GALVANIZED	S	SLOPE	FLOOD LIGHT
GPH	GALLONS PER HOUR	SCL	STORMWATER COLLECTION LINE	SITE LIGHT
GPM	GALLONS PER MINUTE	SCS	STORMWATER COLLECTION SYSTEM	SIGN
HDPE	HIGH DENSITY POLYETHYLENE	SDR	STANDARD DIMENSION RATIO	TRASH CAN
HP	HORSEPOWER	SE	SOUTHEAST	FLAGPOLE
ID	INSIDE DIAMETER	SHT	SHEET	MONITORING WELL
IN.	INCHES	SQ	SQUARE	EDGE OF GRAVEL
INT.	INTERSECTION	SS	STAINLESS STEEL	EDGE OF PAVEMENT
INV.	INVERT	SY	SQUARE YARD	CURBING
TBM		TEMPORARY BENCH MARK	MAJOR FOOT CONTOUR	MAJOR FOOT CONTOUR
TOC		TOP OF CONCRETE	MINOR FOOT CONTOUR	MINOR FOOT CONTOUR
TYP		TYPICAL	WATERLINE	WATERLINE

**LEGEND:**

ITEMS SHOWN MAY NOT APPEAR ON PLANS


DESCRIPTION	EXISTING	PROPOSED
PROPERTY LINE	—	—
BENCHMARK	○	○
SURVEY STATION	●	●
IRON PIN	●	●
DRILL HOLE	○	○
BOUND	□	□
TEST PIT	○	○
SEWER MANHOLE	○	○
GAS VALVE	○	○
UTILITY POLE	○	○
GUY ANCHOR	○	○
ELECTRICAL MANHOLE	○	○
TRANSFORMER	○	○
PULLBOX	○	○
PARKING LIGHT	○	○
FLOOD LIGHT	○	○
SITE LIGHT	○	○
SIGN	○	○
TRASH CAN	○	○
FLAGPOLE	○	○
MONITORING WELL	○	○
EDGE OF GRAVEL	—	—
EDGE OF PAVEMENT	—	—
CURBING	—	—
MAJOR FOOT CONTOUR	—	—
MINOR FOOT CONTOUR	—	—
WATERLINE	—	—
STORM DRAIN	—	—
UNDER DRAIN	—	—
SANITARY SEWER	—	—
FORCE MAIN	—	—
OVERHEAD UTILITIES	—	—
UNDERGROUND UTILITIES	—	—
GAS LINE	—	—
CHAIN LINK FENCE	—	—
GUARDRAIL	—	—
SILT FENCE	—	—
TREE LINE</td		

## LEGEND:


DESCRIPTION	EXISTING
RCRD	ROCKINGHAM COUNTY REGISTRY OF DEEDS
1234/123	DEED BOOK/PAGE
N/F	NOW OR FORMALLY
TYP.	TO BE SET
TBS	INVERT
INV.	ELEVATION
ELV.	FINISHED FLOOR
FF	SINGLE WHITE LINE
SWL	DOUBLE YELLOW LINE
DYL	VERTICAL GRANITE CURB
VGC	
MAP 21 LOT 8	
BENCHMARK	
RAILROAD SPIKE	
BOUND	
IRON ROD/PIPE FOUND	
SET 5/8" REBAR WITH SURVEYOR'S CAP	
CATCH BASIN	
SEWER MANHOLE	
DRAIN MANHOLE	
UTILITY POLE	
GUY WIRE	
HYDRANT	
GATE VALVE	
GAS/WATER SHUTOFF	
TREES	
GAS/ELECTRIC METER	
MAIL BOX	
SIGN	
SPOT GRADE	
PROPERTY LINE	
APPROXIMATE EXTERIOR PROPERTY LINE	
EDGE OF PAVEMENT	
EDGE OF GRAVEL	
MINOR FOOT CONTOUR	
MAJOR FOOT CONTOUR	
WETLAND FLAG/WETLAND	
FRESH WATER WETLAND LINE	
WETLAND BUFFER LINE	
TREELINE	
STORM DRAIN LINE	
OVERHEAD UTILITY LINE	

## PLAN REFERENCES:

- 1) PLAN OF LAND ON SAGAMORE CREEK, PORTSMOUTH, N.H. OWNED BY JOSIAH F. ADAMS, SURVEYED BY E.M.HUNT, JUN. ENGR., SCALE: 1"=1000', DATED: MARCH 1908, RCRD PLAN# 00254.
- 2) PLAN OF LAND PORTSMOUTH, N.H. FOR NORMAN J. & JANET S. SMITH, SCALE: 1IN.=100FT, DATED: NOV. 1964, PREPARED BY JOHN W. DURGIN CIVIL ENGINEERS, RCRD PLAN# 1549.
- 3) BOUNDARY LINE CHANGE LODGE 444 LOYAL ORDER OF MOOSE AND ROBERT & STUART SHAINES, SAGAMORE AVENUE, PORTSMOUTH, NEW HAMPSHIRE, SCALE: 1"=50', DATED MAY 1984, PREPARED BY K.E.MOORE & B.G.STAPLES LAND SURVEYORS, RCRD D-13349.
- 4) SUBDIVISION OF LAND PORTSMOUTH & RYE, N.H. FOR R & S TRUST, SCALE: 1"=100', DATED: DEC. 13, 1984, PREPARED BY JOHN W. DURGIN ASSOCIATES, INC., RCRD D-13415.
- 5) SUBDIVISION OF LAND PORTSMOUTH, N.H. FOR STUART SHAINES & ROBERT SHAINES, SCALE: 1"=40', DATED JAN. 15, 1988, PREPARED BY DURGIN SCHOFIELD ASSOCIATES, RCRD D-18178.
- 6) STANDARDS BOUNDARY SURVEY & PROPOSED EASEMENT PLAN TAX MAP 224 LOT 17, OWNERS CHINBURG DEVELOPMENT, LLC, LAND LOCATED AT 1163 SAGAMORE AVENUE, CITY OF PORTSMOUTH, COUNTY OF ROCKINGHAM, STATE OF NEW HAMPSHIRE, SCALE: 1"=50', DATED MAY 2015, RCRD D-39466.
- 7) STATE HIGHWAY EASEMENT PLAN TAX MAP 224 LOT 18, OWNERS: MICHAEL A. VALINSKI & MAUREEN OAKMAN, 1155 SAGAMORE AVENUE, CITY OF PORTSMOUTH, COUNTY OF ROCKINGHAM, STATE OF NEW HAMPSHIRE, SCALE: 1"=20', DATED JANUARY 2016, RCRD B-39466.
- 8) SEA STAR COVE CONDOMINIUM SITE PLAN TAX MAP 224 LOT 17, OWNER: CHINBURG DEVELOPMENT, LLC, LAND LOCATED AT 1163 SAGAMORE AVENUE, CITY OF PORTSMOUTH, COUNTY OF ROCKINGHAM, STATE OF NEW HAMPSHIRE, SCALE: 1"=50', DATED: APRIL 2016, RCRD D-40524.
- 9) SEWER EASEMENT PLAN SEA STAR COVE CONDOMINIUM TAX MAP 224 LOT 17, OWNER OF RECORD / DECLARANT: CHINBURG DEVELOPMENT, LLC, TO BENEFIT MICHAEL A. VALINSKI & MAUREEN OAKMAN, LAND LOCATED AT 1163 SAGAMORE AVENUE, CITY OF PORTSMOUTH, COUNTY OF ROCKINGHAM, STATE OF NEW HAMPSHIRE, SCALE: AS SHOWN, DATED: MARCH 2021, RCRD D-42662.



1	10/22/2025	OWNERSHIP NAME	PAY	PAY
0	3/26/25	ISSUED FOR COMMENT	RJB	PAY
REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
SITE SURVEY				
 <b>HALEY WARD</b> ENGINEERING   ENVIRONMENTAL   SURVEYING <a href="http://WWW.HALEYWARD.COM">WWW.HALEYWARD.COM</a>				
PROJECT				
BUILD AMERICA 1151 SAGAMORE AVENUE PORTSMOUTH, N.H.				
TITLE				
EXISTING CONDITIONS PLAN				
DATE: FEBRUARY 2025 DRAWN BY: RJB DESIGNED BY: --- CHECKED BY: PAY PROJECT No: 5010314.002 FIELD BOOK/PAGE: FB 450 PG 15 DRAWING No: 10/23/2025 REV: 1				




NOTES:

- 1) PARCEL IS SHOWN ON THE CITY OF PORTSMOUTH ASSESSOR'S MAP 224 AS LOT 19.
- 2) OWNER OF RECORD:  
1151 SAGAMORE AVENUE CBC, LLC  
76 STATE STREET  
NEWBURYPORT, MA 01950  
RCRD 6633/1720
- 3) PARCEL IS NOT IN A SPECIAL FLOOD HAZARD AREA AS SHOWN ON FIRM PANEL 33015C0286F. EFFECTIVE JANUARY 29, 2021.
- 4) EXISTING LOT AREA:  
30,191 S.F.  
0.69 ACRES
- 5) PARCEL IS LOCATED IN MIXED RESIDENTIAL OFFICE (MRO) ZONING DISTRICT.
- 6) DIMENSIONAL REQUIREMENTS:  
MIN. LOT AREA: 7,500 S.F.  
FRONTAGE: 100 FEET  
SETBACKS: 5 FEET  
FRONT: 10 FEET  
SIDE: 15 FEET  
REAR: 40 FEET  
MAXIMUM STRUCTURE HEIGHT: SLOPED ROOF: 30 FEET  
FLAT ROOF: 40 FEET  
MAXIMUM BUILDING COVERAGE: 40%  
MINIMUM OPEN SPACE: 25%

7) THE PURPOSE OF THIS PLAN IS TO SHOW THE EXISTING CONDITIONS ON ASSESSOR'S MAP 224 LOT 19 IN THE CITY OF PORTSMOUTH.


8) VERTICAL DATUM IS NAVD88. BASIS OF VERTICAL DATUM IS REDUNDANT RTN GNSS OBSERVATIONS.


9) ABUTTER INFORMATION TAKEN FROM THE CITY OF PORTSMOUTH GIS WEBSITE.






"I CERTIFY THAT THIS PLAN WAS PREPARED UNDER MY DIRECT SUPERVISION, THAT IT IS THE RESULT OF A FIELD SURVEY BY THIS OFFICE AND HAS AN ACCURACY OF THE CLOSED TRAVERSE THAT EXCEEDS THE PRECISION OF 1:15,000."

10/23/2025  
PHILIP A. YETMAN, LLS 1122 DATE













REV.	DATE	DESCRIPTION	BY																				
DRAWING ISSUE STATUS																							
ISSUED FOR PERMITTING																							
<b>HALEY WARD</b> 200 Griffin Rd, Unit 1A Portsmouth, New Hampshire 03801 603.430.9282																							
PROJECT																							
TITLE																							
GRADING PLAN																							
<table border="1"> <tr> <td>DATE</td> <td>SCALE</td> </tr> <tr> <td>2025.12.22</td> <td>1"=20'</td> </tr> <tr> <td>DRAWN BY</td> <td>DESIGNED BY</td> </tr> <tr> <td>BLQ/PJM</td> <td>BLQ/PJM</td> </tr> <tr> <td colspan="2">CHECKED BY</td> </tr> <tr> <td colspan="2">DJO</td> </tr> <tr> <td colspan="2">PROJECT No.</td> </tr> <tr> <td colspan="2">5010314.002</td> </tr> <tr> <td colspan="2">DRAWING No.</td> </tr> <tr> <td colspan="2">C103</td> </tr> </table>				DATE	SCALE	2025.12.22	1"=20'	DRAWN BY	DESIGNED BY	BLQ/PJM	BLQ/PJM	CHECKED BY		DJO		PROJECT No.		5010314.002		DRAWING No.		C103	
DATE	SCALE																						
2025.12.22	1"=20'																						
DRAWN BY	DESIGNED BY																						
BLQ/PJM	BLQ/PJM																						
CHECKED BY																							
DJO																							
PROJECT No.																							
5010314.002																							
DRAWING No.																							
C103																							







## PROFILE VIEW OF SITE DISTANCE - STA -4+25 TO 4+25

SCALE: H: 1"=40' / V: 1"=4'

## GRAPHIC SCALE

40 0 20 40 80

( IN FEET )

$$1 \text{ inch} = 40 \text{ ft.}$$


2


## NOTES:

1. VERTICAL DATUM IS NAVD88. BASIS OF VERTICAL DATUM IS REDUNDANT RTN GNSS OBSERVATIONS.
2. TRASH PICKUP TO BE CURBSIDE.


## PLAN REFERENCE:

## 1. EXISTING CONDITIONS PLAN FOR BUILD AMERICA, PREPARED FEBRUARY 2025 BY HALEY WARD.

REV.	DATE	DESCRIPTION	BY	CHK.
DRAWING ISSUE STATUS				
<b>ISSUED FOR PERMITTING</b>				
 <a href="http://WWW.HALEYWARD.COM">WWW.HALEYWARD.COM</a>		<b>HALEY WARD</b>		
200 Griffin Rd., Unit 14 Portsmouth, New Hampshire 03801 603.430.9282				
PROJECT				
<b>1151 SAGAMORE AVENUE CBC, LLC</b> <b>1151 SAGAMORE AVE., PORTSMOUTH, NH</b>				
TITLE				
<b>SITE DISTANCE PLAN &amp; PROFILE</b>				
	DATE		SCALE	
	2025.12.22		1"=40'	
	DRAWN BY		DESIGNED BY	
	BLQ/PJM		BLQ/PJM	
	CHECKED BY		DJO	
	PROJECT No.		5010314.002	
DRAWING No.		C202		REV.














## PROJECT

**1151 SAGAMORE AVENUE CBC, LLC**  
1151 SAGAMORE AVE., PORTSMOUTH NH

DWG No.

TR-1

BIM

2025.12.22

**TITLE**

## **TURNING EXHIBIT LEFT TURN ENTERING COMPLEX**

11


5010314.002

REV

SCALE 1"=20'


REV. DATE





PROJECT	1151 SAGAMORE AVENUE CBC, LLC 1151 SAGAMORE AVE., PORTSMOUTH NH		DWG No.	BY
TITLE	TURNING EXHIBIT RIGHT TURN ENTERING COMPLEX	TR-2	PJM	
		JN	DATE	2025.12.22
		5010314.002	REV.	
		SCALE	REV. DATE	1"=20'

 **HALEY WARD**



PROJECT

**1151 SAGAMORE AVENUE CBC, LLC**  
**1151 SAGAMORE AVE., PORTSMOUTH NH**

DWG No.

**TR-3**

244

2025.12.22

**TITLE**

## **TURNING EXHIBIT**

### **RIGHT TURN EXITING COMPLEX**

1


5010314.002

SCALE 1"-20'

REV

114 of 114

 HALEY WARD



PROJECT

**1151 SAGAMORE AVENUE CBC, LLC**  
1151 SAGAMORE AVE., PORTSMOUTH NH

TITLE

**TURNING EXHIBIT**  
**LEFT TURN EXITING COMPLEX**

DWG No.

**TR-4**

BY

**PJM**

DATE

2025.12.22

JN

5010314.002

SCALE

1"=20'

REV.

REV. DATE

**HALEY WARD**

## Plant List - Trees and Shrubs

ID	Qty	Botanical Name	Common Name	Scheduled Size	Mature Height	Mature Width	Growth Habit	Tolerances	Requirements
ARB	6	<i>Acer rubrum 'Bowhall'</i>	Bowhall Maple	3" Cal.	40-60'	10-15'	Upright, Broadly Columnar	Urban, Wet Soil	Full, partial sun. Moist, well drained soils.
ASV	3	<i>Acer rubrum 'Sun Valley'</i>	Sun Valley Maple	3 1/2" Cal.	Height	Spread	Growth Habit	Tolerances	woody
GTH	2	<i>Gleditsia triacanthos inermis 'Halka'</i>	Halka Honeylocust	2" Cal.	30-40'	30-40'	Rounded	Urban, Salt, Drought, Wind, Heat	Full sun. Moist, well drained soils.
JBD	102	<i>Juniperus communis depressa 'Blueberry Delight'</i>	Blueberry Delight Juniper	2 Gal.	18-24"	4-5'	Spreading	Drought, Deer, Urban, Salt	Full, partial sun. Average, well drained soil.
PGD	3	<i>Picea glauca 'Densata'</i>	Black Hills Spruce	7-8' Ht.	20-30'	15-20'	Pyramidal	Drought, Deer, Wind	Full sun. Moist, well drained soils.
QB	5	<i>Quercus bicolor</i>	Swamp White Oak	3" Cal.	40-60'	40-60'	Broad	Drought, Moist Soil, Urban	Full sun, large space. Medium to wet, acidic soil.
RGL	100	<i>Rhus aromatica 'Grow Low'</i>	Grow Low Sumac	18-24"	18-24"	6-8'	Spreading	Drought, Urban, Salt	Full, partial sun. Dry to average, well drained soil.
TOS	7	<i>Thuja occidentalis 'Smaragd'</i>	American Arborvitae	7-8' Ht.	15-20'	5-6'	Upright, Pyramidal	Urban, Moist Soil	Full, partial sun. Average, well drained soil.
VBM	46	<i>Viburnum dentatum 'Blue Muffin®'</i>	Blue Muffin® Viburnum	3-4' Ht.	6-8'	4-5'	Compact	Deer, Moist Soil, Drought, Salt., Urban	Full, partial sun. Average, well drained soil.



terra firma  
landscape architecture

163-a Court Street Portsmouth, NH 03801  
03.531.9109 | [terrence@terrafirmalandarch.com](mailto:terrence@terrafirmalandarch.com)

## Plant List - Perennials

ID	Qty	Botanical Name	Common Name	Scheduled Size	Mature Height	Mature Width	Growth Habit	Tolerances	Requirements
BAP	14	<i>Baptisia australis</i>	False Indigo	1 Gal.	36"	36"	Bushy	Salt, Drought, Urban	Sun, partial shade. Average soil.
PVS	15	<i>Panicum virgatum 'Shenandoah'</i>	Shenandoah Switch Grass	2 Gal.	36"	30-48"	Clump	Drought, Wet soil, Urban, Salt	Sun, partial shade. Average to moist soil.



**Ernst Conservation Seeds**  
8884 Mercer Pike  
Meadville, PA 16335  
(800) 873-3321 Fax (814) 336-5191  
[www.ernstseed.com](http://www.ernstseed.com)

Date: November 06, 2025

## Rain Garden Grass Mix - ERNMX-180-1

<b>Botanical Name</b>	<b>Common Name</b>
40.30 % <i>Schizachyrium scoparium</i> , Fort Indiantown Gap-PA Ecotype	Little Bluestem, Fort Indiantown Gap-PA Ecotype
20.00 % <i>Elymus virginicus</i> , Madison-NY Ecotype	Virginia Wildrye, Madison-NY Ecotype
17.80 % <i>Carex vulpinoidea</i> , PA Ecotype	Fox Sedge, PA Ecotype
9.00 % <i>Panicum clandestinum</i> , Tioga	Deertongue, Tioga
6.00 % <i>Chasmanthium latifolium</i> , WV Ecotype	River Oats, WV Ecotype
5.50 % <i>Panicum rigidulum</i> , PA Ecotype	Redtop Panicgrass, PA Ecotype
0.70 % <i>Juncus effusus</i>	Soft Rush
0.70 % <i>Juncus tenuis</i> , PA Ecotype	Path Rush, PA Ecotype

**100.00 %**

**Seeding Rate:** 15 lb per acre with a cover crop. For sites that drain within 24 hours of a rain event use one of the following cover crops: Oats (1 Jan to 31 Jul; 30 lbs/acre), Japanese Millet (1 May to 31 Aug; 10 lbs/acre), or grain rye (1 Aug to 31 Dec; 30 lbs/acre).

## Grasses & Grass-like Species - Herbaceous Perennial; Stormwater Management

Mix formulations are subject to change without notice depending on the availability of existing and new products. While the formula may change, the guiding philosophy and function of the mix will not.



**Ernst Conservation Seeds**  
8884 Mercer Pike  
Meadville, PA 16335  
(800) 873-3321 Fax (814) 336-5191

Page Number: 07/2025

### **Conservation Shade Mix - ERNMX-129**

<b>Botanical Name</b>	<b>Common Name</b>
30.00 % <i>Festuca rubra</i>	Creeping Red Fescue
30.00 % <i>Festuca rubra ssp. commutata</i>	Chewings Fescue
20.00 % <i>Lolium multiflorum</i>	Annual Ryegrass
10.00 % <i>Poa pratensis, 'Baron'</i>	Kentucky Bluegrass, 'Baron'
10.00 % <i>Poa trivialis</i>	Rough Bluegrass

**Seeding Rate:** 100-200 lb per acre, or 3-5 lb per 1,000 sq ft  
Grasses & Grass-like Species - Herbaceous Perennial; Lawn & Turfgrass  
While designed for deep-shaded areas, this mix requires at least 2 hours of direct sunlight per day to germinate and grow. The grasses and grass-like species in this mix are shade-tolerant and blend very well together. Mix formulations are subject to change.

relevant and broad. Very often together with innovations are subject to change the existing and new products. While the formula may change, the guiding philosophy

**Plant List - Trees and Shrubs**

ID	Qty	Botanical Name	Common Name	Scheduled Size	Mature Height	Mature Width	Growth Habit	Tolerances	Requirements
ARB	6	<i>Acer rubrum 'Bowhall'</i>	Bowhall Maple	3" Cal.	40-60'	10-15'	Upright, Broadly Columnar	Urban, Wet Soil	Full, partial sun. Moist, well drained soils.
ASV	3	<i>Acer rubrum 'Sun Valley'</i>	Sun Valley Maple	3 1/2" Cal.	Height	Spread	Growth Habit	Tolerances	woody
GTH	2	<i>Gleditsia triacanthos 'Inermis 'Halka'</i>	Halka Honeylocust	2" Cal.	30-40'	30-40'	Rounded	Urban, Salt, Drought, Wind, Heat	Full sun. Moist, well drained soils.
JBD	102	<i>Juniperus communis depressa 'Blueberry Delight'</i>	Blueberry Delight Juniper	2 Gal.	18-24"	4-5'	Spreading	Drought, Deer, Urban, Salt	Full sun. Average, well drained soil.
PGD	3	<i>Picea glauca 'Densata'</i>	Black Hills Spruce	7-8' Ht.	20-30'	15-20'	Pyramidal	Drought, Deer, Wind	Full sun. Moist, well drained soils.
QB	5	<i>Quercus bicolor</i>	Swamp White Oak	3" Cal.	40-60'	40-60'	Broad	Drought, Moist Soil, Urban	Full sun, large space. Medium to wet, acidic soil.
RGL	100	<i>Rhus aromatica 'Grow Low'</i>	Grow Low Sumac	18-24"	18-24"	6-8'	Spreading	Drought, Urban, Salt	Full, partial sun. Dry to average, well drained soil.
TOS	7	<i>Thuja occidentalis 'Smaragd'</i>	American Arborvitae	7-8' Ht.	15-20'	5-6'	Upright, Pyramidal	Urban, Moist Soil	Full, partial sun. Average, well drained soil.
VBM	46	<i>Viburnum dentatum 'Blue Muffin'</i>	Blue Muffin® Viburnum	3-4' Ht.	6-8'	4-5'	Compact	Deer, Moist Soil, Drought, Salt, Urban	Full, partial sun. Average, well drained soil.

**Plant List - Perennials**

ID	Qty	Botanical Name	Common Name	Scheduled Size	Mature Height	Mature Width	Growth Habit	Tolerances	Requirements
BAP	14	<i>Baptisia australis</i>	False Indigo	1 Gal.	36"	36"	Bushy	Salt, Drought, Urban	Sun, partial shade. Average soil.
PVS	15	<i>Panicum virgatum 'Shenandoah'</i>	Shenandoah Switch Grass	2 Gal.	36"	30-48"	Clump	Drought, Wet soil, Urban, Salt	Sun, partial shade. Average to moist soil.

**Ernst Conservation Seeds**  
8884 Mercer Pike  
Meadville, PA 16335  
(800) 873-3321 Fax (814) 336-5191  
[www.ernstseed.com](http://www.ernstseed.com)

Date: November 06, 2025

**Rain Garden Grass Mix - ERNMX-180-1**

Botanical Name	Common Name
40.30 % <i>Schizachyrium scoparium</i> , Fort Indianant Gap-PA Ecotype	Little Bluestem, Fort Indianant Gap-PA Ecotype
20.00 % <i>Elymus virginicus</i> , Madison-NY Ecotype	Virginia Wildrye, Madison-NY Ecotype
17.80 % <i>Carex vulpinoidea</i> , PA Ecotype	Fox Sedge, PA Ecotype
9.00 % <i>Panicum clandestinum</i> , Tioga	Deer Tongue, Tioga
6.00 % <i>Chasmanthium latifolium</i> , WV Ecotype	River Oats, WV Ecotype
5.50 % <i>Panicum rigidulum</i> , PA Ecotype	Redtop Panicgrass, PA Ecotype
0.70 % <i>Juncus effusus</i>	Soft Rush
0.70 % <i>Juncus tenuis</i> , PA Ecotype	Path Rush, PA Ecotype

**100.00 %**

**Seeding Rate:** 15 lb per acre with a cover crop. For sites that drain within 24 hours of a rain event use one of the following cover crops: Oats (1 Jan to 31 Jul; 30 lbs/acre), Japanese Millet (1 May to 31 Aug; 10 lbs/acre), or grain rye (1 Aug to 31 Dec; 30 lbs/acre).

Grasses & Grass-like Species - Herbaceous Perennial: Stormwater Management

Mix formulations are subject to change without notice depending on the availability of existing and new products. While the formula may change, the guiding philosophy and function of the mix will not.

**Ernst Conservation Seeds**  
8884 Mercer Pike  
Meadville, PA 16335  
(800) 873-3321 Fax (814) 336-5191  
[www.ernstseed.com](http://www.ernstseed.com)

Date: November 07, 2025

**Conservation Shade Mix - ERNMX-129**

Botanical Name	Common Name
30.00 % <i>Festuca rubra</i>	Creeping Red Fescue
30.00 % <i>Festuca rubra ssp. commutata</i>	Chewings Fescue
20.00 % <i>Lolium multiflorum</i>	Annual Rye grass
10.00 % <i>Poa pratensis, 'Baron'</i>	Kentucky Bluegrass, 'Baron'
10.00 % <i>Poa trivialis</i>	Rough Bluegrass

**100.00 %**

**Seeding Rate:** 100-200 lb per acre, or 3-5 lb per 1,000 sq ft

Grasses & Grass-like Species - Herbaceous Perennial: Lawn & Turfgrass Sites

While designed for deep-shaded areas, this mix requires at least 2 hours of sunlight daily. The fescues and bluegrasses are shade tolerant and blend very well together. Mix formulations are subject to change without notice depending on the availability of existing and new products. While the formula may change, the guiding philosophy and function of the mix will not.

**terra firma landscape architecture**  
163.a Court Street  
Portsmouth, NH

**Build America**  
1151 Sagamore Ave.  
Portsmouth, NH

163.a Court Street Portsmouth, NH 03801  
605.551.9109 | [terrence@terrafirmlandarch.com](mailto:terrence@terrafirmlandarch.com)

**Landscape Plan**

**Sheet Title**  
Landscape Plan

**Sheet No.**

**REVIEWED BY**  
L-1




**terra firma**  
landscape architecture

163-a Court Street Portsmouth, NH 03801  
603.531.9109 | terrence@terrafirmlandarch.com

**Build America**


1151 Sagamore Ave.  
Portsmouth, NH




**TREE PLANTING - 2"+ CAL.**  
SCALE: NTS

DO NOT FILL SOIL OVER TOP OF ROOT BALL  
CUT WIRE BASKET & REMOVE BURLAP AND WIRE ENTIRELY FROM ROOT BALL.  
3" BARK MULCH BED  
6 MIN. DIA. PLANT SAUCER  
SOIL MIX TO BE 3 PARTS EXISTING SCREENED LOAM WITH 1 PART AGED ORGANIC COMPOST.  
CLAY SOILS - USE A SAND MIXTURE  
NOTE:  
ADD MYCOR TREE W/ TERA SORB (1/2 PKG. PER UP TO 3' SHRUB  
1 PKG. PER 3' + SHRUB) OR EQUAL.  
2-3 TIMES ROOT BALL

1  
L-5



**SHRUB/GROUND COVER PLANTING DETAIL**  
SCALE: NTS




**GROUND COVER SPACING DETAIL**  
SCALE: NTS

NOTES:  
1. PLACE PLANTS IN BED AS SHOWN, SPACING AS SPECIFIED IN PLANT SCHEDULE.  
2. GROUNDCOVER SHALL BE TRIANGULAR SPACED IN ROWS PARALLEL TO STRAIGHT EDGES AND SHALL BE EVENLY SPACED IN ROWS PARALLEL TO CURVE EDGES.

APPLY 3" MIN. BARK MULCH  
REMOVE BURLAP AND WIRE FROM ENTIRE ROOT BALL.  
SOIL MIX TO BE 3 PARTS EXISTING SCREENED LOAM WITH 1 PART AGED ORGANIC COMPOST.  
CLAY SOILS - USE A SAND MIXTURE  
ADD BONE MEAL TO SOIL MIX  
ADD MYCOR TREE W/ TERA SORB (1/2 PKG. PER UP TO 3' SHRUB  
1 PKG. PER 3' + SHRUB) OR EQUAL.  
2-3 TIMES ROOT BALL

4  
L-5



NOTE: USE SOIL MIXTURE & EXCAVATE BEYOND BALL DIMENSIONS AS PER SPEC

APPLY 3" MIN. BARK MULCH  
CUT WIRE BASKET & REMOVE BURLAP AND WIRE ENTIRELY FROM ROOT BALL.  
SAUCERS TO BE 4" HIGH & 2' BEYOND SHRUB SPREAD

SOIL MIX TO BE 3 PARTS EXISTING SCREENED LOAM WITH 1 PART AGED ORGANIC COMPOST.  
CLAY SOILS - USE A SAND MIXTURE

NOTE:  
ADD MYCOR TREE W/ TERA SORB (1/2 PKG. PER UP TO 3' SHRUB  
1 PKG. PER 3' + SHRUB) OR EQUAL.

**PYRAMIDAL EVERGREEN TREE PLANTING**  
SCALE: NTS

2  
L-5

**LANDSCAPE NOTES:**

1. THE CONTRACTOR SHALL LOCATE AND VERIFY THE EXISTENCE OF ALL UTILITIES PRIOR TO STARTING WORK.
2. THE CONTRACTOR SHALL SUPPLY ALL PLANT MATERIALS IN QUANTITIES SUFFICIENT TO COMPLETE THE PLANTINGS SHOWN ON THE DRAWINGS.
3. ALL MATERIAL SHALL CONFORM TO THE GUIDELINES ESTABLISHED BY THE CURRENT AMERICAN STANDARD FOR NURSERY STOCK PUBLISHED BY THE AMERICAN ASSOCIATION OF NURSERYMEN.
4. ALL PLANT SUBSTITUTIONS MUST BE APPROVED BY THE LANDSCAPE ARCHITECT.
5. ALL PLANT MATERIALS SHALL BE EXACTLY AS SPECIFIED BY THE LANDSCAPE ARCHITECT. IF PLANT SPECIES CULTIVARS ARE FOUND TO VARY FROM THAT SPECIFIED AT ANY TIME DURING THE GUARANTEE PERIOD, THE LANDSCAPE ARCHITECT RESERVES THE RIGHT TO HAVE THE CONTRACTOR REPLACE THAT PLANT MATERIAL. THE LANDSCAPE ARCHITECT RESERVES THE RIGHT TO REJECT ANY PLANT DELIVERED TO THE SITE FOR AESTHETIC REASONS BEFORE PLANTING. THE LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR THE QUALITY FOR ALL THE PLANTS.
6. PLANTS SHALL BE SUBJECT TO INSPECTION AND APPROVAL AT THE PLACE OF GROWTH, UPON DELIVERY OR AT THE JOB SITE WHILE WORK IS ON-GOING TO CONFORMITY TO SPECIFIED QUALITY, SIZE AND VARIETY.
7. PLANTS FURNISHED IN CONTAINERS SHALL HAVE THE ROOTS WELL ESTABLISHED IN THE SOIL MASS AND SHALL HAVE AT LEAST ONE (1) GROWING SEASON. ROOT-BOUND PLANTS OR INADEQUATELY SIZED CONTAINERS TO SUPPORT THE PLANT MAY BE DEEMED UNACCEPTABLE.
8. NO PLANT SHALL BE PUT IN THE GROUND BEFORE GRADING HAS BEEN FINISHED AND APPROVED BY THE LANDSCAPE ARCHITECT.
9. ALL PLANTS SHALL BE INSTALLED AND DETAILED PER PROJECT SPECIFICATIONS.
10. ALL PLANTS SHALL BE WATERED THOROUGHLY TWICE DURING THE FIRST 24-HOUR PERIOD AFTER PLANTING. ALL PLANTS SHALL BE WATERED WEEKLY, OR MORE OFTEN IF NECESSARY, DURING THE FIRST GROWING SEASON.
11. ALL PLANTS SHALL BE GUARANTEED BY THE CONTRACTOR FOR NOT LESS THAN ONE FULL YEAR FROM THE TIME OF PROVISIONAL ACCEPTANCE. DURING THIS TIME, THE OWNER SHALL MAINTAIN ALL PLANT MATERIALS IN THE ABOVE MANNER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO INSPECT THE PLANTS TO ENSURE PROPER CARE. IF THE CONTRACTOR IS DISSATISFIED WITH THE CARE GIVEN, HE SHALL IMMEDIATELY, AND IN SUFFICIENT TIME TO PERMIT THE CONDITION TO BE RECTIFIED, NOTIFY THE LANDSCAPE ARCHITECT IN WRITING OR OTHERWISE FORFEIT HIS CLAIM. LANDSCAPE CONTRACTOR SHALL PRUNE PLANTINGS OF DEAD LIMBS OR TWIGS DURING THE FIRST YEAR OF GROWTH.
12. FINAL ACCEPTANCE BY THE LANDSCAPE ARCHITECT WILL BE MADE UPON THE CONTRACTOR'S REQUEST AFTER ALL CORRECTIVE WORK HAS BEEN COMPLETED.
13. LANDSCAPE CONTRACTOR SHOULD REPLACE DEAD PLANTINGS IMMEDIATELY UPON OWNER DIRECTION WITHIN THE WARRANTY PERIOD AND AGAIN AT THE END OF THE GUARANTEE PERIOD. THE CONTRACTOR SHALL HAVE REPLACED ANY PLANT MATERIAL THAT IS MISSING, NOT TRUE TO SIZE AS SPECIFIED, THAT HAVE DIED, THAT HAVE LOST THEIR NATURAL SHAPE DUE TO DEAD BRANCHES, EXCESSIVE PRUNING OR INADEQUATE OR IMPROPER CARE, OR THAT ARE, IN THE OPINION OF THE LANDSCAPE ARCHITECT, IN UNHEALTHY OR UNSIGHTLY CONDITION.
14. ALL LANDSCAPE AREAS TO BE GRASS COMMON TO REGION EXCEPT FOR INTERIOR LANDSCAPED ISLANDS OR WHERE OTHER PLANT MATERIAL IS CALLED FOR.
15. ALL TREES AND SHRUBS TO BE PLANTED IN MULCH BEDS WITH DEFINED AND CUT EDGES TO SEPARATE TURF GRASS AREAS.
16. FOR ANY LANDSCAPE AREA SO DESIGNATED TO REMAIN, WHETHER ON OR OFF-SITE, REMOVE WEEDS, ROCKS, CONSTRUCTION ITEMS, ETC., THEN APPLY GRASS SEED OR PINE BARK MULCH AS DEPICTED ON PLANS.
17. LANDSCAPE CONTRACTOR SHALL FEED AND PRUNE EX. TREES, OR JUST OFF SITE, THAT HAVE EXPERIENCED ROOT BASE INTRUSION OR DAMAGE DURING CONSTRUCTION IMMEDIATELY AND FOR THE DURATION OF THE WARRANTY PERIOD AT THE DIRECTION OF THE LANDSCAPE ARCHITECT.
18. EXISTING TREES TO REMAIN SHALL BE PROTECTED WITH TEMPORARY SNOW FENCING AT THE EDGE OF THE EX. TREE CANOPY THE CONTRACTOR SHALL NOT STORE VEHICLES OR MATERIALS WITHIN THE LANDSCAPED AREAS. ANY DAMAGE TO EXISTING TREES, SHRUBS OR LAWN SHALL BE REPAIRED BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
19. ALL MULCH AREAS SHALL RECEIVE A 2" LAYER OF SHREDDED PINE BARK MULCH.
20. ALL WORK SHALL BE DONE IN STRICT ACCORDANCE WITH PROJECT SPECIFICATIONS.

PLEASE NOTE: THIS SHEET IS SCALED FOR 22 BY 34 PAPER, DO NOT REDUCE OR ENLARGE.



Condominium Association Documents are not yet available but will be provided prior to final approval.



HALEY WARD.®

## STORMWATER MANAGEMENT AND EROSION CONTROL PLAN

TO THE CITY OF PORTSMOUTH  
FOR 1151 SAGAMORE AVENUE

Map 224, Lot 19 | Portsmouth, NH

**APPLICANT:**

**1151 Sagamore Avenue CBC LLC**  
76 State Street, Newburyport, ME 01950



December 22, 2025  
JN: 5010314.002

---

**REPORT PREPARED BY:**

**Haley Ward, Inc.**

200 Griffin Road, Unit 14 | Portsmouth, NH 03801



## EXECUTIVE SUMMARY

This drainage analysis examines the pre-development (existing) and post-development (proposed) stormwater drainage patterns for the proposed residential redevelopment project at 1151 Sagamore Avenue in Portsmouth, NH. The site is shown on the City of Portsmouth Assessor's Tax Map 224 as Lot 19. The project proposes to replace an existing building with four (4) single family condominiums. The total size of the lot is 30,191 square-feet (0.69 acres). The size of the total drainage area is 38,239 square-feet (2.90 acres).

The development will provide for the construction of four (4) standalone condominium units, with associated landscaping, utilities, and driveways. The new buildings will be serviced by public water and sewer. The development has the potential to increase stormwater runoff to adjacent properties and therefore must be designed in a manner to prevent that occurrence. This will be done primarily by capturing stormwater runoff and routing it through appropriate stormwater facilities, designed to ensure that there will be no significant increase in peak runoff from the site as a result of this project.

The hydrologic modeling utilized for this analysis uses the "Extreme Precipitation" values for rainfall from The Northeast Regional Climate Center (Cornell University), with a 15% increase to comply with local ordinance.

## INTRODUCTION / PROJECT DESCRIPTION

This drainage report is designed to assist the owner, planning board, contractor, regulatory reviewer, and others in understanding the impact of the proposed development project on local surface water runoff and quality. The project site is shown on the City of Portsmouth, NH Assessor's Tax Map 224 as Lot 19. Bounding the site to north is Wentworth Road. Bounding the site to east is Sagamore Avenue. Bounding the site to south is a condominium complex. Bounding the site to the west is a City owned conservation land.

The property is situated in the Mixed Residential Office Zone. A vicinity map is included in the Appendix to this report. The proposed building replacement will demolish an existing building and associated driveway.

This report includes information about the existing site necessary to analyze stormwater runoff and to design any required mitigation. The report includes maps of pre-development and post-development watersheds, subcatchment areas and



calculations of runoff. The report will provide a narrative of the stormwater runoff and describe numerically and graphically the surface water runoff patterns for this site. Proposed stormwater management and treatment structures and methods will also be described, as well as erosion and sediment control practices. To fully understand the proposed site development the reader should also review a complete site plan set in addition to this report.

## METHODOLOGY

“Extreme Precipitation” values from The Northeast Regional Climate Center (Cornell University) have been used for modeling purposes. These values have been used in this analysis, with a 15% addition to comply with local ordinances.

This report uses the US Soil Conservation Service (SCS) Method for estimating stormwater runoff. The SCS method is published in The National Engineering Handbook (NEH), Section 4 “Hydrology” and includes the Technical Release No. 20, (TR-20) “Computer Program for Project Formulation Hydrology”, and Technical Release No. 55 (TR-55) “Urban Hydrology for Small Watersheds” methods. This report uses the HydroCAD version 10.20 program, written by HydroCAD Software Solutions LLC, Chocorua, N.H., to apply these methods for the calculation of runoff and for pond modeling. Rainfall data and runoff curve numbers are taken from “The Stormwater Management and Erosion Control Handbook for Urban and Developing Areas in New Hampshire.”

Time of Concentration (Tc) is calculated by entering measured flow path data such as flow path type, length, slope and surface characteristics into the HydroCAD program. For the purposes of this report, a minimum time of concentration of 5 minutes is used.

The storm events used for the calculations in this report are the 2-year, 10-year, 25-year, and 50-year (24-hour) storms. Watershed basin boundaries have been delineated using topographic maps prepared by Haley Ward and field observations to confirm.

## SITE SPECIFIC INFORMATION

Based on the United States Department of Agriculture (USDA) Natural Resources Conservation Service (NRCS), Soil Survey of Rockingham County, New Hampshire the site is made up of one soil type:

Soil Symbol	Soil Name and Slopes
140B	Chatfield-Hollis-Canton complex (0-8% slopes), rocky



**Chatfield-Hollis-Canton complex** is well drained with a stated depth to restrictive feature of 20-41 inches.

One test pit was dug on the site in the location of the proposed Rain Garden. A restrictive ledge layer was identified at 41-inches. There was no observed water table. The soil is described as fine, sandy loam, granular, friable, fill.

The physical characteristics of the site consist of flat (0-8%) grades that generally slope downward from the south to the north of the lot. Elevations on the site range from 30 to 35 feet above sea level. The existing site is developed and includes an existing building located in the front of the lot, with an asphalt driveway. Vegetation around the developed portion of the lot consists of established grasses, shrubs, and trees.

There are no protected natural resources on or directly adjacent to the subject property.

According to the Federal Emergency Management Agency (FEMA) Flood Insurance Rate Map (FIRM) number 33015C0286F (effective date January 29, 2021), the project site is located in Zone X and is determined to be outside of the 0.2% annual chance floodplain. A copy of the FIRM map is included in the Appendix.

## **CONSTRUCTION TIMING**

Development of the site has been ongoing throughout 2025; completed activities include blasting/excavation to bring the site to foundation grade, and the existing home has already been demolished. Construction of the proposed development is anticipated to begin in Spring 2026, pending receipt of required land use permits. Prior to further earth moving activities, the site will be stabilized via the proposed erosion control devices as shown on the Site Plan. These devices will not be removed until the site has been stabilized via permanent vegetation, which is expected to occur in Fall/Winter 2026.

## **LOW-IMPACT DEVELOPMENT STATEMENT**

The proposed developed utilized Low-Impact Development to the greatest extent practical. Primarily, runoff generated from the proposed driveway and building roofs is directed to a Rain Garden which has been designed per the New Hampshire Stormwater Manual. Impervious areas have been minimized by including garages within the proposed buildings, eliminating the need for additional outdoor parking spaces.



## **BUFFERS, SETBACKS, EXISTING FEATURES**

The site will adhere to the applicable setbacks found within the City zoning ordinance. There are no setbacks related to protected natural resources. The site is not within a mapped floodplain. There are mature trees between the subject parcel and the abutting property to the south which will be protected as deemed practical. There are no known water quality concerns associated with this site.

## **WASTE**

The majority of the site preparation, including demolition of the existing building, has already been completed at the time of this application's submission. Additional construction debris will be collected in a dumpster and will be disposed of off-site by a licensed hauler. Solid waste and wastewater generated by the proposed residential units will be handled via public systems.

## **PRE-DEVELOPMENT DRAINAGE**

In the pre-development condition, the site has been analyzed as four (4) subcatchment watershed basins based on localized topography and discharge location. A Pre-Development Hydrology map and HydroCAD model results have been provided.

Subcatchment 1 (1S) represents the area to the north of the Site, including undeveloped wooded area and a portion of Wentworth Road. This area drains towards the center of the site and ultimately discharges to the southwest (Summation Point 1, SP1.)

Subcatchment 2 (2S) represents the front of the lot, including developed lawn area, the existing building, and existing driveway, as well as a portion of the abutting condominium site to the south. This area drains to the northeast corner of the site (Summation Point 2, SP2)

Subcatchment 3 (3S) represents the existing condominium site to the south. This area drains to an existing rain garden system, which outlets to SP 1. This area will not be altered by the proposed development.

Subcatchment 4 (4S) represents the existing condominium site to the south. This area drains to the southwest, Summation Point 3 (SP3.) This area will not be altered by the proposed development.



## POST-DEVELOPMENT DRAINAGE

The proposed development has been designed to match the pre-development drainage patterns to the greatest extent feasible. In the post-development condition, the site has been analyzed as nine (9) subcatchment basins. A Post-Development Hydrology map and HydroCAD model results have been provided.

Subcatchment 1 (1S) continues to represent the area to the north of the site. This drainage area will be intercepted by a French drain proposed to be located on the north side of the proposed buildings. This drain will direct runoff around the buildings to Summation Point 1. This drain has been sized to accommodate the 10-year storm event.

Subcatchment 2 (2S) continues to represent the front of the lot. Runoff in this area will continue to be directed to the northeast corner of the lot, Summation Point 2.

Subcatchments 3 and 4 (3S and 4S) continue to represent the abutting condominium property to the south. Flow patterns from these areas will not be altered by this development.

Subcatchment 5 (5S) represents the proposed driveway and landscaped areas. Runoff within this subcatchment will be directed as overland flow to a proposed rain garden at the rear of the site. This rain garden will release controlled flow to Summation Point 1.

Subcatchments 6,7,8, and 9 (6S, 7S, 8S, 9S) represent the roof areas of the four proposed buildings. Units 3 and 4 (6S and 7S) will be equipped with gutters and downspouts which will direct their runoff to the proposed rain garden. Units 1 and 2 (8S and 9S) will also have gutters and downspouts but will discharge to the French drain at the rear of the buildings. These areas all ultimately discharge to Summation Point 1.

## RUNOFF COMPARISON

**Table 1: Pre-Development to Post-Development Comparison**

<b>Design Point</b>	<b>Q2 (CFS)</b>		<b>Q10 (CFS)</b>		<b>Q50 (CFS)</b>		<b>Description</b>
	<b>Pre</b>	<b>Post</b>	<b>Pre</b>	<b>Post</b>	<b>Pre</b>	<b>Post</b>	
<b>SP1</b>	1.20	1.71	3.82	4.48	8.63	9.47	Southwest corner of property
<b>SP2</b>	1.01	0.94	2.14	1.90	4.02	3.46	Northeast corner of property/Sagamore Ave
<b>SP3</b>	0.04	0.04	0.13	0.13	0.30	0.30	Southwest corner of southern abutting property



As shown in Table 1, post-development runoff rates are similar to those observed under pre-development conditions. These rates have been reduced for flows directed towards Sagamore Avenue and are unchanged for those on the abutting lot to the south. Summation Point 1 represents discharge to the City-owned conservation area to the west. Runoff rates for this analysis point are shown to increase by less than 1 cfs, which is considered insignificant and not expected to create adverse impacts on downstream properties. It is unlikely that this abutting land will be developed due to its conservation designation, and so a <1 cfs increase will not have a detrimental impact on the existing wooded environment.

## OFFSITE INFRASTRUCTURE CAPACITY

There is no Town infrastructure utilized in this project in regard to storm drainage. All retention and routing to the final destination of the stormwater is done on-site, therefore no impact to city infrastructure is anticipated.

## EROSION AND SEDIMENT CONTROL PRACTICES

The erosion potential for this site as it exists is moderate due to the presence of soils that are highly erodible. During construction, the major potential for erosion is wind and stormwater runoff. The contractor will be required to inspect and maintain all necessary erosion control measures, as well as installing any additional measures as required. All erosion control practices shall conform to "The Stormwater Management and Erosion Control Handbook for Urban and Developing Areas in New Hampshire." Some examples of erosion and sediment control measures to be utilized for this project during construction may include:

- Silt Soxx (or approved alternative) located at the toe of disturbed slopes
- Stabilized construction entrance at access point to the site
- Temporary mulching and seeding for disturbed areas
- Spraying water over disturbed areas to minimize wind erosion

After construction, permanent stabilization will be accomplished by permanent seeding, landscaping, and surfacing the access drives and parking areas with asphalt paving and other areas with impervious walkways.



## CONCLUSION

The proposed development has been designed to match the pre-development drainage patterns to the greatest extent feasible. With the design of the rain garden, the post- development runoff rates are effectively equivalent to the pre-development runoff rates. Erosion and sediment control practices will be implemented for both the temporary condition during construction and for final stabilization after construction. Therefore, there are no negative impacts to downstream receptors or adjacent properties anticipated as a result of this project.

## REFERENCES

1. Comprehensive Environmental Inc. and New Hampshire Department of Environmental Services. *New Hampshire Stormwater Manual (Volumes 1, 2 and 3)*, December 2008 (Revision 1.0).
2. Minnick, E.L. and H.T. Marshall. *Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire*, prepared by Rockingham County Conservation District, prepared for New Hampshire Department of Environmental Services, in cooperation with USDA Soil Conservation Service, August 1992.
3. HydroCAD Software Solution, LLC. *HydroCAD Stormwater Modeling System Version 10.20* copyright 2013.

**Property Information**

Property ID 0224-0019-0000  
Location 1151 SAGAMORE AVE  
Owner 1151 SAGAMORE AVENUE CBC LLC



**MAP FOR REFERENCE ONLY  
NOT A LEGAL DOCUMENT**

City of Portsmouth, NH makes no claims and no warranties, expressed or implied, concerning the validity or accuracy of the GIS data presented on this map.

Geometry updated 10/23/2025

Print map scale is approximate.  
Critical layout or measurement  
activities should not be done using  
this resource.

# Extreme Precipitation Tables

## Northeast Regional Climate Center

Data represents point estimates calculated from partial duration series. All precipitation amounts are displayed in inches.

Metadata for Point	
Smoothing	Yes
State	
Location	
Latitude	43.052 degrees North
Longitude	70.748 degrees West
Elevation	10 feet
Date/Time	Fri Aug 25 2023 11:03:42 GMT-0400 (Eastern Daylight Time)

### Extreme Precipitation Estimates




	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
<b>1yr</b>	0.26	0.40	0.50	0.65	0.82	1.04	<b>1yr</b>	0.70	0.98	1.21	1.56	2.03	2.67	2.94	<b>1yr</b>	2.36	2.82	3.24	3.96	4.57	<b>1yr</b>
<b>2yr</b>	0.32	0.50	0.62	0.82	1.03	1.30	<b>2yr</b>	0.89	1.18	1.52	1.94	2.49	3.22	3.58	<b>2yr</b>	2.85	3.45	3.95	4.70	5.35	<b>2yr</b>
<b>5yr</b>	0.37	0.58	0.73	0.98	1.25	1.61	<b>5yr</b>	1.08	1.47	1.89	2.44	3.15	4.08	4.60	<b>5yr</b>	3.61	4.42	5.07	5.96	6.73	<b>5yr</b>
<b>10yr</b>	0.41	0.65	0.82	1.12	1.46	1.90	<b>10yr</b>	1.26	1.73	2.24	2.91	3.76	4.88	5.55	<b>10yr</b>	4.32	5.34	6.12	7.14	8.01	<b>10yr</b>
<b>25yr</b>	0.48	0.77	0.97	1.34	1.78	2.35	<b>25yr</b>	1.54	2.15	2.79	3.65	4.76	6.19	7.13	<b>25yr</b>	5.48	6.85	7.85	9.07	10.09	<b>25yr</b>
<b>50yr</b>	0.54	0.87	1.11	1.55	2.09	2.78	<b>50yr</b>	1.80	2.54	3.31	4.35	5.69	7.42	8.62	<b>50yr</b>	6.56	8.29	9.48	10.87	12.02	<b>50yr</b>
<b>100yr</b>	0.60	0.98	1.26	1.79	2.44	3.28	<b>100yr</b>	2.10	3.00	3.93	5.19	6.80	8.88	10.42	<b>100yr</b>	7.86	10.02	11.46	13.03	14.33	<b>100yr</b>
<b>200yr</b>	0.68	1.11	1.44	2.07	2.85	3.87	<b>200yr</b>	2.46	3.54	4.66	6.17	8.12	10.65	12.60	<b>200yr</b>	9.42	12.11	13.85	15.63	17.08	<b>200yr</b>
<b>500yr</b>	0.81	1.33	1.73	2.51	3.52	4.81	<b>500yr</b>	3.03	4.42	5.82	7.76	10.28	13.53	16.20	<b>500yr</b>	11.97	15.58	17.81	19.89	21.57	<b>500yr</b>

### Lower Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
<b>1yr</b>	0.23	0.36	0.44	0.59	0.72	0.88	<b>1yr</b>	0.62	0.86	0.93	1.34	1.69	2.26	2.50	<b>1yr</b>	2.00	2.41	2.88	3.21	3.94	<b>1yr</b>
<b>2yr</b>	0.31	0.49	0.60	0.81	1.00	1.19	<b>2yr</b>	0.86	1.16	1.37	1.81	2.33	3.07	3.47	<b>2yr</b>	2.72	3.33	3.84	4.56	5.11	<b>2yr</b>
<b>5yr</b>	0.35	0.54	0.67	0.92	1.17	1.40	<b>5yr</b>	1.01	1.37	1.61	2.11	2.72	3.80	4.20	<b>5yr</b>	3.36	4.04	4.74	5.56	6.26	<b>5yr</b>
<b>10yr</b>	0.39	0.59	0.74	1.03	1.33	1.60	<b>10yr</b>	1.15	1.57	1.80	2.38	3.05	4.38	4.88	<b>10yr</b>	3.88	4.69	5.47	6.44	7.22	<b>10yr</b>
<b>25yr</b>	0.44	0.67	0.83	1.19	1.56	1.90	<b>25yr</b>	1.35	1.86	2.10	2.74	3.52	4.78	5.91	<b>25yr</b>	4.23	5.68	6.69	7.83	8.72	<b>25yr</b>
<b>50yr</b>	0.48	0.73	0.91	1.31	1.77	2.17	<b>50yr</b>	1.53	2.12	2.35	3.05	3.91	5.41	6.82	<b>50yr</b>	4.79	6.56	7.77	9.10	10.06	<b>50yr</b>
<b>100yr</b>	0.54	0.81	1.02	1.47	2.02	2.47	<b>100yr</b>	1.74	2.41	2.63	3.39	4.31	6.10	7.87	<b>100yr</b>	5.40	7.57	9.04	10.58	11.63	<b>100yr</b>
<b>200yr</b>	0.59	0.89	1.13	1.64	2.28	2.81	<b>200yr</b>	1.97	2.75	2.94	3.74	4.74	6.86	9.09	<b>200yr</b>	6.07	8.74	10.50	12.32	13.45	<b>200yr</b>
<b>500yr</b>	0.69	1.02	1.31	1.91	2.72	3.36	<b>500yr</b>	2.34	3.29	3.42	4.26	5.39	8.01	10.98	<b>500yr</b>	7.09	10.56	12.80	15.09	16.30	<b>500yr</b>

### Upper Confidence Limits

	5min	10min	15min	30min	60min	120min		1hr	2hr	3hr	6hr	12hr	24hr	48hr		1day	2day	4day	7day	10day	
<b>1yr</b>	0.29	0.44	0.54	0.72	0.89	1.09	<b>1yr</b>	0.77	1.06	1.26	1.74	2.20	2.98	3.18	<b>1yr</b>	2.64	3.06	3.59	4.38	5.05	<b>1yr</b>
<b>2yr</b>	0.34	0.52	0.64	0.87	1.07	1.27	<b>2yr</b>	0.92	1.24	1.48	1.96	2.52	3.43	3.72	<b>2yr</b>	3.03	3.58	4.11	4.86	5.64	<b>2yr</b>
<b>5yr</b>	0.40	0.62	0.77	1.05	1.34	1.63	<b>5yr</b>	1.16	1.59	1.89	2.54	3.26	4.36	4.98	<b>5yr</b>	3.85	4.79	5.40	6.40	7.18	<b>5yr</b>
<b>10yr</b>	0.47	0.72	0.89	1.25	1.62	1.99	<b>10yr</b>	1.39	1.94	2.29	3.11	3.97	5.36	6.23	<b>10yr</b>	4.74	5.99	6.85	7.87	8.79	<b>10yr</b>
<b>25yr</b>	0.58	0.88	1.10	1.57	2.06	2.59	<b>25yr</b>	1.78	2.53	2.97	4.08	5.18	7.75	8.38	<b>25yr</b>	6.86	8.05	9.20	10.38	11.45	<b>25yr</b>
<b>50yr</b>	0.68	1.03	1.28	1.84	2.48	3.15	<b>50yr</b>	2.14	3.08	3.61	5.02	6.36	9.69	10.50	<b>50yr</b>	8.57	10.10	11.51	12.78	14.01	<b>50yr</b>
<b>100yr</b>	0.80	1.20	1.51	2.18	2.99	3.84	<b>100yr</b>	2.58	3.76	4.40	6.19	7.83	12.11	13.16	<b>100yr</b>	10.71	12.65	14.40	15.76	17.15	<b>100yr</b>
<b>200yr</b>	0.93	1.41	1.78	2.58	3.60	4.70	<b>200yr</b>	3.10	4.59	5.37	7.63	9.63	15.17	16.51	<b>200yr</b>	13.43	15.87	18.04	19.43	20.98	<b>200yr</b>
<b>500yr</b>	1.16	1.73	2.22	3.23	4.59	6.11	<b>500yr</b>	3.96	5.97	6.97	10.10	12.71	20.46	22.28	<b>500yr</b>	18.11	21.43	24.31	25.62	27.41	<b>500yr</b>



**Routing Diagram for Pre Development**  
Prepared by Haley Ward, Printed 12/16/2025  
HydroCAD® 10.20-7a s/n 00641 © 2025 HydroCAD Software Solutions LLC

Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=78,380 sf 5.34% Impervious Runoff Depth>0.53" Flow Length=375' Tc=9.1 min CN=58 Runoff=0.65 cfs 0.080 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=27,769 sf 34.95% Impervious Runoff Depth>1.38" Tc=5.0 min CN=74 Runoff=1.01 cfs 0.073 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=17,344 sf 56.79% Impervious Runoff Depth>1.95" Tc=5.0 min CN=82 Runoff=0.91 cfs 0.065 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>0.66" Tc=5.0 min CN=61 Runoff=0.04 cfs 0.004 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=1.01 cfs 0.073 af Outflow=1.01 cfs 0.073 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=1.20 cfs 0.133 af Outflow=1.20 cfs 0.133 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.04 cfs 0.004 af Outflow=0.04 cfs 0.004 af
<b>Pond 1P: Rain Garden</b>	Peak Elev=31.43' Storage=830 cf Inflow=0.91 cfs 0.065 af Outflow=0.56 cfs 0.053 af

**Total Runoff Area = 2.902 ac Runoff Volume = 0.221 af Average Runoff Depth = 0.92"**  
**81.22% Pervious = 2.357 ac 18.78% Impervious = 0.545 ac**


**Summary for Subcatchment 1S: SUBCATCHMENT 1**


Runoff = 0.65 cfs @ 12.17 hrs, Volume= 0.080 af, Depth> 0.53"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
65,963	55	Woods, Good, HSG B
8,235	61	>75% Grass cover, Good, HSG B
*	4,182	IMPERVIOUS
78,380	58	Weighted Average
74,198		94.66% Pervious Area
4,182		5.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.2	150	0.0200	2.12		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
9.1	375	Total			



**Subcatchment 1S: SUBCATCHMENT 1**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 1.01 cfs @ 12.08 hrs, Volume= 0.073 af, Depth> 1.38"  
Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
18,063	61	>75% Grass cover, Good, HSG B
*	9,706	IMPERVIOUS
27,769	74	Weighted Average
18,063		65.05% Pervious Area
9,706		34.95% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph




**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 0.91 cfs @ 12.08 hrs, Volume= 0.065 af, Depth> 1.95"  
 Routed to Pond 1P : Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
7,494	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
17,344	82	Weighted Average
7,494		43.21% Pervious Area
9,850		56.79% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3**

**Summary for Subcatchment 4S: SUBCATCHMENT 4**


Runoff = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af, Depth> 0.66"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
2,922	61	>75% Grass cover, Good, HSG B
2,922		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				0.04	Direct Entry,

**Subcatchment 4S: SUBCATCHMENT 4**


**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.637 ac, 34.95% Impervious, Inflow Depth > 1.38" for 2-yr event

Inflow = 1.01 cfs @ 12.08 hrs, Volume= 0.073 af

Outflow = 1.01 cfs @ 12.08 hrs, Volume= 0.073 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2****Hydrograph**

**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.198 ac, 14.66% Impervious, Inflow Depth > 0.73" for 2-yr event


Inflow = 1.20 cfs @ 12.18 hrs, Volume= 0.133 af

Outflow = 1.20 cfs @ 12.18 hrs, Volume= 0.133 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1**

Hydrograph




**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth &gt; 0.66" for 2-yr event

Inflow = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af

Outflow = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3****Hydrograph**

## Summary for Pond 1P: Rain Garden

Inflow Area = 0.398 ac, 56.79% Impervious, Inflow Depth > 1.95" for 2-yr event

Inflow = 0.91 cfs @ 12.08 hrs, Volume= 0.065 af

Outflow = 0.56 cfs @ 12.19 hrs, Volume= 0.053 af, Atten= 38%, Lag= 6.7 min

Primary = 0.56 cfs @ 12.19 hrs, Volume= 0.053 af

Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

Peak Elev= 31.43' @ 12.19 hrs Surf.Area= 907 sf Storage= 830 cf

Plug-Flow detention time= 115.8 min calculated for 0.053 af (82% of inflow)

Center-of-Mass det. time= 43.3 min ( 871.3 - 828.0 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00

**Primary OutFlow** Max=0.56 cfs @ 12.19 hrs HW=31.43' (Free Discharge)

↑ 1=Culvert (Passes 0.56 cfs of 0.73 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 0.56 cfs @ 2.15 fps)



**Pond 1P: Rain Garden****Hydrograph**

Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=78,380 sf 5.34% Impervious Runoff Depth>1.52" Flow Length=375' Tc=9.1 min CN=58 Runoff=2.57 cfs 0.227 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=27,769 sf 34.95% Impervious Runoff Depth>2.86" Tc=5.0 min CN=74 Runoff=2.14 cfs 0.152 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=17,344 sf 56.79% Impervious Runoff Depth>3.63" Tc=5.0 min CN=82 Runoff=1.69 cfs 0.120 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>1.75" Tc=5.0 min CN=61 Runoff=0.13 cfs 0.010 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=2.14 cfs 0.152 af Outflow=2.14 cfs 0.152 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=3.82 cfs 0.336 af Outflow=3.82 cfs 0.336 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.13 cfs 0.010 af Outflow=0.13 cfs 0.010 af
<b>Pond 1P: Rain Garden</b>	Peak Elev=31.74' Storage=1,124 cf Inflow=1.69 cfs 0.120 af Outflow=1.26 cfs 0.109 af

**Total Runoff Area = 2.902 ac Runoff Volume = 0.509 af Average Runoff Depth = 2.11"**  
**81.22% Pervious = 2.357 ac 18.78% Impervious = 0.545 ac**


## Summary for Subcatchment 1S: SUBCATCHMENT 1


Runoff = 2.57 cfs @ 12.15 hrs, Volume= 0.227 af, Depth> 1.52"  
 Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
65,963	55	Woods, Good, HSG B
8,235	61	>75% Grass cover, Good, HSG B
*	4,182	IMPERVIOUS
78,380	58	Weighted Average
74,198		94.66% Pervious Area
4,182		5.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.2	150	0.0200	2.12		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
9.1	375	Total			



**Subcatchment 1S: SUBCATCHMENT 1**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 2.14 cfs @ 12.08 hrs, Volume= 0.152 af, Depth> 2.86"  
 Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
18,063	61	>75% Grass cover, Good, HSG B
*	9,706	IMPERVIOUS
27,769	74	Weighted Average
18,063		65.05% Pervious Area
9,706		34.95% Impervious Area

Tc	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph



**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 1.69 cfs @ 12.07 hrs, Volume= 0.120 af, Depth> 3.63"  
 Routed to Pond 1P : Rain Garden


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
7,494	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
17,344	82	Weighted Average
7,494		43.21% Pervious Area
9,850		56.79% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3**

Hydrograph




**Summary for Subcatchment 4S: SUBCATCHMENT 4**

Runoff = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af, Depth> 1.75"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description			
2,922	61	>75% Grass cover, Good, HSG B			
2,922		100.00% Pervious Area			
Tc	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0	Direct Entry,				

**Subcatchment 4S: SUBCATCHMENT 4**


**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.637 ac, 34.95% Impervious, Inflow Depth > 2.86" for 10-yr event

Inflow = 2.14 cfs @ 12.08 hrs, Volume= 0.152 af

Outflow = 2.14 cfs @ 12.08 hrs, Volume= 0.152 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2****Hydrograph**


**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.198 ac, 14.66% Impervious, Inflow Depth > 1.83" for 10-yr event

Inflow = 3.82 cfs @ 12.15 hrs, Volume= 0.336 af

Outflow = 3.82 cfs @ 12.15 hrs, Volume= 0.336 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1****Hydrograph**


**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth > 1.75" for 10-yr event

Inflow = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af

Outflow = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3****Hydrograph**

## Summary for Pond 1P: Rain Garden

Inflow Area = 0.398 ac, 56.79% Impervious, Inflow Depth > 3.63" for 10-yr event  
 Inflow = 1.69 cfs @ 12.07 hrs, Volume= 0.120 af  
 Outflow = 1.26 cfs @ 12.15 hrs, Volume= 0.109 af, Atten= 26%, Lag= 4.7 min  
 Primary = 1.26 cfs @ 12.15 hrs, Volume= 0.109 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 31.74' @ 12.15 hrs Surf.Area= 1,001 sf Storage= 1,124 cf

Plug-Flow detention time= 78.7 min calculated for 0.109 af (90% of inflow)  
 Center-of-Mass det. time= 31.5 min ( 841.7 - 810.3 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00

**Primary OutFlow** Max=1.25 cfs @ 12.15 hrs HW=31.74' (Free Discharge)

↑ 1=Culvert (Passes 1.25 cfs of 1.82 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 1.25 cfs @ 2.82 fps)



**Pond 1P: Rain Garden****Hydrograph**

Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=78,380 sf 5.34% Impervious Runoff Depth>3.50" Flow Length=375' Tc=9.1 min CN=58 Runoff=6.41 cfs 0.524 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=27,769 sf 34.95% Impervious Runoff Depth>5.40" Tc=5.0 min CN=74 Runoff=4.02 cfs 0.287 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=17,344 sf 56.79% Impervious Runoff Depth>6.36" Tc=5.0 min CN=82 Runoff=2.91 cfs 0.211 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>3.85" Tc=5.0 min CN=61 Runoff=0.30 cfs 0.022 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=4.02 cfs 0.287 af Outflow=4.02 cfs 0.287 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=8.63 cfs 0.723 af Outflow=8.63 cfs 0.723 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.30 cfs 0.022 af Outflow=0.30 cfs 0.022 af
<b>Pond 1P: Rain Garden</b>	Peak Elev=32.09' Storage=1,488 cf Inflow=2.91 cfs 0.211 af Outflow=2.23 cfs 0.199 af

**Total Runoff Area = 2.902 ac Runoff Volume = 1.043 af Average Runoff Depth = 4.31"**  
**81.22% Pervious = 2.357 ac 18.78% Impervious = 0.545 ac**


## Summary for Subcatchment 1S: SUBCATCHMENT 1


Runoff = 6.41 cfs @ 12.14 hrs, Volume= 0.524 af, Depth> 3.50"  
 Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
65,963	55	Woods, Good, HSG B
8,235	61	>75% Grass cover, Good, HSG B
*	4,182	IMPERVIOUS
78,380	58	Weighted Average
74,198		94.66% Pervious Area
4,182		5.34% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.2	150	0.0200	2.12		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
9.1	375	Total			



**Subcatchment 1S: SUBCATCHMENT 1****Hydrograph**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 4.02 cfs @ 12.08 hrs, Volume= 0.287 af, Depth> 5.40"  
Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
18,063	61	>75% Grass cover, Good, HSG B
*	9,706	IMPERVIOUS
27,769	74	Weighted Average
18,063		65.05% Pervious Area
9,706		34.95% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph



**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 2.91 cfs @ 12.07 hrs, Volume= 0.211 af, Depth> 6.36"  
Routed to Pond 1P : Rain Garden


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
7,494	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
17,344	82	Weighted Average
7,494		43.21% Pervious Area
9,850		56.79% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3**

Hydrograph



**Summary for Subcatchment 4S: SUBCATCHMENT 4**


Runoff = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af, Depth> 3.85"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
2,922	61	>75% Grass cover, Good, HSG B
2,922		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				0.30	Direct Entry,

**Subcatchment 4S: SUBCATCHMENT 4**


**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.637 ac, 34.95% Impervious, Inflow Depth > 5.40" for 50-yr event

Inflow = 4.02 cfs @ 12.08 hrs, Volume= 0.287 af

Outflow = 4.02 cfs @ 12.08 hrs, Volume= 0.287 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2****Hydrograph**


**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.198 ac, 14.66% Impervious, Inflow Depth > 3.95" for 50-yr event

Inflow = 8.63 cfs @ 12.14 hrs, Volume= 0.723 af

Outflow = 8.63 cfs @ 12.14 hrs, Volume= 0.723 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1****Hydrograph**


**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth > 3.85" for 50-yr event

Inflow = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af

Outflow = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3****Hydrograph**

## Summary for Pond 1P: Rain Garden

Inflow Area = 0.398 ac, 56.79% Impervious, Inflow Depth > 6.36" for 50-yr event  
 Inflow = 2.91 cfs @ 12.07 hrs, Volume= 0.211 af  
 Outflow = 2.23 cfs @ 12.15 hrs, Volume= 0.199 af, Atten= 23%, Lag= 4.3 min  
 Primary = 2.23 cfs @ 12.15 hrs, Volume= 0.199 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 32.09' @ 12.15 hrs Surf.Area= 1,112 sf Storage= 1,488 cf

Plug-Flow detention time= 56.2 min calculated for 0.198 af (94% of inflow)  
 Center-of-Mass det. time= 25.4 min ( 820.0 - 794.5 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00




**Primary OutFlow** Max=2.22 cfs @ 12.15 hrs HW=32.08' (Free Discharge)

↑ 1=Culvert (Passes 2.22 cfs of 2.89 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 2.22 cfs @ 3.41 fps)



**Pond 1P: Rain Garden****Hydrograph**



**Routing Diagram for Post Development**  
 Prepared by Haley Ward, Printed 12/16/2025  
 HydroCAD® 10.20-7a s/n 00641 © 2025 HydroCAD Software Solutions LLC

Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=67,431 sf 8.92% Impervious Runoff Depth>0.62" Flow Length=525' Tc=9.5 min CN=60 Runoff=0.72 cfs 0.080 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=22,420 sf 41.90% Impervious Runoff Depth>1.58" Tc=5.0 min CN=77 Runoff=0.94 cfs 0.068 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=18,323 sf 53.76% Impervious Runoff Depth>1.87" Tc=5.0 min CN=81 Runoff=0.92 cfs 0.066 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>0.66" Tc=5.0 min CN=61 Runoff=0.04 cfs 0.004 af
<b>Subcatchment5S: SUBCATCHMENT5</b>	Runoff Area=6,943 sf 41.05% Impervious Runoff Depth>1.51" Tc=0.0 min CN=76 Runoff=0.32 cfs 0.020 af
<b>Subcatchment6S: SUBCATCHMENT6</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>3.39" Tc=5.0 min CN=98 Runoff=0.17 cfs 0.014 af
<b>Subcatchment7S: SUBCATCHMENT7</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>3.39" Tc=5.0 min CN=98 Runoff=0.17 cfs 0.014 af
<b>Subcatchment8S: SUBCATCHMENT8</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>3.39" Tc=5.0 min CN=98 Runoff=0.17 cfs 0.014 af
<b>Subcatchment9S: SUBCATCHMENT9</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>3.39" Tc=5.0 min CN=98 Runoff=0.17 cfs 0.014 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=0.94 cfs 0.068 af Outflow=0.94 cfs 0.068 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=1.71 cfs 0.187 af Outflow=1.71 cfs 0.187 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.04 cfs 0.004 af Outflow=0.04 cfs 0.004 af
<b>Pond 1P: Existing Rain Garden</b>	Peak Elev=31.43' Storage=830 cf Inflow=0.92 cfs 0.066 af Outflow=0.56 cfs 0.054 af
<b>Pond 2P: Proposed Rain Garden</b> Discarded=0.02 cfs 0.012 af Primary=0.23 cfs 0.027 af Secondary=0.00 cfs 0.000 af	Peak Elev=31.95' Storage=775 cf Inflow=0.60 cfs 0.047 af Outflow=0.24 cfs 0.039 af

**Total Runoff Area = 2.902 ac Runoff Volume = 0.291 af Average Runoff Depth = 1.20"**  
**71.14% Pervious = 2.064 ac 28.86% Impervious = 0.838 ac**

**Summary for Subcatchment 1S: SUBCATCHMENT 1**


Runoff = 0.72 cfs @ 12.17 hrs, Volume= 0.080 af, Depth> 0.62"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
53,341	55	Woods, Good, HSG B
8,072	61	>75% Grass cover, Good, HSG B
*	6,018	IMPERVIOUS
67,431	60	Weighted Average
61,413		91.08% Pervious Area
6,018		8.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.6	300	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
9.5	525	Total			



**Subcatchment 1S: SUBCATCHMENT 1**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 0.94 cfs @ 12.08 hrs, Volume= 0.068 af, Depth> 1.58"  
Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
13,026	61	>75% Grass cover, Good, HSG B
*		
9,394	98	IMPERVIOUS
22,420	77	Weighted Average
13,026		58.10% Pervious Area
9,394		41.90% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph



**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 0.92 cfs @ 12.08 hrs, Volume= 0.066 af, Depth> 1.87"  
Routed to Pond 1P : Existing Rain Garden


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
8,473	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
18,323	81	Weighted Average
8,473		46.24% Pervious Area
9,850		53.76% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3**

Hydrograph



**Summary for Subcatchment 4S: SUBCATCHMENT 4**


Runoff = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af, Depth> 0.66"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
2,922	61	>75% Grass cover, Good, HSG B
2,922		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				0.04	Direct Entry,


**Subcatchment 4S: SUBCATCHMENT 4**

**Summary for Subcatchment 5S: SUBCATCHEMNT 5**

Runoff = 0.32 cfs @ 12.01 hrs, Volume= 0.020 af, Depth> 1.51"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
4,093	61	>75% Grass cover, Good, HSG B
*	2,850	IMPERVIOUS
6,943	76	Weighted Average
4,093		58.95% Pervious Area
2,850		41.05% Impervious Area


**Subcatchment 5S: SUBCATCHEMNT 5****Hydrograph**

**Summary for Subcatchment 6S: SUBCATCHMENT 6**

Runoff = 0.17 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 3.39"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					


**Subcatchment 6S: SUBCATCHMENT 6****Hydrograph**

**Summary for Subcatchment 7S: SUBCATCHMENT 7**

Runoff = 0.17 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 3.39"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					


**Subcatchment 7S: SUBCATCHMENT 7****Hydrograph**

**Summary for Subcatchment 8S: SUBCATCHMENT 8**

Runoff = 0.17 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 3.39"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					

**Subcatchment 8S: SUBCATCHMENT 8**

**Summary for Subcatchment 9S: SUBCATCHMENT 9**


Runoff = 0.17 cfs @ 12.07 hrs, Volume= 0.014 af, Depth> 3.39"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.70"

Area (sf)	CN	Description
*	2,094	98 IMPERVIOUS
	2,094	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				Direct Entry,	

**Subcatchment 9S: SUBCATCHMENT 9****Hydrograph**

**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.515 ac, 41.90% Impervious, Inflow Depth > 1.58" for 2-yr event


Inflow = 0.94 cfs @ 12.08 hrs, Volume= 0.068 af

Outflow = 0.94 cfs @ 12.08 hrs, Volume= 0.068 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2**

Hydrograph



**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.320 ac, 26.81% Impervious, Inflow Depth &gt; 0.97" for 2-yr event


Inflow = 1.71 cfs @ 12.16 hrs, Volume= 0.187 af

Outflow = 1.71 cfs @ 12.16 hrs, Volume= 0.187 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1**

Hydrograph



**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth &gt; 0.66" for 2-yr event


Inflow = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af

Outflow = 0.04 cfs @ 12.10 hrs, Volume= 0.004 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3**

Hydrograph



**Summary for Pond 1P: Existing Rain Garden**

Inflow Area = 0.421 ac, 53.76% Impervious, Inflow Depth &gt; 1.87" for 2-yr event

Inflow = 0.92 cfs @ 12.08 hrs, Volume= 0.066 af

Outflow = 0.56 cfs @ 12.20 hrs, Volume= 0.054 af, Atten= 39%, Lag= 7.0 min

Primary = 0.56 cfs @ 12.20 hrs, Volume= 0.054 af

Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

Peak Elev= 31.43' @ 12.20 hrs Surf.Area= 907 sf Storage= 830 cf

Plug-Flow detention time= 114.7 min calculated for 0.054 af (82% of inflow)

Center-of-Mass det. time= 42.5 min ( 873.6 - 831.1 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


  


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00

**Primary OutFlow** Max=0.56 cfs @ 12.20 hrs HW=31.43' (Free Discharge)

↑ 1=Culvert (Passes 0.56 cfs of 0.73 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 0.56 cfs @ 2.15 fps)



**Pond 1P: Existing Rain Garden**

**Summary for Pond 2P: Proposed Rain Garden**

Inflow Area = 0.256 ac, 63.23% Impervious, Inflow Depth > 2.22" for 2-yr event  
 Inflow = 0.60 cfs @ 12.04 hrs, Volume= 0.047 af  
 Outflow = 0.24 cfs @ 12.29 hrs, Volume= 0.039 af, Atten= 60%, Lag= 15.0 min  
 Discarded = 0.02 cfs @ 12.29 hrs, Volume= 0.012 af  
 Primary = 0.23 cfs @ 12.29 hrs, Volume= 0.027 af  
 Routed to Reach SP1 : SUMMATION POINT 1  
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 31.95' @ 12.29 hrs Surf.Area= 974 sf Storage= 775 cf

Plug-Flow detention time= 143.7 min calculated for 0.039 af (82% of inflow)  
 Center-of-Mass det. time= 71.8 min ( 868.7 - 796.9 )

Volume	Invert	Avail.Storage	Storage Description	
#1	31.00'	2,688 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
31.00	650	0	0	
33.50	1,500	2,688	2,688	
Device	Routing	Invert	Outlet Devices	
#1	Discarded	31.00'	<b>2.400 in/hr Exfiltration over Surface area above 31.00'</b> Excluded Surface area = 650 sf	
#2	Primary	31.00'	<b>6.0" Round Culvert</b> L= 20.0' CMP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.00' / 30.90' S= 0.0050 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf	
#3	Device 2	31.50'	<b>4.0" Vert. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads	
#4	Device 2	32.80'	<b>12.0" Horiz. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads	
#5	Secondary	32.90'	<b>5.0' long x 5.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88	

**Discarded OutFlow** Max=0.02 cfs @ 12.29 hrs HW=31.95' (Free Discharge)  
 ↗1=Exfiltration (Exfiltration Controls 0.02 cfs)

**Primary OutFlow** Max=0.23 cfs @ 12.29 hrs HW=31.95' (Free Discharge)  
 ↗2=Culvert (Passes 0.23 cfs of 0.63 cfs potential flow)  
 ↗3=Orifice/Grate (Orifice Controls 0.23 cfs @ 2.58 fps)  
 ↗4=Orifice/Grate ( Controls 0.00 cfs)


**Secondary OutFlow** Max=0.00 cfs @ 5.00 hrs HW=31.00' (Free Discharge)  
 ↗5=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Pond 2P: Proposed Rain Garden**

Orifice/Grate  
Exfiltration

### Pond 2P: Proposed Rain Garden

Hydrograph



Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=67,431 sf 8.92% Impervious Runoff Depth>1.67" Flow Length=525' Tc=9.5 min CN=60 Runoff=2.46 cfs 0.215 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=22,420 sf 41.90% Impervious Runoff Depth>3.14" Tc=5.0 min CN=77 Runoff=1.90 cfs 0.135 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=18,323 sf 53.76% Impervious Runoff Depth>3.53" Tc=5.0 min CN=81 Runoff=1.73 cfs 0.124 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>1.75" Tc=5.0 min CN=61 Runoff=0.13 cfs 0.010 af
<b>Subcatchment5S: SUBCATCHMENT5</b>	Runoff Area=6,943 sf 41.05% Impervious Runoff Depth>3.05" Tc=0.0 min CN=76 Runoff=0.65 cfs 0.040 af
<b>Subcatchment6S: SUBCATCHMENT6</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>5.22" Tc=5.0 min CN=98 Runoff=0.27 cfs 0.021 af
<b>Subcatchment7S: SUBCATCHMENT7</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>5.22" Tc=5.0 min CN=98 Runoff=0.27 cfs 0.021 af
<b>Subcatchment8S: SUBCATCHMENT8</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>5.22" Tc=5.0 min CN=98 Runoff=0.27 cfs 0.021 af
<b>Subcatchment9S: SUBCATCHMENT9</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>5.22" Tc=5.0 min CN=98 Runoff=0.27 cfs 0.021 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=1.90 cfs 0.135 af Outflow=1.90 cfs 0.135 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=4.48 cfs 0.427 af Outflow=4.48 cfs 0.427 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.13 cfs 0.010 af Outflow=0.13 cfs 0.010 af
<b>Pond 1P: Existing Rain Garden</b>	Peak Elev=31.76' Storage=1,139 cf Inflow=1.73 cfs 0.124 af Outflow=1.29 cfs 0.112 af
<b>Pond 2P: Proposed Rain Garden</b> Discarded=0.03 cfs 0.015 af Primary=0.36 cfs 0.058 af Secondary=0.00 cfs 0.000 af	Peak Elev=32.40' Storage=1,239 cf Inflow=1.06 cfs 0.082 af Outflow=0.39 cfs 0.073 af

**Total Runoff Area = 2.902 ac Runoff Volume = 0.607 af Average Runoff Depth = 2.51"**  
**71.14% Pervious = 2.064 ac 28.86% Impervious = 0.838 ac**

**Summary for Subcatchment 1S: SUBCATCHMENT 1**


Runoff = 2.46 cfs @ 12.15 hrs, Volume= 0.215 af, Depth> 1.67"  
 Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
53,341	55	Woods, Good, HSG B
8,072	61	>75% Grass cover, Good, HSG B
*	6,018	IMPERVIOUS
67,431	60	Weighted Average
61,413		91.08% Pervious Area
6,018		8.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.6	300	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
9.5	525	Total			



**Subcatchment 1S: SUBCATCHMENT 1**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 1.90 cfs @ 12.08 hrs, Volume= 0.135 af, Depth> 3.14"  
Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
13,026	61	>75% Grass cover, Good, HSG B
*	9,394	IMPERVIOUS
22,420	77	Weighted Average
13,026		58.10% Pervious Area
9,394		41.90% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph



**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 1.73 cfs @ 12.08 hrs, Volume= 0.124 af, Depth> 3.53"  
Routed to Pond 1P : Existing Rain Garden


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
8,473	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
18,323	81	Weighted Average
8,473		46.24% Pervious Area
9,850		53.76% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3**

Hydrograph



**Summary for Subcatchment 4S: SUBCATCHMENT 4**


Runoff = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af, Depth> 1.75"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
2,922	61	>75% Grass cover, Good, HSG B
2,922		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				0.13	Direct Entry,


**Subcatchment 4S: SUBCATCHMENT 4**

**Summary for Subcatchment 5S: SUBCATCHEMNT 5**

Runoff = 0.65 cfs @ 12.00 hrs, Volume= 0.040 af, Depth> 3.05"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description
4,093	61	>75% Grass cover, Good, HSG B
*	2,850	IMPERVIOUS
6,943	76	Weighted Average
4,093		58.95% Pervious Area
2,850		41.05% Impervious Area

**Subcatchment 5S: SUBCATCHEMNT 5****Hydrograph**

**Post Development**

Prepared by Haley Ward

HydroCAD® 10.20-7a s/n 00641 © 2025 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.61"

Printed 12/16/2025

Page 27

**Summary for Subcatchment 6S: SUBCATCHMENT 6**


Runoff = 0.27 cfs @ 12.07 hrs, Volume= 0.021 af, Depth> 5.22"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					

**Subcatchment 6S: SUBCATCHMENT 6**

Hydrograph




**Summary for Subcatchment 7S: SUBCATCHMENT 7**

Runoff = 0.27 cfs @ 12.07 hrs, Volume= 0.021 af, Depth> 5.22"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					


**Subcatchment 7S: SUBCATCHMENT 7****Hydrograph**

**Summary for Subcatchment 8S: SUBCATCHMENT 8**

Runoff = 0.27 cfs @ 12.07 hrs, Volume= 0.021 af, Depth> 5.22"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					


**Subcatchment 8S: SUBCATCHMENT 8****Hydrograph**

**Summary for Subcatchment 9S: SUBCATCHMENT 9**

Runoff = 0.27 cfs @ 12.07 hrs, Volume= 0.021 af, Depth> 5.22"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.61"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					

**Subcatchment 9S: SUBCATCHMENT 9****Hydrograph**

**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.515 ac, 41.90% Impervious, Inflow Depth > 3.14" for 10-yr event


Inflow = 1.90 cfs @ 12.08 hrs, Volume= 0.135 af

Outflow = 1.90 cfs @ 12.08 hrs, Volume= 0.135 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2**

Hydrograph




**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.320 ac, 26.81% Impervious, Inflow Depth > 2.21" for 10-yr event

Inflow = 4.48 cfs @ 12.14 hrs, Volume= 0.427 af

Outflow = 4.48 cfs @ 12.14 hrs, Volume= 0.427 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1****Hydrograph**


**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth > 1.75" for 10-yr event

Inflow = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af

Outflow = 0.13 cfs @ 12.09 hrs, Volume= 0.010 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3****Hydrograph**

**Summary for Pond 1P: Existing Rain Garden**

Inflow Area = 0.421 ac, 53.76% Impervious, Inflow Depth > 3.53" for 10-yr event  
 Inflow = 1.73 cfs @ 12.08 hrs, Volume= 0.124 af  
 Outflow = 1.29 cfs @ 12.15 hrs, Volume= 0.112 af, Atten= 25%, Lag= 4.7 min  
 Primary = 1.29 cfs @ 12.15 hrs, Volume= 0.112 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 31.76' @ 12.15 hrs Surf.Area= 1,005 sf Storage= 1,139 cf

Plug-Flow detention time= 76.1 min calculated for 0.112 af (90% of inflow)  
 Center-of-Mass det. time= 30.4 min ( 843.3 - 812.9 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00

**Primary OutFlow** Max=1.29 cfs @ 12.15 hrs HW=31.75' (Free Discharge)

↑ 1=Culvert (Passes 1.29 cfs of 1.88 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 1.29 cfs @ 2.85 fps)



**Pond 1P: Existing Rain Garden**

**Summary for Pond 2P: Proposed Rain Garden**

Inflow Area = 0.256 ac, 63.23% Impervious, Inflow Depth > 3.86" for 10-yr event  
 Inflow = 1.06 cfs @ 12.03 hrs, Volume= 0.082 af  
 Outflow = 0.39 cfs @ 12.31 hrs, Volume= 0.073 af, Atten= 64%, Lag= 17.0 min  
 Discarded = 0.03 cfs @ 12.31 hrs, Volume= 0.015 af  
 Primary = 0.36 cfs @ 12.31 hrs, Volume= 0.058 af  
 Routed to Reach SP1 : SUMMATION POINT 1  
 Secondary = 0.00 cfs @ 5.00 hrs, Volume= 0.000 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 32.40' @ 12.31 hrs Surf.Area= 1,125 sf Storage= 1,239 cf



Plug-Flow detention time= 108.1 min calculated for 0.073 af (89% of inflow)  
 Center-of-Mass det. time= 56.2 min ( 846.8 - 790.6 )

Volume	Invert	Avail.Storage	Storage Description	
#1	31.00'	2,688 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	
31.00	650	0	0	
33.50	1,500	2,688	2,688	
Device	Routing	Invert	Outlet Devices	
#1	Discarded	31.00'	<b>2.400 in/hr Exfiltration over Surface area above 31.00'</b> Excluded Surface area = 650 sf	
#2	Primary	31.00'	<b>6.0" Round Culvert</b> L= 20.0' CMP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.00' / 30.90' S= 0.0050 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf	
#3	Device 2	31.50'	<b>4.0" Vert. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads	
#4	Device 2	32.80'	<b>12.0" Horiz. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads	
#5	Secondary	32.90'	<b>5.0' long x 5.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88	

**Discarded OutFlow** Max=0.03 cfs @ 12.31 hrs HW=32.40' (Free Discharge)  
 ↗ 1=Exfiltration (Exfiltration Controls 0.03 cfs)

**Primary OutFlow** Max=0.36 cfs @ 12.31 hrs HW=32.40' (Free Discharge)  
 ↗ 2=Culvert (Passes 0.36 cfs of 0.80 cfs potential flow)  
 ↗ 3=Orifice/Grate (Orifice Controls 0.36 cfs @ 4.11 fps)  
 ↗ 4=Orifice/Grate ( Controls 0.00 cfs)

**Secondary OutFlow** Max=0.00 cfs @ 5.00 hrs HW=31.00' (Free Discharge)  
 ↗ 5=Broad-Crested Rectangular Weir ( Controls 0.00 cfs)

**Pond 2P: Proposed Rain Garden****Hydrograph**

Time span=5.00-24.00 hrs, dt=0.05 hrs, 381 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

<b>Subcatchment1S: SUBCATCHMENT1</b>	Runoff Area=67,431 sf 8.92% Impervious Runoff Depth>3.73" Flow Length=525' Tc=9.5 min CN=60 Runoff=5.86 cfs 0.481 af
<b>Subcatchment2S: SUBCATCHMENT2</b>	Runoff Area=22,420 sf 41.90% Impervious Runoff Depth>5.76" Tc=5.0 min CN=77 Runoff=3.46 cfs 0.247 af
<b>Subcatchment3S: SUBCATCHMENT3</b>	Runoff Area=18,323 sf 53.76% Impervious Runoff Depth>6.24" Tc=5.0 min CN=81 Runoff=3.03 cfs 0.219 af
<b>Subcatchment4S: SUBCATCHMENT4</b>	Runoff Area=2,922 sf 0.00% Impervious Runoff Depth>3.85" Tc=5.0 min CN=61 Runoff=0.30 cfs 0.022 af
<b>Subcatchment5S: SUBCATCHMENT5</b>	Runoff Area=6,943 sf 41.05% Impervious Runoff Depth>5.64" Tc=0.0 min CN=76 Runoff=1.20 cfs 0.075 af
<b>Subcatchment6S: SUBCATCHMENT6</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>7.99" Tc=5.0 min CN=98 Runoff=0.41 cfs 0.032 af
<b>Subcatchment7S: SUBCATCHMENT7</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>7.99" Tc=5.0 min CN=98 Runoff=0.41 cfs 0.032 af
<b>Subcatchment8S: SUBCATCHMENT8</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>7.99" Tc=5.0 min CN=98 Runoff=0.41 cfs 0.032 af
<b>Subcatchment9S: SUBCATCHMENT9</b>	Runoff Area=2,094 sf 100.00% Impervious Runoff Depth>7.99" Tc=5.0 min CN=98 Runoff=0.41 cfs 0.032 af
<b>Reach 6R: SUMMATIONPOINT 2</b>	Inflow=3.46 cfs 0.247 af Outflow=3.46 cfs 0.247 af
<b>Reach SP1: SUMMATIONPOINT 1</b>	Inflow=9.47 cfs 0.863 af Outflow=9.47 cfs 0.863 af
<b>Reach SP3: SUMMATIONPOINT 3</b>	Inflow=0.30 cfs 0.022 af Outflow=0.30 cfs 0.022 af
<b>Pond 1P: Existing Rain Garden</b>	Peak Elev=32.12' Storage=1,522 cf Inflow=3.03 cfs 0.219 af Outflow=2.32 cfs 0.207 af
<b>Pond 2P: Proposed Rain Garden</b> Discarded=0.04 cfs 0.018 af Primary=0.82 cfs 0.111 af Secondary=0.01 cfs 0.000 af	Peak Elev=32.91' Storage=1,856 cf Inflow=1.82 cfs 0.139 af Outflow=0.87 cfs 0.129 af

**Total Runoff Area = 2.902 ac Runoff Volume = 1.171 af Average Runoff Depth = 4.84"**  
**71.14% Pervious = 2.064 ac 28.86% Impervious = 0.838 ac**

**Summary for Subcatchment 1S: SUBCATCHMENT 1**


Runoff = 5.86 cfs @ 12.14 hrs, Volume= 0.481 af, Depth> 3.73"  
 Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
53,341	55	Woods, Good, HSG B
8,072	61	>75% Grass cover, Good, HSG B
*	6,018	IMPERVIOUS
67,431	60	Weighted Average
61,413		91.08% Pervious Area
6,018		8.92% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
4.4	25	0.0800	0.09		<b>Sheet Flow,</b> Woods: Light underbrush n= 0.400 P2= 2.70"
1.1	75	0.0500	1.12		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
2.0	85	0.0200	0.71		<b>Shallow Concentrated Flow,</b> Woodland Kv= 5.0 fps
0.4	40	0.0100	1.50		<b>Shallow Concentrated Flow,</b> Grassed Waterway Kv= 15.0 fps
1.6	300	0.0050	3.21	2.52	<b>Pipe Channel,</b> 12.0" Round Area= 0.8 sf Perim= 3.1' r= 0.25' n= 0.013 Corrugated PE, smooth interior
9.5	525	Total			



**Subcatchment 1S: SUBCATCHMENT 1**

**Summary for Subcatchment 2S: SUBCATCHMENT 2**

Runoff = 3.46 cfs @ 12.07 hrs, Volume= 0.247 af, Depth> 5.76"  
Routed to Reach 6R : SUMMATION POINT 2


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
13,026	61	>75% Grass cover, Good, HSG B
*	9,394	IMPERVIOUS
22,420	77	Weighted Average
13,026		58.10% Pervious Area
9,394		41.90% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0					Direct Entry,

**Subcatchment 2S: SUBCATCHMENT 2**

Hydrograph




**Summary for Subcatchment 3S: SUBCATCHMENT 3**

Runoff = 3.03 cfs @ 12.07 hrs, Volume= 0.219 af, Depth> 6.24"  
Routed to Pond 1P : Existing Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
8,473	61	>75% Grass cover, Good, HSG B
*	9,850	IMPERVIOUS
18,323	81	Weighted Average
8,473		46.24% Pervious Area
9,850		53.76% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

**Subcatchment 3S: SUBCATCHMENT 3****Hydrograph**

**Summary for Subcatchment 4S: SUBCATCHMENT 4**


Runoff = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af, Depth> 3.85"  
Routed to Reach SP3 : SUMMATION POINT 3

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
2,922	61	>75% Grass cover, Good, HSG B
2,922		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				0.30	Direct Entry,

**Subcatchment 4S: SUBCATCHMENT 4**

**Summary for Subcatchment 5S: SUBCATCHEMNT 5**


Runoff = 1.20 cfs @ 12.00 hrs, Volume= 0.075 af, Depth> 5.64"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
4,093	61	>75% Grass cover, Good, HSG B
* 2,850	98	IMPERVIOUS
6,943	76	Weighted Average
4,093		58.95% Pervious Area
2,850		41.05% Impervious Area

**Subcatchment 5S: SUBCATCHEMNT 5**

Hydrograph



**Summary for Subcatchment 6S: SUBCATCHMENT 6**


Runoff = 0.41 cfs @ 12.07 hrs, Volume= 0.032 af, Depth> 7.99"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
*	2,094	98 IMPERVIOUS
	2,094	100.00% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0				Direct Entry,	

**Subcatchment 6S: SUBCATCHMENT 6****Hydrograph**

**Summary for Subcatchment 7S: SUBCATCHMENT 7**


Runoff = 0.41 cfs @ 12.07 hrs, Volume= 0.032 af, Depth> 7.99"  
Routed to Pond 2P : Proposed Rain Garden

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
*	2,094	98 IMPERVIOUS
	2,094	100.00% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
5.0				Direct Entry,	

**Subcatchment 7S: SUBCATCHMENT 7**

**Summary for Subcatchment 8S: SUBCATCHMENT 8**


Runoff = 0.41 cfs @ 12.07 hrs, Volume= 0.032 af, Depth> 7.99"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description
*	2,094	98 IMPERVIOUS
	2,094	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0				Direct Entry,	


**Subcatchment 8S: SUBCATCHMENT 8****Hydrograph**

**Summary for Subcatchment 9S: SUBCATCHMENT 9**

Runoff = 0.41 cfs @ 12.07 hrs, Volume= 0.032 af, Depth> 7.99"  
Routed to Reach SP1 : SUMMATION POINT 1

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
Type III 24-hr 50-yr Rainfall=8.53"

Area (sf)	CN	Description			
*	2,094	98 IMPERVIOUS			
2,094		100.00% Impervious Area			
Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	Direct Entry,
5.0					

**Subcatchment 9S: SUBCATCHMENT 9****Hydrograph**


**Summary for Reach 6R: SUMMATION POINT 2**

Inflow Area = 0.515 ac, 41.90% Impervious, Inflow Depth > 5.76" for 50-yr event

Inflow = 3.46 cfs @ 12.07 hrs, Volume= 0.247 af

Outflow = 3.46 cfs @ 12.07 hrs, Volume= 0.247 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach 6R: SUMMATION POINT 2****Hydrograph**


**Summary for Reach SP1: SUMMATION POINT 1**

Inflow Area = 2.320 ac, 26.81% Impervious, Inflow Depth > 4.46" for 50-yr event

Inflow = 9.47 cfs @ 12.14 hrs, Volume= 0.863 af

Outflow = 9.47 cfs @ 12.14 hrs, Volume= 0.863 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP1: SUMMATION POINT 1****Hydrograph**

**Summary for Reach SP3: SUMMATION POINT 3**

Inflow Area = 0.067 ac, 0.00% Impervious, Inflow Depth &gt; 3.85" for 50-yr event


Inflow = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af

Outflow = 0.30 cfs @ 12.08 hrs, Volume= 0.022 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs

**Reach SP3: SUMMATION POINT 3**

Hydrograph



**Summary for Pond 1P: Existing Rain Garden**

Inflow Area = 0.421 ac, 53.76% Impervious, Inflow Depth > 6.24" for 50-yr event  
 Inflow = 3.03 cfs @ 12.07 hrs, Volume= 0.219 af  
 Outflow = 2.32 cfs @ 12.15 hrs, Volume= 0.207 af, Atten= 23%, Lag= 4.3 min  
 Primary = 2.32 cfs @ 12.15 hrs, Volume= 0.207 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 32.12' @ 12.15 hrs Surf.Area= 1,123 sf Storage= 1,522 cf

Plug-Flow detention time= 54.9 min calculated for 0.207 af (94% of inflow)  
 Center-of-Mass det. time= 24.5 min ( 821.4 - 796.9 )

Volume	Invert	Avail.Storage	Storage Description	
#1	28.00'	2,657 cf	<b>Custom Stage Data (Prismatic)</b>	Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
28.00	775	0.0	0	0
31.00	775	20.0	465	465
32.00	1,079	100.0	927	1,392
33.00	1,450	100.0	1,265	2,657


Device	Routing	Invert	Outlet Devices
#1	Primary	31.00'	<b>12.0" Round Culvert</b> L= 11.0' CPP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 31.00' / 30.50' S= 0.0455 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.79 sf
#2	Device 1	31.00'	<b>Custom Weir/Orifice, Cv= 2.62 (C= 3.28)</b> Elev. (feet) 31.00 32.30 32.30 33.00 Width (feet) 0.60 0.60 4.00 4.00

**Primary OutFlow** Max=2.31 cfs @ 12.15 hrs HW=32.11' (Free Discharge)

↑ 1=Culvert (Passes 2.31 cfs of 2.96 cfs potential flow)

↑ 2=Custom Weir/Orifice (Weir Controls 2.31 cfs @ 3.46 fps)



**Pond 1P: Existing Rain Garden****Hydrograph**

**Summary for Pond 2P: Proposed Rain Garden**

Inflow Area = 0.256 ac, 63.23% Impervious, Inflow Depth > 6.53" for 50-yr event  
 Inflow = 1.82 cfs @ 12.02 hrs, Volume= 0.139 af  
 Outflow = 0.87 cfs @ 12.21 hrs, Volume= 0.129 af, Atten= 52%, Lag= 11.4 min  
 Discarded = 0.04 cfs @ 12.21 hrs, Volume= 0.018 af  
 Primary = 0.82 cfs @ 12.21 hrs, Volume= 0.111 af  
 Routed to Reach SP1 : SUMMATION POINT 1  
 Secondary = 0.01 cfs @ 12.20 hrs, Volume= 0.000 af  
 Routed to Reach SP1 : SUMMATION POINT 1

Routing by Stor-Ind method, Time Span= 5.00-24.00 hrs, dt= 0.05 hrs  
 Peak Elev= 32.91' @ 12.21 hrs Surf.Area= 1,298 sf Storage= 1,856 cf



Plug-Flow detention time= 85.2 min calculated for 0.129 af (93% of inflow)  
 Center-of-Mass det. time= 48.9 min ( 832.1 - 783.1 )



Volume	Invert	Avail.Storage	Storage Description
#1	31.00'	2,688 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
31.00	650	0	0
33.50	1,500	2,688	2,688
Device	Routing	Invert	Outlet Devices
#1	Discarded	31.00'	<b>2.400 in/hr Exfiltration over Surface area above 31.00'</b> Excluded Surface area = 650 sf
#2	Primary	31.00'	<b>6.0" Round Culvert</b> L= 20.0' CMP, projecting, no headwall, Ke= 0.900 Inlet / Outlet Invert= 31.00' / 30.90' S= 0.0050 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior, Flow Area= 0.20 sf
#3	Device 2	31.50'	<b>4.0" Vert. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads
#4	Device 2	32.80'	<b>12.0" Horiz. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads
#5	Secondary	32.90'	<b>5.0' long x 5.0' breadth Broad-Crested Rectangular Weir</b> Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50 Coef. (English) 2.34 2.50 2.70 2.68 2.68 2.66 2.65 2.65 2.65 2.65 2.67 2.66 2.68 2.70 2.74 2.79 2.88

**Discarded OutFlow** Max=0.04 cfs @ 12.21 hrs HW=32.90' (Free Discharge)  
 ↗ 1=Exfiltration (Exfiltration Controls 0.04 cfs)

**Primary OutFlow** Max=0.81 cfs @ 12.21 hrs HW=32.90' (Free Discharge)  
 ↗ 2=Culvert (Passes 0.81 cfs of 0.96 cfs potential flow)  
   ↗ 3=Orifice/Grate (Orifice Controls 0.47 cfs @ 5.35 fps)  
   ↗ 4=Orifice/Grate (Weir Controls 0.34 cfs @ 1.05 fps)

**Secondary OutFlow** Max=0.00 cfs @ 12.20 hrs HW=32.90' (Free Discharge)  
 ↗ 5=Broad-Crested Rectangular Weir (Weir Controls 0.00 cfs @ 0.16 fps)

**Pond 2P: Proposed Rain Garden**



**LOCATION MAP:** USGS QUADRANGLE: KITTERY  
MAPTECH® USGS TOPOGRAPHIC SERIES  
CALE: 1"=2000'  
©MAPTECH®, INC. 978-933-3000  
[WWW.MAPTECH.COM/TOPO](http://WWW.MAPTECH.COM/TOPO)


## PRE LEGEND:

The diagram illustrates a flow path with the following components and descriptions:

- PROPERTY LINE**: Represented by a horizontal line with a solid segment at the top and a dashed segment below it.
- WATERSHED BOUNDARY LINE**: Represented by a horizontal line with five black squares.
- WATERSHED DESIGNATION**: Represented by a circle containing the number **1**.
- TIME OF CONCENTRATION FLOW PATH**: Represented by a horizontal line with two arrows pointing to the right.
- FLOW PATH DESCRIPTION**: A label for the flow path types.
- SHEET FLOW**: Represented by the label **SF**.
- SHALLOW CONCENTRATED FLOW**: Represented by the label **SC**.
- CHANNEL FLOW**: Represented by the label **CF**.
- PIPE FLOW**: Represented by the label **PF**.

Below the flow path, the label **50' SF** is positioned under the **SF** entry.


## GRAPHIC SCALE



REV.	DATE	DESCRIPTION	BY	CHK.														
DRAWING ISSUE STATUS																		
<b>NOT FOR CONSTRUCTION</b>																		
 <a href="http://WWW.HALEYWARD.COM">WWW.HALEYWARD.COM</a>		<b>HALEY WARD</b>  200 Griffin Rd., Unit 14 Portsmouth, New Hampshire 03801 603.430.9282																
PROJECT																		
<b>1151 SAGAMORE AVENUE CBC, LLC</b> <b>1151 SAGAMORE AVE., PORTSMOUTH, NH</b>																		
TITLE																		
<b>PRE-DEVELOPMENT HYDROLOGY PLAN</b>																		
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">DATE</td> <td style="width: 50%;">SCALE</td> </tr> <tr> <td>2025.12.22</td> <td>1"=40'</td> </tr> <tr> <td>DRAWN BY</td> <td>DESIGNED BY</td> </tr> <tr> <td>BLQ/PJM</td> <td>BLQ/PJM</td> </tr> <tr> <td colspan="2">PROJECT No.</td> </tr> <tr> <td colspan="2">5010314.002</td> </tr> <tr> <td colspan="2">DRAWING No.</td> </tr> <tr> <td colspan="2">C701</td> </tr> </table>	DATE	SCALE	2025.12.22	1"=40'	DRAWN BY	DESIGNED BY	BLQ/PJM	BLQ/PJM	PROJECT No.		5010314.002		DRAWING No.		C701	
DATE	SCALE																	
2025.12.22	1"=40'																	
DRAWN BY	DESIGNED BY																	
BLQ/PJM	BLQ/PJM																	
PROJECT No.																		
5010314.002																		
DRAWING No.																		
C701																		
		REV.																




## Hydrologic Soil Group—Rockingham County, New Hampshire



## MAP LEGEND

### Area of Interest (AOI)



### Soils

#### Soil Rating Polygons

	A
	A/D
	B
	B/D
	C
	C/D
	D
	Not rated or not available

#### Soil Rating Lines

	A
	A/D
	B
	B/D
	C
	C/D
	D
	Not rated or not available

#### Soil Rating Points

	A
	A/D
	B
	B/D

### C

### C/D

### D

### Not rated or not available

### Water Features



### Streams and Canals

### Transportation



### Rails



### Interstate Highways



### US Routes



### Major Roads



### Local Roads

### Background



### Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:24,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Rockingham County, New Hampshire

Survey Area Data: Version 28, Sep 9, 2025

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 19, 2020—Sep 20, 2020

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.



## Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
140B	Chatfield-Hollis-Canton complex, 0 to 8 percent slopes, rocky	B	3.5	84.8%
140D	Chatfield-Hollis-Canton complex, 15 to 35 percent slopes, rocky	B	0.2	4.9%
699	Urban land		0.4	10.3%
<b>Totals for Area of Interest</b>			<b>4.2</b>	<b>100.0%</b>

### Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

## Rating Options


*Aggregation Method:* Dominant Condition

*Component Percent Cutoff:* None Specified

*Tie-break Rule:* Higher

From the test pit observations taken 7/16/2025 and the Test Pit log created from this reading it is determined that the Soil Permeability Class for the Receiving Layer (0-16") to be Moderate to Moderately Rapid. This permeability Class equates to a permeability rate of 6 cm/hr. This is converted to 26 MPI.

## SOIL DESCRIPTION

Soil type:	Map Unit Symbol:	File No:
Area:	Date:	Described by:
Location	Photo Number:	
Native Veg.	Climate:	
Parent material		
Relief		% Slope
Elevation	Drainage	Gr. water
Additional notes:		
		

**TABLE 17A**  
**Visual indicators of permeability: structural characteristics of soil**

Permeability class (Table 15)	Structure, type and class (Sec. 73) (1)	Structure, grade and consistency (Secs 72 + 80) (2)	Relationship of horizontal and vertical axes, overlap, cleavage, and its direction (3)	Porosity channels and cracks (4)
Very slow permeability	Massive	Very strong		Without visible pores.
	Irregular blocky; often assuming a columnar structure	Clods are very strong and cannot be broken by hand. More force is required to break the blocks vertically than horizontally. Horizontal breakage is usually along the block faces and in some instances the small irregular angular blocks can be flaked off horizontally.	Where the irregular blocky structure dominates, the irregular fragments are very firmly developed with a longer horizontal than vertical axis and with sharp angles. These are meshed shingle-fashion with about 50 percent horizontal overlap. Under proper moisture conditions, the medium to coarse irregular angular blocks break along definite cleavage to fine irregular, angular blocky structure, the arrangement remaining the same regardless of size.	The individual blocks have no visible pores, but some tortuous vertical channels that seem to follow block faces are discernible, usually at 2- to 5-cm intervals which seldom extend more than 5-8 cm without a horizontal jog.
Slow permeability	Fine to medium irregular blocky	More force is required to break the blocks along the vertical than the horizontal axis. The broken faces tend to assume a saw-toothed appearance.	The irregular angular blocks have sharp angles and the horizontal axes are longer than the vertical. The blocks are generally meshed shingle-fashion with about 40 percent horizontal overlap. Horizontal bedding can be easily detected in "chip" form, generally lying in shingle-fashion with horizontal overlap of 40-50 percent or more. Sometimes the thin, laminated layers are continuous.	There are very few small pores discernible. The apparent vertical cracks which follow the block surfaces seldom extend more than a few cm before jogs of 2-5 cm appear. Only a few very fine vertical pores are visible. Flow of water follows apparently tortuous lines around the main chips.
	Usually platy, sometimes structureless	Plates broken horizontally fracture along straight smooth lines, the laminated layers seeming to be made of small flattish "chips" that can be easily removed by tweezers.		
Moderately slow permeability	Medium to fine irregular blocky, fragmental	The blocks (clods) and fragments are less firm and stable than those of the slower permeability classes. They can be more easily broken along the vertical axes.	The angle of the blocks and fragments is not sharp and often very slightly rounded. The horizontal axis is only slightly longer than the vertical. The structural fragments overlap 20-25 percent. If the overlap is oblique, the size of fragments may be larger and the overlap more than 25 percent.	Pores are fine but moderately numerous. The oblique overlap is indicative of free air and water movement. Root penetration is noticeable.
Moderate permeability	Fine to medium subangular blocky (nut-like), partially rounded, some obtuse angles	Cohesion of soil materials is moderate and clods are easily broken by hand, but seldom fractured unless broken individually.	The clods or blocks overlap only slightly and many vertical fractures are almost straight. Cleavage generally occurs along the faces of the nuciform aggregates.	Pores are medium to fine and numerous.
Moderately rapid permeability	Medium subangular blocky (nuciform) coarse granular or crumb structure	The structural aggregates are not firmly developed and the cohesion of soil material is moderately weak.	Vertical cleavage is nearly always along aggregate faces and follows approximately straight vertical or oblique lines, with only occasional slight overlap of structural aggregates.	Pores in the aggregate are large and numerous.
Rapid permeability	Crumb structure (sometimes ranging toward a single-grain condition)	Consistency ranges from slightly plastic when wet to friable or crumbly when dry.		Pore space is large.
Very rapid permeability	Single-grain structure	Consistency ranges from non-plastic when wet to incoherent when moist or dry.		

**TABLE 17 B**  
**Visual Indicators of permeability: texture, physical behaviour and colour of soil**

Permeability class (Table 15)	Texture and profile	Physical behaviour	Colour and mottling
Very slow permeability	Claypans, heavy clay, or in presence of very slowly permeable substratum	Soil cracks severely on drying with exception of hardpan or indurated layers which do not crack or fracture.	Generally mottled.
	Hardpan as distinguished from claypan	The hardpan layers associated with this class often consist of highly indurated layers of sand or sand and gravel. These usually give out a ringing sound when struck with a spade.	High degree of mottling.
Slow permeability	Clay or silty clay, claypans, moderately indurated layers	Shrinkage and cracking are less pronounced than in the very slowly permeable class.	Mottling is moderately strong.
	Silt, "siltpan"		Moderately strong mottling and greyish colour are indications of this type of structure.
Moderately slow permeability	Moderately fine-textured horizons, showing a small amount of granulation or a slight dispersion of particles	Shrinkage is usually not very pronounced and cracks are neither large nor numerous.	Mottling is moderate, but the colour is brighter than for the slow permeability class.
Moderate permeability	Moderately fine textures, slightly plastic when wet and moderately hard when dry		Mottling is generally slight.
Moderately rapid permeability	Moderately fine to medium-textured soils		Occasional mottling. Colour is generally moderately bright yellow.
Rapid permeability	Medium or moderately coarse-textured soils		There are no mottlings unless water-table is high. Colour is generally very bright. Organic matter content is usually moderate or low.
Very rapid permeability	Coarse-textured or gravelly soils		Colour is bright unless the water-table is high.

**TABLE 15**  
**Soil permeability classes for agriculture and conservation**

Soil permeability classes	Permeability rates <sup>1</sup>	
	cm/hour	cm/day
Very slow	Less than 0.13	Less than 3
Slow	0.13 - 0.3	3 - 12
Moderately slow	0.5 - 2.0	12 - 48
Moderate	2.0 - 6.3	48 - 151
Moderately rapid	6.3 - 12.7	151 - 305
Rapid	12.7 - 25	305 - 600
Very rapid	More than 25	More than 600

Conversion Table: cm/h to min/inch			
	cm/hr	min/inch	
60 MPI Slowest	1	152.40	41
Allowable Design	2	76.20	42
	3	50.80	43
	4	38.10	44
	5	30.48	45
	6	25.40	46
	7	21.77	47
	8	19.05	48
	9	16.93	49
	10	15.24	50
	11	13.85	51
	12	12.70	52
	13	11.72	53
	14	10.89	54
	15	10.16	55
	16	9.53	56
	17	8.96	57
	18	8.47	58
	19	8.02	59
	20	7.62	60
	21	7.26	61
	22	6.93	62
	23	6.63	63
	24	6.35	64
	25	6.10	65
	26	5.87	66
	27	5.66	67
	28	5.46	68
	29	5.27	69
	30	5.09	70
	31	4.92	71
	32	4.76	72
	33	4.60	73
	34	4.45	74
	35	4.30	75
	36	4.16	76
	37	4.02	77
	38	3.89	78
	39	3.76	79
	40	3.64	80

# National Flood Hazard Layer FIRMette



70°45'12"W 43°3'21"N



## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

### SPECIAL FLOOD HAZARD AREAS

- Without Base Flood Elevation (BFE) Zone A, V, A99
- With BFE or Depth Zone AE, AO, AH, VE, AR
- Regulatory Floodway

0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X

Future Conditions 1% Annual Chance Flood Hazard Zone X

Area with Reduced Flood Risk due to Levee. See Notes. Zone X

Area with Flood Risk due to Levee Zone D

NO SCREEN Area of Minimal Flood Hazard Zone X

Effective LOMRs

Area of Undetermined Flood Hazard Zone D

GENERAL STRUCTURES

- Channel, Culvert, or Storm Sewer
- Levee, Dike, or Floodwall

20.2 Cross Sections with 1% Annual Chance  
17.5 Water Surface Elevation

8 Coastal Transect

513 Base Flood Elevation Line (BFE)

Limit of Study

Jurisdiction Boundary

Coastal Transect Baseline

Profile Baseline

Hydrographic Feature

Digital Data Available

No Digital Data Available

Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 9/27/2023 at 1:41 PM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.



---

## INSPECTION & LONG-TERM MAINTENANCE PLAN FOR PROPOSED RESIDENTIAL DEVELOPMENT

1151 SAGAMORE AVENUE  
PORTSMOUTH, NH

### Introduction

The intent of this plan is to provide 1151 Sagamore Avenue CBC, LLC (herein referred to as "owner") with a list of procedures that document the inspection and maintenance requirements of the stormwater management system for this development. Specifically, the Rain Garden and associated structures on the project site (collectively referred to as the "Stormwater Management System"). The contact information for the owner shall be kept current, and if there is a change of ownership of the property this plan must be transferred to the new owner.

The following inspection and maintenance program is necessary to keep the stormwater management system functioning properly and will help in maintaining a high quality of stormwater runoff to minimize potential environmental impacts. By following the enclosed procedures, the owner will be able to maintain the functional design of the stormwater management system and maximize its ability to remove sediment and other contaminants from site generated stormwater runoff.

### Annual Report

The owner shall prepare an annual Inspection & Maintenance Report. The report shall include a summary of the system's maintenance and repair by transmission of the Inspection & Maintenance Log and other information as required. A copy of the report shall be delivered annually to the City of Portsmouth Public Works Department, as required.

### Inspection & Maintenance Checklist/Log

The following pages contain the Stormwater Management System Inspection & Maintenance Requirements and a blank copy of the Stormwater Management System Inspection & Maintenance Log. These forms are provided to the owner as a guideline for performing the inspection and maintenance of the Stormwater Management System. This is a guideline and should be periodically reviewed for conformance with current practice and standards.



## Stormwater Management System Components

The Stormwater Management System is designed to mitigate both the quantity and quality of site-generated stormwater runoff. As a result, the design includes the following elements:

### Non-Structural BMPs

Non-Structural best management practices (BMP's) include temporary and permanent measures that typically require less labor and capital inputs and are intended to provide protection against erosion of soils. Examples of non-structural BMP's on this project include but are not limited to:

- Temporary and Permanent mulching
- Temporary and Permanent grass cover
- Trees
- Shrubs and ground covers
- Miscellaneous landscape plantings
- Dust control
- Tree protection
- Topsoiling
- Sediment barriers
- Stabilized construction entrance
- Vegetated buffer area

### Structural BMPs

Structural BMPs are more labor and capital-intensive structures or installations that require more specialized personnel to install. Examples on this project include but are not limited to:

- Rain Garden
- Outlet Control Structures and Storm Drains

## Inspection and Maintenance Requirements

The following summarizes the inspection and maintenance requirements for the various BMPs that may be found on this project.

1. **Grassed areas (until established):** After each rain event of 0.5" or more during a 24-hour period, inspect grassed areas for signs of disturbance, such as erosion. If damaged areas are discovered, immediately repair the damage. Repairs may include adding new topsoil, lime, seed, fertilizer and mulch.



2. **Plantings:** Planting and landscaping (trees, shrubs) shall be monitored bi-monthly during the first year to insure viability and vigorous growth. Replace dead or dying vegetation with new stock and make adjustments to the conditions that caused the dead or dying vegetation. During dryer times of the year, provide weekly watering or irrigation during the establishment period of the first year.  
Make the necessary adjustments to ensure long-term health of the vegetated covers, i.e. provide more permanent mulch or compost or other means of protection.
3. **Vegetated buffer area:** Check for scour or sediment buildup in buffer area, at least annually. Replace any vegetation removed by scour or sediment buildup with similar vegetation.
4. **Rain Garden:** After installation of the rain garden, perform the following inspections on a monthly basis:
  - a. Monitor for excessive or concentrated accumulations of debris, or excessive erosion below the various pipe inlets. Remove debris as required and replace or add inlet fabric strips or rip rap stones.
  - b. Monitor the outflow for problems with erosion. Repair as required.
  - c. After significant rainfalls, monitor rain garden surfaces for ponding of water. If water remains flooded over the surface 24 hours after a 1" rainfall, then investigate the cause, if not related to overflow blockage, then excavate and replace filter media.
  - d. Monitor vegetation on rain garden and replace dead or dying vegetation as required.
  - e. Monitor rain garden for rodent borrows and repair as required; remove persistent occupiers.
  - f. Monitor side slopes of rain garden for damage or erosion—repair, as necessary.
5. **Outlet Control Structures and Storm Drains:** Monitor accumulation of debris in outlet control structures monthly or after significant rain events. Remove sediments when they accumulate within the yard drains and outlet pipe. During construction, maintain inlet protection until the site has been stabilized. Prior to the end of construction, inspect the drains and basins for accumulations and remove and clean by jet-vacuuming.

## **Pollution Prevention**

The following pollution prevention activities shall be undertaken to minimize potential impacts on stormwater runoff quality. The Contractor is responsible for all activities during construction. The Owner is responsible thereafter.



**Spill Procedures:** Any discharge of waste oil or other pollutant shall be reported immediately to the New Hampshire Department of Environmental Services (NHDES). The Contractor/Owner will be responsible for any incident of groundwater contamination resulting from the improper discharge of pollutants to the stormwater system, and may be required by NHDES to remediate incidents that may impact groundwater quality. If the property ownership is transferred, the new owner will be informed of the legal responsibilities associated with operation of the stormwater system, as indicated above.

**Sanitary Facilities:** Sanitary facilities shall be provided during all phases of construction.

**Material Storage:** No on site trash facility is provided until homes are constructed. The contractors are required to remove trash from the site. Hazardous material storage is prohibited.

**Material Disposal:** All waste material, trash, sediment, and debris shall be removed from the site and disposed of in accordance with applicable local, state, and federal guidelines and regulations. Removed sediments shall be if necessary dewatered prior to disposal.

### Invasive Species

Monitor the Stormwater Management System for signs of invasive species growth. If caught early, their eradication is much easier. The most likely places where invasions start is in wetter, disturbed soils or detention ponds. Species such as phragmites and purple loose-strife are common invaders in these wetter areas. If they are found, the owner shall refer to the fact-sheet created by the University of New Hampshire Cooperative Extension (or other source) or contact a wetlands scientist with experience in invasive species control to implement a plan of action for eradication. Measures that do not require the application of chemical herbicides should be the first line of defense.



Figure 1: *Lythrum salicaria*, Purple Loosestrife. Photo by Liz West. Figure 2: *Phragmites australis*. Photo by Le Loup Gris

## RAIN GARDEN MAINTENANCE SHEET

<b>INSPECTION REQUIREMENTS</b>		
<b>ACTION TAKEN</b>	<b>FREQUENCY</b>	<b>MAINTENANCE REQUIREMENTS</b>
<i>-Inspect pond surface for the occurrence of sediment, trash, debris, or structural damage.</i>	Bi-Yearly and following major storm events	<ul style="list-style-type: none"> <li><i>-Remove sediments, trash, and debris, as necessary.</i></li> <li><i>-Repair outlet structures and appurtenances, as necessary.</i></li> </ul>
<ul style="list-style-type: none"> <li><i>-Check to see if pond drains within 72 hours of rainfall.</i></li> <li><i>-Check vegetation health.</i></li> </ul>	Annually	<ul style="list-style-type: none"> <li><i>-If system does not drain within 72 hours of a rainfall event, consult a qualified professional about restoration of function of the dry well.</i></li> <li><i>-Vegetation should be maintained and pruned.</i></li> <li><i>-Dead or diseased vegetation should be removed, as well as any invasive species.</i></li> </ul>

<b>MAINTENANCE LOG</b>	
<b>PROJECT NAME</b>	
<b>INSPECTOR NAME</b>	<b>INSPECTOR CONTACT INFO</b>
<b>DATE OF INSPECTION</b>	<b>REASON FOR INSPECTION</b> <input type="checkbox"/> LARGE STORM EVENT <input type="checkbox"/> PERIODIC CHECK-IN
<b>IS CORRECTIVE ACTION NEEDED?</b>  <input type="checkbox"/> YES <input type="checkbox"/> NO	<b>DESCRIBE ANY PROBLEMS, NEEDED MAINTENANCE</b>
<b>DATE OF MAINTENANCE</b>	<b>PERFORMED BY</b>
<b>NOTES</b>	

## CLOSED DRAINAGE STRUCTURE LONG-TERM MAINTENANCE SHEET

INSPECTION REQUIREMENTS		
ACTION TAKEN	FREQUENCY	MAINTENANCE REQUIREMENTS
-Outlet Control Structures -Drain Manholes -Catch Basins	Monthly for 1 year following construction, Every other Month thereafter	<i>Check for erosion or short-circuiting Check for sediment accumulation Check for floatable contaminants</i>
-Drainage Pipes	Monthly for 1 year following construction, 1 time per 2 years thereafter	<i>Check for sediment accumulation/clogging, or soiled runoff. Check for erosion at outlets.</i>

MAINTENANCE LOG	
<b>PROJECT NAME</b>	
<b>INSPECTOR NAME</b>	<b>INSPECTOR CONTACT INFO</b>
<b>DATE OF INSPECTION</b>	<b>REASON FOR INSPECTION</b> <input type="checkbox"/> LARGE STORM EVENT <input type="checkbox"/> PERIODIC CHECK-IN
<b>IS CORRECTIVE ACTION NEEDED?</b> <input type="checkbox"/> YES <input type="checkbox"/> NO	<b>DESCRIBE ANY PROBLEMS, NEEDED MAINTENANCE</b>
<b>DATE OF MAINTENANCE</b>	<b>PERFORMED BY</b>
<b>NOTES</b>	

## STABILIZED CONSTRUCTION ENTRANCE CONSTRUCTION MAINTENANCE SHEET

INSPECTION REQUIREMENTS		
ACTION TAKEN	FREQUENCY	MAINTENANCE REQUIREMENTS
ENTRANCE SURFACE <i>-Check for sediment accumulation/clogging of stone</i>	After heavy rains, as necessary	<i>-Top dress pad with new stone. -Replace stone completely if completely clogged.</i>
WASHING FACILITIES (if applicable) <i>-Monitor Sediment Accumulation</i>	As often as necessary	<i>-Remove Sediments from traps.</i>

MAINTENANCE LOG	
PROJECT NAME	
INSPECTOR NAME	INSPECTOR CONTACT INFO
DATE OF INSPECTION	REASON FOR INSPECTION <input type="checkbox"/> LARGE STORM EVENT <input type="checkbox"/> PERIODIC CHECK-IN
IS CORRECTIVE ACTION NEEDED? <input type="checkbox"/> YES <input type="checkbox"/> NO	DESCRIBE ANY PROBLEMS, NEEDED MAINTENANCE
DATE OF MAINTENANCE	PERFORMED BY
NOTES	